

## **OIL INDIA LIMITED**

(A Government of India Enterprise)

P.O. Duliajan, Pin – 786602

Dist-Dibrugarh, Assam

### **CORRIGENDUM**

#### **ADDENDUM NO. 1 DATED 09.06.2021 TO TENDER NO SDG6976P22/08 dated 11.05.2021**

This Addendum No.01 dated 09.06.2021 to Tender No. SDG6976P22/08 is issued to amend the following:

#### **1. Technical Specification:**

<b>Item Sl. No.</b>	<b>Original Material Description</b>	<b>Amended Material Description</b>
<b>Item No 10</b>	1.9/16" Tubing Puncture/Circulation charge having Penetration Range - (0.30 to 0.50) inch and Entry Hole Diameter Range - (0.30 to 0.50) inch Tem. Rating- 350 Deg.F, Pressure Rating - 15,000 Psi.	1.9/16" Tubing Puncture/Circulation charge having Penetration Range - (0.30 to 0.50) inch and Entry Hole Diameter Range - (0.30 to 0.50) inch. Tem. Rating- 350 Deg. F.
<b>Item No 30</b>	40 GRAIN/FEET HMX LS RIBBON PRIMACORD Temp. Rating - 350 Deg F" Qty: 150 meters.	40 GRAIN/FEET HMX LS RIBBON PRIMACORD Temp. Rating - 350 Deg F" Qty: 152.5 meters.
<b>Item No 70</b>	1 9/16" Tandem Sub with Dart Seal"	1 9/16" Tandem Sub with or without Dart Seal" Whichever is applicable as per the 1 9/16" Tbg. Puncture to be quoted"
<b>Item No 100</b>	O-ring Nitrile-90 Duro PC-214 for 1 9/16" Tbg. Puncture" Qty : 200.	O-ring Nitrile-90 Duro PC-214 or PC-215 Whichever is applicable as per the 1 9/16" Tbg. Puncture to be quoted" Qty : 200.
<b>Item No 160</b>	Resistorised Detonator for Tubing Cutter: 1. Temperature rated for 350 Deg. F (minimum) & 2. Pressure rated for 15,000 psi (minimum).	Resistorised Detonator for Tubing Cutter: 1. Temperature rated for 350 Deg. F (minimum).

#### **2. General:**

"The tender no. in **page 3** of **Part-A** of the tender document should be read as **SDG6976P22/08** in place of **SDG6784P22/08**".

All other Terms & Conditions of the Tender Document remain unaltered.

sd/-

Tushar Ranjan Dutta

Manager Materials(FD)

For GM-Materials

For Resident Chief Executive