

OIL INDIA LIMITED(A Govt. of India Enterprise)
P.O. Duliajan-786602, Assam.

Fax No. 91-374-2800533, E-mail:material@oilindia.in

Tender No. & Date : DFS1353L11/02 15.03.2011Bid Security Amount : INR 0.00 OR USD 0.00
(or equivalent Amount in any currency)**Bidding Type : Single Bid (Composite Bid)**

Bid Closing On : 18.05.2011 at 13:00 hrs. (IST)

Bid Opening On : 18.05.2011 at 13:00 hrs. (IST)

Performance Guarantee : Not Applicable

OIL INDIA LIMITED have issued Limited tenders to following parties for items detailed below. For General Terms & Conditions, please refer to Document No. MM/GLOBAL/01/2005 available in OIL's web site:

Item No./ Mat. Code	Material Description	Quantity	UOM
10 84402054	<p><u>WIRE ROPES / LINES</u> For detailed technical information regarding the various types of wire ropes manufactured and their selection, application and handling reference should be made to :</p> <p>(a) A.P.I. Standard 9A and RP9B (Latest Edition) (b) B.S.S. 302/621 of 1957; IS:2266-1970; B.S.S. 330 of 1957 and IS:1856:1970. Wires used in manufacture of wire ropes listed in this section shall be made from acid or basic open-hearth steel. - basic oxygen steel. - electric furnace steel. Fibre cores shall be hard-twisted, best quality, manila, sisal, polypropylene or equivalent. The cores shall be of uniform diameter & Hardness, effectively supporting the strands. Manila & sisal cores shall be thoroughly impregnated with a suitable lubricating compound free from acid. Jute cores should not be used.</p> <p>ROPE, WIRE, IMPROVED PLOW STEEL, 175/190 KILOS/SQ.MM TENSILE, PREFORMED, ROUND STRAND, BRIGHT (UNCOATED) OR DRAWN-GALVANIZED, CONFORMING TO BS:302/621 - 1957 AND IS:2266 - 1970 OR APISPECIFICATION 9A.</p> <p>Dia. 16 mm (5/8"), Construction 6 x 36, Classification 6 x 37, Strand construction - Seale/Warrington, Main core - Fibre, Lay - Right Regular, Nominal Strength - 15.1 MT (33,400 lbs or 149 KN), Length per Reel - 2000 Mtrs., Packing - Wooden Reel, (for use as Winch Line)</p>	5	RL
20 84402726	<p>ROPE, WIRE, PLOW STEEL, 160/175 KILOS/SQ.MM TENSILE, PREFORMED, ROUND STRAND, BRIGHT (UN-COATED) OR DRAWN-GALVANIZED, CONFORMING TO BS:302 - 1957 AND IS:2266 - 1970 OR APISPEC. 9A</p> <p>Dia. - 9 mm (3/8"), Construction 6 x 19, Classification 6 x 19,</p>	6000	M

Tender No. & Date : DFS1353L11/02

15.03.2011

Item No./ Mat. Code	Material Description	Quantity	UOM
	Main Core - Fibre, Lay - Right Regular, Nominal Strength - 4.9 MT (10,800 lbs. or 48.18 KN), Length - 2000 Mtrs. per reel, Packing - Wooden Reel (for use as Rigging/Block Lines)		

Note description for item no./nos. : 10**NOTE :**

(For G.I. Nos. 84402054, 84402167, 2065,2076,2305,2316,2327,2338 &2351).

The wire ropes should be properly reeled in steel or wooden(as indicated in above specification)frame of adequate strength to prevent damage of wire rope during transportation & handling. Wire ropes should be properly lubricated during manufacturing process as well as during reeling on to steel or wooden (as indicated in above specification) spool in order to withstand all types of climates. Name of Manufacturer, Reel no., API orIS license number including monogram & date of manufacture, Length of rope, Diameter of rope, Type of construction, Lay, Grade, Type of core, Purchase Order No., Net weight and Gross weight shall be paint stenciled on the body of the Reel

Special Notes : Note:-

The wire rope should be properly reeled in wooden frame of adequate strength to prevent damage of wire rope during transportation & handling. Wire ropes should be properly lubricated during manufacturing process as well as during reeling on to wooden spool in order to with stand all types of climates. Name of Manufacturer,Reel No.API or ISI license number including monogram & date of manufacture, Length of rope, Diameter of rope, Type of construction, Lay,Grade,Type of core, Purchase order No. Net weight and Gross weight shall be paint stenciled on the body of the Reel.

01. THE ITEMS COVERED BY THIS TENDER SHALL BE USED BY OIL INDIA LIMITED IN THE PEL/ML AREAS WHICH ARE ISSUED/RENEWED AFTER 1.4.99 AND HENCE NIL CUSTOM DUTY DURING IMPORT WILL BE APPLICABLE. INDIGENOUS BIDDER SHALL BE ELIGIBLE FOR DEEMED EXPORT BENEFIT AGAINST THIS PURCHASE. DETAILS OF DEEMED EXPORT ARE FURNISHED VIDE ADDENDUM TO MM/GLOBAL/01/2005 ENCLOSED.

02.. BIDDERS ARE REQUIRED TO QUOTE WITH MINIMUM VALIDITY OF 120 DAYS FROM THE BID CLOSING DATE AS PER NIT REQUIREMENT. BIDS WITH LESSER VALIDITY SHALL BE REJECTED.

03.BIDDERS HAVE TO INDICATE THE MINIMUM FOB/FCA CHARGES IN CASE OF PARTIAL ORDER FOR REDUCED QUANTITY/ITEMS. IN CASE THIS IS NOT INDICATED SPECIFICALLY, THE CHARGES QUOTED WOULD BE PRORATA CALCULATED AND THE SAME WILL BE BINDING ON THE BIDDER.

04. BIDDERS ARE REQUIRED TO MENTION THE WEIGHT OF EACH ITEM INDIVIDUALLY.

05. BIDDERS OTHER THAN OEM (ORIGINAL EQUIPMENT MANUFACTURER MUST SUBMIT PROPER VALID AUTHORISATION CERTIFICATE ALONG WITH THE WARRANTY BACK-UP FROM OEM FAILING WHICH OFFER SHALL BE LIABLE TO REJECTION.

06. QUOTATION MUST BE SUBMITTED IN TRIPLICATE.

Tender No. : DFS1353L11/02
Tender Date : 15.03.2011
Bid Closing On : 18.05.2011 at 13:00 hrs.(IST)
Bid Opening On : 18.05.2011 at 13:00 hrs.(IST)

Tender issued to following parties only:

Slno	V_Code	Vendor Name	City/Country
1	101033	WIRECO WORLDGROUP	
2	101066	BRIDON AMERICAN CORPORATION	PENNSYLVANIA-18706
3	200276	USHA MARTIN LIMITED	KOLKATA
4	200278	BHARAT WIRE ROPES LIMITED	MUMBAI
5	200279	MOHATTA & HECKEL LIMITED	MUMBAI - 400 001
6	203124	SHREE STEEL WIRE ROPES LTD	MUMBAI
7	203344	JCT LIMITED (STEEL DIVISION)	PUNJAB.