

OIL INDIA LIMITED
(A Government of India Enterprise)
Rajasthan Project
Jodhpur, Rajasthan

CORRIGENDUM

Amendment No. 1 Dated 10.08.2019
to
Tender No. SJI2037P20

This Amendment No. 1 dated 10.08.2019 to **Tender No. SJI2037P20 for METALLIC FLEXIBLE HOSE** is issued as under:

- A. The technical specifications of both the items is to be read as under in lieu of the existing:

Sl. No.	Material Code	Material Description	Quantity
10	99013454	<p>HOSE, METALIC, FLEXIBLE FOR STEAM NPT/BSP UNION(M/F) CONNECTION AT EITHER END, 4" metallic Corrugated flexible hose assembly for steam injection that can withstand high temperature and pressure. Pressure rating: Min: 3000 psi, Temp: Minimum: 340C. length of each joint: 10 meters will be used for steam injection into wells High pressure & temperature Close pitch annular corrugations. High temperature high pressure hammer union at both ends for each joint along with GRAPHALLOY bushing to withstand high temperature as per design to withstand high temperature and pressure along with concentric reducer and nipple.</p> <p>1. One concentric reducer SIZE 3" to 2" with 2" to be connected to the hammer union of the metallic hose and 3" side having bevel end welded to main steam line. (MATERIAL : XXS) 2. 2" Nipple of length 30 cms, one end to be connected to the hammer union and other end to</p>	20 Nos.

		flow line valve of well (MATERIAL : XXS)	
20	99013454	<p>HOSE, METALIC, FLEXIBLE FOR STEAM NPT/BSP UNION(M/F) CONNECTION AT EITHER END, 4" metallic Corrugated flexible hose assembly for steam injection that can withstand high temperature and pressure. Pressure rating: Min: 2000 psi, Temp: Minimum: 300C. length of each joint: 3 meters High pressure & temperature Close pitch annular corrugations. High temperature hammer union at both ends for each joint along with GRAPHALLOY bushing to withstand high temperature as per design to withstand high temperature and pressure along with two numbers of 4" nipple with NPT Thread (length: 30 cms)</p>	15 Nos.
30	99013454	<p>HOSE, METALIC, FLEXIBLE FOR STEAM NPT/BSP UNION(M/F) CONNECTION AT EITHER END, 4" metallic Corrugated flexible hose assembly for steam injection that can withstand high temperature and pressure. Pressure rating: Min: 3000 psi, Temp: Minimum: 340C. length of each joint: 15 meters will be used for steam injection into wells High pressure & temperature Close pitch annular corrugations. High temperature high pressure hammer union at both ends for each joint along with GRAPHALLOY bushing to withstand high temperature as per design to withstand high temperature and pressure along with concentric reducer and nipple. 1. One concentric reducer SIZE</p>	20 Nos.

		3" to 2" with 2" to be connected to the hammer union of the metallic hose and 3" side having bevel end welded to main steam line. (MATERIAL : XXS) 2. 2" Nipple of length 30 cms, one end to be connected to the hammer union and other end to flow line valve of well (MATERIAL : XXS)	
--	--	--	--

All other Terms & Conditions of the tender remain unchanged.

Sd-
(B. Mody)
Manager Materials (M&C)