

OIL INDIA LIMITED
(A Government of India Enterprise)
P.O. Duliajan, Pin – 786602
District-Dibrugarh, Assam

AMENDMENT NO 3 DATED 25.11.2025 TO TENDER No. SDG0538P26/P7 dated 04.11.2025

This amendment is issued for the following:

1. To amend Annexure B, AA Technical Specification of the tender as below:

Clause No. Description	Tender Clause	Request for Amendment
Annexure B, AA Technical Specification Special Notes to Bidders Item Nos. 10, 20 ,30 Clause No. 1.	Amended Tender Clause (Amendment no. 1 dated 07.11.2025) 1. The rotary shoulder connection should be as per API Spec-7.2 (latest edition). Bidders to confirm the same while quoting. In support of rotary shoulder connection of the item as per API, the bidder should submit copies of API Spec-7.2 certificates for the last five years (i.e. continuous without any break in between), preceding from the original bid closing date along with the bid. Bid without copies of valid API Spec-7.2 certificates or breaks in between will be rejected.	1. The rotary shoulder connection should be as per API Spec-7.2 (latest edition). Bidders to confirm the same while quoting. In support of rotary shoulder connection of the item as per API, the bidder should submit valid API Spec 7-2 certificate and copies of API Spec-7.1 certificates for the last five years (i.e. continuous without any break in between), preceding from the original bid closing date along with the bid. Bid without copies of API Spec. 7-1 certificates (continuous without any break for last five years) and valid API Spec-7.2 certificate will be rejected.
Annexure B, AA Technical Specification. Item No. 20	Item No. 20: Fishing Magnet for 12 1/4" Hole, Qty-03 Nos. Fishing Magnet, to work inside 12.1/4" (311.15 mm) Hole, consisting of body, an integral housing, an integral pole plate, a magnetic element & a standard bottom guide, the fishing magnet will be complete with circulation holes & pressed steel thread protector & having following specifications: Pull of Magnet (LBS) (Approx.) - 3200 – 4000 OD of magnet : 10.1/2" (266.70 mm) Top Connection : 6.5/8" (168.275 mm) API Reg. RH PIN	Item No. 20: Fishing Magnet for 12 1/4" Hole, Qty-03 Nos. Fishing Magnet, to work inside 12.1/4" (311.15 mm) Hole, consisting of body, an integral housing, an integral pole plate, a magnetic element & a standard bottom guide, the fishing magnet will be complete with circulation holes & pressed steel thread protector & having following specifications: Pull of Magnet (LBS) (Approx.)- Minimum pull force not less than 1100 lbs as per manufacturer's standard design for 12 1/4" hole fishing magnets. OD of magnet: 10.1/2" (266.70 mm) Top Connection: 6.5/8" (168.275 mm) API Reg. RH PIN.

2. All other terms and condition of the tender remain unchanged.

Sd/-
(TUHIN ROY)
DGM-FP 07
FOR GM- MATERIALS
FOR RESIDENT CHIEF EXECUTIVE