

Amendment No. 4 dated 12.12.2025 to Tender no. SDG0510P26/P7 DATED 30.10.2025 for Coiled Tubing unit, Qty = 1 No.

- 1.0 This amendment is issued to amend the clauses of the tender as per attached Annexure – A.
- 2.0 All other terms & conditions of the tender remain unchanged.

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
Technical specifications – Annexure AAA			
1	1.0 c	The unit should be capable of operating in ambient temperature ranges of 0° C to +50° C in a 90% relative humidity. The unit with upgraded latest state of the art technology improved version will be acceptable for the basic configuration, accessories, instrumentation, control etc. without affecting the main frame of specification.	The unit should be capable of operating in ambient temperature ranges of 0° C to +45° C in a 90% relative humidity. The unit with upgraded latest state of the art technology improved version will be acceptable for the basic configuration, accessories, instrumentation, control etc. without affecting the main frame of specification.
2	2.2 a.	<p>Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) with 1.5 inch Tubing configuration shall be within 55,000KG.</p> <p>Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) with 1.75 inch Tubing configuration shall be within 55,000KG.</p> <p>Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) is the weight of the complete unit, i.e. total of weight of the Tractor with Driver's cabin etc.; weight of Trailer chassis & deck; weight of all equipment, items, tools, accessories, materials, spare wheels, hydraulic oil, all oil, handling fluid with tank, Diesel etc. that are permanently mounted on the unit and are generally being carried & kept in the unit.</p> <p>All load bearing components of the unit like Chassis, Axles, Suspension, Landing Gears etc. shall be capable of taking the total weight of the complete unit with all equipment, handling fluids, items, fittings & accessories with both 1.5 inch Tubing configuration and 1.75 inch Tubing</p>	<p>Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) with 1.5 inch Tubing configuration shall be within 59,100KG.</p> <p>Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) with 1.75 inch Tubing configuration shall be within 59,100KG.</p> <p>Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) is the weight of the complete unit, i.e. total of weight of the Tractor with Driver's cabin etc.; weight of Trailer chassis & deck; weight of all equipment, items, materials, etc. that are mounted on the unit.</p> <p>All load bearing components of the unit like Chassis, Axles, Suspension, Landing Gears etc. shall be capable of taking the total weight of the complete unit with all equipment, handling fluids, items, fittings & accessories with both 1.5 inch Tubing configuration and 1.75 inch Tubing configuration as mentioned in the tender, in all conditions.</p>

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
		configuration as mentioned in the tender, in all conditions.	
3	3.1 b.	<p>The Tractor unit shall be of the Make: Ashok Leyland/ Tata / Mahindra / Eicher / Bharat Benz / Volvo / Kenworth / International / Peterbilt.</p> <p>The bidder shall take special care in selecting and designing the unit considering its application in national highways, state highways, district roads, rural/village roads, slushy oil & gas well sites which may not be smooth every time. The village roads are sometimes gravel roads as normally encountered in oil & gas fields of India.</p> <p>The offer shall be with make, model, specifications, fittings, accessories etc. as mentioned in the tender.</p>	<p>The Tractor unit shall be of the Make: Ashok Leyland/ Tata / Mahindra / Eicher / Bharat Benz / Volvo / Kenworth / International / Peterbilt / Mercedes Benz.</p> <p>The bidder shall take special care in selecting and designing the unit considering its application in national highways, state highways, district roads, rural/village roads, slushy oil & gas well sites which may not be smooth every time. The village roads are sometimes gravel roads as normally encountered in oil & gas fields of India.</p> <p>The offer shall be with make, model, specifications, fittings, accessories etc. as mentioned in the tender.</p>
4	3.2	GROSS COMBINATION WEIGHT RATING (GCWR):	GROSS COMBINATION WEIGHT FOR REGISTRATION:
5	3.2 a.	<p>Gross Combination Weight Rating (GCWR) of the Tractor unit when coupled with the offered CTU Trailer shall not exceed 55,000 kg. This is required for permanent registration of the unit with government authorities as per Motor Vehicle Act, 1988 & Central Motor Vehicle Rules 1989 of India.</p> <p>Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) with 1.5 inch Tubing configuration and 1.75 inch Tubing configuration shall be within Gross Combination Weight Rating (GCWR) of the Tractor unit.</p>	<p>For the purpose of registration of the unit with government authorities as per Motor Vehicle Act, 1988 & Central Motor Vehicle Rules 1989 of India, Gross Combination Weight of the unit (i.e. Tractor unit when coupled with the offered CTU Trailer) shall be as permitted by the government authorities during the registration process.</p> <p>This is for bidder's information purpose only.</p>
6	3.2 b.	The bidder shall mention & submit the following information in the technical bid:	--- deleted ---
7	3.2 b. (i)	Gross Combination Weight Rating (GCWR) of the Tractor unit when coupled with the offered CTU Trailer	--- deleted ---

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
		shall not exceed 55,000 kg for permanent registration of the unit. (Yes / No).	
8	3.2 b. (ii)	Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) with 1.5 inch Tubing configuration shall be within Gross Combination Weight Rating (GCWR) of the Tractor unit. (Yes / No).	--- deleted ---
9	3.2 b. (iii)	Total combination weight (mass) of each complete unit (Tractor & CTU Trailer combination, i.e., Tractor coupled with the CTU Trailer) with 1.75 inch Tubing configuration shall be within Gross Combination Weight Rating (GCWR) of the Tractor unit. (Yes / No).	--- deleted ---
10	3.16 e.	Type approval certification of individual components shall not be considered as vehicle Type approval certificate.	The above vehicle Type Approval Certificate to be submitted shall be for the entire Tractor unit. However, bidder / supplier is to note that, the Type Approval Certificate of individual component(s) of the vehicle shall not be considered as vehicle Type Approval Certificate.
11	4.12	TYPE APPROVAL CERTIFICATE OF CTU TRAILER:	--- deleted ---
12	4.12 a.	Type Approval Certificate of vehicle is required for the following activities in India: i. Uploading the vehicle details in the relevant Government of India portal (VAHAN / Homologation/ Parivahan portal) for registration of vehicle as per Motor Vehicle Act, 1988 & Central Motor Vehicle Rules, 1989 of India which is mandatory for plying of the vehicle in roads in India. ii. Custom clearance of the vehicle as per import policy conditions/guidelines of India Chapter-87 of ITC (HS), 2022, Schedule 1-Import Policy, Section: XVII, in case of imported vehicle from other countries to India.	--- deleted ---

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
13	4.12 b.	<p>In case the offered Trailer is manufactured in India, the offered Trailer shall be compliant to Central Motor Vehicle Rules 1989 of India and its amendments.</p> <p>In case the offered Trailer is imported from other countries to India, the offered Trailer shall be compliant with the import policy of Government of India.</p> <p>The bidder/supplier shall have to submit the Type Approval Certificate of Trailer, as applicable, along with the supply. Submission of Type Approval Certificate of Trailer shall be as per Central Motor Vehicle Rules of India and/or as per the import policy of Government of India, as applicable, as on the date of supply.</p>	--- deleted ---
14	4.12 c.	<p>The list of Type Approval Certificate issuing agencies are mentioned in Central Motor Vehicle Rules, 1989 of India & its amendments.</p> <p>In case of imported vehicle from other countries to India, at the time of Customs clearance, a Type Approval Certificate/COP, of an international accredited agency including a notarized English translation thereof shall be furnished. This Type Approval Certificate shall stipulate that vehicle to be imported complies with all the ECE Regulations. The list of international accredited agencies approved for issuance of Type Approval Certificate is available on DGFT website, under Policy Circular No. 12 (RE- 2013)/2009-2014 dated 15.01.2014 issued by Ministry of Commerce & Industry, Department of Commerce, Director General of Foreign Trade, New Delhi subjecting "Type Approval issuing agencies under Policy Condition number 7 and 9 of Chapter 87 of ITC (HS) 2012".</p>	--- deleted ---

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
15	4.12 d.	Bidder/supplier shall ensure adherence to any subsequent revisions to the above referred Policy Circulars that may be issued in future by DGFT. Bidder shall note that, they shall be conversant with the policy of Government of India and Oil India Limited (OIL) shall not be liable in this regard whatsoever.	--- deleted ---
16	4.12 e.	Type approval certification of individual components shall not be considered as vehicle Type approval certificate.	--- deleted ---
17	4.12 f.	Notwithstanding anything mentioned elsewhere in this document, submission of Type Approval Certificate/ Conformity of Production (CoP) shall be as per the guideline of Government of India as on the date of supply.	--- deleted ---
18	5.1 v.	The Tractor unit shall preferably have Air Bags for Driver and the Co-driver.	The Tractor unit shall preferably have Air Bags for Driver.
19	7.1 b.	The offered engine shall comply with BS-VI/EURO-VI/TIER IV Final/equivalent or higher emission standard as applicable in the in India at the time of delivery of the unit. The engine should be vibration isolated from the trailer by means of suitable antivibration mounting.	The offered engine shall comply with BS-V/EURO Stage-V/TIER IV Final/equivalent or higher emission standard as applicable in the in India at the time of delivery of the unit. The engine should be vibration isolated from the trailer by means of suitable antivibration mounting.
20	8.1 j.	Cabin floor shall be integral part of the Cabin shell, to have a noise free environment inside the cabin during operation. Cabin of Fixed type floor shall not be acceptable.	Cabin floor shall be integral part of the Cabin shell, to have a noise level < 80dB inside the cabin during operation. Cabin of Fixed type floor shall not be acceptable.
21	8.1 k.	Cabin shall be suitably noise sealed for a Noise free environment considering occupational health of the CTU operator.	Cabin shall be suitably noise sealed for a noise level < 80dB considering occupational health of the CTU operator.
22	10.1 e.	Electronic/Hydraulic Load Cell assembly (0-80,000 lbs) of make Martin Decker/Wagner/Benchmark with dual scale Weight Indicator.	Hydraulic Load Cell assembly (0-80,000 lbs) of make Martin Decker/Wagner/Benchmark with dual scale Weight Indicator.
23	10.1 k.	Goose neck Tubing Arch Guide / shall fold down roller type detachable,72" radius.	Goose neck Tubing Arch Guide / shall fold down roller type detachable, minimum 72" radius.

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
24	10.1 n.	Remote control injector chain lubricating system. Chain type shall be ANSI#180.	Remote control injector chain lubricating system. Chain type shall be minimum ANSI #180.
25	10.1 p.	Easily replaceable chain assembly to adapt gripper block for CT size ranging from 1.25"-1.75" OD . Integral gripper block with insert is not acceptable. There shall be provision of quick removal of plunger / insert from the gripper block assembly during operation without dismounting of Chain Assembly from Drive sprocket.	Easily replaceable chain assembly to adapt gripper block for CT size ranging from 1.5"-1.75" OD . Integral gripper block with insert is not acceptable. There shall be provision of quick removal of plunger / insert from the gripper block assembly during operation without dismounting of Chain Assembly from Drive sprocket.
26	10.1 q.	One set of 4 nos adjustable telescopic support legs 20 ft long with screw, to support injector during operation. Another set of 4 nos of short support legs (of length approx. 5 feet) to facilitate maintenance work at base.	One set of 4 nos adjustable telescopic support legs of minimum 13 ft long with screw, to support injector during operation. Another set of 4 nos of short support legs (of length approx. 5 feet) to facilitate maintenance work at base.
27	10.1 s.	Quick disconnects of make Aeroquip / Parker /Gates / Eaton only.	Quick disconnects of make Aeroquip / Parker / Gates / Eaton / Hansa-Flex / STUCCHI only.
28	10.2 a.	One (01) no. hydraulically operated QUAD BOP of make Bowen / Texas Oil Tool / Forum / Vanoil/ Fidmash/ Parveen	One (01) no. hydraulically operated QUAD BOP of make Bowen / Texas Oil Tool / Forum / Vanoil / Fidmash/ Parveen / NXL Technologies shall be supplied and shall be of the following specification mentioned below. Note: Make for BOP & Stuffing box shall be same.
29	10.3 a.	Hydraulically actuated Side door stripper packer of make Texas Oil Tool / Forum / Parveen / Vanoil of the following specification shall be supplied. i. 3.06" X 10,000 Psi, H2S service, dressed for 1.5" tubing. ii. Connection: H2S rated per NACE MR-0175-03.3.06" 10M CB34 union nut and pin down. The stripper mounts to the injector shall be via a pin on stripper adapter.	Hydraulically actuated Side door stripper packer of make Texas Oil Tool / Forum / Parveen / Vanoil / NXL Technologies of the following specification shall be supplied. i. 3.06" X 10,000 Psi, H2S service, dressed for 1.5" tubing. ii. Connection: H2S rated per NACE MR-0175-03.3.06" 10M CB34 union nut and pin down. The stripper mounts to the injector shall be via a pin on stripper adapter. Note: Make for BOP & Stuffing box shall be same.
30	10.3 b.	The Side door of the stripper shall be designed for integral function, i.e., close/open for replacing interlock packer and energizing/compressing Interlock packer. Lubrication port shall be provided at suitable location for lubricating during operation. Bottom	Hydraulically actuated double door stripper shall be designed for integral function, i.e., close/open for replacing interlock packer and energizing/compressing Interlock packer. Lubrication port shall be provided at suitable location for lubricating during operation. Bottom connection shall be compatible to the supplied BOP/Combi BOP.

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
		connection shall be compatible to the supplied BOP/Combi BOP.	
31	10.3 c.	In addition to the above, a tandem stripper shall be provided which is designed to run in tandem below the side door stripper packer. It may be run independently as a back-up stripper or in conjunction with the upper pack off. It shall have provision for injecting lubricant under pressure between the packers to reduce the well pressure across the tandem packer. The tandem stripper shall be of side door configuration (3.06" X 10,000 Psi, H2S service, dressed for 1-1/2" tubing) and all connections shall be compatible to the above Main stuffing box(stripper) and bottom connection shall be compatible to the supplied BOP.	Clause to be Deleted.
32	16.4	One set of Lubricator Assembly of the following specifications:	One set of Lubricator Assembly of Nominal ID: 3" & Bore: 3.06" having the following specifications:
33	18.0 d.	All operating oils, coolants, and other operating fluids except those required for road drive of the Tractor-Trailer CTU unit will be drained prior to shipment.	All operating oils, coolants, and other operating fluids except those required for road drive of the Truck unit will be drained prior to shipment. However, the same shall be supplied at Duliajan, Assam, during commissioning of the unit.
34	19.0 a.	Frame, Pump, and Control console: RED-315.	Frame, Pump, and Control console: RAL-3000.
35	20.0 a.	ASME standards	ASME standards/ European Standards EN and DIN
36	21.0 j. 2.	Combination Spanners: 3 sets.	Combination Spanners: Size: 10-32 mm (14 pcs): 3 sets. Size: 1/4" to 1" (13 pcs): 3 sets.
37	21.0 j. 3.	Combination Pliers: 2 nos.	Combination Pliers of Sizes: 6", 7", 8": 2 sets
38	21.0 j. 4.	Allen Key Set: 3 nos.	Allen Key Set: Size: 1.5 mm to 10 mm (9 pcs): 3 sets. Size: 1/16" to 3/8" (10 pcs): 3 sets.
39	21.0 j. 8.	Special tools wrenches for Pump servicing.	Special tools wrenches for Pump servicing (if applicable)
40	21.0 j. 10.	Special tools required for hydraulic system: 1 set.	Special tools required for hydraulic system (if applicable): 1 set
41	25.1 a	Supplier shall arrange for Third Party Inspection (TPI) of the unit through OIL's nominated Third-Party Inspection Agency at Bidder's/	Supplier shall arrange for Third Party Inspection (TPI) of the unit at Bidder's/ Manufacturer's plant/premises as per approved QAP and conditions of the Purchase Order, through OIL's nominated Third-Party Inspection

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
		Manufacturer's plant/premises as per approved QAP and conditions of the Purchase Order.	Agency viz., M/s Lloyds, M/s Bureau Veritas, M/s IRS, M/s Rites, M/s Tuboscope Vecto and M/s DNV.
42	29.0 k.	Type Approval Certificate of Trailer of CTU as per Clause No. 4.12.	--- deleted ---
43	36.0	In Case of Foreign Bidder: Materials must be delivered on FOB, Port of Shipment basis within twelve (12) months from the date of opening of Letter of Credit by OIL. The date of unambiguous Bill of Lading (B/L) shall be considered as the date of delivery.	In Case of Foreign Bidder: Materials must be delivered on FOB, Port of Shipment basis within fifteen (15) months from the date of opening of Letter of Credit by OIL. The date of unambiguous Bill of Lading (B/L) shall be considered as the date of delivery.
44	TABLE:1 DOWNHOLE TOOLS 1. a.	1.75" OD x 0.109WT CT with connector Dia 1.687", End connection: 1 AMMT.	02 nos 1.75" OD x 0.109WT CT with connector Dia 2.0", End connection: 1.5 AMMT.
45	TABLE:1 DOWNHOLE TOOLS 11. a.	1.75" Motor Head Assembly, 1" AMMT Box x Pin. Motor Head Assembly shall include a double flapper check valve, hydraulic disconnect, circulation sub and rupture disc in one assembly.	01 No 1.75" Motor Head Assembly, 1" AMMT Box X Pin. Motor Head Assembly shall include a double flapper check valve, hydraulic disconnect, circulation sub and rupture disc in one assembly. Shall provide spare rupture discs and redress kits.
46	TABLE:1 DOWNHOLE TOOLS 11. b.	2.125" Motor Head Assembly, 1.5" Box x Pin AMMT. Motor Head Assembly shall include a double flapper check valve, hydraulic disconnect, circulation sub and rupture disc in one assembly.	01 No 2.125" Motor Head Assembly, 1.5" Box x Pin AMMT. Motor Head Assembly shall include a double flapper check valve, hydraulic disconnect, circulation sub and rupture disc in one assembly. Shall provide spare rupture discs and redress kits.
47	TABLE:1 DOWNHOLE TOOLS NOTE	All tools shall be compatible with 1.5" & 1.75" Coiled tubing and CT end Connectors supplied.	All tools shall be compatible with 1.5" & 1.75" Coiled tubing and CT end Connectors supplied for standard service .
48	Table-2 Section (A) H.2	Power Steering Hoses Set (Set shall comprise of all hoses used in steering system, one each)	01 Set --- Portion deleted ---
49	Table-2 Section (A) H.4	Steering Gear Box Repair Kit (if any)	02 Sets --- Portion deleted ---
50	Table-2 Section (A) I.5	Air Dryer Assembly	02 Nos --- Portion deleted ---
51	Table-2 Section (A)	Air Dryer Filter	08 Nos --- Portion deleted ---

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause		Amended Clause	
	I.6				
52	Table-2 Section (A) 1.7	Brake Shoe Assembly - Tractor Front Wheel	08 Nos	Brake Shoe Assembly - Tractor Front Wheel (in case of Drum Brakes), or Brake Calliper Assembly - Tractor Front Wheel (in case of Disc Brakes)	08 Nos
53	Table-2 Section (A) 1.8	Brake Shoe Assembly - Tractor Rear Wheel	12 Nos.	Brake Shoe Assembly - Tractor Rear Wheel (in case of Drum Brakes), or Brake Calliper Assembly - Tractor Rear Wheel (in case of Disc Brakes)	12 Nos.
54	Table-2 Section (A) 1.9	Brake Shoe Assembly - Trailer Wheel	16 Nos.	Brake Shoe Assembly - Trailer Wheel (in case of Drum Brakes), or Brake Calliper Assembly - Trailer Wheel (in case of Disc Brakes)	16 Nos.
55	Table-2 Section (B) 6	Water Pump Repair Kit	01 Set.	Water Pump Repair Kit, if applicable.	01 Set.
56	Table-2 Section (B) 10	Fuel Pump Repair Kit	01 Set	Fuel Pump Repair Kit, if Applicable.	01 Set
57	Table-2 Section (C) 6	Pressure Transducer/ Transmitter	02 Nos	--- Portion deleted ---	
58	Table-2 Section (D) 10	Reel swivel hydraulic cylinder repair kit	02 Set	Reel swivel hydraulic cylinder repair kit, if Applicable	02 Set
59	Table-2 Section (D) 15	Interlock Packer/Stripper, stuffing box	20 Nos	Interlock Packer / Stripper, stuffing box for both CT sizes.	20 Nos for each size
60	Table-2 Section (D) 16	Stripper / stuffing box repair kit.	02 Set	Stripper / stuffing box repair kit for both CT sizes.	02 Sets for each size
61	Table-2 Section (D) 17	BOP repair kit.	04 set	BOP repair kit for both CT sizes.	04 Sets for each size
62	Table-2 Section (D) 18	Inner seal, pipe ram.	04 nos	Inner seal, pipe ram for both CT sizes.	04 Nos for each size
63	Table-2 Section (D) 19	Slip insert.	2 nos	Slip insert for both CT sizes.	02 Nos for each size
Annexure – B - CC: General Notes to Bidders.					
64	Clause 14.	--		14. Order of Precedence- In the event of any conflict between the clauses of documents of the tender, following order of precedence shall apply: 1. BEC / BRC. 2. Technical specifications.	

Amendment dated 12.12.2025 to SDG0510P26/07 for Coiled Tubing unit

Sl. No	Tender Clause No.	Existing Clause	Amended Clause
			<p>3. Special Notes to bidders.</p> <p>4. General Notes to bidders.</p> <p>5. Additional Notes to the bidder.</p> <p>6. General terms and conditions MM/GLOBAL/E-01/2005 for E-procurement of ICB tenders.</p>
65	Clause 15.	--	15.0 In case PO is placed on Foreign bidder on FOB basis, then after despatch clearance is provided by OIL the Supplier shall intimate Kolkata Shipping office for appointment of Freight Forwarder. OIL shall appoint Freight forwarder within 30 days of receipt of packing list, proforma invoice etc. from Supplier.
66	Clause 16.	--	16.0 Bidders to note that interpretation of all foreign trade terms shall be as per INCOTERMS 2020.
Annexure – C – BID EVALUATION CRITERIA (BEC) A.3 BEC – COMMERCIAL- DD: PRICE EVALUATION CRITERIA			
67	Clause 5.3.	<p>5.3 Concurrent Application of Purchase Preference Policies:</p> <p>The quantities under this tender are splitable in the ratio of 3:2:2 as mentioned above and Public Procurement Policy for MSE Order 2012 and PP(MII) Order 2017 as per Order No. F.1/4/2021-PPD dated 18.05.2023 issued by Public Procurement Division, Department of Expenditure, Ministry of Finance, Govt. of India and any subsequent amendment thereto shall be applicable. Bidders are advised to refer to the said Order for further detail. In case of concurrence application of Purchase Preference Policies, the preference order shall be as mentioned below.</p>	<p>5.3 Concurrent Application of Purchase Preference Policies:</p> <p>The quantities under this tender is not splitable and Public Procurement Policy for MSE Order 2012 and PP(MII) Order 2017 as per Order No. F.1/4/2021-PPD dated 18.05.2023 issued by Public Procurement Division, Department of Expenditure, Ministry of Finance, Govt. of India and any subsequent amendment thereto shall be applicable. Bidders are advised to refer to the said Order for further detail. In case of concurrence application of Purchase Preference Policies, the preference order shall be as mentioned below.</p>
ANNEXURE –E- PRICE SCHEDULE – FOREIGN BIDDERS -			
68		5. Ocean Freight Charges upto Kolkata , India	5. Ocean Freight Charges upto Kolkata / Chennai, India
