

**OIL INDIA LIMITED**  
**(A Government of India Enterprise)**  
**P.O. Duliajan, Pin – 786602**  
**Dist-Dibrugarh, Assam**

**AMENDMENT NO. 1 DATED 02.03.2016**  
**TO TENDER NO SSG0176P16/03**

This Amendment no. 1 dated 02.03.2016 to tender no. SSG0176P16/03 for **Procurement of Well Logging Equipments /Explosives** is issued to change the detailed specification of item nos. 10, 20 & 30 as follows instead of the existing:

Sl. no & Material code	Existing Material Description	Modified Material Description
10 ----- 70025502	WELL LOGGING EXPLOSIVES 53.975 mm (2.1/8") Through Tubing Deep Penetration Perforation charge, HMX/RDX, 0° Phased having the following specification : Temp. rating: 325°F (163°C) min. Pressure rating: 12000 PSI (846 kg/cm.Sqr.)min. Minimum acceptable performance in 5.1/2" cemented (concrete) casing as per both API 'RP-43' OR 'RP-19B' recommended practice are as follows : EHD(min.) = 0.30" (7.65 mm) min. T.T. Penetration(min.) = 30" (766 mm), normalised to 5000 psi.	WELL LOGGING EXPLOSIVES 53.975 mm (2.1/8") Through Tubing Deep Penetration Perforation charge, <b>HMX</b> , 0° Phased having the following specification: Temp. rating: <b>350°F (177°C) min.</b> Pressure rating: <b>15000 PSI(1057 Kg/Cm.Sqr.)min</b> Minimum acceptable performance in 5.1/2" cemented(concrete) Casing as per both API 'RP-43' OR 'RP-19B' recommended practice are as follows : EHD(min.)= 0.30" (7.65 mm) min. T.T. Penetration(min.)= 30" (766 mm.) normalized to 5000 psi.
20 ----- 70025513	WELL LOGGING EXPLOSIVES Resistorised Detonator Assembly for T.T.P. charge having the following specifications : Temp. rating : 325°F (163°C) Pressure rating: 12000 PSI (846 Kg/Cm.Sqr.)	WELL LOGGING EXPLOSIVES Resistorised Detonator Assembly for T.T.P. charge having the following specifications: Temp. rating: <b>350°F (177°C)</b> Pressure rating: <b>15000 PSI (1057 Kg/Cm.Sqr.)</b>
30 ----- 70024246	WELL LOGGING EXPLOSIVES Detonating Cord HMX 80 gr/ft. Rilsan/Teflon or equivalent Jacketed Low shrink (1% Max.) 100% inspected. Recommended to be used in exposed condition.  Temp. Rating : 350° F (177°C) Air rating for 01 hour.	WELL LOGGING EXPLOSIVES Detonating Cord HMX 80 gr/ft. Rilsan/Teflon or equivalent Jacketed Low shrink (1% Max.) 100% inspected. Recommended to be used in exposed condition.  Temp. Rating: <b>400°F(204°C)</b> Air rating for 01 hour

	Pressure rating : 12,000 psi (846 kg/cm sq.) (152.4 mtrs. or 500 ft. per roll)	Pressure rating: <b>15,000 psi (1057 kg/cm sq.)</b> (152.4 mtrs. or 500 ft. per roll)
--	-----------------------------------------------------------------------------------	------------------------------------------------------------------------------------------

All other terms and condition of the tender will remain unchanged.

sd-  
Gitasree Sarmah  
Sr. Purchase Officer (FS)  
For HEAD MATERIALS  
For Resident Chief Executive

\*\*\*