OIL INDIA LIMITED (A Government of India Enterprise) P.O. Duliajan, Pin – 786602 Dist-Dibrugarh, Assam

AMENDMENT NO. 3 DATED 07.06.2018 TO TENDER NO SSG7445P18/03

- 1.0 This Amendment no. 3 dated 07.06.2018 to tender no. SSG7445P18/03 for supply of **Retainer Packer & Accessories** is issued to incorporate the following changes in the tender
- 1.1 To extend the tender sale last date to: **20.06.2018**To extend the Bid Closing/Opening Date to: **27.06.2018**
- 1.2 To revise the tender specification as below:

Item No./	Existing Description	Revised Description
Mat. Code	Existing Description	Revised Description
10	PACKER, RETAINER WITH	PACKER, RETAINER WITH
05181338	ACCESSORIES PRODUCTION	ACCESSORIES PRODUCTION
	RETAINER PACKER	RETAINER PACKER
	Packer, Retainer for 5.1/2",20-	Packer, Retainer for 5.1/2",20-
	23PPF Csg. Packer,	23PPF Csg. Packer,
	Permanent/Retainer Production,	Permanent/Retainer Production,
	similar to Baker Model D' or DA'	similar to Baker Model `D' or `DA'
	Packer as per the following	Packer as per the following
	requirement :	requirement :
	A) The packer shall be suitable for	A) The packer shall be suitable for
	following duty conditions	following duty conditions
	i) Casing Size: 139.77 mm (5.1/2")	i) Casing Size: 139.77 mm (5.1/2")
	OD x 29.82 - 34.3 Kg./m (20 – 23	OD x 29.82 - 34.3 Kg./m (20 – 23
	PPF) ii) Setting Depth: 5000 m (16404	PPF) ii) Setting Depth : 5000 m (16404
	ft.) Maximum	ft.) Maximum
	iii) Maximum working differential	iii) Maximum working differential
	pressure: 528 Kg/Sq.Cm.(7,500	pressure: 528 Kg/Sq.Cm.(7,500
	PSI) from both side.	PSI) from both side.
	iv) Maximum Temperature at	iv) Maximum Temperature at
	setting depth: 135 Deg.C (275 Deg.F)	setting depth: 135 Deg.C (275 Deg.F)
	v) Service : Sweet	v) Service : Sweet
		,
	B) The packer shall fulfill following	B) The packer shall fulfill following
	dimensional parameters and material of	dimensional parameters and material of
	constuction	constuction
	i) Minimum ID of packer: 68.2752	i) Minimum ID of packer: 68.2752
	mm (2.688")	mm (2.688")
	ii) Material Grade : L-80, Type-I.	ii) Material Grade : L-80, Type-I.

- C) The packer shall have the following features
- i) Seal bore extension will be required below the packer for sealing of long locator tube seal assembly (LTSA). Minimum length: 6 ft, Minimum ID same as packer ID.
- ii) The body of packer must be slim & solid in construction for faster running in.
- iii) It must have two opposed sets of full circle full strength slips and one or more packing element for effective pack off when set. iv) The Packer must have both

Wireline and tubing setting features.

Please note that Baker E4 #20 pressure setting tool is available for wireline setting method. Therefore requisite adapter kit if required for setting the packer in conjunction with Baker tool must be supplied.

- D) Each packer shall be provided with following accessories
- i) Shear Release Stud

- C) The packer shall have the following features
- i) Seal bore extension will be required below the packer for sealing of long locator tube seal assembly (LTSA). Minimum length
- : 6 ft, Minimum ID same as packer ID.
- ii) The body of packer must be slim & solid in construction for faster running in.
- iii) It must have two opposed sets of full circle full - strength slips and one or more packing element for effective pack off when set.
- iv) The Packer must have both Wireline and tubing setting features.

Please note that Baker E4 #20 pressure setting tool is available for wireline setting method. Therefore requisite adapter kit if required for setting the packer in conjunction with Baker tool must be supplied.

- D) Each packer shall be provided with following accessories
- i) Shear Release Stud / Shear Screw

Note: In case "Shearing Screw" design of setting tool for the Retainer Packer is quoted, the bidder has to categorically confirm that the adapter kit & setting tool to be supplied will be compatible with Baker E4# 20 pressure setting tool.

Also, Service Engineer of the supplier has to come to OIL Duliajan **FREE OF COST**, to assist in setting up the Retainer Packer with OIL's Baker E4# 20 pressure setting tool for at least in one operation and provide necessary training. The bidder has to confirm the same in the technical bid.

2.0 All other terms and condition of the tender will remain unchanged.

sd-Gitasree Sarmah Mnager Materials (FS) For GM MATERIALS For Resident Chief Executive