OIL INDIA LIMITED

(A Government of India Enterprise)
P.O. Duliajan, Pin – 786602
<u>Dist-Dibrugarh, Assam</u>

Ref: MM/ALB/FD09/025 Date: 31.12.2016

CORRIGENDUM

ADDENDUM No.01_ Dated 31.12.2016

<u>To</u>

Tender No. SDG 2985P17/09

This Addendum No.01 dated 31.12.2016 to Tender No. SDG 2985P17/09 for supply of Rotary Hand Slips (3 items) is issued to amend the tender as under:

i) Amendment to Material Specification:

CLAUSE	EARLIER SPECIFICATIONS	AMMENDED SPECIFICATIONS
NO/Item No:		
	ROTARY HAND SLIP FOR 20" OD CASING.	ROTARY HAND SLIP FOR 20" OD CASING.
	Each Rotary hand slip should consists of:	Each Rotary hand slip should consists of:
10	(a) Extra long Casing slip complete with handles & circular buttons for 508 mm (20") OD casing pipes. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.	(a) Extra long Casing slip complete with handles & circular buttons for 508 mm (20") OD casing pipes. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.
	(b) Extra set of circular buttons for each slip - 1 set (Total 04 set)	(b) Extra set of circular buttons for each slip - 1 set (Total 04 set)
		Minimum load bearing capacity of the casing slips should not be less than 100 ton
20	ROTARY HAND SLIP FOR 13.3/8" OD CASING.	ROTARY HAND SLIP FOR 13.3/8" OD CASING.
	Each Rotary hand slip should consists of:	Each Rotary hand slip should consists of:
	(a) Extra long Casing slip complete with handles & circular buttons for 339.725 mm (13.3/8") OD casing pipes. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.	(a) Extra long Casing slip complete with handles & circular buttons for 339.725 mm (13.3/8") OD casing pipes. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.
	(b) Extra set of circular buttons	(b) Extra set of circular buttons

	for each slip - 1 set (Total 06 set)	for each slip - 1 set (Total 06 set)
		Minimum load bearing capacity of the casing slips should not be less than 250 Tons
30	ROTARY HAND SLIP FOR 9.5/8" OD CASING.	ROTARY HAND SLIP FOR 9.5/8" OD CASING.
	Each Rotary hand slip should consists of:	Each Rotary hand slip should consists of:
	(a) Extra long Casing slip complete with handles & circular buttons for 244.475 mm (9.5/8") OD casing pipes. Hand slip should have an API taper of 4 inch/ft. & suitable for use in 27.1/2" Square drive Rotary Table.	complete with handles & circular buttons for 244.475 mm (9.5/8") OD casing pipes. Hand slip should have an API taper of 4 inch/ft. & suitable for use in
	(b) Extra set of circular buttons for each slip - 1 set (Total 07 set)	(b) Extra set of circular buttons for each slip - 1 set (Total 07 set)
		Minimum load bearing capacity of the casing slips should not be less than 250 Tons

ii) Amendment and Addition in Special Notes to Bidders:

CLAUSE NO/Item No:	EARLIER SPECIAL NOTES	AMMENDED SPECIAL NOTES
Special Notes for Bidders 1.0	Items shall be manufactured, tested & certified as per API Spec.7K. Bidders to confirm the same while quoting. A copy of valid API Spec 7K certificate must be forwarded along with the offer.	Items shall be manufactured, tested & certified as per API Spec. 7K (latest edition). In support of manufacturing the item as per API, the bidder should submit copies of API 7K certificates with validity covering minimum 5 (FIVE) years continuously reckoned prior to the original bid closing date of the tender.
2.0	Markings (including API monogram) shall be done as per API Spec 7K. Additionally, purchase order number should be die stamped along with the name of manufacturer. Bidder should confirm the same while quoting.	Markings (including API monogram & SR1 marking) shall be done as per API Spec 7K. Additionally purchase order number shall be weld written on suitable place at the items. Bidders shall confirm compliance to the same while quoting.
Addition of New Clause		In the event of order the supply must include the manufacturer's data book (wherever applicable) (SR3 of API 7K); mill test

	certificates, Ultrasonic Test Reports etc for all of the items;
	Proof Load testing of primary load carrying components (Clause 8.6 of API 7K) and two sets of Maintenance, Service and Parts Manual. Bidder should categorically confirm while quoting.

All other Terms & Conditions of the Bid Document remain unaltered.

sd/Amrit Loushon Bora
Sr. Purchase Officer(FD)
For Dy. GM Materials
For Resident Chief Executive