

OIL INDIA LIMITED
(A Government of India Enterprise)
P.O. Duliajan, Pin – 786602
Dist-Dibrugarh, Assam

AMENDMENT NO. 2 DATED 09.04.2016
TO TENDER NO SSG0176P16/03

This Amendment no. 2 dated 09.04.2016 to tender no. SSG0176P16/03 for **Procurement of Well Logging Equipments /Explosives** is issued to change the detailed specification of item nos. 10, 30 & 40 as follows instead of the existing:

Sl. no & Material code	Existing Material Description	Modified Material Description
10 ----- 70025502	WELL LOGGING EXPLOSIVES 53.975 mm (2.1/8") Through Tubing Deep Penetration Perforation charge, HMX, 0° Phased having the following specification: Temp. rating: 350°F (177°C) min. Pressure rating: 15000 PSI(1057 Kg/Cm.Sqr.)min Minimum acceptable performance in 5.1/2" cemented(concrete) Casing as per both API 'RP-43' OR 'RP-19B' recommended practice are as follows : EHD(min.)= 0.30" (7.65 mm) min. T.T. Penetration(min.)= 30" (766 mm.) normalized to 5000 psi.	WELL LOGGING EXPLOSIVES 2.1/8 inch, 54 mm(max) Through Tubing Deep Penetration Perforation charge, HMX, 0° Phased having the following specification: Temp. rating: 350°F (177°C) min. Pressure rating: 15000 PSI(1057 Kg/Cm.Sqr.)min Minimum acceptable performance in 5.1/2" cemented(concrete) Casing as per both API 'RP-43' OR 'RP-19B' recommended practice are as follows : EHD(min.)= 0.30" (7.65 mm) min. T.T. Penetration(min.)= 30" (766 mm.) normalized to 5000 psi.
30 ----- 70024246	WELL LOGGING EXPLOSIVES Detonating Cord HMX 80 gr/ft. Rilsan/Teflon or equivalent Jacketed Low shrink (1% Max.) 100% inspected. Recommended to be used in exposed condition. Temp. Rating: 400°F(204°C)Air rating for 01 hour Pressure rating: 15,000 psi (1057 kg/cm sq.) (152.4 mtrs. or 500 ft. per roll)	WELL LOGGING EXPLOSIVES Detonating Cord HMX 80 gr/ft. Rilsan/Teflon or equivalent Jacketed Low shrink (1% Max.) 100% inspected. Recommended to be used in exposed condition. Temp. Rating: 400°F(204°C)Air rating for 01 hour Pressure rating: 15,000 psi (1057 kg/cm sq.) [152.4 mtrs./ 500 ft. in 01 Roll OR in 4 to 6 Pieces also]
40 ----- 70025535	WELL LOGGING EQUIPMENT 53.975 mm (2.1/8") Strip carrier 0 Deg. phased,6 spf, 12 ft. long for the above Through Tubing Millennium Deep Penetration	WELL LOGGING EQUIPMENT 53.975 mm (2.1/8") Strip carrier 0 Deg. phased,6 spf, 12 ft. long for the above Through Tubing Millennium Deep Penetration

	<p>Perforation Charge suitable to pass through 2.2" I.D. restriction in the production tubing. (The carrier should have requisite flexibility to bend in the minor dog legs and pass through smaller I.D. restriction.</p> <p>: Part No. 100008034 : Part No. 100008034 : Part No. 2315274 of DYNA ENERGETICS GMBH & CO. KG</p>	<p>Perforation Charge suitable to pass through 2.2" I.D. restriction in the production tubing. (The carrier should have requisite flexibility to bend in the minor dog legs and pass through smaller I.D. restriction.</p> <p>: Part No. 100008034 : Part No. 100008034 : Part No. 2315274 of DYNA ENERGETICS GMBH & CO. KG</p> <p>Note: Strip carrier size of 3m, 6 spf, 0 Deg. phase is also acceptable if Bidder agrees to supply additional Firing Head (Item sl.- 90 (Mat-70025524) without cost if the Indented Quantity of the same is consumed or damage before consumption of Indented Charge(10,000 nos.)</p>
--	--	--

All other terms and condition of the tender will remain unchanged.

sd-
Gitasree Sarmah
Sr. Purchase Officer (FS)
For HEAD MATERIALS
For Resident Chief Executive
