## **OIL INDIA LIMITED**

(A Government of India Enterprise) P.O. Duliajan, Pin – 786602 <u>Dist-Dibrugarh, Assam</u>

## **CORRIGENDUM**

## Amendment No. 01 Dated 23.06.2020 to Tender No. SDG4234P21/06

1.0 This Amendment No. 01 dated 16.03.2020 is issued to amend the item specification and extend the bid closing date as under in lieu of existing:

Clause No	EXISTING TENDER CLAUSES	AMENDED TENDER CLAUSES
AA: Technical Specifications & Quantity of Items.  SL NO. 10	SLAMMER CABLE, .474 OD, 7-CONDUCTOR WIRELINE LOGGING CABLE, CAMESA TYPE 7H47RXZ-HS OR EQUIVALENT, STEEL ARMOURED AND SPOOLED ON STEEL REEL, HAVING FOLLOWING SPECIFICATIONS:  [1] Outer Diameter: 0.474 " + 0.005" -0.002" (12.04 mm + 0.13 mm - 0.05mm).  [2] Cable Breaking Strength: 23,600 LBS (102.8 KN) Nominal.  [3] Cable Stretch Coefficient:0.61ft/Kft/Klbs (0.69 m/km/5KN)  [4] Temperature Rating: 205 Deg C (400 Deg F) minimum [5] Minimum Conductor Voltage: 1100 VDC.  [6] Minimum Insulation Resistance: 1500 Meg Ohms/Kft @ 500 VDC  [7] No. of Inner / Outer Armor: 18 / 18  [8] Plastic Type: ETFE (Tefzel)  [9] Conductor Resistance : 9.8 Ohms/Kft Typical  [10] Armor Resistance : 1.1 Ohm/Kft Typical	STEEL REEL, HAVING FOLLOWING SPECIFICATIONS:  [1] Outer Diameter: 0.474 " + 0.005" -0.002" (12.04 mm + 0.13 mm - 0.05mm).  [2] Cable Breaking Strength: 23,600 LBS (102.8 KN) Nominal [3] Cable Stretch Coefficient: 0.61 ft/Kft/Klbs (0.69 m/km/5KN).  [4] Temperature Rating: 205 Deg C (400 Deg F) minimum.  [5] Minimum Conductor Voltage: 700-1250 VDC.  [6] Minimum Insulation Resistance: 1500 Meg Ohms/Kft @ 500 VDC  [7] No. of Inner / Outer Armor: 18 / 18  [8] Plastic Type: ETFE (Tefzel) or PFA(Teflon)  [9] Conductor Resistance: 7.5-

2.0 The bid closing date has been extended as under:

Description	Existing Date & Time	Extended upto
Bid Closing Date & Time	24.06.2020 (at 11.00 Hrs. IST)	08.07.2020 (at 11.00 Hrs. IST)
Technical Bid Opening Date & Time	24.06.2020 (at 14.00 Hrs. IST)	08.07.2020 (at 14.00 Hrs. IST)

3.0 All other Terms & Conditions of the Bid Document remain unaltered.

sd/-Kumar Abhimanyu Manager Materials (FD) For GM-Materials For Resident Chief Executive