



Oil India Limited
(A Govt. of India Enterprise)
P.O. Duliajan – 786602, Assam

Telephone No. (91-374) 2808724
Fax No: (91-374) 2800533
Email: matmmfd@oilindia.in ; erp_mm@oilindia.in

Tender No. & Date: SDG0428P16/07 dt.02.03.2016

Tender Fee : INR 4,500.00 OR USD 100.00

Bid Security Amount : INR 52,000.00 OR USD 780.00
(or equivalent amount in any currency)

Bidding Type : SINGLE STAGE COMPOSITE BID SYSTEM

Bid Closing on : 04.05.2016 (at 11.00 Hrs. IST)

Bid Opening on : 04.05.2016 (at 14.00 Hrs. IST)

Bid Validity : Bid should be valid for 120 days from bid closing date.

Bid Bond Validity : Bid Bond should be valid up to 04.03.2017.
(Bid bond format has been changed. Please submit bid bond as per revised format)

Performance Guarantee : Applicable

Item No.	MATERIAL DESCRIPTION	QT Y.	UO M
10	<p><u>Specification of item:</u></p> <p><u>Item Description:</u></p> <p>Item Description: Portable Combustible (LEL) Gas Detector with digital indications and alarms and in-built suction pump for sampling complete with carrying case, shoulder traps, respiratory bulb with not less than 5 m long sampling line.</p> <p>Technical Specification:</p> <ol style="list-style-type: none">1. Type of Sensor: Catalytic Plug & Play2. Measuring principle: Heat of Reaction & Thermal Conductivity3. Measuring Gas: Combustible Gases (LEL)4. Measuring Range: 0 - 100% LEL / 0 - 5 Vol% / 0 - 100 Vol%5. Resolution: 1% LEL (For 0 - 100% LEL), 0.01 Vol% (For 0 - 5 Vol%) & 1 Vol% (For 0 - 100 Vol%)6. Alarm: Audio Visual Alarm for Low Battery,	05	Nos.

	<p>Low and High Range</p> <p>7. Typical Response Time: # 15 Seconds</p> <p>8. Display: 7 Segments LCD (Display for Alarm, LEL%, Low Battery, Calibration etc.) with backlight</p> <p>9. Power Pack: Nickel-Cadmium Rechargeable Battery Pack</p> <p>10. Operating Time: # 12 Hours</p> <p>11. Charging Time: # 4 Hours</p> <p>12. Minimum Sensor Life: 2 Years</p> <p>13. Approval: Directorate General of Mines Safety (DGMS), Dhanbad</p> <p>14. Hazardous area: Intrinsically Safe, Explosion Proof suitable for use in Class - I, Division - I, Group - I, IIA, IIB, IIC and Dust Area Zone 21 and 22</p> <p>15. Operating Temperature: - 20 Deg. C to + 50 Deg. C</p> <p>16. Ingress Protection: IP 66/67</p> <p>17. Features: Auto Zero Self Check, Auto Diagnostics</p> <p>18. Additional Features: Data Logging Capability (up to 50 hrs.)</p> <p>19. Humidity: 10 to 95% R.H.</p> <p>20. Accessories with each unit: Protective Carry Case (Leather), Sampling Kit with Probe/Filter with PVC tubing (5 meter) Aspirator Bulb, Single unit Battery Charger (Supply 230 VAC), Rechargeable Battery, Installation Software with Interface Data link Cable.</p> <p>21. Weight & Size: Light Weight, Hand-Held, Portable, Not more than 450 gm</p> <p>22. Instruction Manual: Complete in all respect should be provided</p> <p>23. Additional Accessories: Spare Sensor for the above Gas Detector: 5 Nos.</p>		
<u>20</u>	<p>Item Description: Portable Combustible (LEL) Gas & Oxygen Level Detector (Multigas) with digital indications and alarms and in-built suction pump for sampling complete with carrying case & shoulder traps. Unit must have integrated pump with visible pump filters. The pump must be capable to sample up to 100 Ft (30.5 M), with line size 0.25 in (6.35 mm) (approx.) in dia, replaceable line filter, should have pump filter window enabling users to visibly & non-intrusively check the pump filter, should have facility for replacement of pump filter with a single captive screw and should have a locking quick release for</p>	01	No.

	<p>sampling hoses & probes.</p> <p>Technical Specification:</p> <ol style="list-style-type: none"> 1. Type of Sensors: Catalytic diffusion & plug-in type for Combustible gases and Electrochemical & plug-in type for Oxygen sensor. 2. Measuring Gas: Combustible Gases (LEL) and Oxygen Level 3. Measuring Range: <ol style="list-style-type: none"> (a) For Combustible Gases (LEL): 0 - 100% LEL / 0 - 5 Vol% / 0 - 100 Vol% (b) For Oxygen: 0 - 30% of Volume 4. Resolution: <ol style="list-style-type: none"> (a) For Combustible Gases (LEL): 1% LEL (For 0 - 100% LEL), 0.01 Vol% (For 0 - 5 Vol%) & 1 Vol% (For 0 - 100 Vol%) (b) For Oxygen: 0.1% increment. 5. Alarm: Audio Visual Alarm for Low Battery, Low and High Range 6. Typical Response Time: # 15 Seconds 7. Display: 7 Segments LCD (Display for Alarm, LEL%, Low Battery, Calibration etc.) with backlight 8. Power Pack: Nickel-Cadmium Rechargeable Battery Pack 9. Operating Time: # 12 Hours 10. Charging Time: # 4 Hours 11. Minimum Sensor Life: 2 Years 12. Approval: Directorate General of Mines Safety (DGMS), Dhanbad 13. Hazardous area: Intrinsically Safe, Explosion Proof suitable for use in Class - I, Division - I, Group - I, IIA, IIB, IIC and Dust Area Zone 21 and 22 14. Operating Temperature: - 20 Deg. C to + 50 Deg. C 15. Ingress Protection: IP 66/67 16. Features: Auto Zero Self Check, Auto Diagnostics 17. Additional Features: Data Logging Capability (up to 50 hrs.) 18. Humidity: 10 to 95% R.H. 19. Accessories with each unit: Protective Carry Case (Leather), Sampling Kit with Probe/Filter with Aspirator Bulb & tube as required, Single unit Battery Charger (Supply 230 VAC), Rechargeable Battery, Installation Software with Interface Data link Cable. 20. Weight & Size: Light Weight, Hand-Held, Portable, Not more than 450 gm 21. Instruction Manual: Complete in all respect should be provided 		
--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--

	22. Additional Accessories: Spare Sensors for above Gas Detector: 1 Set (1 no. each = 1 nos. LEL and 1 no. Oxygen)		
<u>30</u>	<p>Item Description: Portable Combustible (LEL) Gases, H2S, SO2, CO & O2 Detector (Multigas) with digital indications and alarms and in-built suction pump for sampling complete with carrying case & shoulder traps. Unit must have integrated pump with visible pump filters. The pump must be capable to sample up to 100 Ft (30.5 M), with line size 0.25 in (6.35 mm) (approx.) in dia, replaceable line filter, should have pump filter window enabling users to visibly & non-intrusively check the pump filter, should have facility for replacement of pump filter with a single captive screw and should have a locking quick release for sampling hoses & probes.</p> <p>Technical Specification:</p> <p>1. Physical Specification: Instrument must be Portable Hand-held</p> <p>(a) Weight: Should not be more than 450 gm including battery.</p> <p>(b) Case Material: Should be rugged, impact resistant, non-corrosive composite material that will prevent spark generation.</p> <p>(c) Integral Boot: Instrument shall be equipped with a built-in concussion proof boot.</p> <p>(d) Handling: Unit shall easily attach to pocket or belt.</p> <p>(e) Carrying Attachments: Unit shall be equipped with a metal high tension stainless steel alligator clip. A non-conductive suspender swivel type alligator clip shall also be available.</p> <p>(f) Instrument Pump: Unit must have integrated pump with visible pump filters. The pump must be capable to sample up to 100 Ft (30.5 M), with line size 0.25 in (6.35 mm) (approx.) in dia, replaceable line filter, should have pump filter window enabling users to visibly & non-intrusively check the pump filter, should have facility for replacement of pump filter with a single captive screw and should have a locking quick release for sampling hoses & probes.</p> <p>2. Type of Sensors:</p> <p>(a) Gas specific Electrochemical sensors & Plug-in type for H2S, SO2, O2 & CO gases.</p>	20	Nos

	<p>(b) Catalytic diffusion & Plug-in type for Combustible gases.</p> <p>3. Measuring Gases: On a single screen of the gas detector continuous monitoring for Hydrogen Sulphide (H₂S), Carbon Monoxide (CO), Oxygen (O₂), Sulfur Dioxide (SO₂) and Combustible Gases (LEL) with four nos. gases display (min.) at a time.</p> <p>4. Measuring Specifications:</p> <p>(a) Hydrogen Sulphide: Range 0 - 200 ppm, Resolution 1 ppm</p> <p>(b) Carbon Monoxide: Range 0 - 1000 ppm, Resolution 1 ppm</p> <p>(c) Oxygen: Range 0 - 30% of Volume, Resolution 0.1% of Volume</p> <p>(d) Sulfur Dioxide: Range 0 - 100 ppm, Resolution 1 ppm</p> <p>(e) Combustible Gases (LEL): 0 - 100% LEL, Resolution 1% LEL; 0 - 5% V/V, Resolution 0.1%</p> <p>5. User Interfaces:</p> <p>(a) Display Type: Large alphanumeric 7 segments Liquid Crystal Display (LCD) type display with simultaneous readouts for each gas monitored in ppm, %LEL and %V/V values as applicable.</p> <p>(b) Display Symbols (icons): Gas alarm icons will clearly advise alarm type, gas hazard and alarm level encountered, low battery condition and instrument status, safe display, and calibration.</p> <p>(c) Keypad / Switches: One-button operation must for activate the detector, run the self-test, display alarm set points, display peak gas exposures and clears them, calibrate & zero.</p> <p>6. Instrument Alarms: Simultaneous visual display alarms, audible alarms, vibrator alarms in the event of a gas alarm condition, sensor fault or instrument status alarm.</p> <p>(a) Number of Gas alarm: Must be equipped with at least four (4) user selectable alarm levels including instant low, instant high, Time weighted average (TWA), Short term exposure limit (STEL) and Over Limit (OL) alarm.</p> <p>(b) Visual alarm: Must be equipped with at least three flashing alarm bars visible from multiple angles. The backlight must light in all alarm conditions.</p> <p>(c) Audible alarm: Instrument must equipped with two variable pulsed audible alarms that shall be rated at 95 dB at 1 ft/30 cm.</p> <p>(d) Vibrator alarm: Instrument must equipped with an internal vibrator alarm for high noise areas.</p>		
--	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--

	<p>(e) Over Limit Exposure Protection: For exposures above the instrument's measuring range for any sensor, the instrument will provide an over limit latching alarm that must be acknowledged.</p> <p>(f) Low Battery Warning: Must be equipped with low battery and visual alarms.</p> <p>7. Typical Response Time: # 15 Seconds</p> <p>8. Instrument Power:</p> <p>(a) Lithium - ion / Lithium - Polymer Rechargeable Battery Pack</p> <p>(b) Run Time > 12 Hours in normal operation</p> <p>(c) Charging Time < 6 Hours.</p> <p>9. Chargeable Option: 110 - 240 VAC, 50 Hz, Single and Multi cradle charger for 5 instruments must be available.</p> <p>10. Hazardous area: Intrinsically Safe, Explosion Proof suitable for use in Class - I, Division - I, Groups - A, B, C, D</p> <p>11. Operating Temperature: - 20 Deg. C to + 50 Deg. C</p> <p>12. Ingress Protection: IP 66/67</p> <p>13. Calibration: Calibration must be fully automatic with Auto Zero & Auto Span functions, Self Check and Auto Diagnostics facilities.</p> <p>14. Data Logging:</p> <p>(a) Instrument should have all events & occurrences recoding facility.</p> <p>(b) User selectable sampling rate</p> <p>(c) Data must store over 2 months based on normal 40 hours workweek</p> <p>(d) Data must be compatible for download and use with standard office programs (i.e. Excel and Access).</p> <p>15. Humidity: 15 to 95% R.H. (non-condensing) continuous.</p> <p>16. Instrument & Sensors Warranty: Two (02) years.</p> <p>17. Accessories with each unit: Protective Carry Case (Leather), Sampling Kit with Probe/Filter with required tubing, Single unit battery charger, Rechargeable Battery, Installation Software with Interface Data link Cable.</p> <p>18. Instruction Manual: Complete in all respect should be provided</p> <p>19. Approval: Directorate General of Mines Safety (DGMS), Dhanbad.</p> <p>20. Additional Accessories: Multi cradle battery charger for 5 instrument capacity (min.) = 3 nos.</p>		
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--

(A) General Notes for e-tender :

1. The tender will be governed by “General Terms & Conditions” for e-Procurement as per Booklet No.MM/GLOBAL/E-01/2005 for E-procurement(ICB Tenders) including Amendment and Addendum.
2. The general details of tender can be viewed by opening the RFx [Tender] under RFx and Auctions. The details of items tendered can be found in the Item Data and details uploaded under Technical RFX.
3. Bid must be submitted electronically only through OIL’s e-procurement portal. Bid submitted in any other form will be rejected.
4. Please note that all tender forms and supporting documents are to be submitted through OIL’s e-Procurement site only except following documents which are to be submitted manually in sealed envelope super scribed with tender no. and due date to The **Head Materials, Materials Department, Oil India Limited, Duliajan- 786602, Assam or before 13:00 hrs (IST)** on the Bid Closing Date mentioned in the Tender.
 - a) Original Bid Security along with two duplicate copies of Bid Security.
 - b) Any other document which have been specified to be submitted in original.
5. Bidders must ensure that their bid is uploaded in the system before the tender closing date and time. Also, they must ensure that above documents which are to be submitted in a sealed envelope are also submitted at the above mentioned address before the bid closing date and time failing which the offer shall be rejected.
6. Bidders are requested to examine all instructions, forms, terms and specifications in the bid. Failure to furnish all information required as per the bid or submission of offers not substantially responsive to the bid in every respect will be at the bidders risk and may result in the rejection of its offer without seeking any clarifications.
7. All the Bids must be Digitally Signed using “Class 3” digital certificate (*e-commerce application*) with organisation name as per Indian IT Act obtained from the licensed Certifying Authorities operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India.
8. Please do refer the User Manual provided on the portal on the procedure How to create Response for submitting offer.

(B) General Notes for Bidder's :

In the event of an order following conditions to be satisfied:

1. DGMS's Approval / Certification No. shall be affixed or embossed on each of equipment. The supply of material will be treated as complete only after submitting the valid DGMS's Approval Certificate.
2. Materials supplied with valid DGMS's Approval Certificate the payment shall be release as follows:
 - i) 90% of the supply value shall be released against proof of dispatch / shipment of the materials and submission of valid DGMS Approval Certificate.
 - ii) 10% of the value shall be released after receipt of the materials at site and acceptance by OIL.
3. Materials supplied without DGMS Approval Certificate, but with Field Trial Permission only, the payment shall be released as follows:
 - i) 50% of the supply value shall be released against proof of dispatch / shipment of the materials and submission of valid DGMS field Trial Permission Certificate.
 - ii) 50% of the supply value shall be released on receipt of valid DGMS Approval Certificate [Circular Ref.: GM (COM): 01/01-251 dated 02.07.2013]

(C) SPECIAL NOTES :

1. The items shall be brand new, unused & of prime quality. Bidder shall warrant (in the event of an order) that the product supplied will be free from all defects & fault in material, workmanship & manufacture and shall be in full conformity with ordered specifications. This clause shall be valid for 18 months from date of despatch/shipment or 12 months from date of receipt of the item at site which ever is earlier. In case of breakdown during the warranty period, a competent service engineer of the supplier shall make as many visits as shall be necessary to rectify the system. The supplier shall provide all spares required for making the system operational. Bidders must confirm the same while quoting.
2. Validity of the offers should be 120 days from the date of bid opening. Bids with lesser validity shall be summarily rejected.
3. The items covered by this tender shall be used by Oil India Limited in the PEL/ML areas which are issued/renewed after 01/04/99 and hence Nil Customs Duty during import will be applicable. Indigenous bidder shall be eligible for Deemed Export Benefit against this purchase. Details of Deemed Export are furnished vide Addendum to MM/GLOBAL/01/2005 enclosed. However no Recommendatory letters will be issued to Indian Bidders
4. Commercial Check-List vide **Annexure- B** shall be filled-up and submitted along with the offer.

5. To ascertain the substantial responsiveness of the bid OIL reserves the right to ask the bidder for clarification in respect of clauses covered under BRC also and such clarifications fulfilling the BRC clauses in to must be received on or before the deadline given by the company, failing which the offer will be summarily rejected.
 6. Bidders to note that Govt. of India under Micro, Small and Medium Enterprises Development (MSMED) Act 2006, has proclaimed the Public Procurement Policy, 2012 with effect from 1st April, 2012 in respect of procurement of goods and services, produced and provided by micro and small enterprises, by its Ministries, Departments and Public Sector Undertakings for promotion and development of Micro and Small Enterprises. A new Clause on applicability of Public Procurement Policy for procurement of goods from Micro, Small and Medium Enterprises (MSME) in the tender is furnished vide Amendment to General Terms and Conditions for Global Tender (MM/GLOBAL/E-01/2005). Bidders are requested to take note of the same and to submit their offers accordingly.
 7. Other terms and conditions of the tender shall be as per “General Terms & Conditions” for e- Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders). However, if any of the Clauses of the Bid Rejection Criteria (BRC) / Bid Evaluation Criteria (BEC) mentioned here contradict the Clauses in the “General Terms & Conditions” for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders) of the tender and/or elsewhere, those mentioned in this BEC / BRC shall prevail.
-

BID REJECTION CRITERIA (BRC)/BID EVALUATION CRITERIA (BEC)

(I) BID REJECTION CRITERIA (BRC)

A. Technical:

The bidder shall be an Original Equipment Manufacturer of the tender item(s), or shall be an authorized dealer/distributor/ supply house of an Original Equipment Manufacturer of the tender item(s) having valid authorization letter/dealership certificate with warranty/guarantee back up from the principal (OEM). Copy of authorization letter/dealership certificate with warranty/guarantee back up from the principal (OEM) shall be submitted along with the technical bid.

2. Bidder must submit copy of valid DGMS's Approval Certificate along with the offer. In case DGMS's Certified Explosimeter to be supplied is not available, copy of valid DGMS's field trial permission letter with CIMFR (or equivalent) Certificate must be submitted along with the offer, failing which the offer will be rejected. Bidder has to provide a firm confirmation in this regard during submission of their offer.

B. COMMERCIAL:

1. Bids are invited under **Single Stage Composite Bid System**. Bidders shall quote accordingly under Single Stage Composite Bid System.

2.0 **Bid security of US \$ 780.00 or Rs. 52,000.00** shall be furnished as a part of the TECHNICAL BID (refer Clause Nos.9.0 & 12.0 (Section A) of "General Terms & Conditions" for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders)).A bid shall be rejected straightway if Original Bid Security is not received within the stipulated date & time mentioned in the Tender and/or if the Bid Security validity is shorter than the validity indicated in Tender and/or if the Bid Security amount is lesser than the amount indicated in the Tender.

2.1 For exemption for submission of Bid Security, please refer Clause No. 9.8 (Section A) of "General Terms & Conditions" for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders).

2.2 The Bank Guarantee towards Bid Security shall be valid **upto 04.03.2017**.

3. Validity of the bid shall be minimum 120 days from the date of Bid Closing Date. Bids with lesser validity will be straightway rejected.

4. Bidders must confirm that Goods, materials or plant(s) to be supplied shall be new of recent make and of the best quality and workmanship and shall be guaranteed for a period of 18 months from the date of shipment/dispatch or twelve(12) months from the date of receipt of the items at site, whichever is earlier against any defects arising from faulty

materials, workmanship or design. Defective goods/materials or parts rejected by OIL shall be replaced immediately by the supplier at the supplier's expenses at no extra cost to OIL.

5. Successful bidder will be required to furnish a Performance Bank Guarantee @10% of the order value. The Performance Bank Guarantee must be valid for a period of 18 months from the date of shipment/dispatch or twelve(12) months from the date of receipt of the items at site, whichever is earlier. Bidder must confirm the same in their Technical Bid. Offers not complying with this clause will be rejected.
6. Bidders are required to submit the summary of the prices in their price bids as per bid format (Summary), given below :

I) Price Bid Format (SUMMARY) for Foreign Bidders :

- (A) Total Material Value :
- (B) Packing & FOB Charges :
- (C) Total FOB Port of Shipment value, (A + B) above :
- (D) Overseas Freight Charges upto Kolkata, India :
- (E) Insurance Charges :
- (F) Total CIF Kolkata value, (C + D + E) :
- (G) Total Value in words :
- (H) Gross Weight :
- (I) Gross Volume :

II) Price Bid Format (SUMMARY) for Indigenous Bidders:

- (A) Total Material Value :
- (B) Packing and Forwarding Charges:
- (C) Total Ex-works value, (A + B) above :
- (D) Sales Tax, (Please indicate applicable rate of Tax)
- (E) Total FOR Despatching station price, (C + D) above
- (F) Road Transportation charges to Duliajan
- (G) Insurance Charges
- (H) Assam Entry Tax
- (I) Total FOR Duliajan value, (E + F + G + H) above
- (J) Total Value in words :
- (K) Gross Weight :
- (L) Gross Volume :

7. The prices offered will have to be firm through delivery and not subject to variation on any account. A bid submitted with an adjustable price will be treated as non-responsive and rejected.
8. Bids received after the bid closing date and time will be rejected. Similarly, modifications to bids received after the bid closing date & time will not be considered.

9. Bids containing incorrect statement will be rejected.

(II) BID EVALUATION CRITERIA (BEC) :

Bids conforming to the specifications, terms and conditions stipulated in the tender and considered to be responsive after subjecting to the Bid Rejection Criteria will be considered for further evaluation as per the Bid Evaluation Criteria mentioned in Section D of “General Terms & Conditions” for e- Procurement as per Booklet No. MM/GLOBAL/E-01/2005.

=====

ANNEXURE-B**(A) COMMERCIAL CHECK-LIST**

Sl. No.	PARAMETERS/REQUIREMENTS	BIDDER RESPONSE	REMARKS IF ANY
1.	Whether Original Signed quotation submitted?	YES/NO	
2.	Whether quoted as manufacturer?	YES/NO	
3.	Whether quoted as authorized dealer? [To Specify]	YES/NO	
4.	If quoted as authorized dealer,		
5.	(a)Whether submitted valid and proper authorization letter from manufacturer IN ORIGINAL confirming that bidder is their authorized dealer for the product offered?	YES/NO	
6.	(b)Whether manufacturer's back-up Warranty/Guarantee certificate submitted?	YES/NO	
7.	Whether ORIGINAL Bid Bond (not copy of Bid Bond) enclosed with the offer? If YES, provide details	YES/NO	
	(a) Amount :		
	(b) Name of issuing Bank :		
	(c) Validity of Bid Bond :		
8.	Whether offered firm prices?	YES/NO	
9.	Whether quoted offer validity of 120 days from the date of closing of tender?	YES/NO	
10.	Whether quoted a firm delivery period?	YES/NO	
11.	Whether quoted as per NIT (without any deviations)?	YES/NO	
12.	Whether any deviation is there in the offer?	YES/NO	
13.	Whether deviation separately highlighted?	YES/NO	
14.	Whether agreed to the NIT Warranty clause?	YES/NO	
15.	Whether Price Bid submitted as per Price Schedule?	YES/NO	
16.	Whether indicated the country of origin for the items quoted?	YES/NO	
17.	Whether all the items of tender quoted?	YES/NO	
18.	Whether technical literature/catalogue/drawings enclosed?	YES/NO	
19.	For Foreign Bidders - Whether offered FOB/FCA port of dispatch including sea/air worthy packing & forwarding?	YES/NO	
20.	For Foreign Bidders – Whether port of shipment indicated? [To specify]	YES/NO	
21.	For Foreign Bidders only - Whether indicated ocean freight up to C&F Kolkata port (Excluding marine insurance)?	YES/NO	
22.	Whether Indian Agent applicable?	YES/NO	
	If YES, whether following details of Indian Agent provided?		
	(a) Name & address of the agent in India – To		

	indicate	
	(b) Amount of agency commission – To indicate	
	(c) Whether agency commission included in quoted material value?	YES/NO
23.	Whether weight & volume of items offered indicated?	YES/NO
24.	Whether confirmed to submit PBG as asked for in NIT?	YES/NO
25.	Whether agreed to submit PBG within 30 days of placement of order?	YES/NO
26.	For Indian bidders – Whether place of dispatch indicated in the offer? [To specify]	YES/NO
27.	For Indian bidders – Whether road transportation charges up to Duliajan quoted?	YES/NO
28.	For Indian Bidders only - Whether offered Ex-works price including packing/forwarding charges?	YES/NO
29.	For Indian Bidders only - Whether offered Deemed Export prices?	YES/NO
30.	Whether quoted prices are exclusive of Excise duty?	YES/NO
31.	For Indian bidders only – whether import content indicated in the offer?	YES/NO
32.	For Indian Bidders only - whether all Taxes have been indicated categorically?	YES/NO
33.	Whether all BRC/BEC clauses accepted?	YES/NO