

Conquering Newer Horizons

MATERIALS DEPARTMENT P.O. DULIAJAN - 786 602 DIST. DIBRUGARH ASSAM, INDIA

PHONE: 0374 - 2808724 FAX: 0374 - 2800533 EMAIL: matdmmfd1@oilindia.in

#### **FORWARDING LETTER**

M/s	<u> </u>	
	_	

Sub: Tender No. <u>SDG3951P20/06 Dated 26.02.2020</u> for <u>PROCUREMENT OF</u> "MUD MOTOR", TOTAL QUANTITY: 06 NOS.

Dear Sirs,

- 1.0 OIL INDIA LIMITED (OIL), a "Navaratna" Category, Government of India Enterprise, is a premier oil Company engaged in exploration, production and transportation of crude oil & natural gas with its Headquarters at Duliajan, Assam. Duliajan is well connected by Air with nearest Airport being at Dibrugarh, 45 km away.
- 2.0 In connection with its operations, OIL invites International Competitive Bids (ICB) from competent and experienced manufacturers through OIL's e-procurement site for "PROCUREMENT OF MUD MOTORS". One complete set of Bid Document for above is uploaded in OIL's e-procurement portal. You are invited to submit your most competitive bid on or before the scheduled bid closing date and time through OIL's e-procurement portal. For your ready reference, few salient points of the Tender are highlighted below:

E-Tender No	:	SDG3951P20/06 Dated 26.02.2020
Type of Bidding	:	SINGLE STAGE TWO BID SYSTEM
Tender Fee	:	NOT APPLICABLE
Bid Closing Date & Time	:	29.04.2020; 11:00 HRS.
Technical Bid Opening Date & Time	:	29.04.2020; 14:00 HRS.
Price Bid Opening Date & Time	:	To be decided later and shall be intimated separately to the technically qualifying bidders
Bid Security Amount	:	INR 411,670.00 OR USD 5700.00
Bid Security Validity	:	Upto <b>30.12.2020</b>
	1 1	_
Bid Submission Mode	:	Bids must be uploaded online in OIL's E-procurement portal
Bid Submission Mode  Bid Opening Place	:	<del>-</del>
		procurement portal Office of GM-Materials, Materials Department, Oil

Integrity Pact	:	Applicable
Contact Details	:	KUMAR ABHIMANYU, MATERIALS MANAGER (FD) E-MAIL: MATDMMFD1@OILINDIA.IN; PHN: 0374-2808724
E-Tender technical Support	:	TEL: 0374- 2804903, 2807171, 2807192, E-MAIL: ERP_MM@OILINDIA.IN
Bids to be addressed to	:	GM-Materials, Materials Department, Oil India Limited, Duliajan -786602, Assam, India.
LIST OF ANNEXURES A	. <b>PP</b>	LICABLE
General Terms & Conditions	:	MM/GLOBAL/E-01/2005 for E-Procurement ICB Tenders
Annexure-A	:	Specification and various notes to bidders
Annexure-B	:	Bid Evaluation & Rejection Criteria
Annexure-C	:	Commercial Checklist
Annexure-D		Format for certificate of annual turnover & net
		worth
Annexure-I	:	
Annexure-II	:	worth Technical checklist Matrix for Technical Evaluation
	:	worth Technical checklist
Annexure-II	:	worth Technical checklist Matrix for Technical Evaluation
Annexure-II Annexure- III Appendix-A2 Appendix-A3		worth Technical checklist Matrix for Technical Evaluation Matrix for BEC/BRC Evaluation
Annexure-II Annexure- III Appendix-A2		worth Technical checklist Matrix for Technical Evaluation Matrix for BEC/BRC Evaluation PPLC Policy Format of undertaking by Bidders towards

Performance Guarantee : Applicable @ 10% of Order value

3.0 OIL now looks forward to your active participation in the Tender.

Thanking you, Yours faithfully, OIL INDIA LIMITED

sd/-(KUMAR ABHIMANYU) Materials Manager (FD) For GM Materials For Resident Chief Executive

## AA:: TECHNICAL SPECIFICATIONS & QUANTITY OF ITEMS

SL NO	ITEM DESCRIPTION	QUANTITY
10	TECHNICAL SPECIFICATION FOR 3.1/2 INCHES OD MUD MOTOR:	06 NOS.
	A) 3.1/2 INCHES (88.90 MM) OD DOWN HOLE MUD MOTOR WITH SLICK (STRAIGHT) HOUSING, MEDIUM SPEED HIGH TORQUE POWER SECTION, RUGGED BEARING PACK, SAFETY CATCH FEATURES AND DUMP VALVE ASSEMBLY, DESIGNED FOR HIGH PERFORMANCE, EXTREME DOWNHOLE OPERATIONAL ENVIRONMENTS AND SUITABLE FOR CARRYING OUT SAND CLEANING, CEMENT CLEANING AND MILLING OF BRIDGE PLUG, PACKER, JUNK, ETC., INSIDE 5.1/2 INCHES OD (20 PPF) CASING, WITH ALL ACCESSORIES AS PER THE FOLLOWING SPECIFICATIONS:-	
	Note: Bidder to indicate Make & Model of the offered Mud Motor.	
	QUANTITY: 06 (SIX) NUMBERS.	
	B) PHYSICAL SPECIFICATIONS:	
	1) Motor OD: 3.1/2 inches (88.90 mm) 2) Lobe configuration (within): 5:6 to 7:8 3) Number of stages (within): 3.0 to 7.0 4) Overall Length (maximum): 29.5 feet (9.0 m) 5) Top connection (box): 2.7/8 inch API Regular RH 6) Bit box connection: 2.7/8 inch API Regular RH 7) Bit size range indicative (TCR & PDC): 4.1/8 inch to 5.7/8 inch / (105 mm to 149 mm) 8) Bearing type: Mud lubricated 9) Stator Elastomer: High Performance "Hard Rubber" 10) Dump valve: Removable Dump valve assembly with 2.7/8 inch API Reg RH (Box-up x Pin-down) connection 11) Housing: Slick (straight) type housing 12) Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor	
	<ul><li>C) OPERATIONAL SPECIFICATIONS:</li><li>1) Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to</li></ul>	
	946 lpm) 2) Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm 3) Operating Differential pressure at full load (minimum): 1000	
	psi / (70 kg/sq cm) 4) Operating Torque at full load (minimum): 1500 ft-1bs / (2034 N-m)	
	5) Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m) 6) Maximum Differential pressure at Peak/Stall torque	

(minimum): 1500 psi / (106 kg/sq cm) 7) Peak power output (minimum): 100 hp / (75 kw)

8) Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)

- 9) Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)
- 10) Working over-pull (minimum): 60,000 lbs / (30 ton)
- 11) Motor yield (minimum): 175,000 lbs / (87.5 ton)
- 12) Temperature rating (minimum): 248 deg F/ (120 deg C)
- 13) Working fluid:
- a) Salt solution: Sodium dichromate, cutch, common salt, CMC and 6000 ppm salt.
  - b) Drilling fluid: Water base mud and KCL / NaCl mud.
- D) ACCESSORIES:
- 1) Lifting sub compatible with 2.7/8" square shoulder elevator -
- 01 (one) number with each motor. Total-06(six) nos.
- 2) Spare dump valve assembly 01 (one) number with each motor. Total- 06 (six) nos.

&&&

#### **BB:: SPECIAL NOTES TOBIDDERS**

- 1. The items shall be brand new, unused & of prime quality. Bidder shall warrant (in the event of an order) that the product supplied will be free from all defects & fault in material, workmanship & manufacture and shall be in full conformity with ordered specifications. This clause shall be valid for 18 (eighteen) months from date of despatch/shipment or 12 (twelve) months from the date of commissioning whichever is earlier. The defective materials, if any, rejected by us shall be replaced by the supplier at their own expense. Bidders must confirm the same while quoting.
- 2. The Bidder should indicate the name of manufacturer, country of origin and port of dispatch of their offered Mud-Motors.
- 3. The Bidder must provide detailed specifications against all the tender parameters under physical and operational specification including the make and model of the offered Mud-Motor(s) and forward relevant Catalogue, Drawing, Literature and Performance curves (consisting of speed curve, torque curve and power curve with full-load/operating-limit line indicated therein) along with the quotation in support of their offer.
- 4. The threading and gauging of rotary shouldered connections of the offered Mud-Motors are to done as per **API Spec 7-1 (Latest edition)** and Bidder is required to forward a copy of valid API Spec. 7-1 certificate of the manufacturer/threader (depending on who does the threading & gauging) along with the supply in the event of an order. Bidder to confirm the same while quoting.
- 5. All parts of the Mud-Motor(s) should be suitably marked for identification purpose. Additionally, OIL purchase order number should be die stamped on the body of the Mud-Motors in the event of an order. Bidders shall confirm the same while quoting.
- 6. The Mud-Motor(s) should be suitably coated with a protective coating both internally and externally to prevent corrosion and rusting during transit. Bidders must confirm the same while quoting.

- 7. Bidder should forward a list of recommended spares for 02 (two) years operation for the quoted Mud-Motor(s) indicating part numbers, quantity & unit price separately along with the quotation in the commercial bid and categorically confirm the same in the technical bid (price should not be mentioned in the technical bid). The price should remain valid for at least 02 (two) years. However, the cost of these spares will not be considered for bid evaluation purpose.
- 8. Additionally, the Bidder shall submit an un-priced list of recommended spares for 02 (two) years operation against the quoted Mud-Motor(s), indicating year wise requirement, part numbers and quantity along with the technical bid.
- 9. All test certificates/ reports (including Dynamometer test reports consisting of speed curve, torque curve and power curve with full-load/operating-limit line indicated therein) of the supplied Mud-Motors should be submitted to OIL along with the supply. Bidder must confirm the same while quoting.
- 10. The Bidder should confirm to provide along with the supply, 06(six) sets of Operation, service and maintenance manual indicating assembling and disassembling procedures, drawing and spare parts list with part numbers against each size of the Mud Motors.
- 11. The Mud Motors along with the accessories are to be procured from the same source for compatibility of the items. Bidder shall quote accordingly.
- 12. Any deviation(s) from the tender specification should be clearly highlighted specifying justification in support of deviation.
- 13. Bidder shall submit the duly filled in and signed "Technical check list" and "Evaluation Sheet for BEC-Technical & Evaluation Sheet for Technical Specification" along with the technical bid.

\*\*\*\*

## CC:: GENERAL NOTES TO BIDDERS:

Sl No	Clause description
1.0	Tender fee is not applicable against this tender.
2.0	Submission of Bid Security/EMD/Performance Bank Guarantee – Must be paid either through online mode or Submission of Bank Guarantee/LC only. No DD/Cheques/Cashier Cheque or any other mode will be acceptable.
	The Bank Guarantee issued by the Bank must be routed through SFMS platform as per following details:  (i) MT 760 / MT 760 COV for issuance of Bank Guarantee  (ii) MT 760 / MT 767 COV for amendment of Bank Guarantee  The above message / intimation shall be sent through SFMS by the BG issuing Bank branch to HDFC Bank, Duliajan Branch, IFS Code – HDFC0002118; SWIFT Code - HDFCINBBCAL.
	Branch Address: HDFC Bank Limited, Duliajan Branch, Utopia Complex, BOC Gate, Jayanagar, Duliajan, Dibrugarh, PIN – 786602.
	b. The vendor shall submit to OIL the copy of the SFMS message as sent by the issuing bank branch along with the original bank guarantee.

- a) Bidders without having E-tender Login ID and Password should complete their online registration at least seven (7) days prior to the scheduled bid closing date and time of the tender. For online registration, Bidder may visit the OIL's E-tender site <a href="https://etender.srm.oilindia.in/irj/portal">https://etender.srm.oilindia.in/irj/portal</a>
  - b) Necessary Login ID & Password will be issued by OIL only after submitting the complete online registration by the Bidder. In the event of late registration/incomplete registration by Bidder, OIL INDIA LIMITED shall not be responsible for late allotment of User ID & Password and request for bid closing date extension on that plea shall not be entertained by Company.
  - c) MSEs Units (manufacturers/Service Providers only and not their dealers/distributors) who are already registered with District Industry Centers or Khadi & Village Industries Commission or Khadi & Village Industries Board or Coir Board or National Small Industries Corporation or Directorate of Handicrafts & Handloom or any other body specified by Ministry of MSME are exempted from payment of Bid Security (EMD) irrespective of monetary limit mentioned in their registration, provided they are registered for the item they intend to quote/participate.
  - d) For availing benefits under Public Procurement Policy (Purchase preference & EMD exemption), the interested MSE Bidders must ensure that they are the manufacturer/ service provider of tendered item(s) and registered with the appropriate authority for the said item(s). Bids without EMD shall be rejected, if the technical offer does not include a valid copy of relevant MSE Certificate issued by appropriate authority specifying the item as per tender. Therefore, it is in the interest of such MSE Vendors to furnish a copy of complete certificate to the concerned tender handling officer of OIL at least seven (7) days prior to the scheduled Bid Closing Date the tender; seeking of clarification/confirmation as to whether their registered item is eligible for EMD exemption or not. Late communication in this regard and request for bid closing date extension on that plea shall not be entertained by Company.
- 4.0 The tender will be governed by "General Terms & Conditions" for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders) including Amendments & Addendum to "General Terms & Conditions" for e-Procurement.
- 5.0 Bid must be submitted online through OIL's e-procurement portal. Bid submitted in any other form will be rejected.
- Please note that all tender forms and supporting documents are to be submitted through OIL's e-Procurement site only except following documents which are to be submitted manually in sealed envelope super scribing tender no. and due date to The DGM Materials, Materials Department, Oil India Limited, Duliajan-786602, Assam on or before 13:00 hrs (IST) on the Bid Closing Date mentioned in the Tender.
  - a) Original Bid Security along with two duplicate copies of Bid Security.
  - b) Any other documents which have been particularly asked for in this tender for submission.
- 7.0 Bidders must ensure that their bid is uploaded in the system before the tender closing date and time. Also, they must ensure that above documents which are to be submitted in a sealed envelope are also submitted at the above mentioned address before the bid closing date and time, failing which the offer shall be rejected.

The tender is invited under **SINGLE STAGE-TWO BID SYSTEM**. The bidder has to submit both the "**TECHNO-COMMERCIAL UNPRICED BID**" and "**PRICED BID**" through electronic form in the OIL's e-Tender portal within the Bid Closing Date and Time stipulated in the e-Tender. The "Techno-commercial Unpriced Bid" shall contain all technical and commercial details except the prices which shall be kept blank. Details of prices as per Bid format / Commercial bid to be uploaded as attachment in the Attachment Tab "Notes and Attachments". **Any offer not complying with above submission procedure will be rejected as per Bid Rejection Criteria mentioned in the tender.** 

Notes and Attachments → Only Price Details Should Be Uploaded

Technical attachments

→ All technical bid documents except price details

Please do refer "NEW INSTRUCTION TO BIDDER FOR SUBMISSION" for the above two points and also please refer "New Vendor Manual (effective from 12.04.2017)" available in the login Page of the OIL's E-tender Portal.



- 9.0 In Technical Bid opening, only Technical Rfx will be opened. Therefore, the bidder should ensure that "TECHNO-COMMERCIAL UNPRICED BID should contain details as mentioned in the technical specifications as well as BEC/BRC and upload the same in the Technical RFx Response-> User > Technical Bid. No price should begiven in above Technical Rfx otherwise the offer will be rejected. Please go through the help document in details before uploading the document and ensure uploading of technical bid in the Technical RFx Response-> User > Technical Bid only. The "PRICE BID" must contain the price schedule and the bidder's commercial terms and conditions. Details of prices as per Bid format / Commercial bid can be uploaded as Attachment under the attachment option under "Notes & Attachments".
- 10.0 PRICED BIDS OF ONLY THOSE BIDDERS WILL BE OPENED WHOSE OFFERS ARE FOUND TO BE TECHNO-COMMERCIALLY ACCEPTABLE.
- Bidders are requested to examine all instructions, forms, terms and specifications in the bid. Failure to furnish all information required as per the bid or submission of offers not substantially responsive to the bid in every respect will be at the bidders risk and may result in rejection of its offer without seeking any clarifications.

12.0	Please mention clearly in your quotation the Net. Weight, Gross Weight & Volume, Indian Agent's Name and its Commission, Payment Terms, Ocean Freight/Air Freight Charges, Port of Loading, Delivery period, Country of origin with manufacturer's name, etc.
13.0	To ascertain the substantial responsiveness of the bid, OIL reserves the right to ask the bidder for clarification in respect of clauses covered under BRC also and such clarifications fulfilling the BRC clauses in toto must be received on or before the deadline given by OIL, failing which the offer will be summarily rejected.
14.0	Other terms and conditions of the tender shall be as per "General Terms & Conditions" for e- Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders). However, if any of the Clauses of the Bid Rejection Criteria (BRC) / Bid Evaluation Criteria (BEC) mentioned here contradict the Clauses in the "General Terms & Conditions" for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders) of the tender and/or elsewhere, those mentioned in this BEC / BRC shall prevail.
15.0	All the Bids must be Digitally Signed using "Class 3" digital certificate (ecommerce application) only as per Indian IT Act obtained from the licensed Certifying Authorities operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India. The bid signed using other than "Class 3" digital certificate, will be liable for rejection.
16.0	Please do refer the User Manual provided on the portal on the procedure How to create Response for submitting offer.
17.0	Bidders to note that Govt. of India under Micro, Small and Medium Enterprises Development (MSMED) Act 2006, has proclaimed the Public Procurement Policy, 2012 with effect from 1st April, 2012 in respect of procurement of goods and services, produced and provided by micro and small enterprises, by its Ministries, Departments and Public Sector Undertakings for promotion and development of Micro and Small Enterprises. A new Clause on applicability of Public Procurement Policy for procurement of goods from Micro and Small Enterprises (MSE) in the tender is furnished vide Amendment to General Terms and Conditions for Global Tender (MM/GLOBAL/E-01/2005). Bidders are requested to take note of the same and to submit their offers accordingly.
18.0	The items shall be brand new, unused & of prime quality. The manufacturer shall warrant (in the event of an order) that the product supplied will be free from all defects & fault in material, workmanship & manufacture and shall be in full conformity with ordered specifications. This clause shall be valid for 18 months from date of shipment or 12 months from date of receipt at site, whichever is earlier. The defective materials, if any, rejected by OIL shall be replaced by the supplier at their own expense. Bidders must confirm the same in their quotations.
19.0	Quantity of Individual item may be increased or decrease at the time of final placement of order. The minimum FOB/FCA charges in case of partial order for reduced quantity/enhanced quantity shall have to be indicated by the bidder. In case, this is not indicated specifically, the charges quoted would be pro-rata calculated and the same will be binding on the bidder.
20.0	Any deviation(s) from the tender specification should be clearly highlighted specifying justification in support of deviation.

Original Bid Closing Date shall be considered by OIL for evaluation of BRC 21.0 Criteria in case of any extension of the original bid closing date. 22.0 Performance Security clause (Clause No. 10.0 of Section-A) of "General Terms & Conditions for Global Tenders (MM/GLOBAL/01/2005)" has been amended and the new clause is detailed in the Amendment dated 25.04.2016 issued to MM/GLOBAL/01/2005. Successful bidder will be required to furnish a Performance Bank Guarantee @10% of the order value. Bidders to note the same and to confirm its acceptance in their offers. The Bank Guarantee issued by the Bank must be routed through SFMS platform as per following details: MT 760 / MT 760 COV for issuance of Bank Guarantee (i) (ii) MT 760 / MT 767 COV for amendment of Bank Guarantee The above message / intimation shall be sent through SFMS by the BG issuing Bank branch to HDFC Bank, Duliajan Branch, IFS Code - HDFC0002118; SWIFT Code - HDFCINBBCAL. Branch Address: HDFC Bank Limited, Duliajan Branch, Utopia Complex, BOC Gate, Jayanagar, Duliajan, Dibrugarh, PIN – 786602. The vendor shall submit to OIL the copy of the SFMS message as sent by the issuing bank branch along with the original bank guarantee. 23.0 Bidder to sign and submit completely filled up Technical & Commercial check list and Technical Evaluation Matrix for Bid evaluation criteria and Technical specification failing which their offer will be rejected. Refer to "General Terms & Conditions" 24.0 Payment terms: Procurement as per Booklet No. MM/GLOBAL/E-01/2005 E-

procurement (ICB Tenders)

25.0 Liquidated Damage: Refer to "General Terms & Conditions" for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for procurement (ICB Tenders). The applicable GST on the Liquidated Damage shall have to be borne by the seller. Accordingly, the Liquidated Damage shall be recovered from the seller along with applicable GST. The items covered in this Tender shall be used by Oil India Limited in the 26.0 PEL/ML areas and hence Nil rate of Customs Duty towards import (for foreign bidders) and concessional GST @5% (for foreign & indigenous bidder) will be applicable as per Govt. Policy in vogue. Overseas Bidders are not required to include Customs Duty and IGST components in their quoted cost, since all applicable taxes & Duties in India shall be to the account of Oil India Limited. In the event of an order on indigenous bidder, OIL will issue Project Authority Certificate (PAC) under Deemed Export Benefit Scheme, where import content is declared by the bidder for availing Custom Duty benefit on the import content. Supplier shall arrange to provide all necessary documents (invoice etc.) to OIL for applying Essentiality Certificate on receipt of request from OIL, if any. Further, Suppliers shall affect dispatch only on receipt of relevant certificates/shipment clearance from OIL, failing which all related liabilities shall be to Supplier's account. 27.0 Bidders to note that Ministry of Petroleum & Natural Gas, Government of India implemented PPLC Policy to provide Purchase Preference (linked with local notification Ref. O-27011/44/2016-ONG-II/FP no. dtd.25.04.2017. Bidders are requested to take note of the same and to submit their offers accordingly wherever applicable. Policy details are available in APPENDIX-A2. In case of placement of order, OIL reserves the right to convert the order 28.1 from FOB Port of export to C&F Kolkata term considering the ocean freight quoted by the party in their offer. In case the order is converted to C&F Kolkata Port, the performance security amount shall also be enhanced considering the quoted ocean freight charges. 28.2 Bidder should confirm in their quotation that in case of C&F order, their nominated freight forwarder should provide Delivery Order under Single Window facility having office of local agent in India at Kolkata and offer 14 days free detention time of containers at discharging port. 28.3 Bidder should note that in case of C&F order for Tubulars, the same to be supplied in break bulk condition under deck and not through Container load. FURNISHING FRAUDULENT INFORMATION/ DOCUMENT: If it is found that 29.0 a Bidder has furnished fraudulent document/information, the Bid Security/Performance Security shall be forfeited and the party will be debarred for a period of 3(three) years from date of detection of such fraudulent act, besides the legal action. In case of major and serious fraud, period of debarment may be enhanced. In this regard, bidders are requested to submit an Undertaking as per Appendix-A3 along with their offer failing which their offer shall be liable for rejection.

#### 30.0 | Clauses related to GST

- 1. For the purposes of levy and imposition of GST, the expressions shall have the following meanings:
  - (a) GST means any tax imposed on the supply of goods and/or services under GST Law.
  - (b) Cess means any applicable cess, existing or future on the supply of Goods and Services as per Goods and Services Tax (Compensation to States) Act, 2017.
  - (c) GST Law means IGST Act 2017, CGST Act 2017, UTGST Act, 2017 and SGST Act, 2017 and all related ancillary Rules and Notifications issued in this regard from time to time.
- 2. The rates quoted by the bidders shall be inclusive of all taxes, duties and levies. However, bidders are required to provide separately the rate and amount of all types of taxes, duties and levies. In case, the quoted information related to various taxes, duties & levies subsequently proves wrong, incorrect or misleading, OIL will have no liability to reimburse the difference in the duty/ tax, if the finally assessed amount is on the higher side and OIL will have to right to recover the difference in case the rate of duty/ taxes finally assessed is on the lower side. Further, bidders have to clearly show the amount of GST separately in the Tax Invoices. Further, it is the responsibility of the bidders to make all possible efforts to make their accounting / IT system GST compliant in order to ensure availability of Input Tax Credit (ITC) to Oil India Ltd.
- 3. Offers without giving any of the details of the taxes (Including rates and amounts) as specified above will be considered as inclusive of all taxes including GST. When a bidder mentions taxes as extra without specifying the rates & amount, the offer will be loaded with maximum value towards taxes received against the tender for comparison purposes. If the bidder emerges as lowest bidder after such loading, in the event of order on that bidder, taxes mentioned by OIL on the Purchase Order/ Contracts will be binding on the bidder.
- 4. Bidders are required to pass on the benefit arising out of introduction of GST, including seamless flow of Input Tax Credit, reduction in Tax Rate on inputs as well as final goods by way of reduction of price as contemplated in the provision relating to Anti-Profiteering Measure vide Section 171 of the CGST Act, 2017. Accordingly, for supplies made under GST, the bidders should confirm that benefit of lower costs has been passed on to OIL by way of lower prices/taxes and also provide details of the same as applicable. OIL reserves the right to examine such details about costs of inputs/input services of the bidders to ensure that the intended benefits of GST have been passed on to OIL.
- 5. Oil India Ltd. shall declare the value of free issue of materials and services, if any, involved in the execution of the contract. The Contractor should consider the same while working out the GST liability, if any. Further in cases where GST is leviable on any facilities provided by OIL and used by bidders and the consideration for which is recovered by OIL in the form of reduction in the invoice raised by bidders then OIL will raise GST invoices on such transactions and the same will be reimbursed by bidders.

#### 6. When Input tax credit is available for Set Off

Evaluation of L-1 prices shall be done based on Quoted price after deduction of Input Tax Credit (ITC) of GST, if available to OIL.OIL shall evaluate the offers on the basis of the quoted rates only and any claim subsequently by the bidders for additional payment/liability shall not be admitted and has to be borne by the bidders

#### When Input tax credit is NOT available for Set Off

- Evaluation of L-1 prices shall be done based on Quoted price only. OIL shall evaluate the offers on the basis of the quoted rates only and any claim subsequently by the bidders for additional payment/liability shall not be admitted and has to be borne by the bidders
- 7. Bidders agree to do all things not limited to providing GST compliant Tax Invoices or other documentation as per GST law relating to the supply of goods and/or services covered in the instant contract like raising of and /or acceptance or rejection of credit notes / debit notes as the case may be, payment of taxes, timely filing of valid statutory Returns for the tax period on the Goods and Service Tax Network (GSTN), submission of general information as and when called for by OIL in the customized format shared by OIL in order to enable OIL to update its database etc. that may be necessary to match the invoices on GSTN common portal and enable OIL to claim input tax credit in relation to any GST payable under this Contract or in respect of any supply under this Contract.
- 8. In case Input Tax Credit of GST is denied or demand is recovered from OIL by the Central / State Authorities on account of any non-compliance by bidders, including non-payment of GST charged and recovered, the Vendor/Supplier/Contractor shall indemnify OIL in respect of all claims of tax, penalty and/or interest, loss, damages, costs, expenses and liability that may arise due to such non-compliance. OIL, at its discretion, may also withhold/recover such disputed amount from the pending payments of the bidders.
- 31.0 For convenience of the qualified Bidders and to improve transparency, the rates/costs quoted by bidders against OIL's e-tenders shall be available for online viewing by such Bidders whose price bids are opened by Company. A Bidder can view item-wise rates/costs of all other such peer bidders against the tender immediately after price bid opening, if the e-tender is floated by Company with PRICE CONDITION. In case the Price-Bid is invited by Company through attachment form under "Notes & Attachment" (i.e., NO PRICE Condition), Bidders must upload their detailed Price-Bid as per the prescribed format under "Notes & Attachment", in addition to filling up the "Total Bid Value" Tab taking into account the cost of all individual line items and other applicable charges like freight, tax, duties, levies etc. Under NO PRICE Condition (i.e., Price Bid in attachment form), the "Total Bid Value" as calculated & quoted by the Bidder shall only be shared amongst the eligible bidders and Company will not assume any responsibility whatsoever towards calculation errors/omissions therein, if any. Notwithstanding to sharing the "Total Bid Value" or the same is whether filled up by the Bidder or not, Company will evaluate the cost details to ascertain the inter-se-ranking of bidders strictly as per the uploaded attachment and Bid Evaluation Criteria only. Online view of prices as above shall be available to the Bidders only upto seven days from the date of Price-Bid opening of the e-tender.

#### 32.0 OPPORTUNITY TO STARTUP AND MICRO & SMALL ENTERPRISES

In case a Startup [defined as per Ministry of Commerce and Industry (Department of Industrial Policy and Promotion, DIPP) latest notification]/ MSE is interested in supplying the tendered item but does not meet the Pre-Qualifying Criteria (PQC)/ Proven Track Record (PTR) indicated in the tender document, the Startup/MSE is requested to write a detailed proposal separately, and not against the present tender requirement, to the tender issuing authority about its product. Such proposals shall be accompanied by relevant documents in support of MSE (where applicable) or in case of Startup, following documents shall be given:

- 1. Certificate of Recognition issued by the Department of Industrial Policy and Promotion, Ministry of Commerce and Industry, Government of India.
- 2. Certificate of incorporation.
- 3. Audited Profit & Loss (P&L) Statement of all the Financial Years since incorporation. In case where the Balance sheet has not been prepared, bidder shall submit a certificate in original from its CEO/CFO stating the turnover of the bidding entity separately for each Financial Years since incorporation along with a declaration stating the reason for not furnishing the audited P&L Statement. This certificate shall be endorsed by a Chartered Accountant/Statutory Auditor.

The Proposal shall be examined by OIL and OIL may consider inviting a detailed offer from the Startup/MSE with the intent to place a TRIAL or TEST Order, provided the Startup/MSE meets the Quality and Technical Specifications.

In case the Startup/MSE is successful in the Trial Order, the vendor shall be considered for PQC exemption/relaxation (as the case may be) for the next tender for such item till the time it remains a Startup/MSE.

The Integrity Pact is applicable against this tender .OIL shall be entering into an Integrity Pact with the bidders as per format enclosed vide Annexure -XII of the tender document. This Integrity Pact proforma has been duly signed digitally by OIL's competent signatory. The proforma has to be returned by the bidder (along with the technical bid) duly signed (digitally) by the same signatory who signed the bid, i.e., who is duly authorized to sign the bid. Uploading the Integrity Pact with digital signature will be construed that all pages of the Integrity Pact has been signed by the bidder's authorized signatory who sign the Bid. If any bidder refuses to sign Integrity Pact or declines to submit Integrity Pact with the offer, their bid shall be rejected straightway.

OIL's Independent External Monitors at present are as under:

SHRI RAJIV MATHUR, IPS (Retd.), Former Director (IB) Govt. of India e-Mail ID: rajivmathur23@gmail.com

SHRI JAGMOHAN GARG, Ex-Vigilance Commissioner, CVC e-Mail id: jagmohan.garg@gmail.com

Shri RUDHRA GANGADHARAN, IAS (Retd.), Ex-Secretary, Ministry of Agriculture (e-mail id : rudhra.gangadharan@gmail.com)

## Appendix -A3

Format of undertaking by Bidders towards submission of authentic information/documents (To be typed on the letter head of the bidder)

Ref. No	Date
Sub: Undertaking of authenticity of information/doc	uments submitted
Ref: Your tender No Dated	
To, The HOD-Materials Materials Deptt, OIL, Duliajan	
Sir,	
With reference to our quotation against your above-reference that no fraudulent information/documents have been sub-	
We take full responsibility for the submission of authentihe above cited bid.	tic information/documents against
We also agree that, during any stage of the tender/contra information/documents submitted by us are found to be right to reject our bid at any stage including forfeiture of cancel the award of contract and/or carry out any other p	false/forged/fraudulent, OIL has four EMD and/or PBG and/or
Yours faithfully, For (type name of the firm here)	
Signature of Authorised Signatory	
Name:	
Designation:	
Phone No.	
Place:	
Date:	
(Affix Seal of the Organization here, if applicable.	

#### BID REJECTION CRITERIA (BRC) / BID EVALUATION CRITERIA (BEC)

## I. BID REJECTION CRITERIA (BRC)

#### A. TECHNICAL

The bids shall conform generally to the specifications and terms as well as conditions laid out in this tender. Bids will be rejected in case the items offered do not conform to the required parameters stipulated in the technical specifications and to the respective international/national standards wherever stipulated. Notwithstanding the general conformity of the bids to the stipulated specifications and terms and conditions, the following requirements will have to be met by the bids, without which, the same shall be considered as non-responsive and stand rejected.

#### 1.0 IN CASE THE BIDDER IS THE MANUFACTURER:

1.1 The Bidder must have the experience of supplying at least 03 (three) numbers of MUD MOTORS of 3.1/2 inches (88.90 mm) OD or higher size, in the last 05 (five) years preceding the original bid closing date of this tender, to E&P companies/ Drilling Contractors/ Drilling Service providers which are in the business of Oil & Gas.

Documentary evidence in respect of the above should be submitted in the form of copies of relevant Purchase Orders along-with copies of any of the following documents in respect of satisfactory execution of each of those purchase orders, such as:

- I. Signed and sealed Satisfactory supply / completion / installation report (in original on user's letter head) (OR)
- II. Bill of Lading (OR)
- III. Consignee receipted delivery receipt/ challan (OR)
- IV. Central Excise Gate Pass/Tax Invoice issued under relevant rules of Central Excise/Vat. (OR)
- V. Commercial Invoice/ Payment Invoice

Note: The Purchase Order date(s) and Supply Completion date(s) have to be within the last 05(five) years preceding the original bid closing date of this tender.

1.2 Those Manufacturers who have successfully supplied at least 03 (three) numbers of Mud Motors of 3.1/2 inches (88.90 mm) OD or higher size, to OIL INDIA LTD. (OIL) in the last 05 (five) years preceding the original bid closing date of this tender and the performance of which are found to be satisfactory, shall be considered to qualify the experience criteria as stated in the Clause 1.1 above, provided, they indicate in the bid itself, the Purchase Order No(s). & Date(s), Quantity, Details of Mud Motor(s) supplied to OIL in the past.

**Note:** The Purchase Order date need not be within the last 05(five) years, preceding the original bid closing date of this tender. However, the execution of supply should be within the last 05(five) years preceding the original bid closing date of this tender.

- 1.3 The Bidder quoted as Manufacturer should confirm that, the threading and gauging of the rotary shouldered connections of the offered Mud Motors will be done as per API Spec.7-1 [latest edition].
- 1.4 The Bidder quoted as manufacturer should forward along with the technical bid, a copy of API Spec 7-1 certificate for threading and gauging of rotary shouldered connections, valid as on original bid closing date of this tender, from the concerned party as per below:

i) From the Manufacturer, if threading and gauging of the rotary shouldered connections will be carried out by the Manufacturer themself.

OR

- ii) From the API approved Threader, if threading and gauging of the rotary shouldered connections will be carried out through an API approved Threader.
- 1.5 The Bidder quoted as manufacturer, should furnish an undertaking that, the API Spec 7-1 license for threading and gauging of rotary shouldered connections will be kept valid till execution of the purchase order, from the concerned party as per below:
  - i) From the Manufacturer, if threading and gauging of the rotary shouldered connections will be carried out by the Manufacturer themself.

OR

ii) From the API approved Threader, if threading and gauging of the rotary shouldered connections will be carried out through an API approved Threader.

#### 2.0 IN CASE THE BIDDER IS NOT A MANUFACTURER:

In case the Bidder is a sole selling agent/distributor/dealer/supply house of any Manufacturer of the offered item(s), then Bidder must furnish the following documents along with the technical bid failing which the bids will be rejected:

- 2.1 Authorization certificate from the manufacturer (in original on manufacturer's letter head) should be submitted along with the technical bid. This certificate should be valid at the time of bidding and should remain valid during the entire execution period of the order.
- 2.2 Warranty backup from the manufacturer (in original on manufacturer's letter head) against the quality of the tendered item(s) as specified in the tender.
- 2.3 Undertaking from the manufacturer (in original on manufacturer's letter head) guaranteeing supply of items to the bidder in the event of an order on the bidder. This certificate should be valid at the time of bidding and should remain valid during the entire execution period of the order.
- 2.4 The Bidder is required to submit documentary evidences along with the technocommercial bid from the concerned Manufacturer, in respect of the Manufacturer's past supply experience as per clause 1.1 or 1.2 above (as applicable), having supplied such items either by the Manufacturer themself or through their distributor.
- 2.5 The Bidder should submit confirmation from the Manufacturer that the threading and gauging of the rotary shouldered connections of the offered Mud Motors will be as per API Spec.7-1 [latest edition].
- 2.6 The bidder should forward along with the technical bid, a copy of API Spec 7-1 certificate for threading and gauging of rotary shouldered connections, valid as on original bid closing date of this tender, from the concerned party as per below:
  - i) From the Manufacturer, if threading and gauging of the rotary shouldered connections will be carried out by the Manufacturer themself.

- ii) From the API approved Threader, if threading and gauging of the rotary shouldered connections will be carried out through an API approved Threader.
- 2.7 The Bidder should furnish an undertaking that, the API license for threading and gauging of the rotary shouldered connections will be kept valid till execution of purchase order, from the concerned party as per below:
  - i) From the Manufacturer, if threading and gauging of the rotary shouldered connections will be carried out by the Manufacturer themself.

 $\cap R$ 

- ii) From the API approved Threader, if threading and gauging of the rotary shouldered connections will be carried out through an API approved Threader.
- 2.8 Additionally, the Bidder should also have the experience of supplying at least 03(three) numbers of Mud Motors of 3.1/2 inches (88.90 mm) OD or higher size, in the last 05(five) years preceding the original bid closing date of this tender, to E&P companies/ Drilling Contractors/ Drilling Service providers which are in the business of Oil & Gas.

Documentary evidence in respect of the above should be submitted in the form of copies of relevant Purchase Orders along-with copies of any of the following documents in respect of satisfactory execution of each of those purchase orders, such as:

- I. Signed and sealed Satisfactory supply / completion / installation report (in original on user's letter head) (OR)
- II. Bill of Lading (OR)
- III. Consignee receipted delivery receipt/ challan (OR)
- IV. Central Excise Gate Pass/Tax Invoice issued under relevant rules of Central Excise/Vat. (OR)
- V. Commercial Invoice/ Payment Invoice

Note: The Purchase Order date(s) and Supply Completion date(s) have to be within the last 05(five) years preceding the original bid closing date of this tender.

#### 3.0 DELIVERY CRITERIA:

Bidder should categorically confirm in the technical bid a delivery schedule within **O6(six) months**, FOB Port of dispatch, after establishment of letter of credit (in case of foreign Bidder) or for dispatch of the equipment within **O6(six) months** after receipt of formal order (in case of indigenous Bidder) failing which their offer will be rejected.

#### A) FINANCIAL CRITERIA:

- **1.0 Annual Turnover**: The bidder shall have an annual financial turnover of minimum **US\$ 143,210.00** or **Rs. 1,02,91,050.00 Lakhs** during any of the preceding 03 (three) financial years reckoned from the original bid closing date, irrespective of whether their bid is for all the tendered items or not.
- 2.0 "Net Worth" of the bidder should be positive for the financial/accounting year just preceding to the original bid closing date of the tender (i.e., Year 2018-19).
- **3.0** Considering the time required for preparation of Financial Statements, if the last date of preceding financial / accounting year falls within the preceding six months reckoned from the original bid closing date and the Financial Statements of the preceding financial / accounting year are not available with the bidder, then the financial turnover of the

previous three financial / accounting years excluding the preceding financial / accounting year will be considered. In such cases, the Net worth of the previous financial / accounting year excluding the preceding financial / accounting year will be considered. However, the bidder has to submit an affidavit/undertaking certifying that 'the balance sheet/Financial Statements for the financial year (i.e., Year 2018-19) has actually not been audited so far'.

#### Note:

- a) For proof of Annual Turnover & Net worth any one of the following document must be submitted along with the bid:
  - i) A certificate issued by a practicing Chartered/Cost Accountant (with Membership Number and Firm Registration Number), certifying the Annual turnover & Net worth as per format prescribed in ANNEXURE.

OR

- ii) Audited Balance Sheet along with Profit & Loss account. In case of Foreign bidders, self-attested/digitally signed printed published accounts are also acceptable
- b) In case the bidder is a Central Govt. Organization/PSU/State Govt. Organization/Semi-State Govt. Organization or any other Central/State Govt. Undertaking, where the auditor is appointed only after the approval of Comptroller and Auditor General of India and the Central Government, their certificates may be accepted even though FRN is not available. However, bidder to provide documentary evidence for the same.
- 4.0 In case the Audited Balance Sheet and Profit & Loss Account submitted along with the bid are in currencies other than INR or US\$, the bidder shall have to convert the figures in equivalent INR or US\$ considering the prevailing conversion rate on the date of Balance Sheet and Profit & Loss Account. A CA certificate is to be submitted by the bidder regarding converted figures in equivalent INR or US\$

#### B) **COMMERCIAL**

Commercial Bid Rejection Criteria will be as per Section D of General Terms & Conditions of Global Tender (MM/GLOBAL/E-01/2005) with following Special Bid Rejection Criteria.

- 1.0 Bids are invited under **Single Stage Two Bid System**. Bidders shall quote accordingly under Single Stage Two Bid System. **Please note that no price details should be furnished in the Technical (i.e. Unpriced) bid**. The "Unpriced Bid" shall contain all techno-commercial details except the prices, which shall be kept blank. The "Price Bid" must contain the price schedule and the bidder's commercial terms and conditions. Bidder not complying with above submission procedure will be rejected.
- **2.0** The prices offered shall have to be firm through delivery and not subject to variation on any account. A bid submitted with an adjustable price will be treated as non-responsive and rejected. No discount whatsoever should be quoted separately. Rates/prices quoted must be net of all discount.
- 3.0 Bids received in physical form against online invitation through e-portal shall be rejected (except the documents specifically called for in hard copies, if any). Similarly, Bids received after the bid closing date and time shall be rejected. Also, modifications to bids received after the bid closing date & time shall not be considered.

- **4.0** Bids containing incorrect statement shall be rejected.
- **5.0** Validity of the bid shall be **minimum 120 days** from the date of actual Bid Closing Date. Bids with lesser validity will be straightway rejected.
- **6.0 Bid Security in ORIGINAL** shall be furnished by the Bidder as a part of their Bid. The amount of Bid Security & its validity shall be specified in the covering letter of this bid document. **Any bid not accompanied by a proper bid security in ORIGINAL shall be rejected without any further consideration.** A bid shall be rejected straightway if Original Bid Security is not received within the stipulated date & time mentioned in the Tender and/or if the Bid Security validity is shorter than the validity indicated in Tender and/or if the Bid Security amount is lesser than the amount indicated in the Tender.
- **6.1** For exemption for submission of Bid Security please refer Clause No. 9.8 (Section A) of "General Terms & Conditions" for e-Procurement as per Booklet No. MM/GLOBAL/E-01/2005 for E-procurement (ICB Tenders).
- **7.0** Bidders must confirm that Goods, materials or plant(s) to be supplied shall be new of recent make and of the best quality and workmanship and shall be guaranteed for a period of twelve (12) months from the date of commissioning of the items at site, against any defects arising from faulty materials, workmanship or design. Defective goods/materials or parts rejected by OIL shall be replaced immediately by the supplier at the supplier's expenses at no extra cost to OIL.
- **8.0** Successful bidder shall be required to furnish a Performance Security equivalent to ten (10%) of total evaluated value of Order, which should remain valid throughout the period execution, including extension, if any. The successful bidder shall submit Performance Security within 30 days of award, failing which OIL reserves the right to cancel the order and forfeit their Bid Security. Bidders should undertake in their bids to submit Performance Security as stated above.
- **9.0** Offers should be submitted along with Integrity Pact duly signed by the authorized signatory of the bidder. If any bidder refuses to sign Integrity Pact or declined to submit Integrity Pact with the offer, their bid shall be rejected straightway.
- **10.0** Bidder shall accept and comply with the following clauses as given in the Bid Document, failing which bid shall be liable for rejection:
  - i) Liquidated Damages
  - ii) Warranty/Guarantee of material
  - iii) Arbitration / Resolution of Dispute
  - iv) Force Majeure
  - v) Applicable Laws
- **11.0** A bid shall be rejected straightway if it does not conform to any one of the following clauses:
  - a) Validity of bid shorter than the validity indicated in the Tender.

- b) Original Bid Security not received within the stipulated date & time mentioned in the Tender.
- c) Bid Security with (i) validity shorter than the validity indicated in Tender and/or (ii) Bid Security amount lesser than the amount indicated in the Tender.
- **12.0** Bidder must quote for all items and services being sought for in the tender, failing which the bid shall be treated as incomplete and rejected.
- **13.0** Bidders are required to submit the summary of the prices in their price bids as per bid format (Summary), given below:

## (i) Price Bid Format (SUMMARY) for Foreign Bidders:

Name of Bidder: Currency		
Sl. No	Particulars	Price
		quoted
A	Total Material Cost for item No. 10, Quantity: 06 Nos.	
В	Packing & FOB Charges	
С	Total FOB Port of Shipment Value, A+B	
D	Ocean Freight Charges upto Kolkata, India	
E	Insurance Charges @0.5% of C	
F	Banking Charges @1% of C in case of payment through	
	LC (if confirmed LC at buyer's account is required, 2% of	
	D will be loaded)	
G	Total CIF Kolkata Value, C+D+E+F	
Н	IGST @5% of G	
I	Total CIF+GST Kolkata Value, G+H	
J	Total Value in words:	
K	Tentative Gross Weight	
L	Tentative Dimensions	
M	Name of Manufacturer	
N	Port of Despatch	
О	Country of Origin	

## (ii) Price Bid Format (SUMMARY) for Indigenous Bidders:

Name o	f Bidder: Curr	rency:
Sl. No	Particulars	Price
		quoted
A	Total Material Cost for item No. 10, Quantity: 06 Nos.	
В	Packing & Forwarding Charges	
C	Total Ex-Works Value, A+B	
D	GST@5% of C against Essentiality Certificate	
E	FOR Despatching Station Value, C+D	
F	Freight charges upto Duliajan including GST	
G	Insurance charges @0.5% on (E) including GST	
Н	Total FOR Duliajan Value, E+F+G	
I	Total Value in words:	
J	Import Content, if any	
K	Tentative Gross Weight	
L	Tentative Dimensions	
M	Name of Manufacturer	

N	Place of Despatch	
О	Country of Origin	

#### II. BID EVALUATION CRITERIA (BEC)

The bids conforming to the specifications, terms and conditions stipulated in the tender and considered to be responsive after subjecting to the Bid Rejection Criteria shall be considered for further evaluation as per General Terms and Conditions for Global Tender and the Bid Evaluation Criteria given below:

- 1.0 The evaluation of bids shall be done as per the Price Bid Format (SUMMARY) provided in the Tender.
- 2.0 If there is any discrepancy between the unit price and the total price, the unit price will prevail and the total price shall be corrected. Similarly, if there is any discrepancy between words and figure, the amounts in words shall prevail and will be adopted for evaluation.
- 3.0 For conversion of foreign currency into Indian currency, B.C. selling (Market) rate declared by State Bank of India, one day prior to the date of price bid opening shall be considered. However, if the time lag between the opening of the bids and final decision exceed 3(three) months, then B.C. Selling(Market) rate of exchange declared by SBI on the date prior to the date of final decision shall be adopted for conversion and evaluation.
- 4.0 To ascertain the inter-se-ranking, bid prices shall be converted into Indian Rupees and the comparison of the responsive bids shall be made as under, subject to corrections / adjustments given herein.
  - <u>Note:</u> 1) Domestic Bidders must quote inland freight charges upto Duliajan. In case bidder fails to quote inland freight charges, highest freight quoted by domestic bidder (considering pro-rata distance) against this tender or OIL's estimated freight, whichever is higher, shall be loaded to their offer for comparison purpose.
  - 2) For enquiries with duty exemption benefit The items covered under this enquiry shall be used by OIL in the PEL/ML areas issued/renewed after 01/04/99 and hence, applicable customs duty for import of goods shall be zero. However, IGST @5% shall be applicable. Indigenous bidder shall be eligible for concessional rate of GST @5% against Essentiality Certificate for invoice valuing 01 lakh and above.

#### 4.1 When only foreign bidders are involved:

For evaluation of each individual items, Total value as per para **C. 13.0 (i) I** will be compared.

NOTE: \*Banking charge in the country of the foreign bidder shall be borne by the bidder. Banking charge 1% for payment through Letter of Credit. And 1.5 % if confirmed LC at buyer's account is required.

# 4.2 When only domestic bidders are involved or when more than one domestic bidders are in contention in case of mixed response:

For evaluation of each individual items, Total value as per para **C. 13.0 (ii) H** will be compared.

#### 4.3 When both foreign and domestic bidders are involved:

For evaluation of each individual items, Total value as per para <u>C. 13.0 (i) L of Foreign Bidders</u> will be compared with Total value as per para <u>C. 13.0 (ii) H (excluding F & G)</u> of Domestic Bidders.

Note: If the Government of India revises these evaluation criteria the same as applicable on the bid closing date will be adopted for evaluation of the offers.

5.0 Other terms and conditions of the enquiry shall be as per General Terms and Conditions for Global Tender. However, if any of the Clauses of the Bid Rejection Criteria / Bid Evaluation Criteria (BEC / BRC) mentioned here contradict the Clauses in the General Terms & Conditions of Global Tender of the tender and/or elsewhere, those mentioned in this BEC / BRC shall prevail.

#### A) COMMERCIAL CHECKLIST:

THE CHECK LIST MUST BE COMPLETED AND RETURNED WITH YOUR OFFER. PLEASE ENSURE THAT ALL THESE POINTS ARE COVERED IN YOUR OFFER. THESE WILL ENSURE THAT YOUR OFFER IS PROPERLY EVALUATED. PLEASE SELECT "Yes" OR "No" TO THE FOLLOWING QUESTIONS, IN THE RIGHT HAND COLUMN.

S1#	REQUIREMENT	COMPLIANCE
1.0	Whether bid submitted under Single Stage Two Bid System?	Yes / No
2.0	Whether quoted as manufacturer?	Yes / No
2.1	Whether quoted as OEM Dealer / Supply House. To Specify-	Yes / No
2.2	If quoted as OEM Dealer / Supply House	Yes / No
	(a) Whether submitted valid and proper authorization letter from manufacturer confirming that bidder is their authorized Dealer / supply House for the product offered?	
	(b) Whether manufacturer's back-up Warranty/Guarantee certificate submitted?	
3.0	Whether ORIGINAL Bid Bond (not copy of Bid Bond) as per Revised Format(Annexure VII Revised) Sent separately? If YES, provide details (a) Amount:	Yes / No
	(b) Name of issuing Bank :	
	(c) Validity of Bid Bond :	
4.0	Whether offered firm prices ?	Yes / No
4.1	Whether quoted offer <b>validity of 120 days from</b> the bid closing date of tender?	Yes / No
4.2	Whether quoted a firm delivery period?	Yes / No
4.3	Whether agreed to the NIT Warranty clause?	Yes / No
4.4	Whether confirmed acceptance of NIT Payment Terms	Yes / No
5.0	Whether confirmed to submit PBG as asked for in NIT?	Yes / No
5.1	Whether agreed to submit PBG within 30 days of placement of order?	Yes / No
6.0	Whether Price submitted as per Price Schedule?	Yes / No
7.0	Whether quoted as per NIT (without any deviations)?	Yes / No
7.0	Whether quoted any deviation?	Yes / No
7.1	Whether deviation separately highlighted?	Yes / No
8.0	Whether indicated the country of origin for the items quoted?	Yes / No
8.1	Whether technical literature / catalogue enclosed?	Yes / No
8.2	Whether weight & volume of items offered indicated?	Yes / No
9.0	For Foreign Bidders - Whether offered FOB / FCA port of despatch including sea / air worthy packing & forwarding?	Yes / No
9.1	For Foreign Bidders – Whether port of shipment indicated. To specify:	Yes / No
9.2	For Foreign Bidders only - Whether indicated ocean freight up to Kolkata port (Excluding marine insurance ) ?	Yes / No
9.3	Whether Indian Agent applicable ?	Yes / No
	If YES, whether following details of Indian Agent provided?	

	(a) Name & address of the agent in India – To indicate	
	(b) Amount of agency commission – To indicate	
	(c) Whether agency commission included in quoted material value?	
10.0	For Indian Bidders – Whether indicated the place from where the goods will be dispatched. To specify:	Yes / No
10.1	For Indian Bidders – Whether road transportation charges up to Duliajan quoted?	Yes / No
10.2	For Indian Bidders only - Whether offered Ex-works price including packing/forwarding charges?	Yes / No
10.3	For Indian Bidders only - Whether indicated import content in the offer?	Yes / No
10.4	For Indian Bidders only - Whether offered Deemed Export prices?	Yes / No
10.5	For Indian Bidders only – Whether all applicable Taxes & Duties have been quoted?	Yes / No
11.0	Whether all BRC/BEC clauses accepted?	Yes / No
12.0	Whether Integrity Pact with digital signature uploaded?	Yes / No
12.1	Whether all the clauses in the Integrity Pact have been accepted?	Yes / No

## $\underline{\mathbf{B}}$ ) TO BE FILLED UP IN DETAIL:

Requirement	Bidder's Reply
•	
Name of Manufacturer	
Bid validity	
Payment Terms	
Guarantee/Warranty Terms	
Delivery Period	
Port of Despatch / Despatching Station	
Confirm submission Integrity pact, if required	
as per NIT	
Confirm submission PBG, if required as per	
•	
,	
•	
the bid documents	
	Bid validity Payment Terms Guarantee/Warranty Terms Delivery Period Port of Despatch / Despatching Station Confirm submission Integrity pact, if required as per NIT Confirm submission PBG, if required as per NIT Compliance to: Liquidated Damage Warranty/Guarantee Arbitration/Resolution of Dispute Force Majeure Applicable laws Confirm submission of the balance sheet/Financial Statements for the financial year 2018-19. If not, whether declaration as per BRC submitted. Exception/Deviations quoted, if any, to be given in details or refer to respective page of

## TECHNICAL CKECKLIST FOR 3.1/2 INCHES (88.90 MM) OD DOWNHOLE MUD MOTOR

S1. No.	Technical Parameters	Bidder's Response	Bidder's Specification (wherever
			applicable)
1	Whether the Make & Model of the offered MUD Motor has been indicated?	Yes/ No	,
2	Whether the OD of offered MUD MOTOR is 3.1/2 inch (88.90 mm)?	Yes/ No	
3	Whether the length of the offered MUD MOTOR is within 29.5 ft (9.0m)?	Yes/ No	
4	Whether the housing of the offered MUD MOTOR is a SLICK (Straight) housing?	Yes/ No	
5	Whether the offered MUD MOTOR is complete with removable Dump Valve assembly?	Yes/ No	
6	Whether the offered MUD MOTOR is complete with Rotor safety catch system?	Yes/ No	
7	Whether the offered MUD MOTOR is suitable for operation inside 5.1/2 inch (139.70MM) x 20 PPF casing?	Yes/ No	
8	Whether the Bearing package is Mud lubricated?	Yes/ No	
9	Whether the type of Stator Elastomer is High Performance "Hard Rubber"?	Yes/ No	
10	Whether the Bit size range is 4.1/8 inch to 5.7/8 inch / (105 mm to 149 mm)?	Yes/ No	
11	Whether the Lobe configuration is within 5:6 to 7:8?	Yes/ No	
12	Whether the no of Stages is within 3.0 to 7.0?	Yes/ No	
13	Whether the indicative flow rate range is 45 gpm to 250 gpm/ (170 lpm to 946 lpm)?	Yes/ No	
14	Whether the indicative operating bit speed range at full load is (65 to 350) RPM?	Yes/ No	
15	Whether the Operating Differential pressure at full load is more than or equal to 1000 psi (70 kg/sq cm)?	Yes/ No	
16	Whether the Operating Torque at full load is more than or equal to 1500 ft-lbs (2034 N-m) at minimum 1000 psi (70 kg/sq cm) or more differential pressure?	Yes/ No	
17	Whether the Peak/Stall torque is more than or equal to 2000 ft-lbs / (2712 N-m)?	Yes/ No	
18	Whether the maximum Differential pressure at Peak/Stall torque is more than or equal to 1500 psi / (106 kg/sq cm)?	Yes/ No	
19	Whether the peak power output is more than or equal to 100 hp (75 kw)?	Yes/ No	
20	Whether the Dynamic weight on bit is more than or equal to 8,500 lbs / (4.3 ton)?	Yes/ No	
21	Whether the maximum weight on bit is more than or equal to 13,500 lbs / (6.8 ton)?	Yes/ No	
22	Whether the Working over-pull is more than or equal to 60,000 lbs / (30 ton)	Yes/ No	
23	Whether the Motor yield is more than or equal to 175,000 lbs / (87.5 ton)?	Yes/ No	
24	Whether the Temperature rating is more than or equal to 248 deg F/ (120 deg C)?	Yes/ No	
25	Whether the offered MUD MOTOR is suitable for operation with the drilling and work-over fluids as mentioned in this tender?	Yes/ No	
26	Whether threading and gauging of the rotary shouldered connection of the offered MUD MOTOR will be done as per	Yes/ No	

	API Spec.7-1 [latest edition]?		
27	Whether the top connection of offered MUD MOTOR is	Yes/ No	
	2.7/8 inch API Regular RH Box-up?	,	
28	Whether the bit box connection of offered MUD MOTOR is	Yes/ No	
	2.7/8 inch API Regular RH Box-down?		
29	Whether the dump valve assembly connections of the	Yes/ No	
	offered MUD MOTOR are 2.7/8 inch API Regular RH Box-		
	up and Pin-down?		
30	Whether detailed technical catalogue and literature of the	Yes/ No	
	offered MUD MOTOR along with the three performance		
	curves of the offered mud motor(s) consisting of speed		
	curve, torque curve and power curve with full-		
	load/operating-limit line indicated therein, forwarded with		
2.1	the technical bid? Whether the offered MUD MOTOR shall be furnished with	Yes/ No	
31	elevator sub for lifting purpose & suitable for use with	res/ No	
	square shouldered 2.7/8 inch OD drill pipe elevator?		
32	Whether the offered MUD MOTOR shall be furnished with	Yes/ No	
02	spare Dump valve assembly?	165/ 110	
33	Whether list of recommended spare parts for two (02)	Yes/ No	
	years trouble free operation with unit price and part		
	numbers indicating with year wise consumption pattern		
	forwarded separately along with the commercial against		
	the offered MUD MOTOR?		
34	Whether un-priced list of recommended spare parts for	Yes/ No	
	two (02) years trouble free operation with part numbers		
	indicating year wise consumption pattern forwarded along		
	with the technical bid against the offered MUD MOTOR?		
35	Whether quoted as manufacturer?	Yes/ No	
36	Whether the name of manufacturer, country of origin and	Yes/ No	
	port of shipment has been mentioned?		
37	Whether the "Matrix for Technical Evaluation Sheet" has	Yes/No	
	been duly filled in and signed?		

Signature	_ Name	
	_ Designation	

## CERTIFICATE OF ANNUAL TURNOVER & NET WORTH

TO BE ISSUED BY PRALETTER HEAD	ACTISING <b>CHARTARD ACCOUN</b>	TANTS' FIRM ON THEIR
	TO WHOM IT MAY CONCE	RN
financial statements o	the following financial position f M/scompleted accounting years uptect	(Name of the bidder)
YEAR	TURN OVER	NET WORTH
	In INR (Rs.) Crores/ US \$ Million) *	In INR (Rs.) Crores / US \$ Million ) *
*Rate o	f conversion (if used any): USD 1	.00 = INR
Place: Date:		
Seal		
Membership No: Registration Code:		
Signature		

<sup>\*</sup>Applicable only for GLOBAL tenders

# EVALUATION MATRIX FOR TECHNICAL SPECIFICATION (TO BE FILLED IN BY BIDDER DULY SIGNED)

## TECHNICAL SPECIFICATION FOR 3.1/2 INCHES (88.90MM) OD MUD MOTOR

	TECHNICAL SPECIFICATION FOR 3.1/2 INCHES (88.90MM) OD MOTOR			
Clause Number	DESCRIPTION	BIDDER'S RESPONSE (Complied / Not Complied / Deviation / Not Applicable)	TO BE FILLED BY THE BIDDER  (Relevant Location of their Bid to support the remarks / compliance) OR  (Reference of Document name / Serial number / Page number of bid for documentary evidence) OR  (Bidder's Quoted specification of the item wherever applicable)	
A	3.1/2 INCHES (88.90 MM) OD DOWN HOLE MUD MOTOR WITH SLICK (STRAIGHT) HOUSING, MEDIUM SPEED HIGH TORQUE POWER SECTION, RUGGED BEARING PACK, SAFETY CATCH FEATURES AND DUMP VALVE ASSEMBLY, DESIGNED FOR HIGH PERFORMANCE, EXTREME DOWNHOLE OPERATIONAL ENVIRONMENTS AND SUITABLE FOR CARRYING OUT SAND CLEANING, CEMENT CLEANING AND MILLING OF BRIDGE PLUG, PACKER, JUNK, ETC., INSIDE 5.1/2 INCHES OD (20 PPF) CASING, WITH ALL ACCESSORIES AS PER THE FOLLOWING SPECIFICATIONS:-  Note: Bidder to indicate Make & Model of the offered Mud Motor.  Quantity: 06 (Six) Nos			
В	PHYSICAL SPECIFICATIONS:			
1	Motor OD: 3.1/2 inches (88.90 mm)			
2	Lobe configuration (within): 5:6 to 7:8			
3	Number of stages (within): 3.0 to 7.0			
	1.dimed of edges (within), o.e to 1.e			

5 Top connection (box): 2.7/8 inch API Regular RH 6 Bit box connection: 2.7/8 inch API Regular RH 7 Bit size range indicative (TCR & PDC): 4.1/8 inch to 5.7/8 inch / (105 mm to 149 mm) 8 Bearing package: Mud lubricated 9 Stator Elastomer: High Performance "Hard Rubber" 10 Dump valve: Removable Dump valve assembly with 2.7/8 inch API Reg RH (Box-up x Pin-down) connection 11 Housing: Slick (straight) type housing 12 Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor C OPERATIONAL SPECIFICATIONS 1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm) 2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm 3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm) 4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m) 5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m) 6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm) 7 Peak power output (minimum): 15,500 lbs / (4.3 ton) 9 Maximum Weight on bit (minimum): 1,5,500 lbs / (6.8 ton)	4	Overall Length (maximum): 29.5 feet (9.0 m)	
6 Bit box connection: 2.7/8 inch API Regular RH 7 Bit size range indicative (TCR & PDC): 4.1/8 inch to 5.7/8 inch / (105 mm to 149 mm)  8 Bearing package: Mud lubricated 9 Stator Elastomer: High Performance "Hard Rubber"  10 Dump valve: Removable Dump valve assembly with 2.7/8 inch API Reg RH (Box-up x Pin-down) connection  11 Housing: Slick (straight) type housing  12 Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS 1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 10 bp / (75 kw)  8 Dynamic weight on bit (minimum): 1,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 1,5500 lbs / (6.8 ton)			
7 Bit size range indicative (TCR & PDC): 4.1/8 inch to 5.7/8 inch / (105 mm to 149 mm)  8 Bearing package: Mud lubricated  9 Stator Elastomer: High Performance "Hard Rubber"  10 Dump valve: Removable Dump valve assembly with 2.7/8 inch API Reg RH (Box-up x Pin-down) connection  11 Housing: Slick (straight) type housing  12 Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 3,500 lbs / (6.8 ton)  9 Maximum Weight on bit (minimum): 3,500 lbs / (6.8 ton)			
8 Bearing package: Mud lubricated 9 Stator Elastomer: High Performance "Hard Rubber"  10 Dump valve: Removable Dump valve assembly with 2.7/8 inch API Reg RH (Box-up x Pin-down) connection  11 Housing: Slick (straight) type housing  12 Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 3,500 lbs / (6.8 ton)			
9 Stator Elastomer: High Performance "Hard Rubber"  10 Dump valve: Removable Dump valve assembly with 2.7/8 inch API Reg RH (Box-up x Pin-down) connection  11 Housing: Slick (straight) type housing  12 Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 13,500 lbs / (6.8 ton)			
Dump valve: Removable Dump valve assembly with 2.7/8 inch API Reg RH (Box-up x Pin-down) connection  11 Housing: Slick (straight) type housing 12 Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)			
API Reg RH (Box-up x Pin-down) connection  11 Housing: Slick (straight) type housing  12 Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	9		
11 Housing: Slick (straight) type housing 12 Safety catch: In-built rotor safety catch system to prevent fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 13,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	10		
fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	11		
fishing operation on a broken motor  C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	12	Safety catch: In-built rotor safety catch system to prevent	
C OPERATIONAL SPECIFICATIONS  1 Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to 946 lpm)  2 Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  3 Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)			
946 lpm)  Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  Peak power output (minimum): 100 hp / (75 kw)  Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	С		
Indicative Operating Bit speed range at full load: 65 rpm to 350 rpm  Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  Peak power output (minimum): 100 hp / (75 kw)  Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	1	Indicative Flow rate range: 45 gpm to 250 gpm / (170 lpm to	
rpm  Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  Peak power output (minimum): 100 hp / (75 kw)  Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)		1 /	
Operating Differential pressure at full load (minimum): 1000 psi / (70 kg/sq cm)  Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  Peak power output (minimum): 100 hp / (75 kw)  Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	2	Indicative Operating Bit speed range at full load: 65 rpm to 350	
psi / (70 kg/sq cm)  4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)		F	
4 Operating Torque at full load (minimum): 1500 ft-lbs / (2034 N-m) 5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m) 6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm 7 Peak power output (minimum): 100 hp / (75 kw) 8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton) 9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	3		
N-m)  5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m)  6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)			
5 Peak/Stall torque (minimum): 2000 ft-lbs / (2712 N-m) 6 Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm 7 Peak power output (minimum): 100 hp / (75 kw) 8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton) 9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	4	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
Maximum Differential pressure at Peak/Stall torque (minimum): 1500 psi / (106 kg/sq cm)  Peak power output (minimum): 100 hp / (75 kw)  Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)		,	
(minimum): 1500 psi / (106 kg/sq cm  7 Peak power output (minimum): 100 hp / (75 kw)  8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton)  9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)			
7 Peak power output (minimum): 100 hp / (75 kw) 8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton) 9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)	6		
8 Dynamic weight on bit (minimum): 8,500 lbs / (4.3 ton) 9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)			
9 Maximum Weight on bit (minimum): 13,500 lbs / (6.8 ton)		1 1 1 1 1	
$\delta$			
		Working over-pull (minimum): 60,000 lbs / (30 ton)	
11 Motor yield (minimum): 175,000 lbs / (87.5 ton)			
12 Temperature rating (minimum): 248 deg F/ (120 deg C)			
Working fluid:	13		
a) Salt solution: Sodium dichromate, cutch, common salt, CMC and 6000 ppm salt.			
b) Drilling fluid: Water base mud and KCL / NaCl mud.			
b) Diming hulu, water base muu anu KCL / NaCi muu.		b) Drining naid. water base mud and KCL / NaCi mud.	
D ACCESSORIES:	D	ACCESSORIES:	
1 Lifting sub compatible with 2.7/8" square shoulder elevator -	1		

	01 (one) number with each motor. Total- 06 (six) nos.		
2	Spare dump valve assembly - 01 (one) number with each		
	motor. Total- 06(six) nos.		
	GENERAL NOTES FO	R BIDDERS:	
1	The items shall be brand new, unused & of prime quality.		
	Bidder shall warrant (in the event of an order) that the product		
	supplied will be free from all defects & fault in material,		
	workmanship & manufacture and shall be in full conformity		
	with ordered specifications. This clause shall be valid for 18		
	(eighteen) months from date of despatch/shipment or 12		
	(twelve) months from the date of commissioning whichever is		
	earlier. The defective materials, if any, rejected by us shall be		
	replaced by the supplier at their own expense. Bidders must		
	confirm the same while quoting.		
2	The Bidder should indicate the name of manufacturer, country		
	of origin and port of dispatch of their offered Mud-Motors.		
3	The Bidder must provide detailed specifications against all the		
	tender parameters under physical and operational specification		
	including the make and model of the offered Mud-Motor(s) and		
	forward relevant Catalogue, Drawing, Literature and		
	Performance curves (consisting of speed curve, torque curve		
	and power curve with full-load/operating-limit line indicated		
	therein) along with the quotation in support of their offer.		
4	The threading and gauging of rotary shouldered connections of		
	the offered Mud-Motors are to done as per API Spec 7-1 (Latest		
	edition) and Bidder is required to forward a copy of valid API		
	Spec. 7-1 certificate of the manufacturer/threader (depending		
	on who does the threading & gauging) along with the supply in		
	the event of an order. Bidder to confirm the same while		
	quoting.		
5	All parts of the Mud-Motor(s) should be suitably marked for		
	identification purpose. Additionally, OIL purchase order		
	number should be die stamped on the body of the Mud-Motors		
	in the event of an order. Bidders shall confirm the same while		
-	quoting.		
6	The Mud-Motor(s) should be suitably coated with a protective		
	coating both internally and externally to prevent corrosion and		

	rusting during transit. Bidders must confirm the same while	
	quoting.	
7	Bidder should forward a list of recommended spares for two	
	(02) years operation for the quoted Mud-Motor(s) indicating	
	part numbers, quantity & unit price separately along with the	
	quotation in the commercial bid and categorically confirm the	
	same in the technical bid (price should not be mentioned in the	
	technical bid). However, the cost of these spares will not be	
	considered for bid evaluation purpose. The price should	
	remain valid for at least two (02) years.	
8	Additionally, the Bidder shall submit an un-priced list of	
	recommended spares for two (02) years operation against the	
	quoted Mud-Motor(s), indicating year wise requirement, part	
	numbers and quantity along with the technical bid.	
9	All test certificates/ reports (including Dynamometer test	
	reports consisting of speed curve, torque curve and power	
	curve) of the supplied Mud-Motors should be submitted to OIL	
	along with the supply. Bidder must confirm the same while	
	quoting.	
10	The Bidder should confirm to provide along with the supply,	
	06(six) sets of Operation, Service and Maintenance manual	
	indicating assembling and disassembling procedures, drawing	
	and spare parts list with part numbers against each size of the	
	Mud Motors.	
11	The Mud Motors along with the accessories are to be procured	
	from the same source for compatibility of the items. Bidder	
	shall quote accordingly.	
12	Any deviation(s) from the tender specification should be clearly	
	highlighted specifying justification in support of deviation.	
13	Bidder shall submit the duly filled in and signed "Technical	
	check list" and "Technical Evaluation Sheet for BEC &	
	Technical Specification" along with the technical bid.	

	EVALUATION MATRIX FOR BEC-TECHNICAL (TO BE DULY FILLED IN BY BIDDER AND SIGNED)		
	BID EVALUATION	CRITERIA	
Clause Numbe	ibe (TO BE FILLED BY THE BIDDER)		
r	DESCRIPTION	(Complied / Not Complied / Deviation / Not Applicable)	Relevant Location of their Bid to support the remarks / compliance (Reference of Document name / Serial number / Page number of bid for documentary evidence)
A	TECHNICAL: The bids shall conform generally to the specifications and terms as well as conditions laid out in this tender. Bids will be rejected in case the items offered do not conform to the required parameters stipulated in the technical specifications and to the respective international/national standards wherever stipulated. Notwithstanding the general conformity of the bids to the stipulated specifications and terms and conditions, the following requirements will have to be met by the bids, without which, the same shall be considered as non-responsive and stand rejected.		
1.0	IN CASE THE BIDDER IS THE MANUFACTURER:  The Bidder must have the experience of supplying at least 03 (three) numbers of MUD MOTORS of 3.1/2 inches (88.90 mm) OD or higher size, in the last 05 (five) years preceding the original bid closing date of this tender, to		

	E&P companies/ Drilling Contractors/ Drilling Service	
	providers which are in the business of Oil & Gas.	
	Documentary evidence in respect of the above should be	
	submitted in the form of copies of relevant Purchase Orders along-with copies of any of the following	
	documents in respect of satisfactory execution of each of	
	those purchase orders, such as:	
	I. Signed and sealed Satisfactory supply / completion /	
	installation report (in original on user's letter head) (OR) II. Bill of Lading (OR)	
	III. Consignee receipted delivery receipt/ challan (OR)	
	IV. Central Excise Gate Pass/Tax Invoice issued under	
	relevant rules of Central Excise/Vat. (OR) V. Commercial Invoice/ Payment Invoice	
	v. Commercial invoice/ I ayment invoice	
	Note: The Purchase Order date(s) and Supply Completion	
	date(s) have to be within the last 05(five) years preceding	
1.2	the original bid closing date of this tender.  Those Manufacturers who have successfully supplied at	
	least 03 (three) numbers of Mud Motors of 3.1/2 inches	
	(88.90 mm) OD or higher size, to OIL INDIA LTD. (OIL) in	
	the last 05 (five) years preceding the original bid closing date of this tender and the performance of which are	
	found to be satisfactory, shall be considered to qualify the	
	experience criteria as stated in the Clause 1.1 above,	
	provided, they indicate in the bid itself, the Purchase	
	Order No(s). & Date(s), Quantity, Details of Mud Motor(s) supplied to OIL in the past.	
	Note: The Purchase Order date need not be within the last	
	05(five) years, preceding the original bid closing date of this tender. However, the execution of supply should be	
	die tender. However, the execution of supply silould be	

	within the last 05(five) years preceding the original bid closing date of this tender.	
1.3	The Bidder quoted as Manufacturer should confirm that, the threading and gauging of the rotary shouldered connections of the offered Mud Motors will be done as per API Spec.7-1 [latest edition].	
1.4	The Bidder quoted as manufacturer should forward along with the technical bid, a copy of API Spec 7-1 certificate for threading and gauging of rotary shouldered connections, valid as on original bid closing date of this tender, from the concerned party as per below:  iii) From the Manufacturer, if threading and gauging of the rotary shouldered connections will be carried out by the Manufacturer themself.  OR  iv) From the API approved Threader, if threading and gauging of the rotary shouldered connections will be carried out through an API approved Threader.	
1.5	The Bidder quoted as manufacturer, should furnish an undertaking that, the API Spec 7-1 license for threading and gauging of rotary shouldered connections will be kept valid till execution of the purchase order, from the concerned party as per below:  i) From the Manufacturer, if threading and gauging of the rotary shouldered connections will be carried out by the Manufacturer themself.  OR  v) From the API approved Threader, if threading and gauging of the rotary shouldered connections will be carried out through an API approved Threader.	
2.0	IN CASE THE BIDDER IS NOT A MANUFACTURER: In case the Bidder is a sole selling	

	agent/distributor/dealer/supply house of any Manufacturer of the offered item(s), then Bidder must furnish the following documents along with the technical bid failing which the bids will be rejected:	
2.1	Authorization certificate from the manufacturer (in original on manufacturer's letter head) should be submitted along with the technical bid. This certificate should be valid at the time of bidding and should remain valid during the entire execution period of the order.	
2.2	Warranty backup from the manufacturer (in original on manufacturer's letter head) against the quality of the tendered item(s) as specified in the tender.	
2.3	Undertaking from the manufacturer (in original on manufacturer's letter head) guaranteeing supply of items to the bidder in the event of an order on the bidder. This certificate should be valid at the time of bidding and should remain valid during the entire execution period of the order.	
2.4	The Bidder is required to submit documentary evidences along with the techno-commercial bid from the concerned Manufacturer, in respect of the Manufacturer's past supply experience as per clause 1.1 or 1.2 above (as applicable), having supplied such items either by the Manufacturer themself or through their distributor.	
2.5	The Bidder should submit confirmation from the Manufacturer that the threading and gauging of the rotary shouldered connections of the offered Mud Motors will be as per API Spec.7-1 [latest edition].	
2.6	The bidder should forward along with the technical bid, a	

	copy of API Spec 7-1 certificate for threading and gauging of rotary shouldered connections, valid as on original bid closing date of this tender, from the concerned party as per below:  iii) From the Manufacturer, if threading and gauging of the rotary shouldered connections will be carried out by the Manufacturer themself.  OR  iv) From the API approved Threader, if threading and gauging of the rotary shouldered connections will be carried out through an API approved Threader.	
2.7	The Bidder should furnish an undertaking that, the API license for threading and gauging of the rotary shouldered connections will be kept valid till execution of purchase order, from the concerned party as per below:  i) From the Manufacturer, if threading and gauging of the rotary shouldered connections will be carried out by the Manufacturer themself.  OR  ii) From the API approved Threader, if threading and gauging of the rotary shouldered connections will be carried out through an API approved Threader.	
2.8	Additionally, the Bidder should also have the experience of supplying at least 03(three) numbers of Mud Motors of 3.1/2 inches (88.90 mm) OD or higher size, in the last 05(five) years preceding the original bid closing date of this tender, to E&P companies/ Drilling Contractors/ Drilling Service providers which are in the business of Oil & Gas.  Documentary evidence in respect of the above should be	

		1
	submitted in the form of copies of relevant Purchase Orders along-with copies of any of the following documents in respect of satisfactory execution of each of those purchase orders, such as:	
	I. Signed and sealed Satisfactory supply / completion / installation report (in original on user's letter head) (OR) II. Bill of Lading (OR) III. Consignee receipted delivery receipt/ challan (OR) IV. Central Excise Gate Pass/Tax Invoice issued under relevant rules of Central Excise/Vat. (OR) V. Commercial Invoice/ Payment Invoice	
	Note: The Purchase Order date(s) and Supply Completion date(s) have to be within the last 05(five) years preceding the original bid closing date of this tender.	
3.0	Bidder should categorically confirm in the technical bid a delivery schedule within 06(six) months, FOB Port of dispatch, after establishment of letter of credit (in case of foreign Bidder) or for dispatch of the equipment within 06(six) months after receipt of formal order (in case of indigenous Bidder) failing which their offer will be rejected.	

## NO DEVIATION CONFIRMATION

Ref. No	Date:
From:	(Insert name and address of Bidding Entity)
Tel.:	
Fax: E-mail address:	
To GM (MATERIALS MATERIALS DEI OIL INDIA LIMIT DULIAJAN District: DIBRU PIN 786602	D
Sub: Bid for "_ Tender No:	
	nat any 'deviation / exception' in any form may result in rejection of Bid. We, therefore, certify that we have not taken any tion' anywhere in the Bid and we agree that if any 'deviation / exception' is mentioned or noticed, our Bid may be rejected.
Place: Date:	[Signature of Authorized Signatory of Bidder] Name: Designation: Seal:
	****** FND ******