ANNEXURE: II

Other than the vendors to whom the enquiry has been issued, interested vendors who wish to participate in the tender may apply with proper credentials and other relevant details so as to reach Head-Materials, Oil India Limited, P.O. Duliajan, Dist. Dibrugarh, Assam — 786602 (e-mail: material@oilindia.in, Fax: 0374-2800533) within 10 days of publication of the tender on OIL's website.

The vendors must fulfill the following conditions:

- i) The party should have 03 (three) years' experience as on the Bid closing date for the same item.
- ii) The party should have received one order for at least 50% quantity in last 03 (three) years' (as on the Bid closing date) for the item from any reputed firm.
- iii) Annual turnover of the firm in any of the last 3 (three) financial years or current financial year should be more than Rs.09.90 lakhs.

NOTE:

- a. The applicant must meet the above qualifying criteria for which documentary evidence should be enclosed by the applicant with the application without which tender document shall not be issued.
- b. Relevant documents in support of experience, last order and annual turnover must be submitted along with the application.
- c. Application without complete supporting document will not be considered.

Tender No. : DID5425L15/L4
Tender Date : 17.11.2014

Bid Closing On : 08.01.2015 at 13:00 hrs.(IST)
Bid Opening On : 08.01.2015 at 13:00 hrs.(IST)

Tender issued to following parties only:

Slno	V_Code	Vendor Name	City/Country
1	200151	COMMERCIAL FRIENDS	DIBRUGARH
2	200190	KHAITAN PRINTING PRESS	TINSUKIA
3	201242	SANGEETA ELECTRONICS	DULIAJAN
4	201686	LALANI INTERNATIONAL	GUWAHATI
5	207252	BRIGHT LAND COMPUTER	DULIAJAN
6	207367	SATYAM COMPUTER SYSTEM	DULIAJAN
7	210467	VARATI ENTERPRISE	GUWAHATI

OIL INDIA LIMITED

(A Govt. of India Enterprise) P.O. Duliajan-786602, Assam

E-mail:material@oilindia.in, Fax No.91-374-2800533

Tender No. & Date : DID5425L15/L4 17.11.2014

Bid Security Amount : INR 0.00 OR USD 0.00

(or equivalent Amount in any currency)

Bidding Type : Single Bid (Composite Bid)

Bid Closing On : 08.01.2015 at 13:00 hrs. (IST) Bid Opening On : 08.01.2015 at 13:00 hrs. (IST)

Performance Guarantee: Not Applicable

OIL INDIA LIMITED invites Limited tenders for items detailed below:

Item No./ Mat. Code	Material Description	Quantity	UOM
10 99044214	RJ-45 Connector Standard: Category 6 ISO/IEC 11801 Class E, TIA/EIA-568-B.2-1 & TIA/EIA- 568-C.2 Connector Type: Model Cat6 UTP RJ45 Male connector backward compatible with cat5e standard Connector contact plating: 50 μ"/2.54μm gold over 100μ"/1.27μm nickel plating Contact blade: Phosphor bronze Conductor: 8P8C	5000	NO
20 99045297	8-port Unmanaged switch with necessary power adaptor, power cables.Make : DLINK / SMC	50	PC
3 <u>0</u> 99029391	ADSL Modems with USB Interface Make: D-Link - GLB-502T Complete with Standard accessories Driver Software on CD media USB cable, Power Adapter	25	NO
40 99071483	a. D-Link DSL-G684T or equivalent b. Interfaces: 1 RJ-11 ADSL port 4 RJ-45 10/100BASE-TX Fast Ethernet LAN switch ports with auto MDI/MDIX Built-in WLAN Factory reset button c. Wireless LAN IEEE 802.11g standard Wireless speed: up to 54Mbps Frequency range: 2.4 GHz to 2.484G Hz 64/128 bits WEP data encryption Wi-Fi Protected Access (WPA) security d. ADSL: ADSL standards: ANSI T1.413 Issue 2, ITU G.992.1 (G.dmt) Annex B, ITU G.992.2 (G.lite) Annex B ADSL2 standards: ITU G.992.3 (G.dmt.bis) Annex B, ITU G.992.4 (G.lite.bis) Annex B ADSL2+ standards: ITU G.992.5 Annex B Auto-handshake: ITU G.994.1 (G.hs) e. Data Rates ADSL2: 12Mbps downstream, 1Mbps upstream f. Firewall/Access Security: Built-in NAT firewall Stateful Packet Inspection (SPI)DoS attacks prevention (IP Spoofing, Land Attack, Smurf Attack, Ping of Death, TCP SYN flooding)Packet	50	NO

Tender No. & Date : DID5425L15/L4 17.11.2014

Item No./ Mat. Code	Material Description	Quantity	UOM
	filtering based on port, source IP address, destination IP address, MAC address, (ICMP/TCP/UDP) g. Configuration/Management: Quick Installation Wizard Web-based GUI for remote/local management Telnet server for remote/local management h. ATM & PPP Protocols Bridged or routed Ethernet encapsulation i. Power Input: Through 12VAC 1.2A external power adapter		
50 99027710	UTP Patch Cord Category 6 Length: 5m RJ 45 connectors at both ends Factory molded connectors ANSI/TIA-568-C.2 Category 6 Wiring: 23 AWG STranded Unshielded Insulation Resistance: Min 500 MOhm/Km @ 500 Vdc Contact Resistance: max 15 mOhm per contact Jacket Material: PVC RoHS Compliant.	200	NO
<u>60</u> 99029569	SC/ST SMF patch cord 3 metres with 9/125 micron fibre	30	NO
70 99029570	NETWORKING ITEMS FIBER OPTIC PATCH CORD, MULTIMODE 50/125 UM Fiber Optic Patch Cord Specification : As per Annexure.	30	NO
80 99069590	Silicone Coated HDPE pipes Duct Specification a. Nominal Outside Diameter- 40 + 0.4mm b. Wall Thickness- 3.5 ± 0.2mm c. Thickness of inside lubrication in mm- 10% of Pipe Thickness d. Lubrication in mm- Permanently lubricated for blowing of Optical Fiber Cable e. Ovality- 1.0mm HDPE Raw Material Specification a. Density- 0.940 G/CC to 0.958 G/CC at 27° C standard IS: 2530: 1963 b. Melt Flow Rate- 0.2 Gm/10 min. to 1.10 Gm/10 min. at 190° C under 5	10000	M
	Kg Load standard IS: 7328: 1992 Visual Appearance a. Surface Finish-Duct is smooth, clean, round and free from blister, shrink, holes, flaking & other defects standard GR. No.G/CDS 08/02.Nov 04		
	Performance Requirement a. Heat Reversion in %- Max 3% standard IS: 4984: 1995 b. Hydrostatic Pressure Resistance Test- Acceptance Test:Duration: 48 hrs at 80° Induced Stress 3.8 Mpa,Type Test:Duration: 165 hrs at 80° Induced Stress: 3.5 standard IS: 4984: 1995 c. Tensile Strength & Elongation in N/mm2 %- Min. 20 N/mm2 600%		

Tender No. & Date: DID5425L15/L4 17.11.2014

I I I	Item No./ Mat. Code	Material Description	Quantity	UOM
standard IS: 14151(part-1) d. ESCR -No Failure standard ASTMD 1693 e. Impact -Striker Weight 10 kg, Duct Shall not crack or split standard IS:12235 (part-9) f. Crush Resistance in %- Approx. 50 kg Load standard GR. No.G/CDS-08/02.Nov 04 g. Oxidation Induction Test -Time > 30 Min standard GR. No.G/CDS-08/02.Nov 04 h. Internal Co-efficient of Friction-COF < 0.06 standard GR. No.G/CDS-08/02.Nov 04 i. Minimum bending radius during storage-1.25 Mtrs. standard GR. No.G/CDS-08/02.Nov 04 j. Maximum pulling force-300 Kg standard GR. No.G/CDS-08/02.Nov 04 k. Ash Content of Finished Duct-0.3 (Max) standard GR. No.G/CDS-08/02.Nov 04 I. Fading of colors of Duct-No Discoloration standard GR. No.G/CDS-08/02.Nov 04 m. UV Stabilizer Content of Resin in %- 0.15 (Min) standard FT-IR Method n. UV stabilizer Content of Duct-Variation in tensile strength after aging is not more than 20% standard GR. No.G/CDS-08/02.Nov 04 o. Marking Identification-All pipes are marked in white color by hot embossed as per detail specified by the client, with length mark at every meter.4 white strips applied on duct in the longitudinal direction. Color: Orange. standard GR. No.G/CDS-08/02.Nov 04	Iviat. Code	standard IS: 14151(part-1) d. ESCR -No Failure standard ASTMD 1693 e. Impact -Striker Weight 10 kg, Duct Shall not crack or split standard IS:12235 (part-9) f. Crush Resistance in %- Approx. 50 kg Load standard GR. No.G/CDS-08/02.Nov 04 g. Oxidation Induction Test -Time > 30 Min standard GR. No.G/CDS-08/02.Nov 04 h. Internal Co-efficient of Friction-COF < 0.06 standard GR. No.G/CDS-08/02.Nov 04 i. Minimum bending radius during storage-1.25 Mtrs. standard GR. No.G/CDS-08/02.Nov 04 j. Maximum pulling force-300 Kg standard GR. No.G/CDS-08/02.Nov 04 k. Ash Content of Finished Duct-0.3 (Max) standard GR. No.G/CDS-08/02.Nov 04 l. Fading of colors of Duct-No Discoloration standard GR. No.G/CDS-08/02.Nov 04 m. UV Stabilizer Content of Resin in %- 0.15 (Min) standard FT-IR Method n. UV stabilizer Content of Duct-Variation in tensile strength after aging is not more than 20% standard GR. No.G/CDS-08/02.Nov 04 o. Marking Identification-All pipes are marked in white color by hot embossed as per detail specified by the client, with length mark at every meter.4 white strips applied on duct in the longitudinal direction. Color:		

Standard Notes: (1) VALIDITY: Your offer must be valid for 75 days from the date of bid opening. Offer with inadequate validity will be rejected.

- (2) The offer should be submitted in Duplicate.
- (3) Any sum of money due and payable to the contractor (including Security Deposit refundable to them) under this or any other contract may be appropriated by Oil India Limited and set-off against any claim of Oil India Limited (or such other person or persons contracting through Oil India Limited) for payment of a sum of money arising out of this contract or under any other contract made by the contractor with Oil India Limited (or such other person or persons contracting through Oil India Limited).
- (4) In the event you authorize your dealer/stockist/channel partner to quote on your behalf, the dealer/stockist/channel partner while submitting bid should mention on the body of the envelope that they are submitting bid on your behalf.

In the event the dealer/stockist/channel partner do not mention the name of their OEM/principal on the body of the envelope, the offer shall be treated as unsolicited offer and will not be considered for opening.

The dealer/stockist/channel partner should take note of above while submitting bid on behalf of their OEM/principal.

(5) For order with F.O.R. Destination term, 100% payment against despatch

documents will not be entertained. In this regards please refer payment terms in ANNEXURE-MM/TENDER/LP/01/06.

- (6) To evaluate the inter-se ranking of the offers, Assam Entry Tax on purchase value will be loaded as per prevailing Government of Assam Guidelines as applicable on bid closing date. Bidders may check this with the appropriate authority while submitting their bids.
- (7) Bidder must mention page no./nos. in every pages of their offer.
- (8) Bidders should submit their bids (preferably in tabular form) explicitly mentioning compliance / non compliance to all the NIT terms and conditions of NIT.
- (9)Bidder should clearly mention their name and address on the outside of the envelope containing their offer.
- (10) In the event of receipt of only a single offer against the tender within B.C.date, OIL reserves the right to extend the B.C. date as deemed fit by the company. During the extended period, the bidders who have already submitted the bids on or before the original B.C date, shall not be permitted to revise their quotation.

Special Notes: Item has to be delivered in good condition. Damaged or defective items will not be accepted and must be replaced immediately.