OIL INDIA LIMITED

(A GOVT. OF INDIA ENTERPRISE) P.O.DULIAJAN-786602, ASSAM E-TENDER NOTICE

WORKS CONTRACT

OIL INDIA LIMITED (OIL) invites Bids under Limited Composite bid System from OIL Registered B-Class firms/ contractors only through its E-Procurement portal "https://etender.srm.oilindia.in/irj/portal" for the following works.

IFB No.	SHORT DESCRIPTION OF SERVICE	OIL Registered Class	COST OF BID DOCUMENT
CDC8508L22	Civil construction jobs to facilitate the relocation of gas lift compressor from GCS-Ushapur to GCS-Tengakhat. (1) Construction of Operator cum Maintenance Room. (2) Earth filling, brick soling & Cement Concrete work. (3) Extension of shed for Gas Lift Compressor.	В	NIL

Bid Closing / Opening Date & Time for the above work: 09-11-2021 at 11.00/14.00 Hrs.

Bidder shall require User ID and Password for online submission of Bid.

Date: 11.10.2021

Bidders without having E-tender Login ID and Password should complete their online registration at least seven (7) days prior to the scheduled bid closing date and time of the tender. For online registration, Bidder may visit the OIL's E-tender site https://etender.srm.oilindia.in/iri/portal.

Necessary Login ID & Password will be issued by OIL only after submitting the complete online registration by the Bidder. In the event of late registration/incomplete registration by Bidder, OIL INDIA LIMITED shall not be responsible for late allotment of User ID & Password and request for bid closing date extension on that plea shall not be entertained by Company.

No physical Bid documents will be issued. The details of IFB can be viewed using "Guest Login" provided in the E-Procurement portal and also in OIL's web site www.oil-india.com. The link to OIL's E-Procurement portal has also been provided through OIL's web site www.oil-india.com.

All corrigenda, addenda, amendments, time extension, clarifications etc. to the tender will be hosted on the OIL's website and in the e-tender portal only and no separate notification shall be issued in the press. Prospective bidders are requested to regularly visit the website and e-portal to keep them updated.

This tender document is issued to **OIL Registered B-Class contractors** who have submitted revised "One Time Security Deposit" in line with OIL's notification no.: CONT/CIV/988/2016 dated 01.07.2016, on or before 13:30 Hrs. of Bid Closing/Opening date of the tender.

DGM Contracts (Civil)
For GM-Contracts (HOD)

For RESIDENT CHIEF EXECUTIVE

COVERING LETTER

OIL INDIA LIMITED (A Govt. of India Enterprise) Contracts Department, Duliajan

WORKS CONTRACT

OIL INDIA LIMITED, a premier Public Sector Enterprise of Govt. of India engaged in drilling and exploration activities for hydrocarbon invites ON-LINE BIDS from OIL's Registered 'B' Class Civil Contractors only (who have submitted revised "One Time Security Deposit" in line with OIL's notification no.: CONT/CIV/988/2016 dated 01.07.2016, on or before 13:30 Hrs. of Bid Closing/Opening date of this tender) for the following mentioned work under LIMITED COMPOSITE BID SYSTEM through its e-Procurement site:

 $\underline{\rm DESCRIPTION\ OF\ WORK/\ SERVICE} \colon \ \textbf{Civil\ construction\ jobs\ to\ facilitate\ the\ relocation\ of\ gas\ lift\ compressor\ from\ GCS-Ushapur\ to\ GCS-Tengakhat.}$

- (1) Construction of Operator cum Maintenance Room.
- (2) Earth filling, brick soling & Cement Concrete work.
- (3) Extension of shed for Gas Lift Compressor.

TENDER VALUE: ₹ 88,72,196.08

LOCATION OF WORK: GCS-Tengakhat.

CONTRACT PERIOD: 78 Weeks

BID CLOSING/ OPENING DATE & TIME: 09.11.2021 (11:00 HRS/14:00 HRS)

TENDER FEE: Nil

BID SECURITY DEPOSIT: Nil

<u>PERFORMANCE SECURITY DEPOSIT</u>: **3** % **of Total Contract Cost** (shall be kept as retention money from running bill)

2.0 This tender document is issued to **OIL Registered 'B' Class Civil Contractors** only in line with Notification for Amendment of Tendering Rules vide Ref. No. OIL/CONT/V/C/753/2019-20 dated 11.09.2019. OIL Registered Civil Contractors other than **'B'** Class are not eligible to participate in this tender.

OIL Registered 'B' class bidders (if any) having MSE Registration Certificate are requested to upload a scanned copy of their registration certificate along with the technical bid while participating in the tender. This is for Company's information and record only.

- **3.0** If the above mentioned closing / opening day of the tender happens to be non-working day due to Bandh / Strike or any other reason, the bids will be received and opened on the following working day at the same time except on Saturdays.
- **Value"** (under RFx Information > Basic Data > Total Bid Value), taking account of all liabilities including statutory liabilities in their quoted price excluding PF and GST. A screen shot in this regard is shown below. The price quoted under the "Total Bid Value" should be within the range of "At Par" to "+10%" of Company's Internal Estimate. Bids with overall quoted price as indicated in the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) below "at par" and above "10%" of Company's Internal Estimate will be rejected straightway.

Company shall evaluate the inter-se-ranking of the bidders and conduct Draw of Lots amongst the eligible bidders in case of identical bidding, strictly as per the overall quoted price under the "Total Bid

COVERING LETTER

Value" (under RFx Information > Basic Data > Total Bid Value) and awarding of contract shall be done accordingly.

It is the responsibility of the bidder to fill up the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) correctly as per the instructions given herein. OIL INDIA LTD accepts no liability of any nature resulting from any calculation error or omissions while filling up the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) by the bidders and no claim whatsoever shall be entertained thereof.

In case of identical bidding, Draw of Lots shall be conducted amongst the bidders who have quoted the lowest price (within the permissible percentage) under the "Total Bid Value" tab, to select 3 (three) numbers of bidders priority-wise. Scrutiny of bids will be carried out for these 3(three) bidders only for further processing of the tender.

For convenience of the bidders and to improve transparency, the overall rate quoted by the bidders (within the range of "At par" to +10% of the internal estimate) against the tender shall be available for online viewing by all such bidders whose price bids shall be opened. Online view of prices as above shall be available to the bidders only upto 7 (seven) days from the date of price bid opening of the tender.

- **5.0** All techno-commercial documents are to be submitted as per tender requirement under **Technical Attachments Tab**" in E-TENDER PORTAL.
- **6.0** To participate in OIL's E-procurement tender, bidders must have a legally Valid Digital Signature of Class 3 **[Organizational Type]** with Organizations Name along with **Encryption Certificate** as per Indian IT Act from the licensed Certifying Authorities operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India (http://www.cca.gov.in). Digital Signature Certificates having "**Organization Name**" field other than **Bidder's Name (i.e. Firm's Name)** are not acceptable.
- 7.0 The authenticity of above Digital Signature shall be verified through authorized CA after bid opening. If the **Digital Signature Certificate (DSC)** used for signing is not of "**Class -3**" & Organizational type with Organization's name in the name of bidder (i.e. Firm's Name), the bid will be rejected.

Note: Only in case of sole proprietorship firms, Digital Signature Certificates issued in the name of the proprietor is also acceptable provided the bid is submitted in the capacity of a proprietorship firm.

- **8.0** Bidder is responsible for ensuring the validity of Digital Signature Certificate (DSC) and its proper usage by their employee.
- **9.0** The bid including all uploaded documents shall be **digitally signed** by duly authorized representative of the bidding company. The DSC used must be of the type as mentioned above.
- **10.0** Bidders without having E-tender Login ID and Password should complete their online registration at least seven (7) days prior to the scheduled bid closing date and time of the tender. For online registration, Bidder may visit the OIL's E-tender site https://etender.srm.oilindia.in/irj/portal.
- **11.0** Necessary Login ID & Password will be issued by OIL only after submitting the complete online registration by the Bidder. In the event of late registration/incomplete registration by Bidder, OIL INDIA LIMITED shall not be responsible for late allotment of User ID & Password and request for bid closing date extension on that plea shall not be entertained by Company.
- **12.0** The Company reserves the right to reject any or all the bids or accept any bid without assigning any reason.

Note: Bidders must note that in case of any discrepancy or non-compliance to the tender criteria is found in their bids at any stage of tendering prior to the award of contract, such bids shall be rejected straightway. No claims or requests from such bidders shall be entertained thereafter.

13.0 (a) Bidders will be permitted by System to withdraw their bid or make any changes in their bid after the bid has been uploaded by the bidder prior to the Bid Closing date and time as mentioned in the bid. But

COVERING LETTER

no changes or withdrawal would be allowed by the system once the due date and time for submission of bids has been reached and bids are opened. Bidders are requested to take note of the above and arrange to submit their bids within the submission deadline to avoid last minute rush/network problems.

- (b) No Bidder can withdraw his bid within the validity or extended validity of the bid. Withdrawal of any bid within bid validity period will lead to forfeiture of his/her/their Bid Security in full and debarment from participation in future tenders, at the sole discretion of the Company and the period of debarment will be decided as per OIL's banning policy dated 6th Jan 2017 available at OIL's website.
- (c) Once a withdrawal letter is received from any bidder, the offer will be treated as withdrawn and no further claim / correspondence will be entertained in this regard.

14.0

- a) The Bid must be valid for 90 (Ninety) days from the actual date of closing of the tender.
- b) The bidders must upload the Integrity Pact, digitally signed by the authorized signatory (who is authorized to sign the bid) along with the Technical Bid.
- **15.0** Conditional bids are liable to be rejected at the discretion of the Company.
- **16.0** The work may be split up amongst more than one contractor at the sole discretion of the Company.
- 17.0 Wherever applicable, the bidder shall have itself registered under Employees' Provident Fund and Miscellaneous Provisions Act, 1952 and follow the relevant statutory provisions including Rules made thereunder concerning contractual workers to be engaged by such bidder. If the bidder does not have P.F. Code number at the time of applying for this tender, then the bidder must apply for the same if the contract is awarded to the bidder. Such bidder shall furnish the Provident Fund code number issued by the appropriate Govt. Authority, within 45 days of signing of contract, to Company (or when advised by Company, after 45 days of signing the contract); and all PF related statutory guidelines shall be adhered to by the bidder.

18.0 Before Bidding:

- Bidder(s) are advised to inspect the work site with permission from HOD-Civil or his representative, to assess the nature and extent of work and the conditions under which it will be carried out. The bidder may also seek such clarification from this office as are deemed necessary.
- Bidder(s) should clearly understand all the terms & conditions, criteria, specification etc. of this tender.
- **19.0** The selected bidder will be required to enter into a formal contract, which will be based on their bid, i.e. OIL's Standard Form of Contract.
- **20.0** OIL INDIA LIMITED reserves the right to curtail / enhance the scope of the work stated above or cancel, if required.
- **21.0** The amount of retention money shall be released after 6 (six) months from the date of completion certified by the concerned department.
- **22.0** The work shall have to be started within seven days from the date of work order.
- **23.0** Time Schedule: The time allowed for completing the work will be reckoned from the date of issue of work order. Time is the essence of the Contract and failure on part of the contractor to complete the work within the stipulated time, shall entitle the Company to impose liquidated damages and / or penalty from the contractor as per terms of the Contract.
- **24.0** The contractor will be required to allow OIL officials to inspect the work site and documents in respect of the workers payment.

COVERING LETTER

- **25.0 BACKING OUT BY BIDDER**: In case any bidder withdraws their bid within the bid validity period, the Bid Security will be forfeited and be debarred from further tendering as per OIL's banning policy dated 6th Jan 2017 available at OIL's website.
- **26.0 BACKING OUT BY L-1 BIDDER AFTER ISSUE OF LOA**: In case LOA issued is not accepted by the L1 bidder and the contract is not signed within the time specified in the Bid Document, the Bid Security shall be forfeited and the bidder shall be dealt as per OIL's banning policy dated 6th Jan 2017 available at OIL's website.
- **27.0 FURNISHING FRAUDULENT INFORMATION/DOCUMENT**: If it is found that a Bidder/Contractor has furnished fraudulent document/information, the Bid Security/ Performance Security shall be forfeited and the party shall be debarred as per the OIL's Banning Policy dated 6th Jan 2017 available at OIL's website.
- **28.0 ERRING / DEFAULTING AGENCIES:** Erring and defaulting agencies like bidder, contractor, supplier, vendor, service provider will be dealt as per OIL's Banning Policy dated 6th January, 2017 available in OIL's website: www.oil-india.com.

29.0 Bidder(s) must also furnish the followings:

- a) NAME OF FIRM
- b) DETAIL POSTAL ADDRESS
- c) MOBILE / TELEPHONE NO
- d) E-MAIL ADDRESS
- e) FAX NO (If available)
- f) CONTACT PERSON
- g) VENDOR CODE
- h) GST Registration Number (If available):

30.0 The tender will be governed by :

- a) Covering Letter.
- b) Part I General Terms and Conditions for Works Contract. (GCC)
- c) Part II Schedule of Work, Unit and Quantity (SOQ)
- d) Part III Particular Specification, Special Terms, Conditions & Instructions of Contract (SCC)
- e) Part IV SCPME
- f) Part- V- Safety Measures
- g) Part- VI Integrity Pact
- h) Bid Rejection Criteria & Bid Evaluation Criteria (BRC/BEC).
- i) Annexures

Bidders are requested to examine all instructions, forms, terms and specifications in the bid. Failure to furnish all information required as per the bid or submission of offers not substantially responsive to the bid in every respect will be at the bidders risk and may result in the rejection of its offer without seeking any clarifications.

31.0 The bidders shall submit both the "TECHNICAL" and "PRICED" bids through electronic form in the OIL's E-Procurement portal within the Bid Closing Date and Time stipulated in the E-Tender. The Technical Bid should be submitted as per Scope of Work & Technical Specifications along with all technical documents related to the tender and should be uploaded under "Technical Attachment" Tab only. Bidders must note that no price details should be uploaded in "Technical Attachment" Tab Page. Bidders must quote their overall price under the "Total Bid Value" within the range of "at par" to "+10%" of Company's Internal Estimate, taking into account all liabilities including statutory liabilities in their quoted price (excluding PF and GST). Bidder must also upload the Undertaking as prescribed in Proforma-I under the "Notes and Attachment" Tab in e-tender portal. A screen shot in this regard is shown below. Offer not complying with above submission procedure will be rejected as per Bid Rejection Criteria. In Bid opening, both Technical & Priced Bids will be opened.

Please go through the "GENERAL GUIDELINES TO BIDDERS" and "VENDOR USER MANUAL (Effective 15.09.19)" provided in OIL's e-Portal, in detail before uploading the document.

COVERING LETTER

NB: In order to bid for OIL e-tenders all the vendors are required to obtain a legally valid Digital Certificate Class III [Organization] along with Encryption Certificate as per Indian IT Act from the licensed Certifying Authorities (CA) operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India. Digital Signature Certificate comes in a pair of Signing/verification and Encryption/decryption certificate. Bidder should have both the Signing/verification and Encryption/Decryption certificate for Signing and encryption, decryption purpose respectively. The driver needs to be installed once, without which the DSC will not be recognized. While participating on e-Tendering the DSC token should be connected to your system.

Encryption certificate is mandatorily required for submission of bid. In case bidder created response with one certificate (using encryption key) and bidder change his Digital Signature Certificate then old certificate (used for encryption) is required in order to decrypt his encrypted response for getting the edit mode of the response. Once decryption is done, bidder may use new DSC certificate for uploading and submission of their offer. It is the sole responsibility of the bidder to keep their DSC certificate properly. In case of loss of the certificate, OIL INDIA LTD is not responsible.

- **32.0** The Integrity Pact is applicable against this tender: OIL shall be entering into an Integrity Pact with the bidders as per format enclosed vide "Part-VI Integrity Pact" of the tender document. This Integrity Pact proforma has been duly signed digitally by OIL's competent signatory. The proforma has to be returned by the bidder (along with the technical bid) duly signed (digitally) by the same signatory who sign the bid, i.e., who is duly authorized to sign the bid. Any bid not accompanied by Integrity Pact Proforma duly signed (digitally) by the bidder shall be rejected straightway. Uploading the Integrity Pact with digital signature will be construed that all pages of the Integrity Pact has been signed by the bidder's authorized signatory who sign the Bid.
- 32.1 In case of a joint venture, all the partners of the joint venture should sign the Integrity Pact.
- 32.2 In the event of any dispute between the management and the contractor relating to those contracts where Integrity Pact is applicable, in case, both the parties are agreeable, they may try to settle dispute through mediation before the panel of IEMs in a time bound manner. If required, the organizations may adopt any mediation rules for this purpose. In case, the dispute remains unresolved even after mediation by the panel of IEMs, the organization may take further action as per the terms and conditions of the contract.

<u>Note</u>: Bidders may contact the Independent External Monitors for any matter relating to the IP at the following addresses:


Shri Sutanu Behuria, IAS (Retd.), e-Mail ID: sutanu2911@gmail.com, Shri Om Prakash Singh, IPS (Retd.), Former DGP, Uttar Pradesh, e-mail: Ops2020@rediffmail.com and Shri Rudhra Gangadharan, IAS (Retd.), Ex-Secretary, Ministry of Agriculture, e-mail ID: rudhra.gangadharan@gmail.com have been appointed as Independent External Monitors.

COVERING LETTER

33.0 SCREEN SHOT:

Bidders must fill up the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value), taking account of all liabilities including statutory liabilities in their quoted price (excluding PF and GST).

A. Filling of **"Total Bid Value"** with overall quoted price where Detailed Price Information is "No Price": Under "RFx Information"> "Basic Data"> "Total Bid Value"



Note: Total Bid Value" is mandatory in "No Price" RFx only

On **"EDIT"** Mode, bidders are advised to upload **"Technical Bid"** and **"Priced Bid"** in the respective places as indicated below:


Note:

* The "Technical Bid" shall contain all techno-commercial details except the prices.


^{**} The "Priced bid" must contain the price schedule as available in the tender. For uploading Priced Bid, first click on Add Attachment, a browser window will open, select the file from the PC and name the file under Description, Assigned to General Data and click on OK to digitally sign and upload the File. Please click on Save Button of the Response to Save the uploaded files.

COVERING LETTER


B. Uploading of **TECHNICAL BID:** Technical files to be added under RFX Information >"Technical Attachments"



C. Uploading of UNDERTAKING IN RESPECT OF QUOTED PRICE:




D. After Uploading of Proforma-I Click 'Save'



COVERING LETTER


Once Saved ,the Data will be Encrypted & the Encryption Certificate will be in use.

E. Click to select the desired Encryption certificate & Encrypt Bid:




The Encrypted Data will be displayed only when click 'Decrypt data'

F. The Encrypted Data will be displayed only when click 'Decrypt data'




G. Click on 'Close'




COVERING LETTER

H. Click on 'Refresh'. Then Click on 'Response No.'



Now Uploading part is complete. Bidders are requested to go to the Initial screen. It is always better to come to the first screen and refresh the page and then going in into the response for the submission process.

I. On 'Edit' mode Click to select the same Encryption certificate used for De-cryption else data will not Decrypt.



J. After Entering User pin, Click 'Check'. Bidder may submit the response in case there is no error.




COVERING LETTER

K. Click on 'Submit' button




Before submit, Please do check all the documents uploaded and on-line data maintained are correct.

L. After Clicking 'Submit' below pop up will open. Select Digital Signature & Sign




M. After Signing the response has to be encrypted again. Select the encryption certificate and Encrypt Bid.




COVERING LETTER

N. Click 'Close'



O. Click on 'Refresh'. The status of Response must be



This is the end of Response submission with Encryption key process.

34.0 OIL now looks forward for your active participation in the tender.

GM-CONTRACTS (HOD)
For RESIDENT CHIEF EXECUTIVE

BID EVALUATION CRITERIA (BEC)/BID REJECTION CRITERIA (BRC)

(A). BID EVALUATION CRITERIA (BEC):

- 1.0 The bid shall conform generally to the specifications and terms and conditions given in the Tender Documents. Bids will be rejected in case services offered do not conform to the required parameters stipulated in the technical specifications. Not-withstanding the general conformity of the bid to the stipulated specifications, the following mandatory requirements will have to be particularly met by the Bidders without which the same will be considered as non-responsive and rejected. All the documents related to **BEC** must be submitted along with the Techno-Commercial Bid.
- **2.0 OIL Registered 'B' Class Civil Contractors** who have submitted revised "One Time Security Deposit" in line with OIL's notification no.: CONT/CIV/988/2016 dated 01.07.2016, on or before 13:30 Hrs. of Bid Closing/Opening date of this tender are only eligible to participate in this tender.

3.0 Electrical Work Experience Criteria:

a) The bidder shall have a valid Electrical Contractor's License issued by Electrical Licensing board, Govt. of Assam or shall form a consortium / tie-up / collaboration with an Electrical contractor, having required technical credentials as described in Para b) below and holding valid Electrical Contractor's License issued by Electrical Licensing board, Govt. of Assam for executing the jobs. In support of the above the bidder shall submit a copy of either of the above Electrical Contractor's License.

OR

Bidder or their collaborators / consortium partner having valid Electrical Contractors' License issued by any State Government Electrical Licensing Board of India other than that of Assam must submit a copy of valid Electrical Contractors' License in support of above along with an undertaking stating that on award of contract to them they will submit either a valid Electrical Contractors' License issued by Electrical Licensing Board, Government of Assam in their name or get their Electrical Contractors' License recognized / endorsed by Electrical Licensing Board, Government of Assam for executing the job at Assam within 30 days from date of award of the contract and the same will be subsequently renewed till the completion of the contract.

- b) The bidder or their collaborators / consortium partner must have experience in internal electrification works in Office/ Residential Building of PSU/Central Govt./State Govt./Public Limited Company during the last 7(seven) years reckoned from the original bid closing date in any of the above organizations as listed. The bidder or their collaborators / consortium partner must submit documentary evidences such as Purchase Order copies with invoice/ performance certificate /completion certificate or any other documents which substantiate successful execution of internal electrification works in Office/ Residential Building along with their bid.
- c) In case of collaboration / consortium / tie-up with any Electrical firm as mentioned above, the bidder must furnish acopy of MoU entered into with the collaborator / consortium partner towards providing the requisite service as per the terms of the contract.
- **4.0** Bids must be valid for minimum **90 (Ninety) days** from the actual date of Bid closing. If bidder does not submit / declare bid validity period, it will be presumed that the bid validity is **90 (Ninety)** days.
- **5.0** OIL shall be entering into an Integrity Pact with the bidders as per format enclosed vide Part-VI of the tender document. This Integrity Pact proforma has been duly signed digitally by OIL's competent signatory. The proforma has to be uploaded by the bidder (along with the Un-priced Techno-Commercial Bid).-Uploading the Integrity Pact with digital signature will be construed that all pages of the Integrity Pact have been signed by the bidder's authorized signatory who sign the Bid. Any bid not accompanied by Integrity Pact Proforma duly signed (digitally) by the bidder shall be rejected straightway.

6.0 The bidders must have Encryption Certificate along with Digital Signature Certificate (DSC) of Class 3 [Organization Type] to upload all the documents. If the Digital Signature Certificate (DSC) used for signing is not of "Class -3" & Organizational type with Organization's name in the name of bidder (i.e. Firm's Name), the bid will be rejected.

Note: Only in case of sole proprietorship firms, Digital Signature Certificates issued in the name of the proprietor is also acceptable provided the bid is submitted in the capacity of a proprietorship firm.

7.0 While submitting responses against the tender in e-tender portal, bidders must fill up the **"Total Bid Value"** (under RFx Information > Basic Data > Total Bid Value), taking account of all liabilities including statutory liabilities in their quoted price excluding PF and GST. The price quoted under the "Total Bid Value" should be within the range of **"At Par" to "+10%"** of Company's Internal Estimate. Bids with overall quoted price as indicated in the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) below "at par" and above "10%" of Company's Internal Estimate will be rejected straightway.

Company shall evaluate the inter-se-ranking of the bidders and conduct Draw of Lots amongst the eligible bidders in case of identical bidding, strictly as per the overall quoted price under the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) and awarding of contract shall be done accordingly.

It is the responsibility of the bidder to fill up the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) correctly as per the instructions given herein. OIL INDIA LTD accepts no liability of any nature resulting from any calculation error or omissions while filling up the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) by the bidders and no claim whatsoever shall be entertained thereof.

- **8.0** The bids conforming to the specifications, terms and conditions stipulated in the tender documents and considered to be responsive will be evaluated as per the procedure mentioned below:
 - Bid will be opened on schedule date & time as specified in the NIT and all the bids where the bidders have quoted the lowest price (within the permissible percentage as per NIT) under the "Total Bid Value" tab in e-tender portal and who have submitted revised "One Time Security Deposit" in line with OIL's notification no.: CONT/CIV/988/2016 dated 01.07.2016, on or before 13:30 Hrs. of Bid Closing/Opening date of this tender will be selected for conducting Draw of Lots (DoL). In DoL, 3 (three) numbers of bidders will be selected first, in the order of B-1 (Bidder-1), B-2 and B-3. Scrutiny of these three bidders as per tender criteria will be carried out. If the bid of bidder B-1 is found to be acceptable, B-1 will be the successful bidder (Priority-1 bidder) and the contract will be awarded to B-1. If B-1 is not found to be acceptable but B-2 is acceptable, B-2 will be awarded the contract, ---and so on; i.e. whoever becomes the first acceptable bidder in the order of B-1□B-2□B-3, will be the successful bidder (P-1). In this way, P-1 (Priority-1) and P-2 bidders will be selected. The contract will be awarded to the P-1 bidder only. However, in case the bidder P-1 is not able to carry out the job due to any reason, P-2 may be awarded the job, if the same is approved by Company's competent authority. In case, none of these three bidders are found to be technically acceptable, the Draw of Lots will be again conducted to select 3 more bidders and similar steps will be followed thereon as explained above. The system of conducting further draw of lots will be followed till a qualified bidder is selected.
 - ii. Bidder should note that deficit documents will not be sought from the bidders. The bids will be evaluated as per the documents received from the bidders at the time of bid opening. Any bid, which is not supported with the requisite documents as per the NIT, will be rejected straightway without seeking any further clarification and deficit document.

Note:

- a) The Company's Internal Estimated Rates, as indicated in Part-II, are inclusive of all overheads, taxes, duties, levies etc. except P.F. & GST.
- b) Bidder must include all impale plant, labour, supervision, materials, erection of display board, sign/caution board, insurance, profit, taxes and duties, together with all general risks, liabilities and in their quoted rates excluding PF and GST.

(B). BID REJECTION CRITERIA (BRC):

- 1. The bids are to be submitted in single stage under composite bid system i.e. Un-priced Techno-Commercial Bid and Price Bid together. The overall price should be quoted under the "Total Bid Value" tab in the e-tender portal taking into account all liabilities including statutory liabilities in their quoted price (excluding PF and GST). The bidder must upload the Undertaking as prescribed in Proforma-I under the "Notes and Attachments" tab.
- 2. Bid Documents / User Id & Password for OIL's E-Tender portal are not transferable.
- 3. Any bid received in the form of Physical document/ Telex/Cable/Fax/E-mail will not be accepted.
- 4. Bidders must quote their total price under the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) tab within the permissible limit ('at par' to above 10% of Company's Internal Estimate); otherwise the bid will be rejected straightway. If a bidder wants to quote at 'at par' with the Company's Internal Estimate, he must declare the "Total Bid Value" equal to the tender value mentioned in the Covering Letter. If a bidder wants to quote above the Internal Estimate by certain percentage, he must declare the "Total Bid Value" equal to the sum of Internal Estimate and the desired percentage of Internal Estimate. If any bidder has quoted the total price above "at par" with Company's Internal Estimate within the permissible range, the percentage quoted above the internal estimate will be calculated and will be loaded accordingly in the rates of each and every items as specified in the Price Bid. All other techno-commercial documents other than price details to be submitted with Un-priced Techno-Commercial Bid as per tender requirement in the c-Folder link (collaboration link) under "Technical RFx Response" Tab Page only.
- 5. Bidders must accept and comply with the following provisions as given in the tender document. Deviations to such provisions shall make the bid liable for rejection.
 - a. Firm price
 - b. Scope of work
 - c. Specifications
 - d. Price schedule
 - e. Delivery / completion schedule
 - f. Period of validity of bidg. Liquidated Damages

 - h. Performance bank guarantee / Security deposit
 - i. Guarantee of material / work
 - Arbitration / Resolution of Dispute
 - k. Force Majeure
 - 1. Applicable Laws
 - m. Revised One Time Security Deposit
 - n. Integrity Pact

(C). GENERAL:

- Submission of Forged Documents: Bidders should note that Company may verify authenticity of all the documents /certificates / information submitted by the bidder(s) against the tender. In case at any stage of tendering process or Contract execution etc., if it is established that bidder has submitted forged documents / certificates / information towards fulfilment of any of the tender / contract conditions, Company shall immediately reject the bid of such bidder(s) or cancel / terminate the contract and forfeit EMD / SD submitted by the bidder(s), besides taking action as per OIL's Banning Policy dated 6th January 2017, available in the OIL's website.
- In case bidder takes exception to any clause of bidding document not covered under BEC/BRC, then ii the Company has the discretion to load or reject the offer on account of such exception if the bidder does not withdraw / modify the deviation when / as advised by company. The loading so done by the Company will be final and binding on the bidders. No deviation will however be accepted in the clauses covered under BRC.

BEC/BRC

- iii. To ascertain the substantial responsiveness of the bid the Company reserves the right to ask the bidder for clarification in respect of clauses covered under BEC/BRC also and such clarifications fulfilling the BEC/BRC clauses in toto must be received on or before the deadline given by the company, failing which the offer will be evaluated based on the submission. However, mere submission of such clarification shall not make the offer responsive, unless Company is satisfied with the substantial responsiveness of the offer.
- iv. If any of the clauses in the BEC/BRC contradicts with other clauses of Bidding document elsewhere, the clauses in the BEC/BRC shall prevail.
- v. Bidder(s) must note that requisite information/financial values etc. as required in the BEC/BRC & Tender are clearly understandable from the supporting documents submitted by the Bidder(s); otherwise Bids shall be rejected.
- vi. OIL will not be responsible for delay, loss or non-receipt of applications for participating in the bid sent by mail and will not entertain any correspondence in this regard.
- vii. If any of the clauses in the BEC/BRC contradicts with any of the clauses/disclaimer/guideline/user manual/report or any other field displayed in the e-tender portal, the clauses in the BEC/BRC shall prevail.

WORKS CONTRACT

DESCRIPTION OF WORK/SERVICES: Civil construction jobs to facilitate the relocation of gas lift compressor from GCS-Ushapur to GCS-Tengakhat.

- (1) Construction of Operator cum Maintenance Room.
- (2) Earth filling, brick soling & Cement Concrete work.
- (3) Extension of shed for Gas Lift Compressor.

offered

by

the

Company

GENERAL CONDITIONS OF CONTRACT (GCC)

MEMO	RANDUM OF	AGREEM	ENT made this	š	day of			betwee	en OIL
INDIA	LIMITED a	Company	incorporated	under the C	companies Act	1956 and 1	navinę	g its Reg	istered
Office	at Duliajan ii	n the Dist	rict of Dibrugar	h, Assam (hereinafter cal	lled Compa	ny)c	of the on	e part
and S	hri/Smti		and	Shri/Smti			_ carr	ying on bu	ısiness
as par	tners /proprie	etor under	the firm name	and style of	M/s		with	the main	Office
at _		in	the District of	f	·	aforesaid	(h	ereinafter	called
'Contr	actor') on the	other part.							
<u>WITN</u>	ESSETH:								
1.	a) The contr	actor here	by agrees to	carry out the	work set dow	n in the Scl	nedul	e of work v	which
forms	Part-II of this	s Contract	in accordance	with the 19	968 General C	onditions	of C	ontract o	f Oil
India	Limited and	General	Specifications	read in cor	njunction with	any drawi	ings a	and Parti	cular

b) In this Contract all words and expressions shall have the same meaning as are respectively assigned to them in the 1968 General Conditions of Contract of Oil India Limited which the Contractor has perused and is fully conversant with before entering into this Contract.

Specifications & instructions which forms Part-III of the contract utilizing any materials/services as

per

as

Part-IV

of

the

contract at

- c) The clauses of this contract and of the specifications set out hereunder shall be paramount and in the event of anything herein contained being inconsistent with any term or terms of the 1968 General Conditions of Contract of Oil India Limited, the said term or terms of the 1968 General conditions of Contract to the extent of such inconsistency, and no further, shall not be binding on the parties hereto.
- 2. i) The contractor shall provide all labour, supervision and transport and such specified materials described in Part-II of the Contract including tools and plants as necessary for the work and shall be responsible for all royalties and other levies and his rates shall include for these. The work executed and materials supplied shall be to the satisfaction of the Company's Engineer and Contractor's rates shall include for all incidental and contingent work which although not specifically mentioned in this contract are necessary for its completion in a sound and workman like manner
- ii) Contractor shall have to produce necessary cash memos towards forest produce used against the contract to HOD (Civil) used against this contract from the authorities prior to processing of final payment. In absence of cash memos, the final bill shall not be processed.
- **3.** The Company's Engineer shall have power to:
- a) Reduce the rates at which payments shall be made if the quality of work although acceptable is not up to the required standard set forth in the OIL Standard Specifications which have been perused and fully understood by the Contractor.
- b) Order the Contractor to remove any inferior material from the site and to demolish or rectify any work of inferior workmanship, failing which the Company's Engineer may arrange for any such work to be demolished or rectified by any other means at the Contractor's expenses.
- c) Order the Contractor to remove or replace any workman/ supervisor/ engineer/ project-in-charge or any other contactor's personnel who he (The Engineer) considers incompetent or unsuitable; the

Contractor 1 Company

Engineer's opinion as to the competence and suitability of any personnel engaged by the Contractor shall be final and binding on the Contractor.

- d) Issue to the Contractor from time to time during the progress of the work such further drawings and instructions as shall be necessary for the purpose of proper and adequate execution and maintenance of the works and the Contractor shall carry out and be bound by the same.
- e) Order deviations in Part II and III of this Contract. All such deviation orders shall be in writing and shall show the financial effect, if any, of such deviation and whether any extra time is to be allowed. The rates to be applied for such Deviation Order shall be the same for those appearing in Company's Schedule of Rate in force on the date of issue of such Deviation Order, to which the contractor has no objection.
- **4.** The Contractor shall have no claim against the Company in respect of any work which may be withdrawn but only for work actually completed under this contract. The contractor shall have no objection to carry out work in excess of the quantities and items stipulated in Part-II (SOQ). In case of positive variation in quantities of any items from the quantity mentioned in the tender / contract, the contractor will have to carry out the positive varied quantity at the contract rate, or the internally estimated rate, whichever is lower.

However, during the actual execution of the contract, if the contract is to be utilised in a different zone due to Company's operational requirement, and accordingly if the rates of the contractual items are different as in OIL's Schedule of Rates (SOR), then the rates as per the actual zone of execution will be applicable for the contractual items and shall be adopted from the same OIL's SOR which has been adopted in the tender. In that case, the rates shall be applicable for both the contractual quantities as well as for the additional quantities, if required to be executed.

If any additional items (items not covered in the tender / contract) are required to be executed during actual execution of works, the payment of such items shall be made as per the rates of OIL Schedule of Rates (SOR) prevailing in the working zone (the zone where the contract is utilized) at the time of issuance of advice by Company to execute such additional items.

- 5. The Company reserves the right to cancel this Contract at any time upon full payment of work done and the value of the materials collected by the contractor for permanent incorporation in the work under this contract particularly for execution of this contract up to the date of cancellation of the Contract. The valuation of the work done and the materials collected shall be estimated by the company's Engineer in presence of the contractor. The Contractor shall have no claim to any further payment whatsoever. The valuation would be carried out exparte if Contractor fails to turn up despite reasonable notice which will be binding on the Contractor.
- **6.** The Contractor hereby undertakes to indemnify the Company against all claims which may arise under the under noted Acts:-
 - I. The Mines Act.
 - II. The Minimum Wages Act, 1948.
 - III. The Workman's Compensation Act, 1923.
 - IV. The Payment of wages Act, 1963.
 - V. The Payment of Bonus Act, 1965.
 - VI. The Contract Labour (Regulation & Abolition) Act, 1970 and the rules framed there under.
 - VII. Employees' Pension Scheme, 1995.
 - VIII. Inter-State Migrant (Regulation of Employment and Condition of Service) Act. 1979.
 - IX. The Employees Provident Fund and Miscellaneous Provisions Act, 1952.
 - X. Goods and Service Tax (GST) Law,

or any other Acts or Statute not here in above specifically mentioned having bearing over engagement of workers directly or indirectly for execution of work. The Contractor shall not make the Company liable to reimburse the Contractor for the statutory increase in the wage rates of the Contract Labour appointed by the Contractor. Such Statutory increase in the wage rates of Contract Labour shall be borne by the contractor.

- **7.** The Contractor shall clear away all rubbish and surplus material from the site on completion of work and shall leave the site clean and tidy.
- **8.** The Contractor must complete the work within 78 weeks of the written order to commence work. During the currency of the job, the work progress must be commensurate with the time elapsed. In the

Contractor 2 Company

event of any delay on the contractor's part, he/she will be liable to pay to the company liquidated damages at the rate of 1/2% (Half percent) per week of the contract price of the item(s) delayed in completion and the maximum value of the liquidated damage will be 7.5% of the contract price of the item(s) delayed provided the item(s) delayed are not critical for commissioning and final utilization of the work. If, however, the item(s) delayed in completion are critical for commissioning and final utilisation of the work then the contractor will be liable to pay liquidated damages by way of penalty at the rate of 1/2% (Half percent) per week of delay of the total contract cost subject to a maximum of 7.5% of total contract cost.

The HOD-Civil's certificate as to the criticality or otherwise of an item shall be final.

The payment of liquidated damages/penalty may be reduced or waived at the sole discretion of the Company whose decision in this regard will be final.

In the event of there being undue delay in execution of the Contract, the Company reserves the right to cancel the Contract and / or levy such additional damages as it deems fit based on the actual loss suffered by the company attributable to such delay. The company's decision in this regard shall be final.

- **9.** In order to promote, safeguard and facilitate the general operational economic in the interest of the Company during the continuance of this contract the Contractor hereby agrees and undertakes not to take any direct or indirect interest and or support, assist, maintain or help any person or persons engaged in antisocial activities, demonstration, riots, or in any agitation prejudicial to the Company's interest and any such even taking shape or form at any place of the Company's works or and its neighbourhood.

On account payment may be made, not oftener than monthly, up to the amount of 97% of the value of work done. Final payment will be made only after satisfactory completion of the work. Such final payment shall be based on the work actually done allowing for deviations and any deductions and the measurement shall be checked and certified correct by the Company's Engineer before any such final payment is made.

- 11. The contractor employing 20 (twenty) or more workmen on any day preceding 12 months shall be required to obtain requisite licence at his cost from the appropriate Licensing Officer before undertaking any Contract work. The Contractor shall also observe the rules & regulations framed under the Contract Labour (Regulation & Abolition) Act.
- **12.** Wages shall be paid by the Contractor to the workmen directly without any intervention of any Jamadars or Thekaders and that the Contractor shall ensure that no amount by way of commission or otherwise be deducted/recovered by the Jamadar from the wages of the workmen.
- **13.** The Company for any reason whatsoever and of which the company shall be sole judge may terminate this Contract with a 24 hours notice in writing to the Contractor and in the event of Company's so doing the clause 5 here of shall prevail and the accounts between the parties will be in accordance therewith finalised.
- **14.** The Contractor will not be allowed to construct any structure (for storage / housing purpose) with thatch, bamboo or any other inflammable materials within any company's fenced area.
- **15.** The Contractor shall ensure that all men engaged by him/her are provided with appropriate protective clothing and safety wear in accordance with the Oil Mines Regulations 2017. The Company's representative shall not allow/accept those men who are not provided with the same.
- **16.** All Statutory taxes levied by the Central and State Government or any other competent authority from time to time, except PF & GST, will be borne by Contractor and the contract cost is inclusive of all tax liabilities except PF & GST. However, any subsequent increase in such statutory taxes after bid

Contractor 3 Company

opening day will be borne by the Company. Similarly if there is any decrease in such statutory taxes after bid opening, the Company shall recover the decreased amount of such taxes from the contractor.

- **17.** The Contractor shall deploy local persons in all works.
- **18.** The Contractor shall not engage minor labour below 18(eighteen) years of age under any circumstances.
- **19.** The Contractor and his/her workmen shall strictly observe the rules and regulations as per Mines Act (Latest editions).

20. SPECIAL CONDITIONS:

a) The Contractor shall obtain and submit the Labour Clearance Advice (LCA) / Labour Clearance Certificate (LCC) within 14 days of signing the contract agreement. If the contractor fails to submit the LCA / LCC within 14 days of signing the contract agreement, the period of delay in submission of LCA / LCC shall be deducted from the contractual period while issuing the work order. In such cases, the time period mentioned in Clause No. 8 of GCC (Part-I of this contract) shall not be applicable and the contactor must complete the work within the reduced time period allotted to the contractor as per the work order issued.

However, if submission of LCA / LCC is delayed, under some exceptional circumstances, for any reason not attributable to the contractor, the same should be recorded by the contractor with documentary proof. In such cases, the decision as to whether the reason of delay is attributable to the contractor or not shall be taken by the Head of Civil Engineering Department and the work order will be issued accordingly.

- b) Retention Money @ 3 % will be kept as Performance Security Deposit against the contract and will be deducted from the running bill. The amount of retention money shall be released after 6(six) months from the actual date of completion of the work. A part or whole of retention money shall be used by the Company in realisation of liquidated damage or claims, if any, or for adjustment of compensation or loss due to the Company for any reason. The retention money shall not earn any interest.
- c) The contractor will be required to allow OIL Officials to inspect the work site and documents in respect of the workers' payment.
- d) Contractor(s) whosoever is liable to be covered under the P.F. Act and contract cost is inclusive of P.F., must ensure strict compliance of provisions of Provident Fund and Miscellaneous Provisions Act, 1952 in addition to the various Acts mentioned elsewhere in this contract. Any contractor found violating these provisions will render themselves disqualified from any future tendering. As per terms of the contract, if applicable, the Contractor must deposit Provident Fund Contribution (covering Employee's & employer's share) with the competent authority monthly under their direct code. The Contractor shall be required to submit documentary evidence of deposit of P.F. Contribution to the Company. In case of failure to provide such documentary evidence, the Company reserves the right to withhold the amount equivalent to P.F. Contribution on wage component.
- e) The Contract cost is excluding P.F. & GST. The P.F deposited by the Contractor, will be reimbursed on production of documentary evidence of depositing the same to the authority concerned. 12% P.F. will be applicable on the wage component of the contract cost. Wage component of the Contract cost is 37.46 %.
- f) All safety precautions to be maintained by the Contractor at his own cost as per safety rules and regulations.
- g) The Contractor shall use pump if needed for dewatering of pit while excavation for which no extra payment will be made.
- h) The Contractor shall have to work during rainy seasons also.
- i) Watch and ward, loss or damage to Company's property, theft and other incidental charges shall be Contractor's responsibility.
- j) Efficient workmen to be engaged by the Contractor.

Contractor 4 Company

- k) The Contractor's representative should report to Engineer-in-charge on all working days at 7.00 A.M. and 3.00 P.M. for instructions.
- l) Materials if rejected should be removed from site within 48 (forty- eight) hours of rejection, failing which the Company reserves the right to get the rejected materials removed at the risk and cost of the Contractor.
- m) The Company reserves the right to get the part or whole work complete at the risk and cost of the Contractor if he fails to complete the work within the stipulated time without any valid reason. The Company's decision shall be final and binding on the Contractor.
- n) Water that may accumulate on the site during progress of the works or in trenches and excavations from other than accepted risks shall be removed from the site to entire satisfaction of the Engineer-incharge and at the Contractor's expense.
- o) The Contractor shall be in a position to execute 2(two) locations simultaneously.
- p) If required, the Contractor shall have to work in two shifts for which no extra payment will be admissible to him/them.
- q) If needed water and electricity will have to be arranged by the Contractor at his own cost.
- r) The Contractor and his workmen are to strictly observe the safety precautionary rules as per Mines Act (Latest edition) while executing the work.
- s) The Contractor shall have to provide temporary latrine facilities in the entire work site for use of their workmen during progress of work.
- t) The contractor himself (the signatory of the contract) must visit the site at least twice in a week as fixed for taking necessary instruction from the Engineer-in charge.
- u) The program of works to be submitted in the form of Bar Chart within 3 days of receipt of work order.

21. SPECIAL INSTRUCTION

The contractor must quote considering the prevailing minimum Labour wage rate for each day of work.

22. GOODS AND SERVICES TAX (GST) CLAUSES UNDER GCC

22.1 GENERAL REMARKS ON TAXES & DUTIES:

In view of **GST** Implementation from 1st July 2017, all taxes and duties including Excise Duty, CST/VAT, Service tax, Entry Tax and other indirect taxes and duties have been submerged in **GST**. Accordingly reference of Excise Duty, Service Tax, VAT, Sales Tax, Entry Tax or any other form of indirect tax except of **GST** mentioned in the bidding document shall be ignored.

- **22.2** Bidders are required to submit copy of the GST Registration Certificate while submitting the bids wherever **GST** (CGST & SGST/UTGST or IGST) is applicable.
- **22.3** "**GST**" shall mean Goods and Services Tax charged on the supply of material(s) and services. The term "**GST**" shall be construed to include the Integrated Goods and Services Tax (hereinafter referred to as "IGST") or Central Goods and Services Tax (hereinafter referred to as "CGST") or State Goods and Services Tax (hereinafter referred to as "SGST") or Union Territory Goods and Services Tax (hereinafter referred to as "UTGST") depending upon the import / interstate or intrastate supplies, as the case may be. It shall also mean GST compensation Cess, if applicable.
- Quoted price/rate(s) should be inclusive of all taxes and duties, except GST (i.e. IGST or CGST and SGST/UTGST applicable in case of interstate supply or intra state supply respectively and cess on GST if applicable) on the final service. Please note that the responsibility of payment of GST (CGST & SGST or IGST or UTGST) lies with the Supplier of Goods / Services (Service Provider) only. Supplier of Goods / Services (Service Provider) providing taxable service shall issue an Invoice/ Bill, as the case may be as per rules/ regulation of GST. Further, returns

Contractor 5 Company

and details required to be filed under GST laws & rules should be timely filed by Supplier of Goods / Services (Service Provider) with requisite details.

22.5 Where OIL is entitled to avail the input tax credit of GST:

OIL will reimburse the **GST** to the Supplier of Goods / Services (Service Provider) at actuals against submission of Invoices as per format specified in rules/ regulation of GST to enable OIL to claim input tax credit of **GST** paid. In case of any variation in the executed quantities, the amount on which the **GST** is applicable shall be modified in same proportion. Returns and details required to be filed under GST laws & rules should be timely filed by supplier with requisite details.

22.6 Where OIL is not entitled to avail/take the full input tax credit of GST:

OIL will reimburse **GST** to the Supplier of Goods / Services (Service Provider) at actuals against submission of Invoices as per format specified in rules / regulation of **GST**.

- **22.7** Payments to Service Provider for claiming **GST** amount will be made provided the above formalities are fulfilled. Further, OIL may seek copies of challan and certificate from Chartered Accountant for deposit of **GST** collected from OIL.
- **22.8** Contractor/vendor shall be required to issue tax invoice in accordance with GST Act and/or Rules so that input credit can be availed by OIL. In the event that the contractor / vendor fails to provide the invoice in the form and manner prescribed under the GST Act read with GST Invoicing Rules thereunder, OIL shall not be liable to make any payment on account of **GST** against such invoice.
- **22.9 GST** shall be paid against receipt of tax invoice and proof of payment of **GST** to government. In case of non-receipt of tax invoice or non-payment of **GST** by the contractor/vendor, OIL shall withhold the payment of **GST**.
- **22.10 GST** payable under reverse charge mechanism for specified services or goods under GST act or rules, if any, shall not be paid to the contractor/vendor but will be directly deposited to the government by OIL.
- **22.11** Where OIL has the obligation to discharge **GST** liability under reverse charge mechanism and OIL has paid or is /liable to pay **GST** to the Government on which interest or penalties becomes payable as per GST laws for any reason which is not attributable to OIL or ITC with respect to such payments is not available to OIL for any reason which is not attributable to OIL, then OIL shall be entitled to deduct/ setoff / recover such amounts against any amounts paid or payable by OIL to Contractor / Supplier.
- 22.12 Notwithstanding anything contained anywhere in the Agreement, in the event that the input tax credit of the **GST** charged by the Contractor / Vendor is denied by the tax authorities to OIL for reasons attributable to Contractor / Vendor, OIL shall be entitled to recover such amount from the Contractor / Vendor by way of adjustment from the next invoice. In addition to the amount of **GST**, OIL shall also be entitled to recover interest at the rate prescribed under GST Act and penalty, in case any penalty is imposed by the tax authorities on OIL.
- **22.13** TDS under GST, if applicable, shall be deducted from contractor's/vendor's bill at applicable rate and a certificate as per rules for tax so deducted shall be provided to the contractor/vendor.
- **22.14** The Contractor will be under obligation for charging correct rate of tax as prescribed under the respective tax laws. Further the Contractor shall avail and pass on benefits of all exemptions/concessions available under tax laws. Any error of interpretation of applicability of taxes/ duties by the contractor shall be to contractor's account.
- **22.15** Further, it is the responsibility of the bidders to make all possible efforts to make their accounting / IT system GST compliant in order to ensure availability of Input Tax Credit (ITC) to Oil India Ltd.

Contractor 6 Company

22.16 Beyond the contract period, in case OIL is not entitled for input tax credit of **GST**, then any increase in the rate of **GST** beyond the contractual delivery period (in case the delay is attributable to the service provider), shall be to Service provider's account whereas any decrease in the rate of **GST** shall be passed on to the OIL.

Beyond the contract period, in case OIL is entitled for input tax credit of **GST**, then statutory variation in applicable **GST** on supply and on incidental services, shall be to OIL's account.

Claim for payment of **GST**/ Statutory variation, should be raised within two [02] months from the date of issue of 'Government Notification' for payment of differential (in %) **GST**, otherwise claim in respect of above shall not be entertained for payment of arrears.

22.17 The contractor will be liable to ensure to have registered with the respective tax authorities, wherever applicable, and to submit self-attested copy of such registration certificate(s) and the Contractor will be responsible for procurement of material in its own registration (GSTIN) and also to issue its own Road Permit/ E-way Bill, if applicable etc.

22.18 Documentation requirement for GST

The vendor will be under the obligation for invoicing correct tax rate of tax/duties as prescribed under the GST law to OIL, and pass on the benefits, if any, after availing input tax credit.

Any invoice issued shall contain the following particulars

- a) Name, address and GSTIN of the supplier;
- b) Serial number of the invoice;
- c) Date of issue;
- d) Name, address and GSTIN or UIN, if registered of the recipient;
- e) Name and address of the recipient and the address of the delivery, along with the State and its code,
- f) HSN code of goods or Accounting Code of services[SAC];
- g) Description of goods or services;
- h) Quantity in case of goods and unit or Unique Quantity Code thereof;
- i) Total value of supply of goods or services or both;
- j) Taxable value of supply of goods or services or both taking into discount or abatement if any;
- k) Rate of tax (IGST, CGST, SGST/ UTGST, cess);
- l) Amount of tax charged in respect of taxable goods or services (IGST,CGST, SGST/UTGST, cess);
- m) Place of supply along with the name of State, in case of supply in the course of interstate trade or commerce;
- n) Address of the delivery where the same is different from the place of supply and
- o) Signature or digital signature of the supplier or his authorised representative.

 GST invoice shall be prepared in triplicate, in case of supply of goods, in the following manner
 - i. The original copy being marked as ORIGINAL FOR RECIPIENT;
 - ii. The duplicate copy being marked as DUPLICATE FOR TRANSPORTER and
 - iii. The triplicate copy being marked as TRIPLICATE FOR SUPPLIER.

22.19 ANTI-PROFITEERING CLAUSE

In case the GST rating of vendor on the GST portal / Govt. official website is negative / black listed, then the bids may be rejected by OIL. Further, in case rating of bidder is negative / black listed after award of work for supply of goods / services, then OIL shall not be obligated or liable to pay or reimburse GST to such vendor and shall also be entitled to deduct / recover such GST along with all penalties / interest, if any, incurred by OIL.

22.20 OIL will prefer to deal with registered bidder under GST. Therefore, bidders are requested to get themselves registered under GST, if not registered yet.

23. ARBITRATION:

Any dispute under this contract will be settled through Arbitration as per Indian Arbitration and Conciliation Act, 1996.

Place of Arbitration: Duliajan, Dibrugarh, Assam.

24. FORCE MAJEURE:

Contractor 7 Company

In the event of either party being rendered unable by 'Force Majeure' to perform any obligation required to be performed by them under the contract, the relative obligation of the party affected by such 'Force Majeure' will stand suspended as provided herein. The term force majeure as employed herein shall mean Acts of God such as earthquake, hurricane, typhoon, flood, volcanic activity etc.; war (declared / undeclared); riot, revolts, rebellion, terrorism, sabotage by persons other than the CONTRACTOR's Personnel; fires, explosions, ionising radiation or contamination by radio-activity or noxious gas, if not caused by CONTRACTOR's fault; declared epidemic or disaster; acts and regulations of respective Govt. of the two parties, namely the COMPANY and the CONTRACTOR and civil commotions, lockout not attributable to the CONTRACTOR.

Upon occurrence of such cause, the party claiming that it has been rendered unable as aforesaid thereby, shall notify the other party in writing within 72 (Seventy Two) hours of the alleged beginning and ending thereof, giving full particulars and satisfactory evidence in support of its claim.

Should 'force majeure' condition as stated above occurs and should the same be notified within 72 (Seventy two) hours after its occurrence the `force majeure' rate (if specified in the SCC of the Contract) shall apply for the first 15 (fifteen) days for each such occasion.

Either party shall have the right to terminate the Contract if such 'force majeure' conditions continue beyond successive 60 (Sixty) days [or exclusively mentioned in the SCC of the Contract] with prior written notice of 15 days, provided termination of the Contract does not result into safety hazard to the life and property on account of withdrawal of operations or the operation is at critical stage. COMPANY shall have the absolute right to decide whether any safety hazard exists or operation is at critical position and decision of the COMPANY shall binding upon the CONTRACTOR.

Should either party decide not to terminate the Contract even under such condition, no payment would apply after expiry of fifteen (15) days force majeure period. [or exclusively mentioned in the SCC of the Contract]

Time for performance of the relative obligation suspended by Force Majeure shall then stand extended by the period for which such cause lasts.

If however, relative obligation of the party affected by such 'Force Majeure' is limited to part of the obligation(s), the contract shall not be terminated and the parties shall continue to perform their respective obligations, which are not affected by the 'force majeure' condition, provided the obligations affected by the 'force majeure' do not preclude the parties in performing the obligations not affected by such conditions.

25. I.B. VERIFICATION REPORT AND SECURITY REVIEW:

Contractor will be required to submit the verification report to ascertain character and antecedents from the Civil Administration towards the persons engaged under this contract to the Head of the user Department before engagement.

26. In case of any doubt or dispute as to the interpretation of any clause herein contained, the decision of the Company's Engineer shall be final and binding on the contractor.

27. SET OFF CLAUSE:

"Any sum of money due and payable to the contractor (including Security Deposit refundable to them) under this or any other contract may be appropriated by Oil India Limited and set off against any claim of Oil India Limited (or such other person or persons contracting through Oil India Limited) for payment of a sum of money arising out of this contract or under any other contract made by the contractor with Oil India Limited (or such other person or persons contracting through Oil India Limited)."

28. COMMISSION OF MISCONDUCT / SUBMISSION OF FRAUDULENT DOCUMENT BY THE BIDDER/CONTRACTOR AND BANNING THEREOF: The information and documents furnished by the bidder/CONTRACTOR in respect of the tender/contract are accepted by COMPANY to be true and genuine. However, if it comes to the notice of the COMPANY anytime either during the pendency of the tender or after award of the contract or after completion the contract that a Bidder/CONTRACTOR furnished fraudulent document/false information in relation to the subject tender/contract or committed any misconduct, appropriate action shall be taken against the Bidder/CONTRACTOR for debarment/banning of the bidder/CONTRACTOR from participating in any future tender of the COMPANY in terms of the COMPANY's Banning Policy, 2017 besides making the CONTRACTOR liable for other penal action including termination of ongoing contract(s) at his/her risk and peril. In such

Contractor 8 Company

event, the Bid Security/Performance Security in respect of ongoing contract(s) shall be forfeited by the COMPANY.

29. ERRING / DEFAULTING AGENCIES: Erring and defaulting agencies like bidder, contractor, supplier, vendor, service provider will be dealt as per OIL's Banning Policy dated 6th January, 2017 available in OIL's website: www.oil-india.com. Moreover, OIL reserves the right to take legal or any other action on the basis of merit of the case.

30. TERMINATION:

- a) **Termination on expiry of the contract:** This Agreement shall be deemed to have been automatically terminated on the expiry of the contract period unless OIL has exercised its option to extend this contract in accordance with the provisions, if any, of this contract.
- b) **Termination of contract for death:** If the CONTRACTOR is an individual or a proprietary concern and the individual or the proprietor dies or if the CONTRACTOR is a partnership concern and one of the partners dies then unless, the COMPANY is satisfied that the legal heir of the individual or the proprietary concern or the surviving partners are capable of carrying out and completing Contract, the COMPANY is entitled to cancel the Contract for the uncompleted part without being in any way liable for any compensation payment to the estate of the deceased CONTRACTOR and/or to the surviving partners of the CONTRACTOR's firm on account of the cancellation of Contract. The decision of the COMPANY in such assessment shall be final & binding on the parties. In the event of such cancellation, the COMPANY shall not hold the estate of the deceased CONTRACTOR and/or the surviving partners of CONTRACTOR's firm liable for any damages for non-completion of the Contract.
- c) **Termination on account of Force Majeure:** Unless the contract provides otherwise, either party shall have the right to terminate this Contract on account of Force Majeure as set forth in Article-24.0 above.
- d) **Termination on account of insolvency:** In the event that the CONTRACTOR or its collaborator or its guarantor at any time during the term of the Contract, becomes insolvent or makes a voluntary assignment of its assets for the benefit of creditors or is adjudged bankrupt or under the process of insolvency or liquidation, then the COMPANY shall, by a notice in writing have the right to terminate the Contract and all the CONTRACTOR's rights and privileges hereunder, shall stand terminated forthwith.
 - However, COMPANY shall be at liberty to give the Receiver or Liquidator or Insolvency Professional Manager, as appointed by the Competent Court/Tribunal, the option of carrying out the Contract subject to its technical & financial competence and his providing a guarantee for due and faithful performance of the Contract.
- e) **Termination for Unsatisfactory Performance:** If the COMPANY considers that, the performance of the CONTRACTOR is unsatisfactory, or not as per the provision of the Contract, the COMPANY shall notify the CONTRACTOR in writing and specify in details the cause of dissatisfaction. The COMPANY shall have the option to terminate the Contract by giving 15 days' notice in writing to the CONTRACTOR, if CONTRACTOR fails to comply with the requisitions contained in the said written notice issued by the COMPANY. In the event CONTRACTOR rectifies its non-performance to the satisfaction of the COMPANY, the option of termination may not be exercised by the COMPANY. If however CONTRACTOR repeats non-performance subsequently, COMPANY shall exercise the option to terminate contract by giving 07 days' notice. Such CONTRACTOR shall be put on holiday as per the Banning Policy of OIL [available at www.oil-india.in].
- f) **Termination due to change of ownership and Assignment:** In case the CONTRACTOR's rights and /or obligations under this Contract and/or the CONTRACTOR's rights, title and interest to the equipment/ material, are transferred or assigned without the COMPANY's written consent, the COMPANY may at its option, terminate this Contract. COMPANY shall not be however under any obligation to accord consent to the CONTRACTOR for change of ownership & assignment of the contract.
- g) If at any time during the term of this Contract, breakdown of CONTRACTOR's equipment results in CONTRACTORs being unable to perform their obligations hereunder for a period of 15 successive days, COMPANY at its option, may terminate this Contract in its entirety or partially to the extent

Contractor 9 Company

of non-performance, without any further right or obligation on the part of the COMPANY, except for the payment of money then due. No notice shall be served by the COMPANY under the condition stated above.

- h) Notwithstanding any provisions herein to the contrary, the Contract may be terminated at any time by the COMPANY on giving 30 (thirty) days written notice to the CONTRACTOR due to any other reason not covered under the above Article from (a) to (g) and in the event of such termination the COMPANY shall not be liable to pay any cost or damage to the CONTRACTOR except for payment of services as per the Contract upto the date of termination.
- i) **Consequence of Termination:** In all cases of termination herein set forth, the relative obligations of the parties to the Contract shall be limited to the period up to the date of termination. Notwithstanding the termination of this Contract, the parties shall continue to be bound by the provisions of this Contract that reasonably require some action or forbearance after such termination.

Upon termination of this Contract, CONTRACTOR shall return to COMPANY all of COMPANY's properties, which are at the time in CONTRACTOR's possession.

In the event of termination of contract, COMPANY will issue Notice of termination of the contract with date or event after which the contract will be terminated. The contract shall then stand terminated and the CONTRACTOR shall demobilize their personnel & materials. No demobilization charges shall be payable by COMPANY in case of Article from (d) to (g).

IN WITNESS whereof the parties hereunto set their hands seals the day and year first written above:-

(Signature of Acceptor)	
Address:	
(Full name of Signatory)	
(Signature of witness)	
(Seal of Contractor's firm)	
(Full name of signatory)	
(Signature of Contractor or his legal Attorney	·/)

Designation: -----

Contractor 10 Company

WORKS CONTRACT SCHEDULE OF WORK, UNIT AND QUANTITY

SL. NO.	DESCRIPTION OF SERVICE	UOM	QUANTITY	UNIT PRICE	TOTAL
	GROUP A SEC A				
1	:Surface dressing of the ground including removing vegetation andinequalities not exceeding 15 cm deep and disposal of rubbish, leadupto 50 m and lift upto 1.5 m.All kinds of soil	M2	400.00	16.32	6528.00
2	Earth work in excavation of foundation of structures as perdrawing and technical specification, including setting out, construction of shoring and bracing, removal of stumps and other deleterious matter, dressing of sides and bottom, backfilling the excavation earth to the extent required and utilising the remaining earth locally for roadwork.) for Ordinary Soil by Manual Means (Depth upto 3 m)	М3	26.67	419.26	11181.66
3	:Collecting / excavating sand, soil, silt, ordinary earth from anysource, load into lorries, transport it to distant place of workincluding procuring earth and laying in layer of 150mm thickness andcompacting, profile properly made for taking measurement, including allmeasurable lead upto 30m and lift as required. (The contractor shall beresponsible for all formalities of supply of earth such as purchase ofland including royalties, monopoly / other statutory taxes as required from any distance.)	M3	38.36	417.56	16017.60
4	:Laying damp-proof course 40mm thick with cement concrete 1:2:4 (1cement: 2 coarse sand : 4 graded stone aggregate 12.5mm nominal size).	M2	13.52	118.70	1604.82
5	Laying Brick Flat Soling (75mm thick) including grading the baseand spreading 25mm thick sand bed at bottom and grouting solingwith cement mortar (prop. 1:3) and carrying all materials from adistance of upto 30.00m.	M2	60.12	149.22	8971.11
6	:Laying in position cement concrete of specified grade excluding thecost of centring and shuttering - All work upto plinth level: 1:3:6 (1Cement: 3 coarse sand : 6 graded stone aggregate 20 mm nominal size)	М3	8.88	1417.81	12590.15
7	:Laying in position specified grade of reinforced cement concreteexcluding the cost of centring, shuttering, finishing and reinforcement- All work upto plinth level: 1:1.5:3 (1 cement: 1.5 coarse sand: 3graded stone aggregate 20 mm nominal size)	М3	7.00	1767.45	12372.15
8	:Reinforced cement concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. upto floorfive level excluding cost of centring, shuttering, finishing andreinforcement: 1:1.5:3 (1 cement: 1.5 coarse sand: 3 graded stoneaggregate 20 mm nominal size)	M3	2.51	2880.42	7229.85
9	:Reinforced cement concrete work in beams, suspended floors, roofshaving slope upto 15° landings, balconies, shelves, chajjas, lintels,bands, plain window sills, staircases and spiral stair cases upto floorfive level excluding the cost of centring, shuttering, finishing andreinforcement with 1:2:4 (1 cement : 2 coarse sand : 4 graded stoneaggregate 20 mm nominal size).	М3	14.39	3142.92	45226.62
10	:Centring and shuttering including strutting, propping etc. and removalof form for : Foundations, footings, bases of columns, etc. for massconcrete.	M2	32.54	165.43	5383.09
11	:Centring and shuttering including strutting, propping etc. and removalof form for: Suspended floors, roofs, landings, balconies and accessplatform.	M2	95.73	465.77	44588.16
12	:Centring and shuttering including strutting, propping etc. and removaof form for: Lintels, beams, plinth beams, girders, bressumers and cantilevers.	M2	42.53	355.22	15107.51
13	:Centring and shuttering including strutting, propping etc. and removalof form for: Columns, Pillars, Piers, Abutments, Posts and Struts.	M2	44.32	481.44	21337.42
14	:Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete. Thermo-Mechanically Treated bars	KG	2800.29	70.74	198092.51
15	:Brick work with F.P.S. bricks of class designation 75 infoundation and plinth in: Cement mortar 1:4 (1 cement : 4 coarse sand)	МЗ	28.71	1490.30	42786.51

SL. NO.	DESCRIPTION OF SERVICE	UOM	QUANTITY	UNIT PRICE	TOTAL
16	:Brick work with F.P.S. bricks of class designation 75 insuperstructure above plinth level up to floor V level in all shapes andsizes in : Cement mortar 1:4 (1 cement : 4 coarse sand)	МЗ	16.14	2492.22	40231.91
17	:Wood work in frames of doors, windows, clerestory windows and otherframes, wrought framed and fixed in position :Kiln seasoned andchemically treated Hollock wood.	М3	0.35	14491.39	5071.99
18	:Fixing ISI marked flush door shutters conforming to IS: 2202 (Part I)decorative type, core of block board construction with frame of 1 stclass hard wood and well matched teak 3 ply veneering with verticalgrains or cross bands and face veneers on both faces of shutters.35mmthick including ISI marked Stainless Steel butt hinges with necessaryscrews.	M2	12.30	318.19	3913.74
19	:Fixing bright finished brass 100mm mortice latch and lock with 6 leversand a pair of lever handles with necessary screws etc. complete (bestmake of approved quality).	EA	7.00	149.44	1046.08
20	:Fixing bright finished brass hanging type floor door stopper withnecessary screws, etc. complete.	EA	7.00	3.12	21.84
21	:Fixing IS: 3564 marked Aluminium die cast body tubular type universalhydraulic door closer with necessary accessories and screws etc.complete.	EA	7.00	71.58	501.06
22	:Fixing IS : 12817 marked stainless steel butt hinges with stainlesssteel screws etc. complete: 125x64x1.90mm	EA	28.00	15.04	421.12
23	Laying Vitrified tiles in different sizes (thickness to be specified bymanufacturer), with water absorption less than 0.08 % and conforming toI.S. 15622, of approved make, in all colours & shade, in skirting, riserof steps, over 12 mm thick bed of cement mortar 1:3 (1cement: 3 coarsesand), including grouting the joint with white cement & matchingpigments etc. complete. Size of Tile 600x600 mm	M2	106.63	425.09	45327.35
24	:12mm cement plaster of mix:1:4 (1 cement : 4 coarse sand)	M	24.00	97.20	2332.80
25	:Fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A including jointing with seal ring conforming to IS:5382 leaving 10 mm gap for thermal expansion, (i) Single socketedpipes-110 mm dia	EA	12.00	31.41	376.92
26	:Fixing on wall face unplasticised - PVC moulded fittings/accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592Type A including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansionBend 87.5°-110 mm Bend	EA	24.00	183.60	4406.40
27	:Fixing unplasticised -PVC pipe clips of approved design tounplasticised - PVC rain water pipes by means of 50x50x50mm hard woodplugs,screwed with M.S. screws of required length including cuttingbrick work and fixing in cement mortar 1:4(1 cement: 4 coarse sand) andmaking good the wall etc. complete110 mm	M2	354.51	145.14	51453.00
28	:6mm cement plaster of mix:1:3 (1 cement : 3 fine sand)	M2	136.68	134.01	18316.49
29	:Applying one coat of cement primer of approved brand and manufacture onwall surface:Cement primer	M2	305.85	41.84	12796.76
30	:Finishing walls with Acrylic Smooth exterior paint of required shade:New work (Two or more coat applied @ 1.67 ltr/10 sqm over and includingbase coat of water proofing cement paint applied @ 2.20 kg/10 sqm).	M2	96.31	64.29	6191.77
31	Application of white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface toprepare the surface even and smooth complete	M2	305.85	70.04	21421.73
32	Wall painting with acrylic emulsion paint, having VOC (Volatile OrganicCompound)content less than 50 grams/ litre, of approved brand andmanufacture, including applying additional coats wherever required, toachieve even shade and colour: Two Coats	M2	305.85	71.21	21779.58
33	:Fixing white vitreous china pedestal type water closet (European typeW.C. pan) with seat and lid, 10 litre low level white P.V.C. flushingcistern with manually controlled device (handle lever), conforming to IS: 7231, with all fittings and fixtures complete including cutting andmaking good the walls and floors wherever required:W.C. pan with ISImarked white solid plastic seat and lid	EA	2.00	2076.92	4153.84
34	:Fixing wash basin with C.I. brackets, 15mm C.P. brass pillar taps,32mmC.P. brass waste of standard pattern, including painting of fittings andbrackets, cutting and making good the walls wherever require:WhiteVitreous China Wash basin size 630x450mm with a pair of 15mm C. P. brasspillar taps.	EA	2.00	1045.22	2090.44

	PRODUCTION OF CERTAIN	11036		art-ir S	
SL. NO.	DESCRIPTION OF SERVICE	UOM	QUANTITY	UNIT PRICE	TOTAL
35	:Fixing Stainless Steel A ISI 304 (18/8) kitchen sink as per IS 13983with C.I. brackets and stainless steel plug 40mm including painting offittings and brackets, cutting and making good the walls whereverrequired:Kitchen sink with drain board :510x1040mm bowl depth 250mm.	EA	1.00	1247.27	1247.27
36	:Fixing white vitreous china flat back or wall corner type lipped fronturinal basin of 430x260x350mm and 340x410x265mm sizes respectively.	EA	2.00	527.41	1054.82
37	:Fixing G.I. pipes complete with G.I. fittings including trenching andrefilling etc.:15mm dia. nominal bore	EA	2.00	411.61	823.22
38	:Fixing mirror of superior glass (of approved quality) and of requiredshape and size with plastic moulded frame of approved make and shadewith 6mm thick hard board backing:Rectangular shape 453x357mm	EA	2.00	183.68	367.36
39	:Fixing toilet paper holder: C.P. brass	EA	2.00	243.78	487.56
40	:Fixing PTMT towel rail complete with brackets fixed to wooden cleatswith CP brass screws with concealed fitting arrangement of approvedquality and colour. 450mm long towel rail with total length of 495mm,78mm wide and effective height of 88mm, weighing not less than 170gms.	M	24.40	81.96	1999.82
41	:Fixing G.I. Union in G.I. pipe including cutting and threading the pipeand making long screws etc. complete (New work) 15mm nominal bore	EA	5.00	150.52	752.60
42	:Fixing G.I. Union in G.I. pipe including cutting and threading the pipeand making long screws etc. complete (New work) 20mm nominal bore	EA	5.00	150.52	752.60
43	:Fixing C.P. brass bib cock of approved quality conforming toIS:893115mm nominal bore.	EA	2.00	26.88	53.76
44	:Fixing C.P. brass stop cock (concealed) of standard design and ofapproved make conforming to IS:8931.15mm nominal bore.	EA	2.00	26.88	53.76
45	:Providing and fixing C.P. brass angle valve for basin mixer and geyserpoints of approved quality conforming to IS:893115mm nominal bore	EA	2.00	26.28	52.56
46	:Fixing PTMT Soap Dish Holder having length of 138mm, breadth 102mm,height of 75mm with concealed fitting arrangements, weighing not lessthan 106 gms.	EA	2.00	15.71	31.42
47	:Fixing G.I. pipes complete with G.I. fittings including trenching andrefilling etc. :20mm dia. nominal bore	M	24.40	81.96	1999.82
48	:Fixing bright finished brass tower bolts (barrel type) with necessaryscrews etc. complete: 250x10mm	EA	30.00	9.35	280.50
49	:Fixing bright finished brass handles with screws etc. complete: 125mm	EA	30.00	5.61	168.30
50	:Supplying chemical emulsion in sealed containers including delivery asspecified.Chlorpyriphos/ Lindane emulsifiable concentrate of 20%	M2	32.96	70.24	2315.11
51	:Painting with synthetic enamel paint of approved brand and manufactureto give an even shade:Two or more coats on new work	M2	22.47	113.52	2550.79
52	:Varnishing with varnish of approved brand and manufacture: Two or morecoats of glue sizing with copal varnish over an under coat of flattingvarnish.	KG	605.00	26.28	15899.40
53	:Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in positionand applying a priming coat of approved steel primer all complete:	L	60.00	174.35	10461.00
54	:Treatment of soil under existing floors using chemical emulsion @ one litre per hole, 300 mm apart including drilling 12 mmdiameter holes and plugging with cement mortar 1:2 (1 cement: 2 Coarse sand) to match the existing floor ,WithChlorpyriphos/Lindane E.C. 20% with 1% concentration	M2	100.00	159.80	15980.00
55	:15mm cement plaster on rough side of single or halfbrick wall finishedwith a floating coat of neat cement of mix :1:4 (1 cement : 4 fine sand)	M2	10.49	387.91	4069.18
56	Fixing glass panes with putty and glazing clips in steel doors, windows, clerestory windows all complete with 4.0 mm thick glass panes	M2	33.20	198.45	6588.54
	GROUP A SEC B				
1	Supply of Local bricks- First Class	NO	24470.00	11.69	286054.30
2	Supply of Broken stone-Boulder broken(25mm graded down to 12mm), hard and clean.	МЗ	29.60	2838.32	84014.27
3	Supply of Timber for shuttering	DM3	5377.89	24.20	130144.94

17-1	ENDER NO. CDC85U8L22		Γċ	Part-II SOQ			
SL. NO.	DESCRIPTION OF SERVICE	UOM	QUANTITY	UNIT PRICE	TOTAL		
4	Supply of Timber Ist class(Tita chapa), free from knots andweak spots.	DM3	350.00	75.14	26299.00		
5	G.I. pipes 15 mm dia	МЗ	63.78	1344.58	85757.31		
6	Supply of Sand for general use with normal moisture contentto be clean and free from clay rubbish	EA	7.00	460.00	3220.00		
7	Brass mortice latch and lock 100x65 mm with6 levers and a pair ofbrass lever handles	M2	12.30	2070.00	25461.00		
8	:Block board construction flush door with teak wood ply on both faces 35mm thick	М	24.40	104.65	2553.46		
9	G.I. pipes 20 mm dia	M	24.40	138.00	3367.20		
10	:Vitreous china flat back wash basin 630x450 mm	EA	2.00	833.75	1667.50		
11	:Vitreous china pedestal type water closet	EA	2.00	1150.00	2300.00		
12	:Float glass sheet of nominal thickness 4 mm (weight not less than 10kg/sqm).	M2	10.49	345.00	3619.05		
13	:Brass hanging type door stopper 150 mm	EA	7.00	86.25	603.75		
14	:Hydraulic door closer bottle type M.S. body with necessaryaccessories and screws complete	EA	7.00	773.95	5417.65		
15	:Stainless steel kitchen sink - with drain board bowl depth 250 mm.	EA	1.00	2852.00	2852.00		
16	:Rectangular shape 453x357 mm Mirror with Plastic moulded frame	EA	2.00	333.50	667.00		
17	:Prefix #PTMT# - Towel Rail (450MM)	M	24.00	149.50	3588.00		
18	:U-PVC pipes (working pressure 4 kg / cm2) Single socketed pipe 110 mmdia.	EA	12.00	67.85	814.20		
19	:UPVC bend 87.50 110 mm bend	EA	24.00	16.10	386.40		
20	:UPVC pipe clip 110 mm bend	EA	2.00	155.25	310.50		
21	:Stainless steel butt hinges 125x64x1.9 mm IS: 12817 marked	NO	28.00	304.75	853.30		
22	Acrylic exterior paint	L	16.08	195.50	3143.64		
23	Vitrified floor tile 60x60 cm	M2	106.63	758.68	80898.05		
24	Acrylic emulsion , having VOC content less than 50 gm/litre	L	25.69	108.10	2777.09		
25	Water thinnable cement primer for interior wall surface, having VOCcontent less than 50 g	L	21.41	57.50	1231.08		
26	Cement base wall care putty	KG	445.93	14.95	6666.65		
27	:Structural steel such as tees, angles channels and R.S. joists	QTL	6.05	5290.00	32004.50		
	GROUP A SEC C						
1	:Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials : Beyond 4KM and Upto5KM	TON	30.00	124.70	3741.00		
2	:Extra on Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials on every additional KM:Beyond 5KM and Upto 10KM	TPM	150.00	9.84	1476.00		
3	:Extra on Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials on every additional KM:Beyond 10KM and Upto 20KM	TPM	600.00	8.25	4950.00		
	GROUP B SEC A	166	5004.50	448 = 5	0100000		
1	Laying Brick Flat Soling (75mm thick) including grading the baseand spreading 25mm thick sand bed at bottom and grouting soling with cement mortar (prop. 1:3) and carrying all materials from a distance of upto 30.00m.	M3	5034.50	417.56	2102205.82		
2	:Collecting / excavating sand, soil, silt, ordinary earth from anysource, load into lorries, transport it to distant place of workincluding procuring earth and laying in layer of 150mm thickness and compacting, profile properly made for taking measurement, including all measurable lead upto 30m and lift as required. (The contractor shall be esponsible for all formalities of supply of earth such as purchase of land including royalties, monopoly / other statutory taxes as required from any distance.)	M2	4457.67	4.30	19167.98		
3	:Clearing grass and removal of the rubbish upto a distance of 50 moutside the periphery of the area cleared.	DAY	30.00	805.00	24150.00		

17,-1	ENDER NO. CDC8508L22		F	a1 t-11 St	-11 SOQ		
SL. NO.	DESCRIPTION OF SERVICE	UOM	QUANTITY	UNIT PRICE	TOTAL		
4	Hire charges of Pump set of capacity 4000 litres/hour.	M2	4457.67	149.22	665173.52		
5	:Laying in position cement concrete of specified grade excluding thecost of centring and shuttering - All work upto plinth level: 1:3:6 (1Cement: 3 coarse sand : 6 graded stone aggregate 20 mm nominal size)	М3	445.77	1417.81	632017.16		
6	:Clearing, removing, mud, silt etc. from steel / R.C.C. tanks, bowzersetc. including disposing off to a distance of 30m. GROUP B SEC B	M3	2277.83	425.52	969262.22		
1	Supply of Broken stone-Boulder broken(25mm graded down to 12mm),	M3	427.94	2838.32	1214630.66		
	hard and clean.						
2	Supply of Sand for general use with normal moisture contentto be clean and free from clay rubbish	M3	320.95	1344.58	431542.95		
3	Supply of Jhama bricks bats-each bat not smaller then 1/3 of a full brick GROUP B SEC C	М3	334.33	2444.62	817309.80		
1	:Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials : Beyond 4KM and Upto5KM	TON	100.30	124.70	12507.41		
2	:Extra on :Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials on every additional KM:Beyond 5KM and Upto 10KM	TPM	501.49	9.84	4934.66		
3	:Extra on :Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials on every additional KM:Beyond 10KM and Upto 20KM GROUP C SEC A	TPM	2005.95	8.25	16549.09		
1	:Demolishing cement concrete manually / by mechanical means	M3	0.90	1167.57	1050.81		
	including disposal of material within 50 metres lead as per direction of Engineer-in - charge. 1:3:6 or richer mix			1107.07	1000.01		
2	:Earth work in excavation by mechanical means (Hydraulicexcavator) / manual means over areas (exceeding 30cm in depth. 1.5m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m, disposed earth to belevelled and neatly dressed. All kinds of soil	M3	3.00	136.34	409.02		
3	:Laying in position cement concrete of specified grade excluding thecost of centring and shuttering - All work upto plinth level: 1:2:4 (1Cement: 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	М3	3.90	1419.62	5536.52		
4	:Dismantling steel work in built up sections in angles, tees, flats and channels including all gusset plates, bolts, nuts, cutting rivets, welding etc. including dismembering and stacking within 50 metres lead.	KG	500.00	3.00	1500.00		
5	:Dismantling roofing including ridges, hips valleys and gutters etc.,and stacking the material within 50 metres lead of:G.S. Sheet	M2	96.00	87.00	8352.00		
6	:Making or replacing solid bamboo structure members (rafters, purlins,runners etc.) including binding with 18G binding wire.	M	960.00	49.54	47558.40		
7	:Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in positionand applying a priming coat of approved steel primer all complete:	KG	2721.39	26.28	71518.13		
8	:Services with welding and cutting set in carrying out miscellaneous repairs / new construction involving steel work (services of one welderand one jugali per set) to be supplied by the contractor. (New weldingset inclusive fuel etc. to be supplied by the contractor).	PD8	10.00	2068.24	20682.40		
9	:Erecting corrugated G.S. sheet roofing including vertical/curvedsurface fixed with polymer coated J or L hooks, bolts and nuts 8 mmdiameter with bitumen and G.I. limpet washers or with G.I. limpetwashers filled with white lead and including a coat of approved steelprimer and two coats of approved paint on overlapping of sheets completeupto any pitch in horizontal/ vertical or curved surfaces excluding thecost of purlins, rafters and trusses and including cutting to size andshape wherever required-0.63 mm thick with zinc coating not less than 275 gm/m2	M2	192.00	133.90	25708.80		
10	Erecting ridges or hips of width 60 cm over all width plain G.S. sheetfixed with polymer coated J. or L hooks, bolts and nuts 8 mm dia. G.I.limpet and bitumen washers complete. 0.63 mm thick with zinc coating notless than 275gm/m3	M	8.00	302.40	2419.20		

SL.	DESCRIPTION OF SERVICE	UOM	QUANTITY	UNIT	TOTAL
NO.	GROUP C SEC B			PRICE	
1	Supply of Broken stone-Boulder broken(25mm graded down to 12mm),	M3	3.35	2838.32	9508.37
2	hard and clean. Supply of Sand for general use with normal moisture contentto be clean and free from clay rubbish	M3	1.68	1344.58	2258.89
	GROUP C SEC C				
1	:Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials: Beyond 4KM and Upto5KM	TON	10.00	124.70	1247.00
2	:Extra on :Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials on every additional KM:Beyond 5KM and Upto 10KM	TPM	50.00	9.84	492.00
3	:Extra on :Carriage of material by mechanical transport including loadingunloading and stacking: Cement, stone blocks, G.I., C.I., A.C. & C.C.pipes below 100 mm dia and other heavy materials on every additional KM:Beyond 10KM and Upto 20KM	TPM	100.00	8.25	825.00
	GROUP C SEC D (ELECTRICAL ITEMS)				
1	3 phase 8 way TPN MCB DB: Supply and installation of 3 phase 8 way TPNprewired MCB DB with double door of following specification: DB shall beas per IS 8623, Suitable for Flush mounting or surface mountingapplication with minimum 63 A copper busbar for each phase, with neutralbar, earth bar and cable ties for cable management, busbar and neutralbar. DB shall have proper arrangement for door earthing and cornershields for better protection, Pan assembly for ease of installation,masking sheet, complete with four pole RCBO (63A, 300mA) as incomer and3 phase & single phase MCBs as outgoing, supplied with wire set andMCBs. Wires shall be FRLS copper single core cables of sufficientcapacity. DB shall have protection against mechanical impact, minimumprotection index shall be IK 09 with acrylic door of IEC-62262 andIngress protection of IP43. Dimension of DB shall be as per IS 8623. DBshall be complete with adequate no. of knockouts of standard size on thetop and bottom of the DB. Blank plate to be used in places of blankmodules. Make of DB and components: Schneider / ABB /Legrand / L&T /Siemens.Part 1: Incomer - DB shall have 63 A,10kA, 300 mA, 4 pole RCBO asincomer as per IS: 12460 with latest amendments,Part 2: Outgoing Distribution - In each phase 8 nos. of Single Pole MCBeach of 20 A, all C curve, 10 KA capacity. Total outgoing - 24 Nos.	NO	1.00	25705.93	25705.93
2	100A, TPN Switch Disconnector Fuses (SDF) Unit: Supply & Installation 100A, TPN, Switch Disconnector Fuse Unit, complete with sheet steelenclosure box, operating handle, HRC Fuses etc. Model range Legrand, Schneider, Indoasian, ABB as approved by OIL including installation, necessary connection, earthing, testing and commissioning	NO	1.00	7159.32	7159.32
3	20A, 30mA, DP (1P+N) RCBO: Supply and installation of 20A, 30mA, DP(1P+N) RCBO Unit complete with metallic enclosure. RCBO unit to beinstalled in the modular switchboard, power points as per wiring scheme.RCBO shall comply to standards IEC/EN 61009, AC Class Protection; Tripping characteristics - C curve; RCBO shall be complete with testbutton and trip indication. Make Schneider/ ABB / Legrand / L&T / Siemens. RCBO shall be installed in the metallic enclosure whereverrequired / as directed by OIL's Elect. Engineer	NO	5.00	5957.63	29788.15
4	12 Module Modular Switchboard: Supply and fixing/installation of whitecolour, 12 modules, horizontal, surface mounted, PVC/Plastic Surface Boxalong with modular double plates (base & cover plate) for fixing modularswitches, socket, fan regulator, call bell switch etc. as	NO	6.00	393.22	2359.32
5	required,complete with screws etc., as approved by OIL 4 Module Modular Switchboard: Supply and fixing/installation of whitecolour, 4 modules, horizontal, surface mounted, PVC/Plastic Surface Boxalong with modular double plates (base & cover plate) for fixing modularswitches, socket, fan regulator, call bell switch etc. as required,complete with screws etc., as approved by OIL.	NO	10.00	166.10	1661.00
6	5A/6A Switch: Supplying and fixing of 5 or 6 Amp one way modular clip inswitch, model range Legrand, Schneider, Indoasian, including makingnecessary connection as per OIL's approval	NO	60.00	24.58	1474.80
7	15A/16A Switch: Supplying and fixing of 15 or 16 Amp one way modularclip in switch, model range Legrand, Schneider, Indoasian, includingmaking necessary connection as per OIL's approval	NO	10.00	68.64	686.40

SL. NO.	DESCRIPTION OF SERVICE	UOM	QUANTITY	UNIT PRICE	TOTAL
8	6A Socket: Supply and fixing of socket outlet 6 Amps 3 pin universalcombine shuttered complete, model range Legrand, Schneider, Indoasian, Crabtree including necessary connection as approved by OIL	NO	20.00	50.85	1017.00
9	6A/16A Socket: Supply and fixing of socket outlet 6/16 Amps 3 pincombine shuttered complete, model range Legrand, Schneider, Indoasian, Crabtree including necessary connection as approved by OIL	NO	10.00	94.92	949.20
10	Electronic Fan Regulator: Supplying, fixing/installation of 2 moduleselectronic polycarbonate type, fan step regulator, 5 step, 100W/240V,white, Modular Fan speed controller. Make: Legrand /Schneider /Indoasian/Havells /Siemens. Internal connection of wire as per direction of OIL's Electrical Engineer is included in the item	NO	5.00	276.27	1381.35
11	Ceiling Fan: Supply and fixing of 1400 mm, Sweep, 230 V AC and 60 W (Havells / Bajaj / ORIENT – PSPO / USHA) AC Ceiling fan, white in colour, complete with all accessories like down rod. Canopy etc. without regulator as approved by OIL. Necessary connection shall be made as directed by Electrical Dept. of OIL	NO	5.00	1808.47	9042.35
12	Exhaust Fan: Supply, installation, testing and commissioning of 200mm sweep fan (Decorative type Fresh Air Fan) size of propeller type AC exhaust fan, plastic body complete with louvers/shutter mounting rings, frame bracket etc. but without regulator suitable for use on 230/240 V, 50 Hz single phase AC supply. Fan shall be as per IS: 2997-1964 and marked /embossed with ISI logo. Warrantee 2 years. Make: Usha/Bajaj/Crompton Greaves/Havells	NO	5.00	2759.32	13796.60
13	Supply and installation of LED Batten (20W LED Tube light fitting):Supply, Installation and commissioning of surface mounting Powdercoated, Aluminum extrusion housing, IP20 Diffused Acrylic glass fitted4ft LED Batten LM-79 certified luminaire & LM-80 certified LED completewith integrated electronic driver and all mounting accessories. The product should have an even light distribution with system lumen greaterthan 2000 Lumen with 22 +/-10% W system wattage. and CCT 6500k, CRI >80and system efficacy >100 lm/W. Lifetime should be at least 40,000 hours. The product should have an Electronic constant currentdriver with Open & Short circuit protection, reverse polarity protectionand surge protection, PF >0.9, THD <10%.Make: Bajaj / Syska / Havells / Philips / Osram	NO	40.00	618.64	24745.60
14	Point Wiring: Wiring for light point/ fan point/ exhaust fan point with 3 Nos. of 1.5 sq.mm FRLS PVC insulated single core copper conductor in surface medium grade ISI approved 25mm size PVC Casing Capping, suitable PVC casing box for fixing ceiling rose, 3 pin Ceiling rose, blank plate for empty slot and earthing the point with 1.5 sq.mm. FRLS PVC insulated single core multi-stranded copper conductor as required. (identical size for phase, neutral and earth wires, colour coded red, black and green respectively). During measurement, one unit (or one number) shall mean 'a point wiring complete with supply of all materials as above including labour charge for fixing'	NO	50.00	636.44	31822.00
15	Power Wiring: Wiring for Circuit/ Submain (DB to Switchboard) / Power wiring along with earth wire with 2 Nos. of 4 sq.mm. and earth continuity with 1 no. 2.5 sq.mm sizes of FRLS PVC insulated copper conductor, single core multi-stranded cable in surface/ recessed for voltage grade 1100 volts (Finolax/Havells/Polycab/L&T) medium grade ISI approved 25 mm PVC casing capping as required. Wiring shall be done from MCB DB to desired Switch Board/power point. (phase, neutral and earth wires, colour coded red, black and green respectively) During measurement, one unit (or one meter) shall mean 'wiring of one meter length complete with 3 nos. wires, casing capping etc. as above including labour charge for fixing	M	180.00	188.98	34016.40
16	Blank Plate: Supply and fixing of 1 Module Blank Plate single in modular switch system, including necessary connection as per direction of Engineer in Charge	NO	100.00	2.54	254.00
17	Junction Box for wiring: Supply and fixing PVC box of 250 mm X 300 mm X 60 mm deep (nominal size) on surface. This PVC box will be used as a junction box for wiring. Make: Presto Plast/AKG/Richa or as approved by OIL	NO	8.00	139.83	1118.64

P	ar	t-	II	S	O	O
-	uı	•		\sim	J	$\mathbf{}$

SL. NO.	DESCRIPTION OF SERVICE	UOM	QUANTITY	UNIT PRICE	TOTAL
NO.				PRICE	
18	Misc. Works towards electrification which includes the following: (1) Power wiring from the nearby source to the 63A SDF and from MCCB to the TPN DB as directed by the Electrical Engineer of OIL. Necessary materials like cable etc. will be provided by OIL. (2) Earthing works (2 nos. earth pits and interconnection etc.) as required for the electrification. Necessary earthing materials like earth electrode, GI wire, GI Strip would be provided by OIL. (3) Standard Testing of the wiring works before charging. (4) Supply of two piece 'as built drawing' in A3 size paper, laminated and drawn in computer. (5) Other essential misc. works like testing of circuit before charging etc. as required for completion of the Electrification Works.	AU	1.00	11000.00	11000.00

Note:

- a) Bidder must quote overall price within the range of "At Par" to "+10%" of Company's Internal Estimate.
- b) Bidder must include all impale plant, labour, supervision, materials, erection of display board, sign/caution board, insurance, profit, taxes and duties, together with all general risks, liabilities and in their quoted rates excluding PF and GST.

WORKS CONTRACT

SPECIAL CONDITIONS OF CONTRACT

DESCRIPTION OF WORK/SERVICES: Civil construction jobs to facilitate the relocation of gas lift compressor from GCS-Ushapur to GCS-Tengakhat.

- (1) Construction of Operator cum Maintenance Room.
- (2) Earth filling, brick soling & Cement Concrete work.
- (3) Extension of shed for Gas Lift Compressor.

A. SCOPE OF CIVIL WORK

1.00 GENERAL:

The contractor must complete the work in all respect within the work duration allotted to him as per work order. However, any delay in completion of the work due to reasons not attributable to the contractor will be considered during delay analysis of the work after its completion and the same will be considered during calculation of LD as per Contract. Moreover, the duration of the work allotted to the contractor is excluding such type of hindrances not attributable to the contractor.

All materials used in the work shall conform to the latest revision of the relevant Indian Standard Specifications to the extent practicable. Where no such specifications exist they shall be of the best quality available in the market. Wherever ISI certified materials and products are available these alone shall be used. All materials shall be stored at site in accordance with IS-4082-1996.

Unless specially provided for in the contract the tendered rates shall include the cost of carriage, transport, loading, unloading and stacking as directed for all materials required on the work. Where a tender provides a rate for transport of materials, it includes for all loading, unloading and stacking on the site in such position and manner as directed. Any materials found not conforming to specification must be removed from site within 48 hours.

2.00 SITE CLEARANCE, EXCAVATION AND DISPOSAL:

Before the earthwork is started, the area coming under cutting and/refilling shall be cleared of shrubs, vegetation, grass, uprooting of tree stumps and such others, and rubbish removed upto a distance of 50 metres outside the periphery of the area under clearance.

All excavations shall be done to the minimum dimensions as required for safety and working facility. Prior approval of the Engineer shall be obtained by the Contractor, in each individual case, for the method he proposes to adopt for the excavations including dimension, side slopes, shoring, dewatering, disposal, etc. This approval, however, shall not in any way make the Engineer responsible for any consequent loss or damage. The excavation must be carried out in the most expeditious and efficient manner.

The excavated spoils will be disposed off in any or all the following manners:

- a) By using it for backfilling straightway.
- b) By stacking it temporarily for use in backfilling at a later date during execution of the Contract.
- c) i) By either spreading, Or
- ii) Spreading and compacting at designated disposal areas.

3.00 STORAGE:

Materials shall be transported, handled and stored at site carefully to the approval of Engineer so as to prevent any damage of any kind to be kept at his own risk and cost.

Cement shall be stored in a weather proof shed, the floor of which shall be raised 300 mm clear from the ground and 600 mm away from the wall all round in order to protect from rain and moisture. Empty cement bag shall be returned to the Company in good condition.

4.00 CEMENT CONCRETE/REINFORCED CEMENT CONCRETE WORK:

All C.C. work in 1:3:6 proportions unless otherwise specified shall be done with 18 mm graded down broken stone. Broken stone shall be properly screened before use. All reinforced cement concrete work to be done in prop. 1:1.5:3 unless otherwise specified -18mm down to 12mm graded down broken stone as per related drawings and

PART-III SCC

instructions of site Engineer to be followed in case of any discrepancies. Proper vibration to be done as per IS recommendation. Floor panelling to be done in the line of expansion joint as directed by Engineer-In-charge.

Fine Aggregate - Fine aggregate shall be hard, durable, clean and free from adherent coating and organic matter. It shall not contain harmful impurities such as pyrites, coal, lignite, mica, shale or similar laminated material, clay, alkali, soft fragments, sea shells and organic impurities in such quality as to affect the strength or durability of the concrete. Fine aggregate to be used for reinforced concrete shall not contain any material liable to attack the steel reinforcement. Fine aggregate which is chemically reactive with alkalis of cement is harmful as cracking of concrete may take place.

Coarse Aggregate - Coarse aggregate shall be obtained from natural sources such as stone, gravel, etc. crushed or un-crushed or a continuation thereof from approved quarries. This shall consist of coarse material most of which is retained on 4.75mm sieve. Aggregate shall be hard, strong, dense, durable, clean and free from veins and adherent coatings. It shall be free from soft, feeble, thin, elongated or laminated pieces and shall be roughly cubical in shape. It shall be clear and free from dirt and any other deleterious matter.

Reinforcement bars - The following types of steel for reinforcement shall be used in reinforced concrete construction and these shall conform to Indian Standards or as revised from time to time mentioned against each

- 1) Mild steel and medium tensile steel bars and hard drawn steel wire IS: 432.
- 2) HYSD bars IS: 1786.

Bending & Placing steel reinforcement in position - Bending shall be carried out as per relevant IS specification and direction of the Engineer-in-charge. All reinforcement bars shall be accurately placed in position with spacing and cover as shown in the drawing or as specified and firmly held so during the placing and vibrating and setting of concrete. Bars shall be thoroughly cleared of rust, seals, grease, oil and any other foreign matter before placing them in position. The overlap jointing shall be staggered. The bars shall be fixed with 22G binding wire. Precast cover blocks 1:2 (1 cement: 2sand) cement mortar 40 mm square and necessary thickness shall be used to keep the reinforcement bars in proper position. For this block, no extra payment to be made. Wire required for binding shall not be measured separately. Tack welding shall also be permitted in lieu of building with steel wire.

Proportioning of mix - Proportioning shall be done by volume. Boxes of suitable size shall be used for measuring sand and aggregates. The size of the boxes (internal) shall be $35 \times 25 \text{cm}$ and 40 cm deep. The unit of measurement for cement, shall be a bag of cement weighting 50 Kg and this shall be taken as 0.035 cubic metre. While measuring the aggregate and sand the boxes shall be filled without shaking, ramming or hammering. The proportioning of sand shall be on the basis of its dry volume and in case of damp sand, allowances for bulkage shall be made.

Mixing - Mixing of reinforced cement concrete shall, as a rule be done in a mechanical mixer. However, the Engineer-in-charge may permit hand mixing in specific cases where in his opinion it is not practicable to resort to mechanical mixing, either on account of the quality of cement concrete required is small or for any other reason. In such cases, it should be ensured that the inferior quality of concrete produced by hand mixing will not adversely affect the structure.

Consistency - The quantity of water to be used for each batch containing 50 Kg of cement, to give the required consistency shall not be more than 34 litres for 1:3:6, mix 32 litres for 1:2:4 mix, 30 litres for 1:1.5:3 mix and 27 litres for 1:1:2 mix. In case of vibrated concrete, the above quantity shall be suitably reduced. The quantity of water shall be regulated by carrying out regular Slump Test.

Placing of concrete - Before placing the concrete the sub-base/form work shall be cleared of all injurious or foreign matter, watered and well consolidated. Formwork shall be clean and free from all foreign material. It is necessary that the time between mixing and placing of concrete does not exceed the initial setting process. Mixed concrete that has been left standing shall not be used after the initial set has commenced the addition of water (or cement) to make such a mixture more workable shall not be allowed. In foundation trenches or such other situations, the entire concrete used in the work shall be laid gently (not thrown) in layers not exceeding 15cm. The concrete so deposited shall be thoroughly vibrated by means of mechanical vibrators till dense concrete is obtained.

Curing - Concrete shall be carefully protected during first stage of hardening from harmful effects or excessive heat, drying winds, rain or running water and shock. After the concrete has begun to harden i.e. about 1 to 2 hours after its laying it shall be protected from quick drying with moist gunny bags or any other material approved by the Engineer-in-charge. After 24 hours of laying of concrete the surface shall be cured by flooding water upto 25mm depth or by covering with wet adsorbent materials. The curing shall be done for a minimum period of 7 days from the date of pouring of concrete, unless otherwise specified.

PART-III SCC

Finishing - In case of roof slabs the top surface shall be finished even and smooth with wooden trowel, before the concrete beings to set. The surface of RCC slab on which the cement concrete or mosaic floor is to be laid shall be roughened with brushes while the concrete is green. This shall be done carefully without disturbing the concrete. Before laying the floor, the laitance shall be removed, the surface of slab hacked and a coat of cement slurry at 2.75 Kg of cement per square metre shall be applied, so as to get a good bond between RCC and concrete floor. The exposed surface which is to receive plaster or where it is to be joined with brick masonry wall shall be properly roughened immediately after the removal of form work, taking care to remove the laitance completely without disturbing the concrete. Before the surface is plastered, it shall be cleaned and wetted so as to give good bond between concrete and plaster.

5.00 FORM WORK:

The formwork shall be rigid and so corrected as to retain the shape and dimensions of the member being cast. Form work for concrete shall be seasoned timber or other approved materials as per directions of the Engineer. It shall be sufficiently tightened to prevent loss of cement slurry and all holes and joints shall be chaulked with putty. It shall have sufficient strength and rigidity to withstand the load of concrete, and vibrations, movement of men, materials and plants and any other incidental loads without excessive deflection beyond permissible limits. The formwork shall be so constructed as to be removable in sections by inscribing or otherwise loosing - them without hammering or levering with force. Only wedges, clamps bolts or screws etc. shall be used in preference to nails or spikes. All side pieces shall be easily removable without disturbing the bottom pieces. Where however, use of nails and spikes become unavoidable, these shall be left projecting so that they can easily be withdrawn.

Surface treatment for shuttering - Forms shall be cleaned of all dust, wood shavings, dirt and other matter by washing with water. This process is facilitated by providing draining holes in the shuttering. The surface shall then be coated with soap solution applied before concreting is done. Soap solution for the purpose shall be prepared by dissolving yellow soap in water to get consistency of paint. Alternatively a coat of raw linseed oil/refined pale paraffin mineral oil or form oil of approved manufacture may be applied. In case steel shuttering is used, soap solution or row linseed oil shall be applied after thoroughly cleaning the surface. Care shall be taken that such approved composition is kept out of contact with the reinforcement.

In normal circumstances and where ordinary Portland cement is used form may generally be removed after the expiry of the following periods.

a) Walls, columns and vertical face of all structural members as may be decided by the Site Engineer: 24 to 48 hours.

b)Slabs side (props left under): 3 days

c)Beam soffits (props. left under):14 days

d)Removal of props under slabs

i)Spanning up to 4.5 m: 14 days

ii)Spanning over 4.5 m: 21 days

e)Removal of props under beams:

i)Spanning up to 6 m: 21 days

ii)Spanning above 6 m: 28 days

In no circumstances shall forms be struck until the concrete reaches a strength of at least twice the stress to which concrete may be subjected at the time of removal of form work. All form works shall be removed without such shock or vibration as would damage the concrete. Form work for long span deep beams to be supported by MS props or Bhaluka Bamboo props as required based on the design for the formwork to take care the massive load of the green concrete.

6.00 BRICKWORK:

- a) All bricks shall be of 7.5 class designation quality locally available as approved by the Site Engineer.
- b) Bricks shall be of size as specified in the item of work or of nominal size where no particular size is mentioned.
- c) Bricks shall be well burnt, sound, hard with sharp edges of uniform size and shape free from cracks, stones or particles of lime and other defects, shall be kiln burnt and satisfy the following requirement:
- i) They shall give a clear metallic sound when struck.
- ii) They shall be of uniform colour and size.
- iii) They shall not be cracked, stratified or under or over burnt.
- iv) The tolerance in dimensions shall be +/-12mm in length, 6mm in width and 3mm in height.

PART-III SCC

- v) Keys or frogs shall be formed on one of the larger size, except in the case of machine extruded bricks where no frogs are required
- vi) The increase in weight when soaked in water for 24 hours shall not be more than 20% of the dry weight of the bricks.
- d) If required by the Site Engineer, necessary test shall be conducted at the contractor's expense to ensure quality. In general, the bricks shall be the best quality locally available.

Bricks used for masonry in cement mortar or composite mortar shall be thoroughly soaked in clean water for at least an hour immediately before use (The absence of bubbling when the soaked brick is immersed in water is the test for thorough soaking). The soaked bricks shall be kept on a platform free from dirt, mud or any foreign element. Bricks shall be laid in English bond unless otherwise specified. Care must be taken that the bricks are perfectly clean and free from lime, moss or dirt of any kind. If necessary they must be scrubbed before use. Half or cut bricks shall be not used except for closures which may be required to complete the bond. It shall be ensured that all horizontal and vertical joints are completely filled with mortars without any void in brickwork. Brickwork shall be raised truly plum (or true to required better where so specified). All courses shall be laid truly horizontal. Vertical joints shall be truly vertical and those in alternate courses shall be in the same vertical line. The thickness of brick courses shall be uniform. Great care must be taken to masonry in progress of construction damp. When work is left off for the day troughs shall be formed, by means of fillets of mortar 51mm high all-round the unfinished work and shall be kept filled with water. Vertical or inclined surfaces must be frequently watered from a rose headed can. Water should not be dashed with violence against new work as this washes out the mortar. Should the work be delayed owing to holidays or for other reason, the contractor must make adequate arrangements for keeping the work wetted, and shall continue to do so for at least ten days or such longer time as directed, after the brickwork has been completed.

7.00 CEMENT MORTAR:

- i) Must be freshly mixed: Cement mortar will only be mixed in such quantities as can be used up on the work within half an hour of mixing. Mortar which has been mixed longer or which has taken its initial set will on no account be used on the work or remixed with fresh mortar. It must be immediately removed from the site or work.
- ii) Method of mixing: The cement and sand will be mixed dry in the specified proportions, by turning over atleast three times on the mixing platform. Only sufficient water will then be added, thorough a rose of a watering can, to produce a workable mixture. The wet mortar will be thoroughly worked or mixed by repeatedly turning over, not less than three times on the mixing board.
- iii) Size of mixing platform and precaution against list: All mixing of mortar must be done on platforms of angle size and workman bringing the material to and from the platform must not be permitted to walk about on it, thereby bringing mud or dirt to the place, where the mortar is being mixed. The platform must be clean and level and all joints closed or filled so that the cement is not washed out.
- iv)Proportion of cement and sand: Where not otherwise specified, cement mortar for plaster will consist of one part of cement to two parts of sand. For mortar for brick or stone masonry work the proportion unless otherwise specified, will be one part of cement to three parts sand.

8.00 WOOD WORK:

The work shall be carried out as per detailed drawings and/or as directed by the Engineer-in-charge. The wooden members of the frame shall be planed smooth and accurate to the full dimensions. Rebates, rounding, moldings etc. as shown in the drawing shall be done before the members are joined into frames. Timber will be 1st class seasoned as approved by the Engineer-in-charge.

Jointing - Jointing in timber frames must be made carefully and accurately. They shall be strong, neat and shall fit without wedging or filling. The joints shall be pinned with hard wood 10 to 15mm dia after the members of the frame are pressed together in a suitable vice-mechanism.

Surface treatment- Woodwork shall be painted. oiled, polished or otherwise treated as specified. All portions of timber abutting against masonry or concrete portion of building shall be coated with boiling coat tar or other type of approved wood preservative or primer, before placing them in final position.

Hold fasts - Hold fasts used for fixing doors and window frame shall be made of 40×3 mm flat iron long. It shall have a hole on one end for fixing to frame with 10mm dia bolt, at the other end the flat iron shall be split and bent at right angles in the opposite direction. The hold fast shall be tightly fixed to the frame by means of bolts, the bolt

PART-III SCC

hole in frame being plugged suitably and finished neat. The hole fast shall be embedded into masonry by concrete block as described in the item of work.

9.00 DOORS:

- i) The flush door shutters (solid core type) decorative and non-decorative type shall conform to IS: 202 (Part I). The door should be fixed using 4 nos. of hinges 125mm long ensuring that the hinges are not fixed less than 150mm from the edges with 8 nos. parallel sunk fully threaded screws 38mm long, should be used for fixing the hinges to the flush door after drilling a pilot hole 2.50mm dia 40mm long. Screws should not be hammered. Lock, tower bolts etc. necessary, if any to be paid separately.
- ii) Door frame (Chowkhat) of doors, windows, other similar works wrought, framed and fixed in position in contact with C.C. or brick masonry walls including supplying, fitting and fixing with M.S. flat hold fast ($40 \text{mm} \times 3 \text{mm} \times 250 \text{mm}$) as per design and embedded in cement concrete block in prop 1:2:4 and with two coats of kiricide oiling to the timber faces in contact with C.C. and masonry as directed and specified.

10.00 PLASTER WORK

- i) Preparation of surface: All putlog holes in brick work and junction between concrete and brick work shall be properly filled in advance. Joints in brick work shall be raked about 10mm and concrete surface hacked to provide grip to the plaster. Projecting burrs of mortar formed due to gaps at joints in shuttering shall be removed. The surface shall be scrubbed clean with wire brush/coil brush to remove dirt, dust etc. and the surface thoroughly washed with clean water to remove efflorescence, grease and oil etc. and shall be kept wet for a minimum of six hours before application of plaster.
- ii) Proportion: The cement plaster shall be in specified proportion of cement and sand.
- iii) Mixing: The cement and sand should be thoroughly mixed in dry condition. After dry mixing the materials shall be wetted with just sufficient water to bring the mortar to proper consistency of thick paste. Mortar should be used immediately after mixing and arrangements shall be made so that not more than 30 minutes elapse between the cement first coming in contact with the moisture and laying. In all exterior plaster works waterproofing compound to be added to the mortar as per the specification of the manufacturer, if not indicated in the item rate quoted should be inclusive of the same.
- iv) Placing: Plaster shall be laid over the prepared surface in one coat to the specified thickness and rubbed with "PATAS" and trowel and shall be smooth, free from waviness and trowel marks.
- v) Sequence of operations: For external plaster, the plastering operations shall be started from the top floor and carried downwards. For internal plaster, the plastering operations may be started wherever the building frame and cladding work are ready and the temporary supports of the ceiling resting on the wall or the floor have been removed.
- vi) Curing: Each coat shall be kept damp continuously till the next coat is applied or for a minimum period of 7 days.

Moistening shall commence as soon as plaster is hardened sufficiently. Soaking of walls shall be avoided and only as much water as can be readily absorbed shall be used.

11.00 WASHABLE DISTEMPER/OIL BOUND DISTEMPER/ EMULSION PAINTING

Preparation of surfaces: The surface shall be thoroughly brushed free from dust, dirt, grease, mortar droppings and other foreign matter and sand papered smooth. Thereafter a smooth surface shall be prepared by applying putty, made of plaster of paris mixed with water on the entire surface including filling up the undulation and then sand papering the same after it is dry.

Primer coat: The primer where used as on undecorated surfaces shall be alkali resistance primer or acrylic based cement primer as specified in the item. These shall be of the same manufacture as oil bound distemper/ plastic emulsion paint. If the wall surface plaster has not dried completely alkali resistance primer shall be applied before distempering the walls. But if the distempering is done after the wall surface is dried completely, cement primer shall be applied.

Application of distemper/plastic paint coat: For undecorated surfaces, after the primer coat has dried for at least 48 hours, the surface shall be lightly sand papered to make it smooth for receiving the distemper/plastic paint taking care not to rub out the priming coat. All loose particles shall be dusted off after rubbing. Minimum two coats of distemper/plastic paint shall be applied with brushes in horizontal strokes followed immediately by vertical, which together shall constitute one coat. The subsequent coats shall be applied after a time interval of at

PART-III SCC

least 24 hours between consecutive coats to permit of the proper drying of the preceding coat. For decorated surfaces, the distemper/plastic paint shall be applied in two coats or more over the prepared surface in the same manner as for undecorated surfaces.

Purchase of paint, varnish or oil: Only the best brands obtainable will be used and should the contract permit the contractor to supply any paint, oil or varnish he shall purchase only such brands as the Site Engineer shall approve of in writing. All purchases must be made direct from the manufacturers or through an agent approved of in writing by the Site Engineer. Should the Site Engineer so direct copies of all indents and receipts for purchase must be submitted for inspection. Paint, etc. to be purchased in sealed containers. All paints, oil or varnishes supplied by the contractor must be produced for the inspection of the Site Engineer of the work in the manufacturers sealed and unopened containers. All containers from which the contents have been removed and are not required on the work must be destroyed and no extra payment will be granted for such destruction. Only ready mixed or varnished of the make or brand specified will be permitted to be used exactly as received from the manufacturer without any admixture what so ever unless previously authorised, in writing, by the Site Engineer.

12.00 EXTERIOR PAINTING:

The paint shall be of approved brand and manufacture.

This paint shall be brought to the site of work by the contractor in its original containers in sealed condition. For new work, the surface shall be thoroughly cleaned off all mortar dropping, dirt dust, algae, fungus or moth, grease and other foreign matter of brushing and washing, pitting in plaster shall make good, surface imperfections such as cracks, holes etc. should be repaired using white cement.

Before pouring into smaller containers for use, the paint shall be stirred thoroughly in its container, when applying also the paint shall be continuously stirred in the smaller containers so that its consistency is kept uniform. Dilution ratio of paint with potable water can be altered taking into consideration the nature of surface climate and as per recommended dilution given by manufacturer. In all cases, the manufacturer's instructions & directions of the Engineer-in-charge shall be followed meticulously.

The lids of paint drums shall be kept tightly closed when not in use as by exposure to atmosphere the paint may thicken and also be kept safe from dust.

Paint shall be applied with a brush on the cleaned and smooth surface. Horizontal strokes shall be given, First and vertical strokes shall be applied immediately afterwards. This entire operation will constitute one coat. The surface shall be finished as uniformly as possible leaving no brush marks.

13.00 SYNTHETIC ENAMEL PAINT:

Preparation of surface: The surfaces before painting shall be cleaned of all rust, scale, dirt and other foreign matter sticking to it with wire brushes, steel wool in case of steel surfaces and sand papering in case of wooden surfaces. Thereafter, one coat approved primer paint will be applied on the surface. Synthetic enamel paint (Superior quality as approved) shall be applied-two or more coats to give an even shade.

14.00 DAMP PROOFING COURSE:

It shall consist of 1:2:4 plain cement concrete with approved water proofing materials such as cico, impermo etc. of specified thickness. Edges of DPC shall be straight, even and vertical side shuttering shall consist of wooden or steel forms and shall be strong and properly fixed so that it is not disturbed during compaction and mortar or cement slurry does not leak through. When forms are struck the surface should be smooth without any honeycombing. The surface shall be kept wet for seven days. Before commencing the superstructure work, the top of concrete course shall be dried and cleaned of all materials. Blown type bitumen shall then be applied uniformly on the surface and the side of the concrete coming in contract with flooring on the inside shall also be painted with bitumen.

15.00 CERAMIC TILE FLOORING/SKIRTING:

a) Preparing of Plinth Filling: All plinth fillings shall be properly consolidated in layers, watered, rammed and allowed to consolidate to the Site Engineer's satisfaction before any flooring is laid. When the flooring is to be laid over a foundation of sand, broken stone, brick or a combination of sand and broken stone or brick the filling shall be removed to a depth equal to the thickness of the flooring plus such foundation layers.

b) Foundations:

- i) Sub-layer of sand : After the plinth filling has been prepared as detailed in specification above a sublayer of sand 300mm deep shall be laid watered and brought to an even surface.
- ii) Layer of broken stone or brick: Over the sand a foundation course of bricks shall be laid and the interstices filled in with sand. The bricks shall be tightly packed and laid so as to break joint.
- c) Tile floors:
- i) Foundation and cement floating under tiles: Over the foundation as in (b) above 2 coats of cement plaster, 1part of cement to 1 part of sand, prepared in a very liquid condition will be floated over it and allowed to set.
- ii)Laying: After the tiles have been soaked in water for at least two hours and the cement foundation sprinkled with water, laying work may commence and shall start from the centre of the room or area to be tiled, work being continued in both directions so that borders are laid last. A layer of 20mm thick (average) cement mortar: 1:4 (1 cement: 4 sand) (unless otherwise specified) shall be provided as bedding for the tiles. Each tile will be laid in and drawn up in neat cement of honey like consistency at 4.40 Kg of cement per sqm, care being taken to exclude air bubbles. Threads shall be stretched across the surface, at intervals, parallel to the short sides of the area to be tiled to serve as guide lines. Each tile being gently tapped with a wooden mallet till it is properly bedded. The joints shall be grouted with white cement and matching pigment complete. The surface of the flooring shall be checked frequently with a straight edge so as to obtain a true surface with slope, if required. At position where full tiles cannot be fixed, the tiles shall be cut to size and smoothened to give straight and true joints.
- iii) Cleaning: After a small area has been laid all superfluous cement will be wiped off the surface. Stains shall be removed by moistening with hydrochloric acid and rubbing with pumice stone and afterwards washing with warm water.

iv)Curing: The floor shall be kept wet for a minimum of 7 days so that bedding and joints set properly.

16.00 PLINTH PROTECTION AND STORM WATER DRAIN:

Plinth protection and storm water drain shall be provided along the outer periphery of the building as per drawing and with PCC (1:3:6) over bricks flat laid in CM 1:4 and finished with 15mm thick cement plaster in prop. 1:2 with floating coat of neat cement finish.

17.00 ANTITERMITE TREATMENT (IS 6313):

Injecting chemical emulsion of Chlorpyriphosemulsificable concentrates 20% with 1% concentration for preconstruction Anti-termite treatment and creating a continuous chemical barrier under and all-round the column pits, trenches, top surface of plinth filling, junction of walls and floor along the external perimeter of building expansion joints, surroundings of pipes and conduits etc complete as per specification (plinth area of the building at ground floor only shall be measured for payment) and to be executed by reputed party.

18.00 ANODISED ALUMINIUM WORKS:

Aluminium sections used for fixed/openable windows, ventilators, partitions, frame work & doors etc. shall be suitable for use to meet architectural designs to relevant works and shall be subject to approval of the Engineer-in-Charge for technical, structural, functional and visual considerations. The aluminium extruded sections shall conform to IS 733 and IS 1285 for chemical composition and mechanical properties. The stainless steel screws shall be of grade AISI 304. The permissible dimensional tolerances of the extruded sections shall be as per IS 6477 and shall be such as not to impair the proper and smooth functioning/operation and appearance of door and windows. Aluminium glazed doors, windows etc. shall be of sizes, sections and details as shown in the drawings. The details shown in the drawings may be varied slightly to suit the standards adopted by the manufacturers of the aluminium work, with the approval of Engineer-in-Charge.

GLAZING: Glass used for glazing shall be sheet glass of best approved quality, free from flaws, specks, bubbles and shall be of specified thickness.

EPDM- GASKETS: The EPDM Gaskets shall be of size and profile as shown in drawings and as called for, to render the glazing, doors, windows, ventilators etc. air and water tight. Samples of gaskets shall be submitted for approval and the EPDM gasket approved by Engineer-in-Charge shall only be used.

PART-III SCC

SEALANT: The sealants of approved grade and colour shall only be used. The silicone for perimeter joints (between Aluminum section and RCC/Stone masonry) shall be of make approved by the Engineer in Charge.

- 19.00 The contractor must provide following minimum numbers of equipment in operational condition capable of providing uninterrupted services under the contract as and when required.
- i) Concrete mixer machine 02 Nos.
- ii) Water pump / Sump pump 01 No.
- iii) Welding and cutting set 01 Set
- iv) Vibrator 03 Nos.
- v) Slump cone 01 No

20.00 TESTS FOR QUALITY CONTROL:

The various tests shall be carried out by the contractor as and when instructed by the Engineer-in-charge based on the prevailing OIL SOP (Standard Operating procedure) of Civil Engineering Contract jobs and no separate payment shall be made unless otherwise specified in the contract. Following tests /test certificate to be produced by the contractor at his own cost as and when directed by the Engineer-in-charge.

- i) Test report of water for construction and curing should be produced ('PH' value should not be less than 6).
- ii) Cube test for RCC work. (Test to be performed in presence of company representative.)
- iii) Test report for quarry materials should be produced.
- iv) Any other tests as per the direction of Engineer-in-charge.

21.00 MEASUREMENT & PAYMENT:

Payment for all works done shall be made on the basis of actual work done as per the schedule of rates. For all extra work done on the advice of the Company's Engineer and which is not included in the schedule of rates, deviation order for the same shall be made on the rates as decided by the Company's Engineer.

22.00 SAFETY MEASURE:

Safety measure as per OIL regulations shall be strictly adhered to by the Contractor. Safety belts and other measure taken by the Contractors shall be borne by the Contractor. If any loss or damage caused to life during the erection and execution, the contractor shall be fully responsible for the loss.

23.00 RECORD KEEPING:

- i) A site order book will be maintained at site which will be in the custody of the Engineer-in-charge or his representative and all instructions given to the Contractor including hindrance(if any) will be recorded in the site order book and the same has to be signed by the contractor to comply with the instruction given therein.
- ii) A register to be maintained at site which will be in the custody of the Engineer-in-charge or his representative to maintain the records of cement the same has to be signed by the contractor.

24.00 In case of any ambiguity/conflict among various documents the decision of Engineer-in-charge will be final and binding.

B. SCOPE OF ELECTRICAL WORK

- 1) The contractor shall get approved all the items to be supplied (on basis of sample/ catalogue) for the wiring works from the concerned Electrical Engineer of the OIL before bulk purchasing of the materials. OIL will have the right to reject any procured item if any mismatch/discrepancy with respect to approved sample / contract specification is found.
- 2) All materials and works shall be guaranteed for minimum one year.
- 3) The supplied materials, design and workmanship shall satisfy the relevant Indian Standards, the job specifications contained herein & codes referred to. All electrical works shall be carried out in accordance with the provisions of CEA Regulations 2010, BIS standard, National Electric Code & National Building Code.

- PART-III SCC
- 4) The items given under Schedule of Quantity shall be read in conjunction with scope of work, scope of supply and job specifications.
- 5) Contractor shall employ work persons with valid wireman license issued or recognized by Electrical Licensing Board to carry out all electrical jobs and shall employ one supervisor holding valid supervisory certificate of competency issued by Electrical Licensing Board for supervision of electrical jobs.
- 6) Contractor should have his/her own set of tools and tackles required for wiring / installation works.
- 7) Contractor should arrange of his own (a) 1000V Insulation tester (megger), (b) Earth Resistance Tester, (c) Multi-meter for installation, testing and commissioning works.
- 8) SCOPE OF WORK: Brief details of work to be carried out by the contractor are as described below. This will include supply, storage, laying, installation, jointing and testing, obtaining approvals, testing and commissioning and completion of different works. The work shall be carried out as described in Schedule of Quantities (SOQ), specifications.

The scope of work shall cover complete electrification works of the Field Engg. Office Building for ITF Tengakhat Area. The broad items/activities covered under internal electrical works shall include the followings:

- (a) Preparation of layout/ single line diagram/ wiring diagram in consultation with OIL's electrical engineer.
- (b) Supply and fixing of materials as per SOQ and above mentioned layout/ single line diagram/ wiring diagram
- (c) Testing of the wirings and rectifications/corrections in the wiring etc. if any. Contactor shall inform OIL's electrical engineer well in advance to witness testing works. Contractor need submit a copy of the test certificate duly signed by competent licensed supervisor to the OIL before charging.
- (d) Final charging and commissioning.
- (e) Handing over
- 9) SCHEDULE OF QUANTITIES/RATE. : The quantities in the SOQ, against the various items are estimated maximum quantity required for the electrification of the said office building. However, billing will be done as per actual quantity utilised in the electrification work.
- 10) Quality of materials: All materials and equipment supplied by the contractor shall be brand new. They shall be of such design, size and material as to satisfactorily function under the rated conditions of operation and to withstand the environmental conditions at site.
- 11) Ratings of components: All components in a wiring installation, conductors, switches and accessories shall be of appropriate ratings of voltage, current, and frequency, as indicated in SOQ.

12) CABLES:

Wiring cables: All wiring cables shall be BIS marked, FRLS, single core, PVC insulated, PVC sheathed, 1100V grade, FIA, TAC, IS-694 approved with flexible stranded copper conductor. The smallest size of conductor for lighting circuits shall have a nominal cross sectional area of be 1.5 sq mm. The minimum size of conductor for 'power' wiring shall be 4 sq mm. Colour Code for cables must be followed as (a) Red, Yellow and Blue for individual phases, (b) Green for Earth, (c) Black for Neutral.

13) PVC Casing and Capping

- i) Fixing casing-capping: PVC casing and capping shall be BIS marked & of standard material free from defects of any kind. PVC casing and capping should be strong and properly fitted so as to hold wires laid in it 70% to its full capacity.
- ii) The earth continuity wire shall be provided in the casing throughout the length of wiring. The size of earth continuity wire shall be same size with the main wire for circuits. All metallic parts, switchboards, light fittings and power sockets shall be connected to the earth wires and the connection shall be electrically and mechanically sound.

PART-III SCC

- iii) The maximum number of PVC insulated 650/1100V grade copper conductors that can be drawn in a given size of casing capping should not be more than 70% of its cross sectional area.
- iv) Casing and capping system shall be complete in all respects, including their accessories.
- 14) WORK AND WORKMANSHIP: The work shall have to be coordinated with the electrical work and other allied jobs/trades to the entire satisfaction of Electrical Engineer-in-charge of OIL.
- 15) SAFETY REQUIREMENTS: Safety provisions in conformity with CEA regulations 2010 shall generally be under taken by the contractor to avoid any accidents during the execution of jobs. Safety measures to be taken by the Contractor:
- (a) While carrying out a job, contractor personnel must ensure isolation of live parts by switching off incoming power supply or by removing fuses. Testing tools like test lamps etc. must be used before start of work for ascertaining non-availability of power. Appropriate type of work permit (Cold work, Hot work, Electrical Work Permit, Excavation permit etc.) must be obtained from the Installation Manager/Concerned Engineer on daily basis before starting of any works at site.
- (b) When a ladder is used, one person shall be engaged at all times for holding the ladder.
- (c) The contractor shall submit one undertaking on safety measures to be adopted at site that he himself is aware of all electrical/safety and other hazards associated with the execution of the contract and has understood the necessary safety requirements to be adopted and that he/she shall not violate:
- (i) Stated safety procedures.
- (ii) Statutory rules and regulation.
- (iii) Shutdown procedure.
- (iv) Company (OIL) and departmental procedure / guidance while execution of the contract.
 - C. All safety precautions as per Company's guidelines are to be strictly adhered to. In this connection, the following guidelines are to be followed.
 - a) The Contractor shall be solely responsible to comply all the statutory norms as applicable while executing the job. It will be solely the Contractor's responsibility to fulfill all the legal formalities with respect to the Health, Safety and Environmental aspects of the entire job (namely: the person employed by him, the equipment, the environment, etc.) under the jurisdiction of the district of that state where it is operating. Ensure that all subcontractors hired by him comply with the same requirement as the Contractor himself and shall be liable for ensuring compliance of all HSE laws by the sub-contractors. It will be the responsibility of the Contractor/his Supervisor/representative to ensure strict adherence to all HSE measures and statutory Rules during operation in OIL's installations and safety of workers engaged by him. The crew members will not refuse to follow any instruction given by representative of OIL.
 - b) The Contractor shall ensure complete safety of the personnel and all the equipment engaged by him. They shall take full responsibility for their safety.
 - c) Contractor's arrangements for health and safety management shall be consistent with those for the company (OIL).
 - d) Contractor must, while at work, take reasonable care for the health and safety of people who are at the employee's place of work and who may be affected by the employee's act or omission at work. The contractor must cooperate with his/ her employee or other persons as far as is necessary to enable compliance with any requirement under the act or the regulations that is imposed in the interest of health, safety and welfare of the employee or any other person.
 - e) The Contractor may frame a mutually agreed bridging document if required between OIL & the Contractor for all issues not envisaged under the terms and conditions of the contract with the roles and responsibilities clearly defined.
 - f) The contractor has to keep a register of the persons employed by him/ her. The Contractor's supervisor shall take and maintain attendance of his/ her men every day for the work, punctually.

PART-III SCC

- g) Every person deployed by the Contractor must use appropriate PPEs (Personal Protective Equipment) to be provided by the Contractor. The Contractor shall provide Personnel Protective Equipment as per the hazard identified and risk assessed for the job and conforming to statutory requirement. Safety appliances like protective footwear, Safety Helmet and Full Body harness, Fall Prevention Devises (FPD) shall conform to relevant IS codes. If the Contractor fails to provide the safety items as mentioned above to the working personnel, the Contractor may request to the Company (OIL) for providing the same. In case of exigency OIL will provide the safety items if available. However in turn, OIL will recover the actual cost of the items by deducting from Contractor's Bill. However, it will be the Contractor's sole responsibility to ensure that the persons engaged by him use the proper PPE while at work. Contractor employees should be encouraged for proper use and maintenance of PPE. In absence of appropriate PPEs, the representative of OIL has the right to stop the work which will be binding for the Contractor. Moreover, the accountability towards any delay in work/ penalty due non-adherence to PPE shall be binding to the Contractor.
- h) All safety gears as per requirement of job are to be provided to the working personnel before commencement of the work.
- i) Standard Operating Procedures (SOPs) related to scope of work shall be handed over to the representative of OIL by Contractor including an assessment of risk, wherever possible and safe methods to deal with it/ them. The SOP should clearly mention the risk arising to men, machineries & material from the operations to be done by the contractor and how it is to be managed. However; in case of any doubts, the Contractor shall reconfirm the same from the Engineer In Charge (OIL).
- j) Contractor has to ensure that all work is carried out in accordance with the SOP and for the purpose he may deploy competent personnel for the purpose of carrying out the job in a safe manner. For the work which is not covered under SOP, the Contractor shall develop it and submit to the representatives of OIL.
- k) In case of deviation of SOP or non-availability of SOP, Job Safety Analysis (JSA) shall be carried out before commencement of the work.
- Necessary cold and hot work permits, wherever applicable, including excavation clearance and permission for working at height, Confined Space Entry are to be obtained by the competent person of the Contractor from Installation Manager before start of the job(s). Work Permit System should be inline as per guidelines issued by HSE Department.
- m) If the Company (OIL) arranges any safety awareness program/ training for the working personnel at site (company employee, Contractor worker, etc.) the Contractor will not have any objection to any such training.
- n) The Contractor or his representative shall arrange tool bod meetings and regular site safety meetings and maintain records.
- o) Contractor should ensure that all his personnel deployed are of sound health and medically fit as per the requirement of the job. The Contractor shall not engage minor labor below eighteen (18) years of age under any circumstances
- p) OIL will communicate all information to the Contractor or his authorized representative only. Contractor shall submit details of authorized representative wherever applicable.
- q) The Contractor shall have to report all incidents including near miss to the representative of OIL.
- r) Any compensation arising out of the job carried out by the Contractor whether related to pollution, Safety or Health will be paid by the Contractor only.
- s) Any compensation arising due to accident of the Contractor's personnel while carrying out the job, will be payable by the Contractor and their medical treatment/ facilities in case of accidents should be provided by the same contractor.

PART-III SCC

- t) The Contractor should prevent frequent change of his deployed employees as far as practicable. However, of OIL's Engineer In Charge found any person not suitable for the job, the Contractor has to remove the person and replace a suitable person.
- u) Necessary sign-board/ warning signals like "caution", "hot work in progress", "men at work", emergency telephone numbers etc. should be used wherever applicable. The said signals/ sign-boards shall have to be arranged by the contractor and shall be in line with the circular of signboards issued by HSE Department, Oil India Limited.
- v) Barricading of area to be done with reflecting tapes as applicable during work.
- w) The First-Aid box should be provided by the Contractor and the same has to be kept ready to use at the site.
- x) Smoking is prohibited in all Company restricted areas except in authorized smoking areas/ shelters. Carrying of matches and lighters into the Hazardous Area is prohibited. Cellular phones shall not be used in operating areas/ hazardous areas unless they have been classified as "intrinsically safe" for use in that atmosphere. Consumption of alcohol and possession of non-prescribed drug in Company work site is strictly prohibited.
- y) When there is a significant risk to health, environment or safety of a person or place arising because of a non-compliance of HSE Measures Company will have the right to direct the Contractor to cease work until the non-compliance is corrected.
- z) In case Contractor is found non-compliant of HSE laws as required and all the above mentioned general HSE points, company will have the right for directing the Contractor to take action to comply with the requirements, and for further non-compliance, appropriate action will be initiated against the Contractor.
- aa) Any requirement arise by the Statutory Authorities during the period of contract shall be applicable and binding for the Contractor.
- bb) For any HSE matters not specified in the contract document, the contractor will abide the relevant and prevailing Acts/rules/regulations/pertaining to Health, Safety and Environment.
- cc) Considering the ongoing Covid-19 pandemic, those who are engaged in the above operations should be followed the Covid-19 Protocol as per the prevailing Government Guidelines.
- dd) Job specific additional HSE points pertaining to Electrical jobs shall be added as per requirement.

D. CONTRACTOR'S RISKS:

All risks of loss of or damage to physical property and of physical injury and death to the personnel, which arise during the course of and in consequence of the performance of the contract, are the responsibility of the contractor.

E. INDEMNITY AND INSURANCE:

- a) The contractor shall provide suitable insurance coverage from the date of issuance of work order to the end of defect liability period of the contract for the following events which are due to the contractor's risks, irrespective of whether such loss or damages are caused on account of negligence of the Contractor or their personnel.
 - a. Loss of or damage to the works plants and materials.
 - b. Loss of or damage to the equipment.
 - c. Loss of or damage of property (except the works, plant, materials & equipment) in connection with the contract.
 - d. Physical injury or death of all his manpower deployed by him.
- b) In the event of any loss or damage, it shall be the responsibility of contractor to lodge the claim with insurer and Contractor shall put his best effort with the insurer for early settlement of the claim.

PART-III SCC

- c) The policies and certificates for insurance shall be submitted by the contractor to the engineer in charge before the issuance of Work Order. In case, the Contractor fails to arrange the Insurance or arranges insufficient insurance, for the events, as mentioned above against any or all insurable risks, the Contractor shall be solely liable for loss or damage arising from such events or causes.
- d) Contractor shall at his own expense arrange, secure, maintain and renew insurance for the events mentioned above throughout the contract period including the defect liability period.
- e) Indemnity Agreement:
 - The contractor shall at all times indemnify and keep indemnified the Company and its personnel from and against all third party claims whatsoever, including but not limited to property loss and damage, personal accident, injury or death of or to property or person and any sub-contractor or agents of the contractor or Company.
 - F. The contractor shall deposit the PAN and GST registration number (if applicable, as per Statutory GST Regulations) as and when required by the Company. If the above are not available with the contractor, the contractor must apply for the same after signing of the Contract and submit the same within 45 days of signing the contract (or as and when advised by the Company, after 45 days of signing the contract). Moreover, the statutory guidelines of Goods and Service Tax (GST) shall be adhered to by the contractor.
 - G. A Hindrance Register shall be maintained in the enclosed Format to record all hindrances encountered during execution of works against the contract. The items of work affected due to any hindrance shall be clearly recorded in the Hindrance Register and the Engineer-in-charge of the Company as well as the site representative of the Contractor will sign on the register against the recorded hindrance. In case of encountering multiple hindrances simultaneously over a period of time affecting the same item or different items, the net period of hindrance will be worked out considering the overlapping period.
 - H. Company reserves the right to initiate actions against the bidder / contractor during processing of tender and / or during continuation of the contract as per OIL's Banning Policy dated 6th Jan 2017 available at OIL's website.
 - I. Defect liability period shall be 6 months beyond the date of completion of works as certified by Engineer-In-Charge. During defect liability period, all corrective works shall be carried out entirely at Contractor's own expenses. If such corrective works are not carried out within a reasonable time, the Company, at its discretion, may have such remedial works carried out by other agencies and charge the cost thereof to the Contractor. This amount shall be deducted from contractor's bill/ Retention money/ Performance security.

OIL INDIA LIMITED (A Govt. of India Enterprise) Contracts, Duliajan

WORKS CONTRACT

Schedule of Company's Plants, Materials and Equipment

- A. SCHEDULE OF MATERIALS AVAILABLE AT THE COMPANY'S STORES/STOCK PILES for permanent incorporation in works and
- B. SCHEDULE OF COMPANY'S PLANTS AND EQUIPMENT for use in the execution of work.
- 1) **MATERIALS:** Cement will be supplied by company (i.e. OIL).
- 2) PLANTS AND EQUIPMENT: Nil.

Notes:

- 1. The Contractor is to arrange transport of the above materials to site of work with proper safety.
- 2. Plants and equipment if issued to Contractor must be under proper watch so that no part is pilfered. These must be handled only by Company's operators. Contractor shall be responsible for any loss or damage to these plants and equipment while these are under his/their custody.
- 3. Materials issued to Contractor must be under proper watch & ward so that no part is pilfered. If any pilferage takes place the matter will be referred to appropriate Govt. authorities for legal action as well as realization of the materials issued.
- 4. Cement issued to Contractor by the Company is meant only for the specific Company work relating to the Contract. However, if any quantity of Cement is left over from the quantities issued for any reason whatsoever, on the completion / cancellation / termination of the Contract the same shall have to be returned to the Company in full within one week of completion/cancellation of the work failing which the matter will be referred to appropriate Govt. authorities for legal action as well as realization of the Cement.
- 5. All empty Cement bags must be returned to material's Godown, failing which a sum of Rs.8.00 (Rupees Eight) only per bag will be recovered from contractor's bill.

PART-V SAFETY MEASURES

To, GM-CONTRACTS (HOD) OIL INDIA LIMITED DULIAJAN-786602

SUB: SAFETY MEASURES

<u>DESCRIPTION OF WORK/SERVICE</u>: Civil construction jobs to facilitate the relocation of gas lift compressor from GCS-Ushapur to GCS-Tengakhat.

- (1) Construction of Operator cum Maintenance Room.
- (2) Earth filling, brick soling & Cement Concrete work.
- (3) Extension of shed for Gas Lift Compressor.

Sir,

We hereby confirm that we have fully understood the safety measures to be adopted during execution of the above contract and that the same have been explained to us by the concerned authorities. We also give the following assurances.

- a) Only experienced and competent persons shall be engaged by us for carrying out work under the said contract.
- b) The names of the authorized persons who would be supervising the jobs on day to day basis from our end are the following:

i) _	
ii)	
iii)	

The above personnel are fully familiar with the nature of jobs assigned and safety precautions required.

- c) Due notice would be given for any change of personnel under item (b) above.
- d) We hereby accept the responsibility for the safety of all the personnel engaged by us and for the safety of the Company's personnel and property involved during the course of our working under this contract. We would ensure that all the provisions under the Oil Mines Regulations, 2017 and other safety rules related to execution of our work would be strictly followed by our personnel. Any violation pointed out by the Company's Engineers would be rectified forthwith or the work suspended till such time the rectification is completed by us and all expenditure towards this would be on our account.
- e) We confirm that all persons engaged by us would be provided with the necessary Safety Gears at our cost.
- f) All losses caused due to inadequate safety measures or lack of supervision on our part would be fully compensated by us and the Company will not be responsible for any lapses on our part in this regard.
- g) We shall abide by the HSE (Health Safety & Environment) points mentioned in SCC.

(Seal)	Yours Faithfully
Date	M/s
	CONTRACTOR

PART-VI INTEGRITY PACT

INTEGRITY PACT

Between

Oil India Limited (OIL) hereinafter referred to as "The Principal"
And

(Name of the bidder).....hereinafter referred to as "The Bidder/Contractor"

Preamble:

The Principal intends to award, under laid down organizational procedures, contract/s for

Civil construction jobs to facilitate the relocation of gas lift compressor from GCS-Ushapur to GCS-Tengakhat.

- (1) Construction of Operator cum Maintenance Room.
- (2) Earth filling, brick soling & Cement Concrete work.
- (3) Extension of shed for Gas Lift Compressor.

The Principal values full compliance with all relevant laws and regulations, and the principles of economic use of resources, and of fairness and transparency in its relations with its Bidder/s and Contractor/s.

In order to achieve these goals, the Principal cooperates with the renowned international Non-Governmental Organisation "Transparency International" (TI). Following TI's national and international experience, the Principal will appoint an external independent Monitor who will monitor the tender process and the execution of the contract for compliance with the principles mentioned above.

Section 1 - Commitments of the Principal

- (1) The Principal commits itself to take all measures necessary to prevent Corruption and to observe the following principles:-
 - I. No employee of the Principal, personally or through family members, will in connection with the tender for, or the execution of a contract, demand, take a promise for or accept, for him/herself or third person, any material or immaterial benefit which he/she is not legally entitled to.
 - II. The Principal will, during the tender process treat all Bidders with equity and reason. The Principal will in particular, before and during the tender process, provide to all Bidders the same information and will not provide to any Bidder confidential/ additional information through which the Bidder could obtain an advantage in relation to the tender process or the contract execution.
 - III. The Principal will exclude from the process all known prejudiced persons.
- (2) If the Principal obtains information on the conduct of any of its employees which is a criminal offence under the relevant Anti-Corruption Laws of India, or if there be a substantive suspicion in this regard, the Principal will inform its Vigilance Office and in addition can initiate disciplinary actions.

Section 2 - Commitments of the Bidder/Contractor

- (1) The Bidder/Contractor commits itself to take all measures necessary to prevent corruption. He commits himself to observe the following principles during his participation in the tender process and during the contract execution.
 - I. The Bidder/Contractor will not, directly or through any other person or firm, offer, promise or give to any of the Principal's employees involved in the tender process or the execution of the contract or to any third person any material or immaterial benefit which he/she is not legally entitled to, in order to obtain in exchange any advantage of any kind whatsoever during the tender process or during the execution of the contract.
- II. The Bidder/Contractor will not enter with other Bidders into any undisclosed agreement or understanding, whether formal or informal. This applies in particular to prices, specifications,

Contractor 1 Company

PART-VI INTEGRITY PACT

certifications, subsidiary contracts, submission or non-submission of bids or any other actions to restrict competitiveness or to introduce cartelisation in the bidding process.

- III. The Bidder/Contractor will not commit any offence under the relevant anticorruption Laws of India; further the Bidder/Contractor will not use improperly, for purposes of competition or personal gain, or pass on to others, any information or document provided by the Principal as part of the business relationship, regarding plans, technical proposals and business details, including information contained or transmitted electronically.
- IV. The Bidder/Contractor will, when presenting his bid, disclose any and all payments he has made, is committed to or intends to make to agents, brokers or any other intermediaries in connection with the award of the contract.
- V. Bidders to disclose any transgressions with any other company that may impinge on the anticorruption principle.
- VI. The Bidder (s)/ Contractor of foreign origin shall disclose the name and address of the Agents/ representatives in India, if any. Similarly, the Bidder (s)/ Contractor (s) of Indian Nationality shall furnish the name and address of the foreign principals, if any. Further, all the payments made to the Indian agent/ representative have to be in India Rupees only.
- VII. Bidders not to pass any information provided by Principal as part of business relationship to others and not to commit any offence under PC/ IPC Act.
- (2) The Bidder/Contractor will not instigate third persons to commit offences outlined above or be an accessory to such offences.
- (3) The Bidder/Contractor signing Integrity Pact shall not approach the Courts while representing the matters to IEMs and he/she will await their decision in the matter.

Section 3 - Disqualification from tender process and exclusion from future Contracts

If the Bidder, before contract award has committed a transgression through a violation of Section 2 or in any other form such as to put his reliability or risibility as Bidder into question, the Principal is entitled to disqualify the Bidder from the tender process or to terminate the contract, if already signed, for such reason.

- 1. If the Bidder/Contractor has committed a transgression through a violation of Section 2 such as to put his reliability or credibility into question, the Principal is entitled also to exclude the Bidder/Contractor from future contract award processes. The imposition and duration of the exclusion will be determined by the severity of the transgression. The severity will be determined by the circumstances of the case, in particular the number of transgressions, the position of the transgressions within the company hierarchy of the Bidder and the amount of the damage. The exclusion will be imposed for a minimum of 6 months and maximum of 3 years.
- 2. The Bidder accepts and undertakes to respect and uphold the Principal's Absolute right to resort to and impose such exclusion and further accepts and undertakes not to challenge or question such exclusion on any ground, including the lack of any hearing before the decision to resort to such exclusion is taken. This undertaking is given freely and after obtaining independent legal advice.
- 3. If the Bidder/Contractor can prove that he has restored/recouped the Damage caused by him and has installed a suitable corruption prevention system, the Principal may revoke the exclusion prematurely.
- 4. A transgression is considered to have occurred if in light of available evidence no reasonable doubt is possible.
- 5. Integrity Pact, in respect of a particular contract, shall be operative from the date Integrity Pact is signed by both the parties till the final completion of the contract **or as mentioned in Section 9- Pact Duration whichever is later**. Any violation of the same would entail disqualification of the

Contractor 2 Company

PART-VI INTEGRITY PACT

bidders and exclusion from future business dealings. Any issue relating to execution of contract, if specifically raised before the IEMs shall be looked into by IEMs.

Section 4 - Compensation for Damages

- 1. If the Principal has disqualified the Bidder from the tender process prior to the award according to Section 3, the Principal is entitled to demand and recover from the Bidder liquidated damages equivalent to Earnest Money Deposit / Bid Security.
- 2. If the Principal has terminated the contract according to Section 3, or if the Principal is entitled to terminate the contract according to section 3, the Principal shall be entitled to demand and recover from the Contractor liquidated damages equivalent to Security Deposit / Performance Bank Guarantee.
- 3. The bidder agrees and undertakes to pay the said amounts without protest or demur subject only to condition that if the Bidder/Contractor can prove and establish that the exclusion of the Bidder from the tender process or the termination of the contract after the contract award has caused no damage or less damage than the amount or the liquidated damages, the Bidder/Contractor shall compensate the Principal only to the extent of the damage in the amount proved.

Section 5 - Previous transgression

- 1. The Bidder declares that no previous transgression occurred in the last 3 years with any other Company in any country conforming to the TI approach or with any other Public Sector Enterprise in India that could justify his exclusion from the tender process.
- 2. If the Bidder makes incorrect statement on this subject, he can be disqualified from the tender process or the contract, if already awarded, can be terminated for such reason.

Section 6 - Equal treatment of all Bidders/Contractor/Subcontractors

- 1. The Principal will enter into Pacts on identical terms with all bidders and contractors.
- 2. The Bidder / Contractor undertake(s) to procure from all subcontractors a commitment in conformity with this Integrity Pact. The Bidder/Contractor shall be responsible for any violation(s) of the provisions laid down in this agreement/Pact by any of its sub-contractors/sub-vendors.
- 3. The Principal will disqualify from the tender process all bidders who do not sign this Pact or violate its provisions.

Section 7 - Criminal charges against violating Bidders/Contractors/Subcontractors

If the Principal obtains knowledge of conduct of a Bidder, Contractor or Subcontractor, or of an employee or a representative or an associate of a Bidder, Contractor or Subcontractor, which constitutes corruption, or if the Principal has substantive suspicion in this regard, the Principal will inform the Vigilance Office.

Section 8 - External Independent Monitor/Monitors (three in number depending on the size of the contract) (to be decided by the Chairperson of the Principal)

- 1. The Principal appoints competent and credible external independent Monitor for this Pact. The task of the Monitor is to review independently and objectively, whether and to what extent the parties comply with the obligations under this agreement.
- 2. The Monitor is not subject to instructions by the representatives of the parties and performs his functions neutrally and independently. He reports to the Chairperson of the Board of the Principal.

Contractor 3 Company

PART-VI INTEGRITY PACT

- 3. The Contractor accepts that the Monitor has the right to access without restriction to all Project documentation of the Principal including that provided by the Contractor. The Contractor will also grant the Monitor, upon his request and demonstration of a valid interest, unrestricted and unconditional access to his project documentation. The same is applicable to Subcontractors. The Monitor is under contractual obligation to treat the information and documents of the Bidder/Contractor/Subcontractor with confidentiality. However, the documents/ records/ information having National Security implications and those documents which have been classified as Secret/ Top Secret are not to be disclosed.
- 4. The Principal will provide to the Monitor sufficient information about all meetings among the parties related to the Project provided such meetings could have an impact on the contractual relations between the Principal and the Contractor. The parties offer to the Monitor the option to participate in such meetings.
- 5. As soon as the Monitor notices, or believes to notice, a violation of this agreement, he will so inform the Management of the Principal and request the Management to discontinue or heal the violation, or to take other relevant action. The monitor can in this regard submit non-binding recommendations. Beyond this, the Monitor has no right to demand from the parties that they act in a specific manner, refrain from action or tolerate action. However, the Independent External Monitor shall give an opportunity to the bidder / contractor to present its case before making its recommendations to the Principal.
- 6. The Monitor will submit a written report to the Chairperson of the Board of the Principal within 8 to 10 weeks from the date of reference or intimation to him by the 'Principal' and, should the occasion arise, submit proposals for correcting problematic situations.
- 7. If the Monitor has reported to the Chairperson of the Board a substantiated suspicion of an offence under relevant Anti-Corruption Laws of India, and the Chairperson has not, within reasonable time, taken visible action to proceed against such offence or reported it to the Vigilance Office, the Monitor may also transmit this information directly to the Central Vigilance Commissioner, Government of India.
- 8. The word 'Monitor' would include both singular and plural.
- 9. In case of any complaints referred under IP Program, the role of IEMs is advisory and would not be legally binding and it is restricted to resolving the issues raised by an intending bidder regarding any aspect of the tender which allegedly restricts competition or bias towards some bidder.

Section 9 - Pact Duration

This Pact begins when both parties have legally signed it. It expires for the Contractor 12 months after the last payment under the respective contract, and for all other Bidders 6 months after the contract has been awarded.

If any claim is made/ lodged during this time, the same shall be binding and continue to be valid despite the lapse of this pact as specified above, unless it is discharged/determined by Chairperson of the Principal.

Section 10 - Other provisions

- 1. This agreement is subject to Indian Law. Place of performance and jurisdiction is the Registered Office of the Principal, i.e. New Delhi. The Arbitration clause provided in the main tender document / contract shall not be applicable for any issue / dispute arising under Integrity Pact.
- 2. Changes and supplements as well as termination notices need to be made in writing. Side agreements have not been made.
- 3. If the Contractor/ bidder is a Joint Venture or a partnership concern or a consortium, this agreement must be, signed by all partners or consortium members. In case of sub-contracting, the Principal

Contractor 4 Company

PART-VI INTEGRITY PACT

contractor shall take the responsibility of the adoption of IP by the sub-contractor and all sub-contractors shall also sign the IP.

4. Should one or several provisions of this agreement turn out to be invalid, the remainder of this agreement remains valid. In this case, the parties will strive to come to an agreement to their original intensions.

5. Issues like warranty/ guarantee, etc. shall be outside the purview of IEMs.

UNDERTAKING BY BIDDER IN RESPECT OF QUOTED PRICE AGAINST TENDER

<u>Description of Work:</u> Civil construction jobs to facilitate the relocation of gas lift compressor from GCS-Ushapur to GCS-Tengakhat.

- (1) Construction of Operator cum Maintenance Room.
- (2) Earth filling, brick soling & Cement Concrete work.
- (3) Extension of shed for Gas Lift Compressor.

I/We do hereby solemnly affirm and declare as under:

- a) That I/we have gone through all the tender documents (i) Covering Letter (ii) BEC/BRC (iii) GCC (iv) SOQ (iv) SCC (v) SCPME (vi) SM (vii) IP and agree with all the terms and conditions provided there in.
- b) I/We have submitted the "One Time Security Deposit" in line with OIL's notification no.: CONT/CIV/988/2016 dated 01.07.2016, on or before 13:30 Hrs. of Bid Closing/Opening date of this tender.
- c) That I/we hereby offer to execute the work described above at the price quoted in the "Total Bid Value" (under RFx Information > Basic Data > Total Bid Value) inclusive of all liabilities including statutory liabilities except PF & GST in accordance with the Contract Terms & Conditions, which I/ we have fully understood.

(Note: Uploading in the OIL's e-portal with digital signature will be construed that the same has been signed by the bidder's authorized signatory who has signed the bid).

(To be typed on the letter head of the bidder)

To GM-CONTRACTS (HOD) OIL INDIA LIMITED DULIAJAN

Dear Sirs,		
Sub: UNDERTAKING/DECLARATION BY THE BIDDER (S) IN RESPECT OF TENDER NO.		
(To be submitted by the Bidders who are not covered under EPF&MP Act, 1952)		
This is in connection with the Bid submitted by(Name of the Bidder) against Tenderfor(subject of the Tender). As per the conditions stipulated in Clause no(Name of the Provision/Covering Letter etc.), we/I ,being authorized on behalf of(Name of the Contractor) hereby confirm and undertake as follows;		
 That our Firm/Company shall be responsible to comply with all the applicable labour laws in respect of the present Contract. 		
 That we are fully conversant with the applicable laws and confirm that our Firm/Company is not covered under the Employees Provident Funds and Misc. Provisions Act, 1952 and applicable Rules there under, and therefore I we have not obtained any registration or Provident Fund Code under the Act. 		
 That if, during the period of the present Contract, we/our Firm /Company comes within the coverage of the aforesaid Acts or any other statutes; we shall comply with the same and submit the necessary documents to OIL. We further confirm that we will indemnify OIL towards any future statutory compliances/claims raised from any corner including statutory authorities against the Labour engaged by our Firm/Company in the Contract. 		
 That in the event of any contravention towards the applicable laws found on our part in respect of the present Contract, we undertake to indemnify OIL and deposit the claims, if any. 		
 That we shall fulfill all the obligations arising from under the labour laws in force from time to time and keep OIL indemnified against any loss/liability arising out of failure of our avoiding the laws. 		
We, further agree and undertake that in case of any violation of the above undertaking, OIL shall be at liberty to take appropriate action against us in terms of the Tender including but not limited to termination of contract and debarment from future business with OIL.		
I/We declare that the information given above is true and any misstatement or misrepresentation or suppression of facts in connection with the above undertaking may entail rejection of the bid and cancellation of contract, if awarded.		
Yours faithfully,		
1. Authorized Signatory(BIDDER)		
Place:- Date:-		

ANNEXURE II - FORMAT FOR HINDRANCE REGISTER

Descr	ription of Project :		Contract No. & Date :					
Contractor's Name :				Scheduled Completion Date :				
Sl. No.	Nature of Hindrance	Items of work that could not be executed because of this hindrance	Date of start of hindrance	Date of Removal of hindrance	Period of hindrance	Overlapping Period, if any	Net hindrance days	Remarks
	Signature of Contractor's	s Representative	Signa	iture of Engine	eer-in-charge		Signat	ture of HoD

Annexure- III

Format of undertaking by Bidders towards submission of authentic information/documents (To be typed on the letter head of the bidder)

Ref. No

Ref. No	Date
Sub: Undertaking of authenticity of informa Ref: Your tender No Dated	
To, CGM - Contracts Contracts Deptt, OIL, Duliajan	
Sir,	
With reference to our quotation against your fraudulent information/documents have been	above-referred tender, we hereby undertake that no submitted by us.
We take full responsibility for the submission above cited bid.	on of authentic information/documents against the
information/documents submitted by us are	he tender/contract agreement, in case any of the found to be false/forged/fraudulent, OIL has right to of our EMD and/or PBG and/or cancel the award of on on us, as deemed fit.
Yours faithfully, For (Name of the firm)
Signature of Authorised Signatory	
Name:	
Designation:	
Phone No.	
Place:	
Date:	
(Affix Seal of the Organization here, if applicab	le)