OIL INDIA LIMITED

(A Govt. of India Enterprise) P.O. Duliajan-786602, Assam.

Fax No. 91-374-2800533, E-mail:material@oilindia.in

Tender No. & Date : DFD6554L15/06 16.03.2015

Bid Security Amount : INR 0.00 OR USD 0.00

(or equivalent Amount in any currency)

Bidding Type : Single Bid (Composite Bid)

Bid Closing On : 15.07.2015 at 13:00 hrs. (IST) Bid Opening On : 15.07.2015 at 13:00 hrs. (IST)

Performance Guarantee: Not Applicable

OIL INDIA LIMITED have issued Limited tenders to following parties for items detailed below. For General Terms & Conditions, please refer to Document No. MM/GLOBAL/01/2005 available in OIL's web site:

| Item No./ | Material Description | Quantity | UOM |
|-----------------------------|---|----------|-----|
| Mat. Code 10 0C000493 | ROTARY SUB | | NO |
| 00000433 | X-OVER SUB, 27/8" IF(B)LH X 27/8" SLH 90(P)LH | | |
| | Rotary substitutes manufactured from AISI 4145 H modified alloy steel fully heat-treated to 285-341 Brinell hardness and 52 Joules minimum impact strength conforming to the requirement of API Spec 7. All connections are to be machined and finished to API standards. Thread roots are to be cold rolled. Connections are phosphatized, coated with lubricant and equipped with pressed steel thread protectors installed at both ends. | | |
| | ITEM SPECIFICATION: | | |
| | Crossover sub, in conformance with API Spec 7-1. | | |
| | OD = 4.1/8 inch (104.77 mm) ID / Bore = 2.5/32 inch (54.768 mm) Overall length = 36 inch (914.40 mm) | | |
| | API Connection = 2.7/8 inch (73.025 mm) IF LH Box X 2.7/8 inch (73.025 mm) SLH 90 LH Pin. | | |
| <u>20</u> | ITEM DESCRIPTION | 2 | NO |
| 0C000493 | X-OVER SUB, 27/8" Tbg(P)LH X 27/8" SLH 90(B)LH, 2 Nos | | |
| | Rotary substitutes manufactured from AISI 4145 H modified alloy steel fully heat-treated to 285-341 Brinell hardness and 52 Joules minimum impact strength conforming to the requirement of API Spec 7. All connections are to be machined and finished to API standards. Thread roots are to be cold rolled. Connections are phosphatized, coated with lubricant and equipped with pressed steel thread protectors installed at both ends. | | |

Tender No. & Date : DFD6554L15/06 16.03.2015

| Item No./ Mat. Code | Material Description | Quantity | UOM |
|------------------------|---|----------|-----|
| | ITEM SPECIFICATION: | | |
| | Crossover sub, in conformance with API Spec 7-1. | | |
| | OD = 3.7/8 inch (98.425 mm) ID / Bore = 2.5/32 inch (54.768 mm) Overall length = 36 inch (914.40 mm) | | |
| | API Connection = 2.7/8 inch (73.025 mm)Tbg EUE LH Pin X 2.7/8 inch (73.025 mm) SLH 90 LH Box. | | |
| 30 | ITEM DESCRIPTION | 2 | NO |
| 0C000493 | X-OVER SUB, 27/8" Tbg(B)LH X 27/8" IF(P)LH, 2 Nos. | | |
| | Rotary substitutes manufactured from AISI 4145 H modified alloy steel fully heat-treated to 285-341 Brinell hardness and 52 Joules minimum impact strength conforming to the requirement of API Spec 7. All connections are to be machined and finished to API standards. Thread roots are to be cold rolled. Connections are phosphatized, coated with lubricant and equipped with pressed steel thread protectors installed at both ends. | | |
| | ITEM SPECIFICATION: | | |
| | Crossover sub, in conformance with API Spec 7-1. | | |
| | OD = 4.1/8 inch (104.775 mm) ID / Bore = 2.5/32 inch (54.768 mm) Overall length = 36 inch (914.40 mm) | | |
| | API Connection = 2.7/8 inch (73.025 mm)Tbg EUE LH Box X 2.7/8 inch (73.025 mm) IF LH Pin. | | |
| 40 | ITEM DESCRIPTION | 2 | NO |
| 0C000493 | X-OVER SUB, 27/8" SLH 90(B)LH X 27/8" SLH 90(P)RH, 2 Nos | | |
| | Rotary substitutes manufactured from AISI 4145 H modified alloy steel fully heat-treated to 285-341 Brinell hardness and 52 Joules minimum impact strength conforming to the requirement of API Spec 7. All connections are to be machined and finished to API standards. Thread roots are to be cold rolled. Connections are phosphatized, coated with lubricant and equipped with pressed steel thread protectors installed at both ends. | | |
| | ITEM SPECIFICATION: | | |
| | Crossover sub, in conformance with API Spec 7-1. | | |
| | OD = 3.7/8 inch (98.425 mm) | | |

Page: 3/4

Tender No. & Date: DFD6554L15/06 16.03.2015

| Item No./ Mat. Code | Material Description | Quantity | UOM |
|------------------------------|---|----------|-----|
| | ID / Bore = 2.5/32 inch (54.768 mm) Overall length = 36 inch (914.40 mm) | | |
| | API Connection = 2.7/8 inch (73.025 mm) SLH 90 LH Box X 2.7/8 inch (73.025 mm) SLH 90 RH Pin. | | |
| <u>50</u> 0C000493 | ITEM DESCRIPTION | 2 | NO |
| 0000493 | X-OVER SUB, 27/8" SLH 90(B)LH X 27/8" Reg(P)LH, 2 Nos. | | |
| | Rotary substitutes manufactured from AISI 4145 H modified alloy steel fully heat-treated to 285-341 Brinell hardness and 52 Joules minimum impact strength conforming to the requirement of API Spec 7. All connections are to be machined and finished to API standards. Thread roots are to be cold rolled. Connections are phosphatized, coated with lubricant and equipped with pressed steel thread protectors installed at both ends. | | |
| | ITEM SPECIFICATION: | | |
| | Crossover sub, in conformance with API Spec 7-1. | | |
| | OD = 3.7/8 inch (98.425 mm) ID / Bore = 2.5/32 inch (54.768 mm) Overall length = 36 inch (914.40 mm) | | |
| | API Connection = 2.7/8 inch (73.025 mm) SLH 90 LH Box X 2.7/8 inch (73.025 mm) Reg LH Pin. | | |

- Special Notes: 1. The items shall be brand new, unused & of prime quality. Bidder shall warrant (in the event of an order) that the product supplied will be free from all defects & fault in material, workmanship & manufacture and shall be in full conformity with ordered specifications. This clause shall be valid for 18 months from date of despatch/shipment or 12 months from date of receipt items at site whichever is earlier. The defective materials, if any, rejected by us shall receipt items at site whichever is earlier. The defective materials, if any, rejected by us shall be replaced by the supplier at their own expense. Bidders must confirm the same while quoting.
 - 2. The minimum FOB/FCA charges in case of partial order for reduced quantity/ items shall have to be indicated by the bidder. In case this is not indicated specifically, the charges quoted would be prorata calculated and the same will be binding on the bidder.
 - 3. All rotary substitutes shall have API bore back box and / or API stress relief groove on pin ends (wherever applicable) as per API Spec 7.
 - 4. Thread roots of all the rotary substitutes shall be cold rolled & phosphatised.
 - 5. All the connections should be coated with thread lubricants and protected with pressed steel thread protectors.

- 6. Items shall be manufactured, tested & certified as per API Spec.7-1 and mill inspection certificate thereof should be forwarded along with supply. Bidders to confirm the same while quoting. A copy of valid API Spec 7-1 certificate must be forwarded along with the offer.
- 7. Markings (including API monogram) shall be done as per API Spec 7-1. Additionally, purchase order number should be die stamped along with the name of manufacturer. Bidder should confirm while quoting.
- 8. The quotation must accompany relevant catalogue, literature, drawing, etc. Drawing indicating length, OD, bore, size & style of connection should be forwarded for each item.
- 9. Bidder should have an experience of minimum 5 (five) years in manufacturing the quoted items under API Spec.7-1 certification. For this purpose the period reckoned shall be the period prior to the date of opening of the techno-commercial bid. Copies of API Spec.7-1 certificates for the last 5 (Five) years (i.e. continuous without having any break in between) must be submitted along with techno- commercial bid. Bids without copies of valid API Spec.7-1 certificates or with a break in between will be rejected.
- 10. In case the bidder is sole selling agent / distributor / dealer / supply house of any API approved manufacturer, then bidder must furnish the following documents:
- (i) Back-up authority cum warranty letter in original on manufacturer's letter head, valid at the time of bidding which should remain valid during the entire execution period of the order, from the concerned manufacturer guaranteeing supply of the items to the bidder in the event of an order on the bidder and also authorized them to market their products.
- (ii) Copies of valid API Spec.7-1 certificate of manufacturer as stated in point 6 above.

Validity of the offers should be 120 days from the date of bid opening. Bids with lesser validity shall be rejected.

- 11. Quotation must be submitted in triplicate.
- 12. The items covered by this tender shall be used by Oil India Limited in the PEL/ML areas which are issued/renewed after 01/04/99 and hence Nil Customs Duty during import will be applicable. Deemed Export Benefit for domestic bidders is not applicable against this tender. Domestic Bidders to quote their prices without considering the Deemed Export Benefit. Domestic bidders to alsoquote the applicable rate of Excise Duty in their price bid. If a domestic bidder emerges L1 after loading of applicable rate of Excise Duty, order shall be placed upon the bidder inclusive of the Excise Duty amount.

Tender No. : DFD6554L15/06 Tender Date : 16.03.2015

Bid Closing On : 15.07.2015 at 13:00 hrs.(IST)
Bid Opening On : 15.07.2015 at 13:00 hrs.(IST)

Tender issued to following parties only:

| Class | \/_ O = d = | Mandan Nama | Oit /Os water |
|-------|-------------|-------------------------------------|-----------------|
| Slno | V_Code | Vendor Name | City/Country |
| 1 | 100039 | HACKER INTERNATIONAL, LLC | TEXAS |
| 2 | 100070 | SMF INTERNATIONAL | COSNE COURS SUR |
| 3 | 100079 | VALLOUREC & MANNESMANN TUBES | CEDEX |
| 4 | 100119 | OMSCO INDUSTRIES INC | TEXAS |
| 5 | 100142 | PACKARD INTERNATIONAL INC. | TEXAS |
| 6 | 100457 | WEATHERFORD OIL TOOL MIDDLE-EAST LT | DUBAI |
| 7 | 100458 | BAKER HUGHES INTEQ GMBH | CELLE |
| 8 | 100557 | GOTCO INTERNATIONAL INC , | HOUSTON |
| 9 | 100596 | GRANT PRIDECO(SINGAPORE) PTE LTD. | SINGAPORE |
| 10 | 100615 | DARRON OIL TOOLS | |
| 11 | 100617 | NATIONAL OILWELL VARCO | U.S.A. |
| 12 | 100707 | HYDRIL COMPANY | HOUSTON |
| 13 | 100829 | TUBE-ALLOY | EDO,ZULIA |
| 14 | 100843 | GRANT PRIDECO | TEXAS |
| 15 | 100867 | CROSSOVER INC | LOS ANGLES |
| 16 | 100984 | SMITH INTERNATIONL INC. | DUBAI |
| 17 | 101113 | VETCO GRAY PETROLEUM EQUIPMENTS | JURANG TOWN |
| 18 | 101520 | DRILCO INDUSTRIAL | USA |
| 19 | 101916 | VAM DUBAI LLC | DUBAI |
| 20 | 200103 | OIL COUNTRY TUBULAR LIMITED | HYDERABAD |

NOTICE

Other than the vendors to whom the enquiry has been issued, interested vendors who wish to participate in the tender may apply with proper credentials and other relevant details so as to reach Head-Materials, Oil India Limited, P.O. Duliajan, Dist. Dibrugarh, Assam – 786602 (E-mail: material@oilindia.in, Fax: 0374-2800533) within 10 days of publication of the tender in OIL's website.

The vendors must fulfill the following conditions:

- i) The party should have three years' experience as on the Bid closing date for the same item.
- ii) The party should have received one order for at least 50% quantity in last three years (as on the Bid closing date) for the item from any reputed firm.
- iii) Annual turnover of the firm in any of the last three financial years or current financial year should be more than Rs 10 Lakhs.
- <u>NOTE</u>: i) Relevant documents in support of experience, last order and annual turnover must be submitted along with the application.
 - ii) Application without complete supporting document will not be considered.
