OIL INDIA LIMITED (A Govt. of India Enterprise) Udyan Vihar, Narengi, Guwahati, Fax-91 0361 2643686 Email-oilmatpl@oilindia.in

Assam

Tender No. & Date : GOD6538L15/2K 12.03.2015

Bid Security Amount : INR 0.00 OR USD 0.00

(or equivalent Amount in any currency)

Bidding Type : Single Bid (Composite Bid)

Bid Closing On : 09.04.2015 at 13:00 hrs. (IST) Bid Opening On : 09.04.2015 at 13:00 hrs. (IST)

Performance Guarantee: Not Applicable

OIL INDIA LIMITED invites Limited tenders for items detailed below:

Item No./ Mat. Code	Material Description	Quantity	UOM
10	Multi Grade, Non-Metallic, Single Mode, Composite Optical Fibre cable with 24 Fibre counts, out of this 6 fibre counts are as per ITU-G.655 and 18 fibre counts are as per ITU-G.652D specifications. Both grades of fibers(ITU G.652D and ITUG.655) must be manufactured as per TEC specifications.	30	KM

Special Notes: 1.Detailed technical specification as per copy of Annexure I attached.

- 2. Bidders other than OEM must submit valid authorized dealership/authorization certificate from OEM along with their offer.
- 3. To evaluate the inter-se ranking of the offers, Assam Entry Tax on purchase value will be loaded as per prevailing government of Assam Guidelines as applicable on bid closing date. Bidders may check this With the appropriate authority, while submitting their bids.
- 4. Bidder should quote transportation charges on actual separately if not included in basic price. Transportation charges have to be quoted for transportation by mode as below:-
- i) For consignments weighing around 100 Kgs, Actual transportation charge to be quoted for transportation by courier service (Air/Road).
- ii) For consignment weighing more than the weight mentioned in Sl.No.(i), actual transportation cost shall be quoted for transportation by Road transport.
- 5. Any sum of money due and payable to the contractor (including Security Deposit refundable to them) under this or any other contract may be appropriated by Oil India Limited and set off against any claim of Oil India Limited (or such other person or person contracting through Oil India Limited) for payment of a sum of money arising out of this contract or under any other contract made by the contractor with Oil India Limited (or such other person or persons contracting though Oil India Limited).
- 6. Any statutory variation (increase / decrease)in the rate of excise duty / sales tax/Customs

Duty or any statutory levy after the closing date of tenders / revised priced bid, as the case may be, but within the contractual delivery /completion period will be to the account of OIL subject to documentary evidence. However, any increase in excise duty /sales tax / Customs Duty or any statutory levy after the expiry of the scheduled date of delivery shall be to the supplier's account.

- 7. Please confirm acceptance of NIT payment terms.
- 8. Terms and conditions applicable to this tender is enclosed vide Annexure II to VI
- 9. Bidders must keep their offer valid for minimum 60 days from Date of Bid Closing failing which their offer will be straightway rejected.

ANNEXURE I TECHNICAL SPECIFICÁTIONS

Optical Fibre (OF) Cable :

- 1.1 General: (Bidders to provide Clause by Clause compliance statement).
- 1.1.1 The non metallic duct OF Cable to be supplied shall be 24 fibre count step index Single Mode fibre, out of which 6 fibre counts shall be Non-Zero Dispersion Shifted (NZ-DSF) type as per ITU G.655 specification and remaining 18 fibre counts shall be Non Dispersion Shifted Fibre (NDSF) as per ITU G.652D specification.
- 1.1.2 The metal free duct OF Cable shall be suitable for underground installation in permanently lubricated HDPE duct buried at an approximate depth of 1.65 meters from the ground level and be required to cross various roads, railways, canals, small rivers, marshy areas etc. through appropriate casings. The optical fibre cable shall be low weight, small volume and high flexibility for laying in a permanently lubricated HDPE duct using blowing techniques. The cable shall have build-in protection against termites and rodents.
- 1.1.3 The life of the cables should be more than 25 yrs.
- 1.1.4 The metal free-duct OF cable to be supplied is 2 Km in length per single drum without any joint/splice,

1.2 Cable Construction Details:

- 1.2.1 The inner strength member shall be Fiber Reinforced Plastic (FRP) rod, non metallic member with minimum diameter of 2mm. The strength member shall provide strength and adequate flexibility of the cable and shall have anti buckling property. This shall also keep the fibre strain within the permissible value.
- 1.2.2 Around the strength member, 4 Nos of loose tubes made of Polyamide/PBTP or other thermoplastic material are to be symmetrically placed using helical or reverse lay technique with 6 nos of primary coated fibres in each tube. Two polyethylene dummy fillers tubes are to be added so that the cable gets packed into near round configuration. The tubes are to be filled up moisture resistant thixotropic jelly, which should be compatible with the coated fibres in the tube. The colour of the loose tubes containing fibres shall be of 4 different distinct colours. The 6 fibre counts of G. 655 type shall be housed in a single tube, rest of 18 fibres to be distributed equally in remaining

3(three) tubes. The loose tube containing G.655 type fibre shall be **Red Colour** and other three tubes containing G.652 type fibres shall be **Yellow**, **Green** and **Brown Colour**. The tube assembly and the core shall be flooded with the moisture resistant jelly.

- 1.2.3 Aramid yarn strength members distributed equally over the periphery of loose tube should be provided along with the solid FRP strength member for peripheral strength.
- 1..2.4 The main cable core containing fibres shall be wrapped with a water blocking polyester of foil / tape of minimum 0.15 thickness. The nylon/polyester binder thread shall be used to hold the tape.
- 1...2. 5 The cable core containing fibres and core assembly shall be protected by flooding water resistant jelly having non-hygroscopic dielectric compound.
- 1.2.6 The loose tube wrapped with water resistant tapes are to be enclosed by a weather resistant inner black coloured HDPE sheath of minimum 1.8 mm thickness. The material of the HDPE shall be UV stabilized.
- 1.2.7 An outer covering jacket of termite and rodent resistant material free from pin holes, scratches and other defects and with sufficient thickness and diameter (nominal) of 12.0 ± 0.5 mm shall be provided for the non metallic cable.
- 1.2.8 Suitable rip cord (s) shall be provided which shall be used to open the HDPE sheath of the cables. The rip cord (s) shall be properly waxed to avoid wicking action and shall not work as water carrier.
- 1.2.9 The fibre in a single cable drum length shall NOT have any joints.
- **1.2.10** The filling compound used in loose tube and in the cable core shall be compatible to fibre, secondary protection of fibre, core wrapping etc. The fibre movement shall not be constrained by stickiness and shall be easily removable for splicing.
- 1.2.11 The bidder shall submit a core sectional diagram of the cables with dimensional and material details of each layer including the fibre refractive index, index profile and percentage of excess fibre length in the cable jacket length along with the **Technical Bid.**

1.3 Material

- **1.3.1** The material used in the manufacturing the optical fibre cable shall be non-toxic and dermatologically safe in its lifetime.
- 1.3.2 The cable shall use the raw materials as per the Telecommunication Engineering Centre (TEC) specification GR No.: TEC/GR/TX/ORM-01/04/SEP 2009 and its subsequent amendments (if any).
- **1.3.3** The material used in optical fibre cable must not evolve hydrogen, which will affect the fibre loss.
- 1.3.4 The raw material used for manufacturing the cable shall be clearly indicated by the bidder.

1.4 Mechanical & Environmental Characteristics:

As per relevant TEC Specs

1.5 Geometrical Characteristic of Optical Fibre :

As per relevant TEC Specs

1.6 Mechanical Characteristics of OF:

As per relevant TEC Specs

1.7 Transmission Characteristic of Fibre:

As per relevant TEC Specs

- **1.8** OIL at its own discretion will delete or include certain Telecommunication Engineering Centre (TEC) recommended test(s) if the cable is manufactured under strict quality assurance programme and raw materials are procured from reputed sources. All the tests will be conducted as per relevant IEC and TEC guidelines.
- 1.9 It shall be explicitly understood that under no circumstances shall any approval of OIL or its representative relieve the supplier of its responsibility of reliable performance of the supplied material

1.10 Fibre Identification Colour:

The coatings shall be in various distinct colours in order to facilitate fibre identification. Fibres colours shall correspond to IEC publication 793-2 and 304. The colours shall correspond reasonably with standard colours and shall readily be identifiable and shall be durable. The colours used should have fast colours properties and should not fade during the lifetime of cable. The coating and colour shall not react with surrounding jelly. The supplier shall take prior approval from OIL for the colour scheme for fibre identification before commencement of manufacture of OFC.

Colour Scheme of the 6 fibers per loose tube:

Blue

Orange

Green

Brown

Slate/grey

Yellow

2. Packaging:

2.1 The cable shall be rolled in wooden drums with rugged construction to withstand multiple transhipment and handling as well as storage in open area under adverse weather conditions. The drum (confirming to GR No. G/CBD-01/02 Nov. 94 and subsequent amendments) should be marked to identify the direction of rotation of the drum. Both ends of the cable should be kept inside the drums.

- 2.2 Packaging of cable shall be done in a manner in such a way that it will allow 2 meter length of cable at each end to be pulled out for performing various tests. The end shall be protected by heat shrinkable sleeves.
- 2.3 The cable drums shall have adequate protection from rain, dust, insect and rodents.
- 2.4 The cable drum shall be marked with an arrow to indicate the coiling sense.
- 2.6 The cable drum and crate shall be marked with the following:

Consignees Name : Oil India Ltd.

Site Name :

Material :

Quantity :

Overall weight :

Batch Name :

Date of Manufacturing :

Manufactured and Supplied by :

2.7 A packing list containing details of cable and test certificate shall accompany each cable drum, secured by abrasion and waterproof jacket fixed to the drum in a strategic location.

Documents:

The bidder shall submit 2 copies of technical documents in English original bound volume containing comprehensive information on the following pertaining to the supplied material:

- i) Fibre cable construction detail
- ii) Fibre preparation for splicing
- iii) Test and measurement procedure and equipment at bidder's site
- iv) Fibre splicing types and procedures
- v) Safety in handling of fibre cable
- vi) Various types of connector and practical method of connectors
- vii) Jointing and termination box detail
- 4. Clause by Clause compliance statement shall be provided for all clauses from 1 to 3 (including all sub clauses).
- 5. Successful bidder must provide test certificate of the product during supply of the material.

Tender No. : GOD6538L15/2K

Tender Date : 12.03.2015

Bid Closing On : 09.04.2015 at 13:00 hrs.(IST)

Bid Opening On : 09.04.2015 at 13:00 hrs.(IST)

Tender issued to following parties only:

Slno	V_Code	Vendor Name	City/Country
1	200151	COMMERCIAL FRIENDS	DIBRUGARH
2	203548	KEC INTERNATIONAL LIMITED	KOLKATA
3	207126	TERACOM LIMITED	NOIDA
4	207252	BRIGHT LAND COMPUTER	DULIAJAN
5	207367	SATYAM COMPUTER SYSTEM	DULIAJAN
6	208796	FINOLEX CABLES LIMITED	GUWAHATI
7	209386	STERLITE TECHNOLOGIES	NOIDA
8	209387	BIRLA ERICSSON OPTICAL LIMITED	KOLKATA
9	209388	AKSH OPTIFIBRE LIMITED	NEW DELHI
10	211298	TECHNICHE CONSULTING SERVICES	KOLKATA
11	211772	VINDHYA TELELINKS LIMITED	NEW DELHI
12	211773	PARAMOUNT COMMUNICATIONS LTD	ALWAR
13	211774	HIMACHAL FUTURISTIC COMMUNICATIONS	GOA
14	211775	APAR INDUSTRIES LTD	UMBERGAON,
15	211776	UM CABLES LTD.	SILVASSA
16	211777	SUDARSHAN TELECOM	MYSORE
17	211778	TAMIL NADU TELECOMMUNICATIONS LTD.,	MARAIMALAI NAGAR