## Addendum-3

In addition to Addendum-1 and Addendum-2, please find following additional data of e-tender SKI6639P18/08 provided as clarification against queries asked:

Query	Clarification. Additional data of SKI6639P18/08
Regarding Dimensions	Height of floor from ground level- 5M
	Height between floor and ceiling- 3 M
	Height of control room floor from cylinder
	location- 5M
Regarding Technical Specifications	Technical specification provided in Annexure AAA
	of document SKI6639P18 already uploaded.
	All agricum and shall be amores and by
	All equipment shall be approved by UL/FM/Vds/LPC and cylinders along with cylinder
	valve assemblies shall be seamless and
	PESO/CCoE approved.
	1 L30/ CCOL approved.
	The Clean Agent system to be provided shall
	meet the requirements of NFPA-2001 (2012
	edition).
	,
	Fire Detection system is included in bidder's
	scope.
Height of False floor, Room height and above	Height of floor from ground level- 5 M
ceiling.	Room height- 3 M
Fire Detection system included in bidder's scope	Yes
or not?	103
Which approvals acceptable for clean agent	All equipment shall be approved by
system like UL/FM, Vds/LPCB etc.?	UL/FM/Vds/LPC and cylinders along with cylinder valve assemblies shall be seamless and
	PESO/CCoE approved.
Any Explosion proof equipment included in	No; provided it is not a part of your system.
bidder's scope or not?	
Other than been seen and other sees :-	The Class Agent existence to be provided at the H
Other than Inert gas any other gases is	The Clean Agent system to be provided shall
acceptable or not, like FM200, NOVEC 1230 etc.	meet the requirements of NFPA-2001 (2012
	edition).

All other terms and conditions of the tender remain unchanged.