#### OIL INDIA LIMITED

(A GOVT. OF INDIA ENTERPRISE) P.O.DULIAJAN-786602, ASSAM E-TENDER NOTICE

OIL INDIA LIMITED (OIL) invites Bids under Composite bid System from established Civil Engineering firms / contractors through its E-Procurement portal "<a href="https://etender.srm.oilindia.in/irj/portal">https://etender.srm.oilindia.in/irj/portal</a>" for the following works.

IFB No.	SHORT DESCRIPTION OF SERVICE	BID SECURITY	COST OF BID DOCUMENT
CDC9676P19	Construction of maintenance godown at Well-50 including supply of all materials except cement.	₹ 32,000.00 /-	NIL

Bid Closing / Opening Date & Time for the above work: 13-12-2018 at 11.00/14.00 Hrs.

Bidder shall require User ID and Password for online submission of Bid.

Bidders without having E-tender Login ID and Password should complete their online registration at least seven (7) days prior to the scheduled bid closing date and time of the tender. For online registration, Bidder may visit the OIL's E-tender site <a href="https://etender.srm.oilindia.in/irj/portal">https://etender.srm.oilindia.in/irj/portal</a>.

Necessary Login ID & Password will be issued by OIL only after submitting the complete online registration by the Bidder. In the event of late registration/incomplete registration by Bidder, OIL INDIA LIMITED shall not be responsible for late allotment of User ID & Password and request for bid closing date extension on that plea shall not be entertained by Company.

**No physical Bid documents will be issued.** The details of IFB can be viewed using "Guest Login" provided in the E-Procurement portal and also in OIL's web site <a href="www.oil-india.com">www.oil-india.com</a>. The link to OIL's E-Procurement portal has also been provided through OIL's web site <a href="www.oil-india.com">www.oil-india.com</a>.

All corrigenda, addenda, amendments, time extension, clarifications etc. to the tender will be hosted on the OIL's website and in the e-tender portal only and no separate notification shall be issued in the press. Prospective bidders are requested to regularly visit the website and e-portal to keep them updated.

GM Contracts (Civil) For CGM-Contracts For, RESIDENT CHIEF EXECUTIVE

Date: 09.11.2018

## **COVERING LETTER**

OIL INDIA LIMITED (A Govt. of India Enterprise) Contracts Department, Duliajan

OIL INDIA LIMITED, a premier Public Sector Enterprise of Govt. of India engaged in drilling and exploration activities for hydrocarbon invites ON-LINE BIDS from experienced and established firms / contractors meeting the requisite criteria for the following mentioned work under **SINGLE STAGE Composite Bid System** through its e-Procurement site:

<u>DESCRIPTION OF WORK/ SERVICE</u>: Construction of maintenance godown at Well-50 including supply of all materials except cement.

**TENDER VALUE: ₹ 63,48,966.67** 

LOCATION OF WORK: Well No-50 near CGGS, Duliajan

CONTRACT PERIOD: 96 Weeks.

BID CLOSING/ OPENING DATE & TIME: 13.12.2018 (11:00 HRS/14:00 HRS)

BID SECURITY DEPOSIT: ₹ 32,000.00 /- (Rupees Thirty Two Thousand only).

a)	Bid	Security	deposited	vide	Bank	Guarantee/LC	No	dated	
of									

(Original hard copy of (a) should reach the office of CGM-CONTRACTS before Bid opening date and time, otherwise Bid will be rejected. A scanned copy of this document should also be uploaded along with the Unpriced bid documents.)

- b) Bidders to confirm that in the event of the award of Contract he/she/they will submit Performance Security Deposit @ 2.5% of the total contract price within two weeks of issue of LOI/LOA and this will not earn any interest. Immediately after deposit of Performance security, successful bidder shall have to sign the formal contract Agreement.
- 2.0 SEALED ENVELOPES containing the Bid Security Deposit (EMD) shall be marked with the above Tender Number and description of work and addressed to

CGM-CONTRACTS
CONTRACTS DEPARTMENT
OIL INDIA LIMITED
Duliajan – 786602
Assam.

2.1 The bidders shall pay the requisite Bid security against the individual IFBs through the online payment gateway. Alternatively, the bidders may deposit the requisite BID SECURITY in the form of Letter of Credit/Bank Guarantee {BG should be submitted in the prescribed format enclosed with this tender (Annexure-III)} from a Nationalized / Scheduled Bank in favour of M/s Oil India Limited and payable at DULIAJAN. DD/Cheques/ Cashier Cheque etc. will not be accepted. This Bid Security shall be refunded to all unsuccessful bidders, but is liable to be forfeited in full or part, at Company's discretion, as per Clause No. 6 below. Bids without Bid Security in the manner specified above will be summarily rejected. Bid should be submitted on-line through OIL's e-Tendering Portal up to 11:00 hrs (IST) (Server Time) on the date as mentioned and will be opened on the same day at 14:00 hrs (IST) at Office of the CGM-Contracts in presence of authorized representative of the bidder. If the bid security is submitted in the form of BG/LC, the same should be dropped in the tender box placed at the office of the CGM-Contracts on or before 1:30 p.m. of the schedule date of opening of tender.

<u>Note:</u> The bidders are requested to advise the Bank Guarantee issuing bank to comply with the following and ensure to submit, the receipt of the copy of SFMS message as sent by the issuing bank branch, along with the original Bank Guarantee in OIL's tender issuing office:

## **COVERING LETTER**

The Bank Guarantee issued by the Bank shall be routed through SFMS platform as per following details:

- i. "MT 760 / MT 760 COV for issuance of Bank Guarantee.
- ii. "MT 760 / MT 767 COV for amendment of Bank Guarantee.

The above message/intimation shall be sent through SFMS (indicating the Contract Number) by the BG issuing bank branch to Axis Bank, Duliajan Branch, IFS Code: UTIB0001129, Branch address: AXIS Bank Ltd., Duliajan Branch, Daily Bazar, Jyotinagar, Duliajan, District Dibrugarh, PIN: 786602.

Bank Guarantee issued by a Scheduled Bank in India at the request of some other Non-Scheduled Bank of India shall not be acceptable.

#### Exemption from submission of bid security:

- a. Central Govt. Department & Public Sector Undertaking Companies are exempted from submission of bid security.
- b. OIL registered 'A' and 'B' class bidders are exempted from depositing the bid security against this tender considering they have submitted revised "One Time Security Deposit" in line with OIL's notification no.: CONT/CIV/1296/2016 dated 25.08.2016, on or before 13:30 Hrs. of Bid Closing/Opening date of this tender.
- 2.2 THE PHYSICAL BID SECURITY IS TO BE SUBMITTED ALONGWITH A COVERING LETTER MENTIONING THE e-TENDER NO AND THE BIDDER'S NAME AND ADDRESS IN A DULY SEALED ENVELOPE ADDRESSED TO CGM-CONTRACTS, OIL INDIA LIMITED, CONTRACTS DEPARTMENT, DULIAJAN 786602
- 2.3 If the bidders deposit the requisite Bid security in the form of Bank Guarantee, then the Bank Guarantee should be valid for 30 days beyond the required bid validity period.
- 3.0 However, if the above mentioned closing / opening day of the tender happens to be non-working day due to Bandh / Strike or any other reason, the bids will be received and opened on the following working day at the same time except on Saturdays.
- 4.0 The rate shall be quoted in percentage (At par to +10%) of the internal estimate as specified in the "Price Bidding Format" attached just below the "Tendering text". Bidder should note that no pricing information is furnished in the "c-Folder" (Technical Bid) otherwise the bid will be rejected.
- 4.1 All other techno-commercial documents other than price details to be submitted with un-priced bid as per tender requirement placed in the 'un-priced' bid folder.
- 4.2 To participate in OIL's E-procurement tender, bidders must have a legally Valid Digital Signature of Class 3 [Organizational Type] with Organizations Name along with Encryption Certificate as per Indian IT Act from the licensed Certifying Authorities operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India (http://www.cca.gov.in). Digital Signature Certificates having "Organization Name" field other than Bidder's Name (i.e. Firm's Name) are not acceptable.
- 4.3 The authenticity of above Digital Signature shall be verified through authorized CA after bid opening. If the **Digital Signature Certificate (DSC)** used for signing is not of "Class -3" & Organizational type with Organization's name, the bid will be rejected.
- 4.4 Bidder is responsible for ensuring the validity of Digital Signature Certificate (DSC) and its proper usage by their employee.
- 4.5 The bid including all uploaded documents shall be **digitally signed** by duly authorized representative of the bidding company.

## **COVERING LETTER**

- 4.6 Bidders without having E-tender Login ID and Password should complete their online registration at least seven (7) days prior to the scheduled bid closing date and time of the tender. For online registration, Bidder may visit the OIL's E-tender site https://etender.srm.oilindia.in/irj/portal.
- 4.7 Necessary Login ID & Password will be issued by OIL only after submitting the complete online registration by the Bidder. In the event of late registration/incomplete registration by Bidder, OIL INDIA LIMITED shall not be responsible for late allotment of User ID & Password and request for bid closing date extension on that plea shall not be entertained by Company.
- **5.0** The Company reserves the right to reject any or all the tenders or accept any tender without assigning any reason.
- **6.0** (a) No Bidder can withdraw his bid within the validity or extended validity of the bid. Withdrawal of any bid within bid validity period will lead to forfeiture of his/her/their Bid Security in full and debarment from participation in future tenders, at the sole discretion of the Company and the period of debarment will be decided as per OIL's banning policy dated 6th Jan 2017 available at OIL's website.
- (b) Once a withdrawal letter is received from any bidder, the offer will be treated as withdrawn and no further claim / correspondence will be entertained in this regard.

#### 7.0

- a) The Bid must be valid for 90 (Ninety) days from the date of opening of the tender.
- b) In case of extension of Bid Opening Date, Bid validity must be extended suitably by the bidder, as and when advised by OIL.
- c) The amount of Bid Security shall be as specified in the NIT.
- d) In case the Bidder submits Bid security in the form of Bank Guarantee (BG), the BG must be valid for minimum 120 days (One Hundred Twenty) from the date of bid opening.
- e) In case of extension of Bid Opening Date, Bid Security validity must be extended suitably by the bidder, as and when advised by OIL.
- f) The bidders must upload the Integrity Pact, digitally signed by the authorized signatory (who is authorized to sign the bid) along with the Technical Bid.
- **8.0** Conditional bids are liable to be rejected at the discretion of the Company.
- **9.0** The work may be split up amongst more than one contractor at the sole discretion of the Company.
- **10.0** Before submission of bids, the bidder is advised to inspect the work site with permission from GM Civil or his representative, to assess the nature and extent of work and the conditions under which it will be carried out. He may also seek such clarification from this office as are deemed necessary.
- 11.0 The bidder should offer their overall rate only as a percentage of Company's internally estimated cost within the limit of "At Par" to "+10%" on the Company's internal estimated contract cost. The bids with overall rates quoted below "at par" and above (+10%) of Company's internal estimate will be rejected outright.
- **12.0** The bidders are required to furnish the composition and status of ownership of the firm in whose name bid documents have been purchased/issued along with one or more of the following documentary evidences (which are applicable to the bidder) in support of the same and scanned copies of the same should be uploaded along with the Un priced bid documents.
- **12.1** In case of Sole Proprietorship Firm, Copies of Telephone/Electricity/Mobile Bill, PAN card, latest Income Tax Return form indicating therein the name, business and residential address, E-mail and phone numbers of the owner and copies of GST Registration Certificate.

## **COVERING LETTER**

- **12.2** In case of HUF, Copies of Telephone/Electricity/Mobile Bill, PAN card, latest Income Tax Return form, Family Arrangement indicating therein the name, residential address, E-mail and phone numbers of the owners in general and Karta in particular and copies of GST Registration Certificate.
- **12.3** In case of Partnership Firm, Copies of Telephone/Electricity/Mobile Bill, PAN card, latest Income Tax Return form indicating therein the name, residential address, E-mails and phone numbers of all the partners (including the Managing Partner), registered partnership agreement/deed and copies of GST Registration Certificate.
- **12.4** In case of Co-Operative Societies, Copies of Telephone/Electricity/Mobile Bill, PAN card, latest Income Tax Return form indicating therein the name, residential address, E-mails and phone numbers of all the Directors or persons who are at the helm of affairs, registration certificate from Registrar of Co-Operative Societies and copies of GST Registration Certificate.
- **12.5** In case of Societies registered under the Societies Registration Act, Copies of Telephone/Electricity/Mobile Bill, PAN card, latest Income Tax Return form indicating therein the name, residential address, E-mail and telephone numbers of all the Directors or persons who are at the helm of affairs, registration certificate from the Registrar of the state and copies of GST Registration Certificate.
- **12.6** In case of Joint Stock Companies registered under the Indian Companies Act, Copies of Telephone/Electricity/Mobile Bill, PAN card, latest Income Tax Return form indicating therein the name, residential address, E-mail and telephone numbers of all the Directors or persons who are at the helm of affairs, Certificate of Incorporation from the Registrar of Companies, Memorandum and Articles and copies of GST Registration Certificate.
- **12.7** In case of Trusts registered under the Indian Trust Act, Copies of Telephone/Electricity/Mobile Bill, PAN card, latest Income Tax Return form indicating therein the name, residential address, E-mail and telephone numbers of all the Trustee or persons who are at the helm of affairs, registration certificate from the Registrar of the state, Trust Deed and copies GST Registration Certificate.

# NOTE: Point no. 12.1 to 12.7 is not applicable for contractors who are already registered with OIL INDIA LIMITED.

13.0 Wherever applicable, the bidder shall have itself registered under Employees' Provident Fund and Miscellaneous Provisions Act, 1952 and follow the relevant statutory provisions including Rules made thereunder concerning contractual workers to be engaged by such bidder. If the bidder does not have P.F. Code number at the time of applying for this tender, then the bidder must apply for the same if the contract is awarded to the bidder. Such bidder shall furnish the Provident Fund code number issued by the appropriate Govt. Authority, within 45 days of signing of contract, to Company (or when advised by Company, after 45 days of signing the contract); and all PF related statutory guidelines shall be adhered to by the bidder.

#### **14.0** Before Bidding:

- Bidder(s) are advised to inspect the work site with permission from GM-Civil or his representative, to assess the nature and extent of work and the conditions under which it will be carried out.
- Bidder(s) should clearly understand all the terms & conditions, criteria, specification etc. of this tender.
- **15.0** The selected bidder will be required to enter into a formal contract, which will be based on their bid, i.e. OIL's Standard Form of Contract.

#### 16.0 PERFORMANCE SECURITY DEPOSIT:

The successful bidder shall furnish a Performance Security Deposit in the form of Letter of Credit/Bank Guarantee (PBG in prescribed format of **Annexure-IV**) as specified above before signing the formal contract. The Security Deposit will be refunded to the Contractor after satisfactory completion of the work, but a part or whole of which shall be used by the Company in realization of liquidated damages or claims, if any or for

## **COVERING LETTER**

adjustment of compensation or loss due to the Company for any reason. This Security Money shall not earn any interest.

<u>Note:</u> The bidders are requested to advise the Performance Bank Guarantee issuing bank to comply with the following and ensure to submit, the receipt of the copy of SFMS message as sent by the issuing bank branch, along with the original Performance Bank Guarantee in OIL's tender issuing office:

The Performance Bank Guarantee issued by the Bank shall be routed through SFMS platform as per following details:

- i. "MT 760 / MT 760 COV for issuance of Performance Bank Guarantee.
- ii. "MT 760 / MT 767 COV for amendment of Performance Bank Guarantee.

The above message/intimation shall be sent through SFMS (indicating the Contract Number) by the BG issuing bank branch to Axis Bank, Duliajan Branch, IFS Code: UTIB0001129, Branch address: AXIS Bank Ltd., Duliajan Branch, Daily Bazar, Jyotinagar, Duliajan, District Dibrugarh, PIN: 786602.

Bank Guarantee issued by a Scheduled Bank in India at the request of some other Non-Scheduled Bank of India shall not be acceptable.

- **17.0** OIL INDIA LIMITED reserves the right to curtail / enhance the scope of the work stated above or cancel, if required.
- **18.0** The amount of retention money shall be released after 6 (six) months from the date of completion certified by the concerned department.
- **19.0** The work shall have to be started within seven days from the date of work order.
- **20.0** Time Schedule: The time allowed for completing the work will be reckoned from the date of issue of work order. Time is the essence of the Contract and failure on part of the contractor to complete the work within the stipulated time, shall entitle the Company to impose liquidated damages and / or penalty from the contractor as per terms of the Contract.
- **21.0** The contractor will be required to allow OIL officials to inspect the work site and documents in respect of the workers payment.
- **22.0 BACKING OUT BY BIDDER**: In case any bidder withdraws their bid within the bid validity period, the Bid Security will be forfeited and be debarred from further tendering as per OIL's banning policy dated 6<sup>th</sup> Jan 2017 available at OIL's website.
- **23.0 BACKING OUT BY L-1 BIDDER AFTER ISSUE OF LOA**: In case LOA issued is not accepted by the L1 bidder or the Performance Security is not submitted as per the terms of the contract within the time specified in the Bid Document, the Bid Security shall be forfeited and the bidder shall be dealt as per OIL's banning policy dated 6<sup>th</sup> Jan 2017 available at OIL's website.
- **24.0 FURNISHING FRAUDULENT INFORMATION/DOCUMENT**: If it is found that a Bidder/Contractor has furnished fraudulent document/information, the Bid Security/ Performance Security shall be forfeited and the party shall be debarred as per the OIL's Banning Policy dated 6<sup>th</sup> Jan 2017 available at OIL's website. Annexure VI must be duly filled in bidder's letter head and upload the scanned copy of the same along with techno-commercial bid.

# 25.0 <u>Bidder(s) must also furnish the followings:</u>

- a) NAME OF FIRM
- b) DETAIL POSTAL ADDRESS
- c) MOBILE / TELEPHONE NO
- d) E-MAIL ADDRESS
- e) FAX NO (If available)
- f) CONTACT PERSON
- g) VENDOR CODE

## **COVERING LETTER**

h) GST Registration Number (If available):

#### 26.0 The tender will be governed by:

- a) Covering Letter.
- b) Part I General Terms and Conditions for Works Contract. (GCC)
- c) Part II Schedule of Work, Unit and Quantity (SOQ)
- d) Part III Particular Specification, Special Terms, Conditions & Instructions of Contract (SCC)
- e) Part IV SCPME
- f) Part- V- Safety Measures
- g) Part- VI Integrity Pact
- h) Bid Rejection Criteria & Bid Evaluation Criteria (BRC/BEC).
- i) Annexure-III (Format for **Bid Security** in the form of Bank Guarantee.)
- j) Annexure-IV (Format for Performance Bank Guarantee in the form of Bank Guarantee.)

#### Special Note:

Please note that all tender forms and supporting documents are to be submitted on-line through OIL's E-Procurement site only except following documents which are to be submitted manually in sealed envelope super scribed with tender no. and due date at following address:

CGM Contracts, Contracts Department, Oil India Limited, Duliajan- 786602, Assam

a. ORIGINAL BID SECURITY (Only in case of Bidder(s) submitting Bid Security in the form of LC/Bank Guarantee.

A scanned copy of Bid Security should also be uploaded along with the Unpriced Techno-Commercial Bid documents.

**b.** Any other document required to be submitted in original as per tender requirement.

Scanned copy(s) of the same should also be uploaded along with the Un-priced Techno-Commercial Bid documents.

The above documents including the Original Bid Security (in case of bidders submitting Bid Security in the form of Bank Guarantee/LC) must be received at OIL's CGM (Contracts) office at Duliajan on or before the scheduled date & time specified in the NIT, failing which the bid shall be rejected.

Bidders are requested to examine all instructions, forms, terms and specifications in the bid. Failure to furnish all information required as per the bid or submission of offers not substantially responsive to the bid in every respect will be at the bidders risk and may result in the rejection of its offer without seeking any clarifications. Offers sent without the requisite value of prescribed Bid Security (if called for in the bid) in original will be ignored straightway.

27.0 The tender is invited under SINGLE STAGE - COMPOSITE BID SYSTEM. The bidders shall submit both the "TECHNICAL" and "PRICED" bids through electronic form in the OIL's E-Procurement portal within the Bid Closing Date and Time stipulated in the E-Tender. The Technical Bid should be submitted as per Scope of Work & Technical Specifications along with all technical documents related to the tender and uploaded under "Technical Attachment" Tab only. Bidders must note that no price details should be uploaded in "Technical Attachment" Tab Page. Details of prices as per Price Bid format/Priced bid to be uploaded under "Notes and Attachment" Tab. A screen shot in this regard is shown below. Offer not complying with above submission procedure will be rejected as per Bid Rejection Criteria. In Bid opening, both Technical & Priced Bids will be opened.

Please go through the "General Guidelines to bidders"> NEW VENDOR MANUAL (Effective 12.04.17)" provided in OIL's e-Portal, in detail before uploading the document.

## **COVERING LETTER**

<u>NB</u>: In order to bid for OIL e-tenders all the vendors are required to obtain a legally valid Digital Certificate Class III [Organization] along with Encryption Certificate as per Indian IT Act from the licensed Certifying Authorities (CA) operating under the Root Certifying Authority of India (RCAI), Controller of Certifying Authorities (CCA) of India. Digital Signature Certificate comes in a pair of Signing/verification and Encryption/decryption certificate. Bidder should have both the Signing/verification and Encryption/Decryption certificate for Signing and encryption, decryption purpose respectively. The driver needs to be installed once, without which the DSC will not be recognized. While participating on e-Tendering the DSC token should be connected to your system.

Encryption certificate is mandatorily required for submission of bid. In case bidder created response with one certificate (using encryption key) and bidder change his Digital Signature Certificate then old certificate (used for encryption) is required in order to decrypt his encrypted response for getting the edit mode of the response. Once decryption is done, bidder may use new DSC certificate for uploading and submission of their offer. It is the sole responsibility of the bidder to keep their DSC certificate properly. In case of loss of the certificate, OIL INDIA LTD is not responsible.

28.0 The Integrity Pact is applicable against this tender: OIL shall be entering into an Integrity Pact with the bidders as per format enclosed vide "Part-VI Integrity Pact" of the tender document. This Integrity Pact proforma has been duly signed digitally by OIL's competent signatory. The proforma has to be returned by the bidder (along with the technical bid) duly signed (digitally) by the same signatory who sign the bid, i.e., who is duly authorized to sign the bid. Any bid not accompanied by Integrity Pact Proforma duly signed (digitally) by the bidder shall be rejected straightway. Uploading the Integrity Pact with digital signature will be construed that all pages of the Integrity Pact has been signed by the bidder's authorized signatory who sign the Bid.

<u>Note</u>: Shri Rajiv Mathur, IPS (Retd.), Former Director, IB, Govt. of India, E-Mail ID: <u>rajivmathur23@gmail.com</u>, Shri Satyananda Mishra, IAS(Retd.) Former Chief Information Commissioner & Ex-Secretary, DOPT, Govt. of India, e-Mail id: <u>satyanandamishra@hotmail.com</u> and Shri Jagmohan Garg, Ex-Vigilance Commissioner, CVC e-Mail id: <u>jagmohan.garg@gmail..com</u> have been appointed as Independent External Monitors.

#### 29.0 SCREEN SHOT:

On "EDIT" Mode, bidders are advised to upload "Technical Bid" and "Priced Bid" in the respective places as indicated below:


#### Note:

\* The "Technical Bid" shall contain all techno-commercial details except the prices.


\*\* The "Priced bid" must contain the price schedule and the bidder's commercial terms and conditions, if any. For uploading Priced Bid, first click on Add Attachment, a browser window will open, select the file from the PC and name the file under Description, Assigned to General Data and click on OK to digitally sign and upload the File. Please click on Save Button of the Response to Save the uploaded files.

## **COVERING LETTER**


**A.** Uploading of **Technical Bid**: Technical files to be added under RFX Information > "Technical Attachments"



B. Uploading of Price Bid:




C. After Uploading of Price bid Click 'Save'



Once Saved ,the Data will be Encrypted & the Encryption Certificate will be in use.


# **COVERING LETTER**

**D.** Click to select the desired Encryption certificate & Encrypt Bid:




# The Encrypted Data will be displayed only when click 'Decrypt data'

E. The Encrypted Data will be displayed only when click 'Decrypt data'




F. Click on 'Close'



## **COVERING LETTER**

G. Click on 'Refresh'. Then Click on 'Response No.'




Now Uploading part is complete. Bidders are requested to go to the Initial screen. It is always better to come to the first screen and refresh the page and then going in into the response for the submission process.

**H.** On 'Edit' mode Click to select the same Encryption certificate used for De-cryption else data will not Decrypt.




I. After Entering User pin, Click 'Check'. Bidder may submit the response in case there is no error.




# **COVERING LETTER**

J. Click on 'Submit' button




Before submit, Please do check all the documents uploaded and on-line data maintained are correct.

K. After Clicking 'Submit' below pop up will open. Select Digital Signature & Sign.



L. After Signing the response has to be encrypted again. Select the encryption certificate and Encrypt Bid.




# **COVERING LETTER**

M. Click 'Close'



N. Click on 'Refresh'. The status of Response must be



This is the end of **Response submission with Encryption key** process.

**30.0** OIL now looks forward for your active participation in the tender.

CGM-CONTRACTS For RESIDENT CHIEF EXECUTIVE

BEC/BRC

#### BID EVALUATION CRITERIA (BEC)/BID REJECTION CRITERIA (BRC)

#### (A). BID EVALUATION CRITERIA (BEC):

- **1.0** The bid shall conform generally to the specifications and terms and conditions given in the Tender Documents. Bids will be rejected in case services offered do not conform to the required parameters stipulated in the technical specifications. Not-withstanding the general conformity of the bid to the stipulated specifications, the following mandatory requirements will have to be particularly met by the Bidders without which the same will be considered as non-responsive and rejected. All the documents related to **BEC** must be submitted along with the Techno-Commercial Bid.
- 2.1 Interested bidders shall have to submit the following documents to qualify for the tender:

#### 2.1.1

- a. One successfully completed similar work of minimum value of ₹ 31,75,000.00 under tender with CPWD, Railways, APWD, MES, NRL, ONGCL, OIL or any other Government Organization / Public Sector Undertaking during the last seven (07) years reckoned from the original bid closing date.
- b. For proof of requisite experience of **SIMILAR work**, Job Completion Certificate clearly mentioning Gross value of job done, Nature of works, Contracts period/ Contract Start and Completion date issued by CPWD, Railways, APWD, MES, NRL, ONGCL, OIL or any other Government Organization / Public Sector Undertaking must be submitted along with the bid.
- c. SIMILAR work executed by a bidder for its own organization / subsidiary will not be considered as experience for the purpose of meeting BEC.

#### 2.1.2

- a) Annual Financial Turnover of the bidder during any of preceding three financial / accounting years from the original bid closing date should be at least ₹ 10,32,000.00.
- b) **Net worth** of bidder must be positive for preceding financial/accounting year.
- c) Considering the time required for preparation of Financial Statements, if the last date of preceding financial/accounting year falls within the preceding six months reckoned from the original bid closing date and the Financial Statements of the preceding financial / accounting year are not available with the bidder, then the financial turnover of the previous three financial/ accounting years excluding the preceding financial / accounting year will be considered. In such cases, the Net worth of the previous financial / accounting year excluding the preceding financial / accounting year will be considered. However, the bidder has to submit an affidavit / undertaking certifying that "the balance sheet / Financial Statements" for the financial year ......(as the case may be) has actually not been audited so far.

<u>Note:</u> For proof of Annual Turnover & Net worth any one of the following document must be submitted along with the bid:-

i) A certificate issued by a practicing Chartered/ Cost Accountant (with Membership Number and Firm Registration Number), certifying the Annual turnover & Net worth as per format prescribed in **Annexure-II**.

OR

ii) Audited Balance Sheet along with Profit & Loss account.

Note: In case the bidder is Central Govt. organization/ PSU/ State Govt. organization/ Semi-State Govt. Organization or any other Central/ State Govt. Undertaking, where the auditor is appointed only after the approval of Comptroller and Auditor General of India and the Central Government, their certificates may be accepted even though FRN is not available. However, bidder has to provide documentary evidence for the same.

**2.1.3** Bids must be valid for minimum **90 (Ninety) days** from the date of Technical Bid opening. If bidder does not submit / declare bid validity period, it will be presumed that the bid validity is **90 (Ninety)** days.

BEC/BRC

<u>Note:</u> In case of extension of Bid Opening Date, Bid validity should be extended suitably by the bidder, as and when advised by OIL.

**2.1.4** Bid Security must be furnished (except those exempted) as a part of the Technical Bid. Bidders already having User ID & Password for OIL's e-portal can pay the requisite Bid security against the individual IFBs through the online payment gateway on or before 1:30 p.m. on the bid closing date. Alternatively, bidder can submit Bid Security amount through Bank Guarantee (in original) in prescribed format enclosed with this tender, which must reach the Office of CGM-Contracts, OIL, Duliajan on or before 1:30 p.m. on the bid closing date.

**Bid Security (EMD):**- Only payments through online payment gateway or Bank Guarantee /LC (to be submitted in original) will be accepted. **DD/Cheques/Cashier Cheque etc.** will not be accepted.

The amount of Bid Security shall be as specified in the NIT.

#### Note:

- (a) In case the Bidder submits Bid security in the form of Bank Guarantee (BG), the BG must be valid for **minimum 120 days** from the original bid opening date.
- (b) In case of extension of Bid Opening Date, Bid Security validity should be extended suitably by the bidder, as and when advised by OIL.
- **2.1.5** OIL shall be entering into an Integrity Pact with the bidders as per format enclosed vide Part-VI of the tender document. This Integrity Pact proforma has been duly signed digitally by OIL's competent signatory. The proforma has to be uploaded by the bidder (along with the Un-priced Techno-Commercial Bid).-Uploading the Integrity Pact with digital signature will be construed that all pages of the Integrity Pact have been signed by the bidder's authorized signatory who sign the Bid.
- **2.1.6** The bidders must submit documentary evidence for BEC clause numbers 2.1.1 and 2.1.2. All the documents should be legible. The bidders must have Encryption Certificate along with Digital Signature Certificate (DSC) of Class 3 [Organization Type] to upload all the documents.

OIL registered 'A' and 'B' class bidders are exempted from submitting documents fulfilling their experience & turnover criteria as well as depositing the bid security amount as specified in the Clauses 2.1.1, 2.1.2 & 2.1.4 of BEC/BRC of this tender document, providing submission of his/her/their revised "One Time Security Deposit" in line with OIL's notification no.: CONT/CIV/1296/2016 dated 25.08.2016, on or before 13:30 Hrs. of Bid Closing/Opening date of this tender. Moreover, no earnest money deposit / bid security will be necessary for procurement from Central Government department and Public Sector Undertaking.

#### 3.0 Notes to Clause no. 2.1.1 above:

(a) "Similar work" mentioned in Paragraph 2.1.1 above means the following:

<u>Definition of similar work:</u> Construction of RCC framed boundary wall/ Construction of RCC / Assam type Building/ Construction of RCC water tank.

- (b) Non-submission of the documents as specified in all the paragraphs above will result in rejection of bids.
- **4.0** The bids conforming to the specifications, terms and conditions stipulated in the tender documents and considered to be responsive will be evaluated as per the procedure mentioned below:
  - i. Bid will be opened on schedule date & time as specified in the NIT and all the bids where the bidders have quoted the lowest price (within the permissible percentage as per NIT) will be selected for conducting Draw of Lots (DoL). DoL will be conducted within a short period after Bid Closing Date. In the DoL, 7 (seven) numbers of bidders will be selected first, in the order of B-1 (Bidder-1), B-2 B-3, B-4, B-5, B-6 and B-7. The technical scrutiny will be carried out for these seven bidders only. If the bid of bidder B-1 is found to be technically qualified, B-1 will be the successful bidder (Priority-1).

BEC/BRC

bidder) and the contract will be awarded to B-1. If B-1 is not found to be technically qualified but B-2 is technically qualified, B-2 will be awarded the contract, ---- and so on; i.e. whoever becomes the first technically qualified bidder in the order of B-1  $\rightarrow$ B-2 $\rightarrow$ B-3 $\rightarrow$ B-4 $\rightarrow$ B-5 $\rightarrow$ B-6 $\rightarrow$ B-7, will be the successful bidder (P-1). In this way, P-1 (Priority-1) and P-2 bidders will be selected. The contract will be awarded to the P-1 bidder only. However, in case the bidder P-1 is not able to carry out the job due to any reason, P-2 may be awarded the job, if the same is approved by Company's competent authority. In case, none of these seven bidders are found to be technically acceptable, the draw of Lot will be again conducted to select 7 more bidders as B-8 to B-14 and similar steps will be followed thereon as explained above. The system of conducting further draw of lots will be followed till a technically acceptable bidder is selected.

ii. Bidder should note that deficit documents will not be sought from the bidders. The bids will be evaluated as per the documents received from the bidders at the time of bid opening. Any bid, which is not supported with the requisite documents as per the NIT, will be rejected straightway without seeking any further clarification and deficit document.

**Note:** The Company's Internal Estimated Rates, as indicated in Part-II, are inclusive of all overheads, taxes, duties, levies etc. except P.F. & GST.

#### (B). BID REJECTION CRITERIA (BRC):

- 1. The bids are to be submitted in single stage under composite bid system i.e. Un-priced Techno-Commercial Bid and Price Bid together. Only the Price Bid should contain the quoted price (percentage only).
- 2. Bid security shall be furnished as a part of the Techno Commercial Un-priced Bid. The amount of bid security should be as specified in the NIT. Any bid not accompanied by a proper bid security will be summarily rejected.
- 3. Bid Documents / User Id & Password for OIL's E-Tender portal are not transferable.
- 4. Any bid received in the form of Physical document/ Telex/Cable/Fax/E-mail will not be accepted.
- 5. Bidders must quote clearly and strictly in accordance with the price schedule outlined in Price Bidding Format attached under "Notes and Attachments" tab in the main bidding engine of OIL's e-Tender portal; otherwise the bid will be rejected. All other techno-commercial documents other than price details to be submitted with Un-priced Techno-Commercial Bid as per tender requirement in the c-Folder link (collaboration link) under "Technical RFx Response" Tab Page only.
- 6. Bidders must accept and comply with the following provisions as given in the tender document. Deviations to such provisions shall make the bid liable for rejection.
  - a. Firm price
  - b. EMD / Bid Bond
  - c. Scope of work
  - d. Specifications
  - e. Price schedule
  - f. Delivery / completion schedule
  - g. Period of validity of bid
  - h. Liquidated Damages
  - i. Performance bank guarantee / Security deposit
  - j. Guarantee of material / work
  - k. Arbitration / Resolution of Dispute
  - I. Force Majeure
  - m. Applicable Laws
  - n. Integrity Pact

## (C). GENERAL:

i. <u>Submission of Forged Documents:</u> Bidders should note that Company may verify authenticity of all the documents /certificates / information submitted by the bidder(s) against the tender. In case at

BEC/BRC

any stage of tendering process or Contract execution etc., if it is established that bidder has submitted forged documents / certificates / information towards fulfilment of any of the tender / contract conditions, Company shall immediately reject the bid of such bidder(s) or cancel / terminate the contract and forfeit EMD / SD submitted by the bidder(s), besides taking action as per OIL's Banning Policy dated  $6^{th}$  January 2017, available in the OIL's website.

- ii. In case bidder takes exception to any clause of bidding document not covered under BEC/BRC, then the Company has the discretion to load or reject the offer on account of such exception if the bidder does not withdraw / modify the deviation when / as advised by company. The loading so done by the Company will be final and binding on the bidders. No deviation will however be accepted in the clauses covered under BRC.
- iii. To ascertain the substantial responsiveness of the bid the Company reserves the right to ask the bidder for clarification in respect of clauses covered under BEC/BRC also and such clarifications fulfilling the BEC/BRC clauses in toto must be received on or before the deadline given by the company, failing which the offer will be evaluated based on the submission. However, mere submission of such clarification shall not make the offer responsive, unless Company is satisfied with the substantial responsiveness of the offer.
- iv. If any of the clauses in the BRC contradicts with other clauses of Bidding document elsewhere, the clauses in the BRC shall prevail.
- v. Bidder(s) must note that requisite information/financial values etc. as required in the BEC/BRC & Tender are clearly understandable from the supporting documents submitted by the Bidder(s); otherwise Bids shall be rejected.
- vi. OIL will not be responsible for delay, loss or non-receipt of applications for participating in the bid sent by mail and will not entertain any correspondence in this regard.

OIL INDIA LIMITED (A Govt. of India Enterprise) Contracts Department, Duliajan, DISTRICT: DIBRUGARH ASSAM, PIN: 786602 **Works Contract** 

**DESCRIPTION OF WORK/SERVICES**: - Construction of maintenance godown at Well-50, including supply of all materials except cement.

GENERAL CONDITIONS OF CONTRACT (GCC)
MEMORANDUM OF AGREEMENT made this day of between OIL INDIA LIMITED a Company incorporated under the Companies Act 1956 and having its Registered Office at Duliajan in the District of Dibrugarh, Assam (hereinafter called Company) of the one part and Shri/Smti and Shri/Smti carrying on business as partners /proprietor under the firm name and style of M/s with the main Office at in the District of aforesaid (hereinafter called 'Contractor') on the other part.
WITNESSETH:
1. a) The contractor hereby agrees to carry out the work set down in the Schedule of work which forms part-II of this Contract in accordance with the 1968 General Conditions of Contract of Oil India Limited and General Specifications read in conjunction with any drawings and Particular Specifications & instructions which forms Part-III of the contract utilizing any materials/services as offered by the Company as per Part-IV of the contract at location  b) In this Contract all words and expressions shall have the same meaning as are respectively assigned
to them in the 1968 General Conditions of Contract of Oil India Limited which the Contractor has perused and is fully conversant with before entering into this Contract.
c) The clauses of this contract and of the specifications set out hereunder shall be paramount and in the event of anything herein contained being inconsistent with any term or terms of the 1968 General Conditions of Contract of Oil India Limited, the said term or terms of the 1968 General conditions of Contract to the extent of such inconsistency, and no further, shall not be binding on the parties hereto.
2. i) The contractor shall provide all labour, supervision and transport and such specified materials described in part-II of the Contract including tools and plants as necessary for the work and shall be responsible for all royalties and other levies and his rates shall include for these. The work executed and materials supplied shall be to the satisfaction of the Company's Engineer and Contractor's rates shall include for all incidental and contingent work which although not specifically mentioned in this contract are necessary for its completion in a sound and workman like manner. ii) Contractor shall have to produce necessary cash memos towards forest produce used against the contract to Head (Civil) used against this contract from the authorities prior to processing of final payment. In absence of cash memos, the final bill shall not be processed.
3. The Company's Engineer shall have power to: a) Reduce the rates at which payments shall be made if the quality of work although acceptable is not up to the required standard set forth in the OIL Standard Specifications which have been perused and fully understood by the Contractor.
b) Order the Contractor to remove any inferior material from the site and to demolish or rectify any work of inferior workmanship, failing which the Company's Engineer may arrange for any such work to be

Contractor 1 Company

c) Order the Contractor to remove or replace any workman/supervisor/engineer/project-in-charge or any other contactor's personnel who he (The Engineer) considers incompetent or unsuitable; the Engineer's opinion as to the competence and suitability of any personnel engaged by the Contractor

demolished or rectified by any other means at the Contractor's expenses.

shall be final and binding on the Contractor.

- d) Issue to the Contractor from time to time during the progress of the work such further drawings and instructions as shall be necessary for the purpose of proper and adequate execution and maintenance of the works and the Contractor shall carry out and be bound by the same.
- e) Order deviations in Part II and III of this Contract. All such deviation orders shall be in writing and shall show the financial effect, if any, of such deviation and whether any extra time is to be allowed. The rates to be applied for such Deviation Order shall be the same for those appearing in Company's Schedule of Rate in force on the date of issue of such Deviation Order, to which the contractor has no objection.
- 4. The Contractor shall have no claim against the Company in respect of any work which may be withdrawn but only for work actually completed under this contract. The contractor shall have no objection to carry out work in excess of the quantities and items stipulated in Part-II (SOQ). In case of positive variation in quantities of any items from the quantity mentioned in the tender / contract, the contractor will have to carry out the positive varied quantity at the contract rate, or the internally estimated rate, whichever is lower.

However, during the actual execution of the contract, if the contract is to be utilised in a different zone due to Company's operational requirement, where the rates of the contractual items in the OIL's Schedule of Rates (SOR) are different from the contractual rates, then the rates of OIL's SOR, prevailing in the working zone (the zone where the contract is actually utilised) at the time of floating the tender, will be applicable for the contractual items (for the contractual quantities as well as for the additional quantities, if required to be executed).

If any additional items (items not covered in the tender / contract) are required to be executed during actual execution of works, the payment of such items shall be made as per the rates of OIL Schedule of Rates (SOR) prevailing in the working zone (the zone where the contract is utilized) at the time of issuance of advice by Company to execute such additional items.

- 5. The Company reserves the right to cancel this Contract at any time upon full payment of work done and the value of the materials collected by the contractor for permanent incorporation in the work under this contract particularly for execution of this contract up to the date of cancellation of the Contract. The valuation of the work done and the materials collected shall be estimated by the company's Engineer in presence of the contractor. The Contractor shall have no claim to any further payment whatsoever. The valuation would be carried out exparte if Contractor fails to turn up despite reasonable notice which will be binding on the Contractor.
- **6.** The Contractor hereby undertakes to indemnify the Company against all claims which may arise under the under noted Acts:-
  - I. The Mines Act.
  - II. The Minimum Wages Act, 1948.
  - III. The Workman's Compensation Act, 1923.
  - IV. The Payment of wages Act, 1963.
  - V. The Payment of Bonus Act, 1965.
  - VI. The Contract Labour (Regulation & Abolition) Act, 1970 and the rules framed there
  - VII. Employees' Pension Scheme, 1995.
  - VIII. Inter-State Migrant (Regulation of Employment and Condition of Service) Act. 1979.
    - IX. The Employees Provident Fund and Miscellaneous Provisions Act, 1952.
    - X. Goods and Service Tax (GST) Law,

or any other Acts or Statute not here in above specifically mentioned having bearing over engagement of workers directly or indirectly for execution of work. The Contractor shall not make the Company liable to reimburse the Contractor for the statutory increase in the wage rates of the Contract Labour appointed by the Contractor. Such Statutory increase in the wage rates of Contract Labour shall be borne by the contractor.

- 7. The Contractor shall clear away all rubbish and surplus material from the site on completion of work and shall leave the site clean and tidy.
- 8. The Contractor must complete the work within 96 weeks of the written order to commence work. During the currency of the job, the work progress must be commensurate with the time elapsed. In the event of any delay on the contractor's part, he/she will be liable to pay to the company liquidated damages at the rate of 1/2% (Half percent) per week of the contract price of the item(s) delayed in completion and the maximum value of the liquidated damage will be 7.5% of the

Contractor 2 Company

contract price of the item(s) delayed provided the item(s) delayed are not critical for commissioning and final utilization of the work. If, however, the item(s) delayed in completion are critical for commissioning and final utilisation of the work then the contractor will be liable to pay liquidated damages by way of penalty at the rate of 1/2% (Half percent) per week of delay of the total contract cost subject to a maximum of 7.5% of total contract cost.

The GM Civil's certificate as to the criticality or otherwise of an item shall be final.

The payment of liquidated damages/penalty may be reduced or waived at the sole discretion of the Company whose decision in this regard will be final.

In the event of there being undue delay in execution of the Contract, the Company reserves the right to cancel the Contract and / or levy such additional damages as it deems fit based on the actual loss suffered by the company attributable to such delay. The company's decision in this regard shall be final.

**9.** In order to promote, safeguard and facilitate the general operational economic in the interest of the Company during the continuance of this contract the Contractor hereby agrees and undertakes not to take any direct or indirect interest and or support, assist, maintain or help any person or persons engaged in antisocial activities, demonstration, riots, or in any agitation prejudicial to the Company's interest and any such even taking shape or form at any place of the Company's works or and its neighbourhood.

10.	The tend	dered all-	inclusi	ve Price (i.e. t	the Contract	price) is ₹	<u> </u>	(No	t to be	filled u	ıp by
bidder	while s	submittii	ng the	offer in c-Fo	older. This	figure wil	II be t	filled up by	OIL at	the tin	ne of
award		of	the	contra	act to	) tl	he	success	ful	bid	lder.)
(₹							(	only) but the	e Com	pany	shall
pay the	. Contrac	ctor only	for actu	ual work done	e at the all ir	nclusive ra	ates s	set down in th	ne Sche	dule of	work
part II	of this C	ontract.									

On account payment may be made, not oftener than monthly, up to the amount of 92.5% of the value of work done. Final payment will be made only after satisfactory completion of the work. Such final payment shall be based on the work actually done allowing for deviations and any deductions and the measurement shall be checked and certified correct by the Company's Engineer before any such final payment is made.

- **11.** The contractor employing 20 (twenty) or more workmen on any day preceding 12 months shall be required to obtain requisite licence at his cost from the appropriate Licensing Officer before undertaking any Contract work. The Contractor shall also observe the rules & regulations framed under the Contract Labour (Regulation & Abolition) Act.
- **12.** Wages shall be paid by the Contractor to the workmen directly without any intervention of any Jamadars or Thekaders and that the Contractor shall ensure that no amount by way of commission or otherwise be deducted/ recovered by the Jamadar from the wages of the workmen.
- 13. The Company for any reason whatsoever and of which the company shall be sole judge may terminate this Contract with a 24 hours notice in writing to the Contractor and in the event of Company's so doing the clause 5 here of shall prevail and the accounts between the parties will be in accordance therewith finalised.
- **14.** The Contractor will not be allowed to construct any structure (for storage / housing purpose) with thatch, bamboo or any other inflammable materials within any company's fenced area.
- **15.** The Contractor shall ensure that all men engaged by him/her are provided with appropriate protective clothing and safety wear in accordance with the Oil Mines Regulations 2017. The Company's representative shall not allow/accept those men who are not provided with the same.
- **16.** All Statutory taxes levied by the Central and State Government or any other competent authority from time to time, except PF & GST, will be borne by Contractor and the contract cost is inclusive of all tax liabilities except PF & GST. However, any subsequent increase in such statutory taxes after bid opening day will be borne by the Company. Similarly if there is any decrease in such statutory taxes after bid opening, the Company shall recover the decreased amount of such taxes from the contractor.

Contractor 3 Company

- **17.** The Contractor shall deploy local persons in all works.
- **18.** The Contractor shall not engage minor labour below 18(eighteen) years of age under any circumstances.
- **19.** The Contractor and his/her workmen shall strictly observe the rules and regulations as per Mines Act (Latest editions).

#### 20. SPECIAL CONDITIONS:

- a) The amount of retention money shall be released after 6(six) months from the actual date completion of the work.
- b) The contractor will be required to allow OIL Officials to inspect the work site and documents in respect of the workers' payment.
- c) Contractor(s) whosoever is liable to be covered under the P.F. Act and contract cost is inclusive of P.F., must ensure strict compliance of provisions of Provident Fund and Miscellaneous Provisions Act, 1952 in addition to the various Acts mentioned elsewhere in this contract. Any contractor found violating these provisions will render themselves disqualified from any future tendering. As per terms of the contract, if applicable, the Contractor must deposit Provident Fund Contribution (covering Employee's & employer's share) with the competent authority monthly under their direct code. The Contractor shall be required to submit documentary evidence of deposit of P.F. Contribution to the Company. In case of failure to provide such documentary evidence, the Company reserves the right to withhold the amount equivalent to P.F. Contribution on wage component.
- d) In case P.F. is not included in the contract cost and later on required to be deposited by the Contractor, the same will be reimbursed on production of documentary evidence of depositing the same to the authority concerned. 12% P.F. will be applicable on the wage component of the contract cost.
- e) All safety precautions to be maintained by the Contractor at his own cost as per safety rules and regulations.
- f) The Contractor shall use pump if needed for dewatering of pit while excavation for which no extra payment will be made.
- g) The Contractor shall have to work during rainy seasons also.
- h) Watch and ward, loss or damage to Company's property, theft and other incidental charges shall be Contractor's responsibility.
- i) Efficient workmen to be engaged by the Contractor.
- j) The Contractor's representative should report to Engineer-in-charge on all working days at 7.00 A.M. and 3.00 P.M. for instructions.
- k) Materials if rejected should be removed from site within 48 (forty- eight) hours of rejection, failing which the Company reserves the right to get the rejected materials removed at the risk and cost of the Contractor.
- I) The Company reserves the right to get the part or whole work complete at the risk and cost of the Contractor if he fails to complete the work within the stipulated time without any valid reason. The Company's decision shall be final and binding on the Contractor.
- m) The Contractor must complete all statutory formalities within 7(seven) days of issuance of LOI.
- n) Water that may accumulate on the site during progress of the works or in trenches and excavations from other than accepted risks shall be removed from the site to entire satisfaction of the Engineer-incharge and at the Contractor's expense.
- o) The Contractor shall be in a position to execute 2(two) locations simultaneously.

Contractor 4 Company

- p) If required, the Contractor shall have to work in two shifts for which no extra payment will be admissible to him/them.
- q) If needed water and electricity will have to be arranged by the Contractor at his own cost.
- r) The Contractor and his workmen are to strictly observe the safety precautionary rules as per Mines Act (Latest edition) while executing the work.
- s) The Contractor shall have to provide temporary latrine facilities in the entire work site for use of their workmen during progress of work.
- t) The contractor himself (the signatory of the contract) must visit the site at least twice in a week as fixed for taking necessary instruction from the Engineer-in charge.
- u) The program of works to be submitted in the form of Bar Chart within 3 days of receipt of work order.
- v) The Contract cost is excluding P.F. & GST. Wage component of the Contract cost is 22.95 %.

#### 21. SPECIAL INSTRUCTION

The contractor must quote considering the prevailing minimum Labour wage rate for each day of work.

## 22. GOODS AND SERVICES TAX (GST) CLAUSES UNDER GCC

#### 22.1 GENERAL REMARKS ON TAXES & DUTIES:

In view of **GST** Implementation from 1st July 2017, all taxes and duties including Excise Duty, CST/VAT, Service tax, Entry Tax and other indirect taxes and duties have been submerged in **GST**. Accordingly reference of Excise Duty, Service Tax, VAT, Sales Tax, Entry Tax or any other form of indirect tax except of **GST** mentioned in the bidding document shall be ignored.

- 22.2 Bidders are required to submit copy of the GST Registration Certificate while submitting the bids wherever GST (CGST & SGST/UTGST or IGST) is applicable.
- 22.3 "GST" shall mean Goods and Services Tax charged on the supply of material(s) and services. The term "GST" shall be construed to include the Integrated Goods and Services Tax (hereinafter referred to as "IGST") or Central Goods and Services Tax (hereinafter referred to as "SGST") or Union Territory Goods and Services Tax (hereinafter referred to as "UTGST") depending upon the import / interstate or intrastate supplies, as the case may be. It shall also mean GST compensation Cess, if applicable.
- 22.4 Quoted price/rate(s) should be inclusive of all taxes and duties, except GST (i.e. IGST or CGST and SGST/UTGST applicable in case of interstate supply or intra state supply respectively and cess on GST if applicable) on the final service. Please note that the responsibility of payment of GST (CGST & SGST or IGST or UTGST) lies with the Supplier of Goods /Services (Service Provider) only. Supplier of Goods / Services (Service Provider) providing taxable service shall issue an Invoice/ Bill, as the case may be as per rules/ regulation of GST. Further, returns and details required to be filed under GST laws & rules should be timely filed by Supplier of Goods / Services (Service Provider) with requisite details.

#### 22.5 Where OIL is entitled to avail the input tax credit of GST:

OIL will reimburse the **GST** to the Supplier of Goods / Services (Service Provider) at actuals against submission of Invoices as per format specified in rules/ regulation of GST to enable OIL to claim input tax credit of **GST** paid. In case of any variation in the executed quantities, the amount on which the **GST** is applicable shall be modified in same proportion. Returns and details required to be filed under GST laws & rules should be timely filed by supplier with requisite details.

#### 22.6 Where OIL is not entitled to avail/take the full input tax credit of GST:

OIL will reimburse **GST** to the Supplier of Goods / Services (Service Provider) at actuals against submission of Invoices as per format specified in rules/ regulation of **GST**..

Contractor 5 Company

- 22.7 Payments to Service Provider for claiming **GST** amount will be made provided the above formalities are fulfilled. Further, OIL may seek copies of challan and certificate from Chartered Accountant for deposit of **GST** collected from OIL.
- 22.8 Contractor/vendor shall be required to issue tax invoice in accordance with GST Act and/or Rules so that input credit can be availed by OIL. In the event that the contractor / vendor fails to provide the invoice in the form and manner prescribed under the GST Act read with GST Invoicing Rules thereunder, OIL shall not be liable to make any payment on account of GST against such invoice.
- **22.9 GST** shall be paid against receipt of tax invoice and proof of payment of **GST** to government. In case of non-receipt of tax invoice or non-payment of **GST** by the contractor/vendor, OIL shall withhold the payment of **GST**.
- **22.10 GST** payable under reverse charge mechanism for specified services or goods under GST act or rules, if any, shall not be paid to the contractor/vendor but will be directly deposited to the government by OIL.
- 22.11 Where OIL has the obligation to discharge GST liability under reverse charge mechanism and OIL has paid or is /liable to pay GST to the Government on which interest or penalties becomes payable as per GST laws for any reason which is not attributable to OIL or ITC with respect to such payments is not available to OIL for any reason which is not attributable to OIL, then OIL shall be entitled to deduct/ setoff / recover such amounts against any amounts paid or payable by OIL to Contractor / Supplier.
- 22.12 Notwithstanding anything contained anywhere in the Agreement, in the event that the input tax credit of the **GST** charged by the Contractor / Vendor is denied by the tax authorities to OIL for reasons attributable to Contractor / Vendor, OIL shall be entitled to recover such amount from the Contractor / Vendor by way of adjustment from the next invoice. In addition to the amount of **GST**, OIL shall also be entitled to recover interest at the rate prescribed under GST Act and penalty, in case any penalty is imposed by the tax authorities on OIL.
- 22.13 TDS under GST, if applicable, shall be deducted from contractor's/vendor's bill at applicable rate and a certificate as per rules for tax so deducted shall be provided to the contractor/vendor.
- 22.14 The Contractor will be under obligation for charging correct rate of tax as prescribed under the respective tax laws. Further the Contractor shall avail and pass on benefits of all exemptions/concessions available under tax laws. Any error of interpretation of applicability of taxes/ duties by the contractor shall be to contractor's account.
- **22.15** Further, it is the responsibility of the bidders to make all possible efforts to make their accounting / IT system GST compliant in order to ensure availability of Input Tax Credit (ITC) to Oil India Ltd.
- 22.16 Beyond the contract period, in case OIL is not entitled for input tax credit of GST, then any increase in the rate of GST beyond the contractual delivery period (in case the delay is attributable to the service provider), shall be to Service provider's account whereas any decrease in the rate of GST shall be passed on to the OIL.
  - Beyond the contract period, in case OIL is entitled for input tax credit of **GST**, then statutory variation in applicable **GST** on supply and on incidental services, shall be to OIL's account.
  - Claim for payment of **GST**/ Statutory variation, should be raised within two [02] months from the date of issue of 'Government Notification' for payment of differential (in %) **GST**, otherwise claim in respect of above shall not be entertained for payment of arrears.
- 22.17 The contractor will be liable to ensure to have registered with the respective tax authorities, wherever applicable, and to submit self-attested copy of such registration certificate(s) and the Contractor will be responsible for procurement of material in its own registration (GSTIN) and also to issue its own Road Permit/ E-way Bill, if applicable etc.

#### 22.18 Documentation requirement for GST

Contractor 6 Company

The vendor will be under the obligation for invoicing correct tax rate of tax/duties as prescribed under the GST law to OIL, and pass on the benefits, if any, after availing input tax credit.

Any invoice issued shall contain the following particulars

- a) Name, address and GSTIN of the supplier;
- b) Serial number of the invoice;
- c) Date of issue;
- d) Name, address and GSTIN or UIN, if registered of the recipient;
- e) Name and address of the recipient and the address of the delivery, along with the State and its code.
- f) HSN code of goods or Accounting Code of services[SAC];
- g) Description of goods or services;
- h) Quantity in case of goods and unit or Unique Quantity Code thereof;
- i) Total value of supply of goods or services or both;
- j) Taxable value of supply of goods or services or both taking into discount or abatement if any;
- k) Rate of tax (IGST, CGST, SGST/ UTGST, cess);
- Amount of tax charged in respect of taxable goods or services (IGST,CGST, SGST/UTGST, cess);
- m) Place of supply along with the name of State, in case of supply in the course of interstate trade or commerce;
- n) Address of the delivery where the same is different from the place of supply and
- Signature or digital signature of the supplier or his authorised representative.
   GST invoice shall be prepared in triplicate, in case of supply of goods, in the following manner
  - i. The original copy being marked as ORIGINAL FOR RECIPIENT;
  - ii. The duplicate copy being marked as DUPLICATE FOR TRANSPORTER and
  - iii. The triplicate copy being marked as TRIPLICATE FOR SUPPLIER.

#### 22.19 ANTI-PROFITEERING CLAUSE

In case the GST rating of vendor on the GST portal / Govt. official website is negative / black listed, then the bids may be rejected by OIL. Further, in case rating of bidder is negative / black listed after award of work for supply of goods / services, then OIL shall not be obligated or liable to pay or reimburse GST to such vendor and shall also be entitled to deduct / recover such GST along with all penalties / interest, if any, incurred by OIL.

**22.20** OIL will prefer to deal with registered bidder under GST. Therefore, bidders are requested to get themselves registered under GST, if not registered yet.

#### 23. ARBITRATION:

Any dispute under this contract will be settled through Arbitration as per Indian Arbitration and Conciliation Act, 1996.

Place of Arbitration: Duliajan, Dibrugarh, Assam.

#### 24. FORCE MAJEURE:

Force Majeure (exemption) Clause of the International Chamber of Commerce (ICC Publication No. 421) is hereby incorporated in this contract.

## 25. I.B. VERIFICATION REPORT AND SECURITY REVIEW:

Contractor will be required to submit the verification report to ascertain character and antecedents from the Civil Administration towards the persons engaged under this contract to the Head of the user Department before engagement.

**26.** In case of any doubt or dispute as to the interpretation of any clause herein contained, the decision of the Company's Engineer shall be final and binding on the contractor.

# 27. <u>SET OFF CLAUSE:</u>

"Any sum of money due and payable to the contractor (including Security Deposit refundable to them) under this or any other contract may be appropriated by Oil India Limited and set off against any claim of Oil India Limited (or such other person or persons contracting through Oil India Limited) for payment of a sum of money arising out of this contract or under any other contract made by the contractor with Oil India Limited (or such other person or persons contracting through Oil India Limited)."

Contractor 7 Company

Date\_\_\_

## 28. FURNISHING FRAUDULENT INFORMATION/DOCUMENT:

If it is found that a Bidder/Contractor has furnished fraudulent document/information, the Bid Security/ Performance Security shall be forfeited and the party shall be debarred as per the OIL's Banning Policy dated 6<sup>th</sup> Jan 2017 available at OIL's website.

# 29. <u>LIQUIDATED DAMAGES FOR DELAY IN MOBILISATION AND/ OR COMPLETION OF WORKS</u> AND SERVICES

In normal case of works /service contracts, liquidated damages will be applicable @ 0.5% of the contract value per week or part thereof, for delay in contract mobilization /completion date subject to a maximum ceiling of 7.5% of contract value .

IN WITNESS whereof the parties hereunto set their hands seals the day and year first written above:-

SIGNED & DELIVERED FOR AND (Signature of Contractor or his legal Attorney) ON BEHALF OF By the hand of (Full Name of Signatory) -----It's Partner/Legal Attorney (Seal of Contractor's Firm) \_\_\_\_\_ And in presence of (Signature of witness) -----Date: \_\_\_\_\_ (Full Name of Signatory) Address: (Signature of Acceptor) SIGNED & DELIVERED FOR & ON BEHALF OF OIL INDIA LIMITED Designation \_\_\_\_\_

Contractor 8 Company

# OIL INDIA LIMITED (A Govt. of India Enterprise) <u>Duliajan, Assam</u> <u>WORKS CONTRACT</u>

SI. No.	Description of Work	Qty	UOM	Curr.	Rate
	Group A SEC-A				
10	Jungle cutting and clearing including removal of cut materials upto 100m from site and disposing as directed (all jungle to be cut at ground level). For light jungle including plants and trees upto 300mm girth. (OIL SOR-41.1.5)	1600.00	M2	INR	1.72
20	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means over areas (exceeding 30cm in depth. 1.5m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m, disposed earth to be levelled and neatly dressed. All kinds of soil.( Rate as per CPWD 2016, Item No-2.6.1)	185.00	M3	INR	122.56
30	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.(Rate as per CPWD 2016, Item No-2.25)	185.00	M3	INR	124.48
40	Supplying and filling in plinth with sand under floors including, watering, ramming consolidating and dressing complete(cost of sand will be paid separately).( Rate as per CPWD-2016, Item No- 2.27)	162	M3	INR	1017.07
50	Surface dressing of the ground including removing vegetation and in-equalities not exceeding 15 cm deep and disposal of rubbish, lead upto 50 m and lift upto 1.5 m. All kinds of soil (Rate as per CPWD 2016, Item No-2.28.1)	504.00	M2	INR	13.68
60	Collecting / excavating sand, soil, silt, ordinary earth from any source, load into lorries, transport it to distant place of work including procuring earth and laying in layer of 150mm thickness and compacting, profile properly made for taking measurement, including all measurable lead upto 30m and lift as required. (The contractor shall be responsible for all formalities of supply of earth such as purchase of land including royalties, monopoly / other statutory taxes as required from any distance.) (OIL SOR-41.7.2)	171	М3	INR	359.79
70	Supplying & laying in position cement concrete of specified grade excluding the cost of centring and shuttering - All work upto plinth level: 1:3:6 ( 1 Cement: 3 coarse sand : 6 graded stone aggregate 20 mm nominal size)(Rate as per CPWD 2016, Item No- 4.1.5)	54.00	M3	INR	3936.09
80	Supplying and Providing and laying damp-proof course 40mm thick with cement concrete 1:2:4 (1 cement:2 coarse sand(zone -III):4 graded stone aggregate 12.5 mm nominal size. (Rate as per CPWD 2016, Item No- 4.10)	12.00	M2	INR	235.29
90	Supplying & Providing & Laying in position specified grade of reinforced cement concrete excluding the cost of centring, shuttering, finishing and reinforcement - All work upto plinth level: 1:1.5:3 (1 cement: 1.5 coarse sand: 3 graded stone aggregate 20 mm nominal size).(Rate as per CPWD 2016, Item No- 5.1.2).	62.00	М3	INR	3879.76

SI. No.	Description of Work	Qty	UOM	Curr.	Rate
100	Supplying & Providing concrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. upto floor five level excluding cost of centring, shuttering, finishing and reinforcement: 1:1.5:3 (1 cement: 1.5 coarse sand: 3 graded stone aggregate 20 mm nominal size) (Rate as per CPWD 2016, Item No- 5.2.2)	68.00	МЗ	INR	4785.44
110	Supplying & providing Brick work with F.P.S. bricks of class designation 75 in foundation and plinth in: Cement mortar 1:4 (1 cement : 4 coarse sand) (Rate as per CPWD 2016, Item No- 6.1.1)	40.00	M3	INR	7052.93
120	Supplying & providing Half brick masonry with F.P.S. bricks of class designation 75 in superstructure above plinth level up to floor V level. Cement mortar 1:4 (1 cement :4 coarse sand) (Rate as per CPWD 2016, Item No- 6.13.2)	500.00	M2	INR	927.14
130	Supplying and Extra for placing in position 2 Nos. 6mm dia. M.S. bars at every third course of half brick masonry(with F.P.S. Bricks) (Rate as per CPWD 2016, Item No- 6.15)	550.00	M2	INR	54.01
140	Supplying & providing 12mm cement plaster of mix:1:4 (1 cement : 4 fine sand) (Rate as per CPWD 2016, Item No-13.1.1)	515.00	M2	INR	142.40
150	Supplying & providing 15mm cement plaster on the rough side of single or half brick wall of mix:1:4 (1 cement : 4 fine sand) (Rate as per CPWD 2016, Item No- 13.2.1)	1490.00	M2	INR	163.61
160	Supplying & providing 6mm cement plaster of mix:1:3 (1 cement : 3 fine sand) (Rate as per CPWD 2016, Item No-13.16.1)	515.00	M2	INR	121.93
170	Supplying & providing Cement plaster skirting (up to 30cm height) with cement mortar 1:3 (1 cement: 3 coarse sand) finished with a floating coat of neat cement.18mm thick. (Rate as per CPWD 2016, Item No- 11.6.1)	25.00	M2	INR	347.89
180	Supplying & centring and shuttering including strutting, propping etc. and removal of form for: Foundations, footings, bases of columns, etc. for mass concrete. (Rate as per CPWD 2016, Item No- 5.9.1)	170.00	M2	INR	196.52
190	Supplying & Centring and shuttering including strutting, propping etc. and removal of form for: Suspended floors, roofs, landings, balconies and access platform.(Rate as per CPWD 2016, Item No- 5.9.3)	180.00	M2	INR	441.28
200	Supplying, Centring and shuttering including strutting, propping etc. and removal of form for: Lintels, beams, plinth beams, girders, bressumers and cantilevers. (Rate as per CPWD 2016, Item No- 5.9.5)	500	M2	INR	355.08
210	Supplying, Centring and shuttering including strutting, propping etc. and removal of form for: Columns, Pillars, Piers, Abutments, Posts and Struts. (Rate as per CPWD 2016, Item No- 5.9.6)	221.00	M2	INR	483.68
220	Supplying, Centring and shuttering including strutting, propping etc and removal or form tor: Stairs, (excluding landings) except spiral-staircases. (Rate as per CPWD 2016, Item No- 5.9.7)	23.00	M2	INR	428.87
230	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more (Refer CPWD SOR 2016, Item No. 5.22.6)	16115.00	KG	INR	62.25

SI. No.	Description of Work	Qty	UOM	Curr.	Rate
240	Supplying and Steel work in built up tubular (round, square or rectangular hollow tubes etc.) including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. Hot finished seamless type tubes. (Rate as per CPWD 2016, Item No- 10.16.2)	7200.00	KG	INR	90.21
250	Providing and fixing M.S. fan clamp type I or II of 16 mm dia M.S. bar, bent to shape with hooked ends in R.C.C. slabs or beams during laying, including painting the exposed portion of loop, all as per standard design complete.	50	EA	INR	110.82
260	Supplying and Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel as required. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works. (Rate as per CPWD 2016, Item No- 10.25.2)	4500.00	KG	INR	88.02
270	Supplying & Fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansionBend 87.5°-110 mm Bend. (Rate as per CPWD 2016, Item No- 12.42.5.2)	60.00	EA	INR	107.45
280	Supplying & Installation of precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-Charge) 0.50mm +/- 5% total coated thickness (TCT) Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat' 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-Charge. The sheet shall be fixed using self drilling / self tapping screws of size (5.5x 55mm) with EPDM seal or with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen and G.I. limpet washers or with G.I. limpet washers filled with white lead complete upto any pitch in horizontal / vertical or curved surfaces excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required. (Rate as per CPWD 2016, Item No-12.50)	478.00	M2	INR	529.12
290	Supplying & Fixing precoated galvanised steel sheet roofing accessories 0.50 mm + 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws or with polymer coated J or L hooks, bolts and nuts and or G.I. seam bolts and nuts, G.I. plain and bitumen washers complete: Ridges plain (500 - 600mm). (Rate as per CPWD 2016, Item No- 12.51.1)	40.00	М	INR	347.08
300	Supplying & Fixing precoated galvanised steel sheet roofing accessories 0.50 mm + 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws or with polymer coated J or L hooks, bolts and nuts and or G.I. seam bolts and nuts, G.I. plain and bitumen washers complete: Barge board (Upto 300 mm).(Rate as per CPWD 2016, Item No- 12.51.4)	100.00	М	INR	307.33

SI. No.	Description of Work	Qty	UOM	Curr.	Rate
310	:Supplying & Fixing precoated galvanised steel sheet roofing accessories 0.50 mm + 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws or with polymer coated J or L hooks, bolts and nuts and or G.I. seam bolts and nuts, G.I. plain and bitumen washers complete: Gutter (600 mm over all girth) (Rate as per CPWD 2016, Item No- 12.51.6)	78.00	М	INR	824.31
320	Supplying & Fixing chicken wire netting with timber beads on timber frame (or with steel flat on steel frame). (Rate as per OIL SOR 2016, Item No- 41.78.1)	76.00	M2	INR	598.60
330	Supplying & Fixing in position collapsible steel shutters with vertical channels 20x10x2mm and braced with flat iron diagonals 20x5mm size with top and bottom rail of T-iron 40x40x6mm with 40mm dia, steel pulleys complete with bolts, nuts, locking arrangement, stoppers, handles, including applying a priming coat of approved steel primer.(Rate as per CPWD 2016, Item No- 10.3)	12.00	M2	INR	5679.57
340	Supplying & Fixing 1mm thick M.S. sheet door with frame of 40x40x6mm angle iron and 3mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, including applying a priming coat of approved steel primer. Using flats 30x6mm for diagonal braces and central cross piece. (Rate as per CPWD 2016, Item No- 10.5.2)	2	M2	INR	2831.29
350	Supplying & providing Wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position: Kiln seasoned and chemically treated Hollock wood. (Rate as per CPWD 2016, Item No-9.1.3)	4.50	M3	INR	54644.57
360	Supplying and Providing and fixing frame for false ceiling in true horizontal level, suspended on interlocking metal grid of hot dipped galvanized steel sections (galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings, fixtures, smoke detectors etc. Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanized butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be prepainted with polyester paint, all complete for all heights as per specifications, drawings and as directed by Engineer-incharge. (Rate as per CPWD 2016, Item No- 12.58)	323.00	M2	INR	443.89

SI. No.	Description of Work	Qty	UOM	Curr.	Rate
370	Providing and fixing multi-purpose cement board (High pressure steam cured) with suitable screws for cement particle board in ceiling etc complete (framework to be paid separately). 6 mm thick cement fibre board as per IS: 14862.(Rate as per CPWD 2016, Item No- 12.26.1)	323.00	M2	INR	530.34
380	Supplying & providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25mm to 40mm thick: Particle Board 12mm thick Pre-laminated particle board with decorative lamination on both sides, Grade I, Type II, IS:12823 marked.(Rate as per CPWD 2016, Item No- 9.7.5.4)	40	M2	INR	1408.23
390	Supplying & Fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25mm to 40mm thick: 5.5 mm thick float glass pane thick Prelaminated particle board with decorative lamination on both sides, Grade I, Type II, IS:12823 marked.( Rate as per CPWD 2016, Item No- 9.7.7.1)  P/F ISI marked flush door shutter - non-decorative 30mm	24.00	M2	INR	1197.60
400	thick i/c stainless steel butt hinges: (Rate as per CPWD 2016, Item No- 9.21.2)	2.00	M2	INR	1578.54
410	Supplying & Fixing bright finished brass tower bolts (barrel type) with necessary screws etc. complete: 250x10mm. (Rate as per CPWD 2016, Item No- 9.74.1)	6.00	EA	INR	299.04
420	Supplying & Fixing chromium plated brass handles with necessary screws etc. complete: 125mm.(Rate as per CPWD 2016, Item No- 9.92.1)	4.00	EA	INR	202.15
430	Supplying & Fixing rolling shutters of approved make, made of required size M.S. laths interlocked together through their entire length and jointed together at the end by end locks mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete including the cost of providing and fixing necessary 27.5cm long wire springs grade No.2 and M.S. top cover of required thickness for rolling shutters. (Rate as per CPWD 2016, Item No- 10.6.1)	16.00	M2	INR	2259.55
440	Supplying & Fixing glass panes with putty and glazing clips in steel doors, windows, clerestory windows all complete with 4.0 mm thick glass panes. (Rate as per CPWD 2016, Item No- 10.30.1)	21.00	M2	INR	666.69
450	Supplying & Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade: New work (Two or more coats applied @ 1.43 ltr/10 sqm over and including base coat of water proofing cement paint applied @ 2.20 kg/10 sqm).(Rate as per CPWD 2016, Item No- 13.47.1)	615	M2	INR	98.14
460	Supplying & Painting with synthetic enamel paint of approved brand and manufacture to give an even shade: Two or more coats on new work. (Rate as per CPWD 2016, Item No- 13.61.1)	780.00	M2	INR	80.26
470	Supplying & Application of white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. (Rate as per CPWD 2016,	750.00	M2	INR	90.35

# Part-II SOQ

SI.	Description of Work	Qty	UOM	Curr.	Rate
No.	Item No- 13.8)				
480	Supplying & Wall painting with premium acrylic emulsion paint of interior grade, having VOC (Volatile Organic Compound) content less than 50 grams/ litre. of approved brand and manufacture, including applying additional coats wherever required to achieve even shade and colour: Two Coats.(Rate as per CPWD 2016, Item No- 13.83.2)	750.00	M2	INR	73.20
490	Services with welding and cutting set in carrying out miscellaneous repairs / new construction involving steel work (services of one welder and one jugali per set) to be supplied by the contractor. (New welding set inclusive fuel etc. to be supplied by the contractor).(Rate as per OIL SOR 2016, Item No- 41.5.1)	10	PD8	INR	1812.14
500	Supplying and construction of 40mm thick marble chips flooring rubbed and polished to granolithic finish, under layer 34mm thick cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 12.5mm nominal size) and top layer 6mm thick with white, black, chocolate, grey, yellow or green marble chips of sizes from 1mm to 4mm nominal size laid in cement marble powder mix 3:1 (3 cement : 1 marble powder) by weight in proportion of 4:7 (4 cement marble powder mix : 7 marble chips) by volume including cement slurry etc. complete: Dark shade pigment with ordinary cement. (Rate as per CPWD 2016, Item No-11.9.1)	330.00	M2	INR	549.19
510	Supplying and Hydraulic Excavator (3D) with driver and fuel.(Rate as per OIL SOR 2016, Item No- 0020)	3.00	DAY	INR	7984.99
520	Supplying and diluting and injecting chemical emulsion for post constructional antitermite treatment (excluding the cost of chemical emulsion) .Along the external wall below concrete or masonry apron using chemical emulsion @ 2.25 litres per linear metre including drilling and plugging holes etc.: With Chlorpyriphos/ Lindane E.C. 20% with 1% concentration. (Rate as per CPWD 2016, Item No- 2.35.2.1)	105.00	М	INR	23.64

• Bidder must include all liabilities including statutory liabilities in their quoted rates (excluding PF and GST).

## Note:

1. The Company's Internal Estimated Rates, as indicated in Part-II, are inclusive of all overheads, taxes, duties, levies etc. except P.F. & GST.

E- TENDER NO.: CDC9676P19 PART-III SCC

OIL INDIA LIMITED (A Govt. of India Enterprise) DULIAJAN (ASSAM) WORKS CONTRACT

#### PARTICULAR SPECIFICATIONS AND INSTRUCTIONS:

<u>DESCRIPTION OF WORK/SERVICES</u>: Construction of maintenance godown at Well-50 including supply of all materials except cement.

#### SCOPE OF CIVIL WORK

#### 1.0 GENERAL:

All materials used in the work shall conform to the latest revision of the relevant Indian Standard Specifications to the extent practicable. Where no such specifications exist they shall be of the best quality available in the market. Wherever ISI certified materials and products are available these alone shall be used. All materials shall be stored at site in accordance with IS-4082-1996.

Unless specially provided for in the contract the tendered rates shall include the cost of carriage, transport, loading, unloading and stacking as directed for all materials required on the work. Where a tender provides a rate for transport of materials, it includes for all loading, unloading and stacking on the site in such position and manner as directed. Any materials found not conforming to specification must be removed from site within 48 hours.

#### 2.0 SITE CLEARANCE, EXCAVATION AND DISPOSAL:

Before the earthwork is started, the area coming under cutting and/refilling shall be cleared of shrubs, vegetation, grass, uprooting of tree stumps and such others, and rubbish removed upto a distance of 50 metres outside the periphery of the area under clearance. The rate of such site clearance is included in the rate of earthwork.

All excavations shall be done to the minimum dimensions as required for safety and working facility. Prior approval of the Engineer shall be obtained by the Contractor, in each individual case, for the method he proposes to adopt for the excavations including dimension, side slopes, shoring, dewatering, disposal, etc. This approval, however, shall not in any way make the Engineer responsible for any consequent loss or damage. The excavation must be carried out in the most expeditious and efficient manner.

The excavated spoils will be disposed off in any or all the following manners:

- a) By using it for backfilling straightway.
- b) By stacking it temporarily for use in backfilling at a later date during execution of the Contract.
- c) (i) By either spreading, Or
  - (ii) Spreading and compacting at designated disposal areas.

#### 3.0 STORAGE:

Materials shall be transported, handled and stored at site carefully to the approval of Engineer so as to prevent any damage of any kind to be kept at his own risk and cost.

Cement shall be stored in a weather proof shed, the floor of which shall be raised 300 mm clear from the ground and 600 mm away from the wall all round in order to protect from rain and moisture. Empty cement bag shall be returned to the Company in good condition.

#### 4.0 CEMENT CONCRETE/ REINFORCED CEMENT CONCRETE WORK:

All C.C. work in 1:3:6 proportions shall be done with 18 mm graded down coarse aggregate. Coarse aggregate shall be properly screened before use. All reinforced cement concrete work to be done in prop. 1:1.5:3 unless otherwise specified -- 18mm down to 12mm graded down coarse aggregate as per related

**PART-III SCC** 

drawings and instructions of site Engineer to be followed in case of any discrepancies. Proper vibration to be done as per IS recommendation. Floor paneling to be done in the line of expansion joint as directed by Engineer-In-charge.

Fine Aggregate - Fine aggregate shall be hard, durable, clean and free from adherent coating and organic matter. It shall not contain harmful impurities such as pyrites, coal, lignite, mica, shale or similar laminated material, clay, alkali, soft fragments, sea shells and organic impurities in such quality as to affect the strength or durability of the concrete. Fine aggregate to be used for reinforced concrete shall not contain any material liable to attack the steel reinforcement. Fine aggregate which is chemically reactive with alkalis of cement is harmful as cracking of concrete may take place.

Coarse Aggregate - Coarse aggregate shall be obtained from natural sources such as stone, gravel, etc crushed or un-crushed or a continuation thereof from approved quarries. This shall consist of coarse material most of which is retained on 4.75mm sieve. Aggregate shall be hard, strong, dense, durable, clean and free from veins and adherent coatings. It shall be free from soft, feeble, thin, elongated or laminated pieces and shall be roughly cubical in shape. It shall be clear and free from dirt and any other deleterious matter.

Reinforcement bars - The following types of steel for reinforcement shall be used in reinforced concrete construction and these shall conform to Indian Standards or as revised from time to time mentioned against each

- 1) Mild steel and medium tensile steel bars and hard drawn steel wire IS: 432.
- 2) HYSD bars IS: 1786.

Bending & Placing steel reinforcement in position - Bending shall be carried out as per relevant IS specification and direction of the Engineer-in-charge. All reinforcement bars shall be accurately placed in position with spacing and cover as shown in the drawing or as specified and firmly held so during the placing and vibrating and setting of concrete. Bars shall be thoroughly cleared of rust, seals, grease, oil and any other foreign matter before placing them in position. The overlap jointing shall be staggered. The bars shall be fixed with 22G binding wire. Precast cover blocks 1:2 (1 cement: 2sand) cement mortar 40 mm square and necessary thickness shall be used to keep the reinforcement bars in proper position. For this block, no extra payment to be made. Wire required for binding shall not be measured separately. Tack welding shall also be permitted in lieu of building with steel wire.

Proportioning of mix - Proportioning shall be done by volume. Boxes of suitable size shall be used for measuring sand and aggregates. The size of the boxes (internal) shall be 35 x 25cm and 40cm deep. The unit of measurement for cement shall be a bag of cement weighting 50 Kg and this shall be taken as 0.035 cubic metre. While measuring the aggregate and sand the boxes shall be filled without shaking, ramming or hammering. The proportioning of sand shall be on the basis of its dry volume and in case of damp sand; allowances for bulkage shall be made.

Mixing - Mixing of reinforced cement concrete shall, as a rule be done in a mechanical mixer. However, the Engineer-in-charge may permit hand mixing in specific cases where in his opinion it is not practicable to resort to mechanical mixing, either on account of the quality of cement concrete required is small or for any other reason. In such cases, it should be ensured that the inferior quality of concrete produced by hand mixing will not adversely affect the structure.

Consistency - The quantity of water to be used for each batch containing 50 Kg of cement, to give the required consistency shall not be more than 34 litres for 1:3:6, mix 32 litres for 1:2:4 mix, 30 litres for

**PART-III SCC** 

1:1.5:3 mix and 27 litres for 1:1:2 mix. In case of vibrated concrete, the above quantity shall be suitably reduced. The quantity of water shall be regulated by carrying out regular Slump Test.

Placing of concrete - Before placing the concrete the sub-base/form work shall be cleared of all injurious or foreign matter, watered and well consolidated. Formwork shall be clean and free from all foreign material. It is necessary that the time between mixing and placing of concrete does not exceed the initial setting process. Mixed concrete that has been left standing shall not be used after the initial set has commenced the addition of water (or cement) to make such a mixture more workable shall not be allowed. In foundation trenches or such other situations, the entire concrete used in the work shall be laid gently (not thrown) in layers not exceeding 15cm. The concrete so deposited shall be thoroughly vibrated by means of mechanical vibrators till dense concrete is obtained.

Curing - Concrete shall be carefully protected during first stage of hardening from harmful effects or excessive heat, drying winds, rain or running water and shock. After the concrete has begun to harden i.e. about 1 to 2 hours after its laying it shall be protected from quick drying with moist gunny bags or any other material approved by the Engineer-in-charge. After 24 hours of laying of concrete the surface shall be cured by flooding water upto 25mm depth or by covering with wet adsorbent materials. The curing shall be done for a minimum period of 7 days from the date of pouring of concrete, unless otherwise specified.

Finishing - In case of roof slabs the top surface shall be finished even and smooth with wooden trowel, before the concrete beings to set. The surface of RCC slab on which the cement concrete or mosaic floor is to be laid shall be roughened with brushes while the concrete is green. This shall be done carefully without disturbing the concrete. Before laying the floor, the laitance shall be removed, the surface of slab hacked and a coat of cement slurry at 2.75 Kg of cement per square metre shall be applied, so as to get a good bond between RCC and concrete floor. The exposed surface which is to receive plaster or where it is to be joined with brick masonry wall shall be properly roughened immediately after the removal of form work, taking care to remove the laitance completely without disturbing the concrete. Before the surface is plastered, it shall be cleaned and wetted so as to give good bond between concrete and plaster.

#### 5.0 FORM WORK:

The formwork shall be rigid and so corrected as to retain the shape and dimensions of the member being cast. Form work for concrete shall be seasoned timber or other approved materials as per directions of the Engineer. It shall be sufficiently tightened to prevent loss of cement slurry and all holes and joints shall be chaulked with putty. It shall have sufficient strength and rigidity to withstand the load of concrete, and vibrations, movement of men, materials and plants and any other incidental loads without excessive deflection beyond permissible limits. The formwork shall be so constructed as to be removable in sections by inscribing or otherwise loosing – them without hammering or levering with force. Only wedges, clamps bolts or screws etc shall be used in preference to nails or spikes. All side pieces shall be easily removable without disturbing the bottom pieces. Where however, use of nails and spikes become unavoidable, these shall be left projecting so that they can easily be withdrawn.

Surface treatment for shuttering - Forms shall be cleaned of all dust, wood shavings, dirt and other matter by washing with water. This process is facilitated by providing draining holes in the shuttering. The surface shall then be coated with soap solution applied before concreting is done. Soap solution for the purpose shall be prepared by dissolving yellow soap in water to get consistency of paint. Alternatively a coat of raw linseed oil/refined pale paraffin mineral oil or form oil of approved manufacture may be applied. In case steel shuttering is used, soap solution or row linseed oil shall be applied after thoroughly cleaning the surface. Care shall be taken that such approved composition is kept out of contact with the reinforcement.

In normal circumstances and where ordinary Portland cement is used form may generally be removed after the expiry of the following periods.

- a) Walls, columns and vertical face of all structural members as may be decided by the Site Engineer: 24 to 48 hours.
- b) Slabs side (props left under): 3 days
- c) Beam soffits (props. left under):14 days
- d) Removal of props under slabs
  - i) Spanning up to 4.5 m: 14 days
  - ii) Spanning over 4.5 m: 21 days
- e) Removal of props under beams:
  - i) Spanning up to 6 m: 21 days
  - ii) Spanning above 6 m: 28 days

In no circumstances shall forms be struck until the concrete reaches strength of at least twice the stress to which concrete may be subjected at the time of removal of form work. All form works shall be removed without such shock or vibration as would damage the concrete. Form work for long span deep beams to be supported by MS props or Bhaluka Bamboo props as required based on the design for the formwork to take care the massive load of the green concrete.

#### 6.0 BRICKWORK:

- a) All bricks shall be of 75 class designation quality locally available as approved by the Site Engineer.
- b) Bricks shall be of size as specified in the item of work or of nominal size where no particular size is mentioned.
- c) Bricks shall be well burnt, sound, hard with sharp edges of uniform size and shape free from cracks, stones or particles of lime and other defects, shall be kiln burnt and satisfy the following requirement:
  - (i) They shall give a clear metallic sound when struck
  - (ii) They shall be of uniform colour and size
  - (iii) They shall not be cracked, stratified or under or over burnt
  - (iv) The tolerance in dimensions shall be +/- 12mm in length, 6mm in width and 3mm in height.
- (v) Keys or frogs shall be formed on one of the larger size, except in the case of machine extruded bricks where no frogs are required
- (vi) The increase in weight when soaked in water for 24 hours shall not be more than 20% of the dry weight of the bricks.
- d) If required by the Site Engineer, necessary test shall be conducted at the contractor's expense to ensure quality. In general, the bricks shall be the best quality locally available.

Bricks used for masonry in cement mortar or composite mortar shall be thoroughly soaked in clean water for at least an hour immediately before use (The absence of bubbling when the soaked brick is immersed in water is the test for thorough soaking). The soaked bricks shall be kept on a platform free from dirt, mud or any foreign element. Bricks shall be laid in English bond unless otherwise specified. Care must be taken that the bricks are perfectly clean and free from lime, moss or dirt of any kind. If necessary they must be scrubbed before use. Half or cut bricks shall be not used except for closures which may be required to complete the bond. It shall be ensured that all horizontal and vertical joints are completely filled with mortars without any void in brickwork. Brickwork shall be raised truly plum (or true to required better where so specified). All courses shall be laid truly horizontal. Vertical joints shall be truly vertical and those in alternate courses shall be in the same vertical line. The thickness of brick courses shall be uniform. Great care must be taken to masonry in progress of construction damp. When work is left off for the day troughs shall be formed, by means of fillets of mortar 51mm high all-round the unfinished work and shall be kept filled with water. Vertical or inclined surfaces must be frequently watered from a rose headed can. Water should not be dashed with violence against new work as this washes out the mortar. Should the work be delayed owing to holidays or for other reason, the contractor must make adequate arrangements for keeping the work wetted, and shall continue to do so for at least ten days or such longer time as directed, after the brickwork has been completed.

- a) Brick work in cement mortar with 75 designation brick including racking out joints and curing complete as directed, in sub structure and superstructure in mortar of specified proportion.
- b) 115mm thick 75 designation brick nogged wall in cement mortar embedded with protruding M.S. rod 6 mm dia in column including racking out joint and curing complete as directed in super structure above plinth in proportion as specified.

#### 7.0 CEMENT MORTAR:

- i) Must be freshly mixed: Cement mortar will only be mixed in such quantities as can be used up on the work within half an hour of mixing. Mortar which has been mixed longer or which has taken its initial set will on no account be used on the work or remixed with fresh mortar. It must be immediately removed from the site or work.
- ii) Method of mixing: The cement and sand will be mixed dry in the specified proportions, by turning over atleast three times on the mixing platform. Only sufficient water will then be added, thorough a rose of a watering can, to produce a workable mixture. The wet mortar will be thoroughly worked or mixed by repeatedly turning over, not less than three times on the mixing board.
- iii) Size of mixing platform and precaution against list: All mixing of mortar must be done on platforms of angle size and workman bringing the material to and from the platform must not be permitted to walk about on it, thereby bringing mud or dirt to the place, where the mortar is being mixed. The platform must be clean and level and all joints closed or filled so that the cement is not washed out.
- iv) Proportion of cement and sand: Where not otherwise specified, cement mortar for plaster will consist of one part of cement to two parts of sand. For mortar for brick or stone masonry work the proportion unless otherwise specified, will be one part of cement to three parts sand.

#### 8.0 PLASTER WORK:

- i) Preparation of surface: All putlog holes in brick work and junction between concrete and brick work shall be properly filled in advance. Joints in brick work shall be raked about 10mm and concrete surface hacked to provide grip to the plaster. Projecting burrs of mortar formed due to gaps at joints in shuttering shall be removed. The surface shall be scrubbed clean with wire brush/coil brush to remove dirt, dust etc. and the surface thoroughly washed with clean water to remove efflorescence, grease and oil etc. and shall be kept wet for a minimum of six hours before application of plaster.
- ii) Proportion: The cement plaster shall be in specified proportion of cement and sand.
- iii) Mixing: The cement and sand should be thoroughly mixed in dry condition. After dry mixing the materials shall be wetted with just sufficient water to bring the mortar to proper consistency of thick paste. Mortar should be used immediately after mixing and arrangements shall be made so that not more than 30 minutes elapse between the cement first coming in contact with the moisture and laying. In all exterior plaster works waterproofing compound to be added to the mortar as per the specification of the manufacturer, if not indicated in the item rate quoted should be inclusive of the same.
- iv) Placing: Plaster shall be laid over the prepared surface in one coat to the specified thickness and rubbed with "PATAS" and trowel and shall be smooth, free from waviness and trowel marks.
- v) Sequence of operations: For external plaster, the plastering operations shall be started from the top floor and carried downwards. For internal plaster, the plastering operations may be started wherever the building frame and cladding work are ready and the temporary supports of the ceiling resting on the wall or the floor have been removed.
- vi) Curing: Each coat shall be kept damp continuously till the next coat is applied or for a minimum period of 7 days. Moistening shall commence as soon as plaster is hardened sufficiently. Soaking of walls shall be avoided and only as much water as can be readily absorbed shall be used.

#### 9.0 STEEL WORKS:

Laying Out: A figure of the steel structure to be fabricated shall be drawn on a level platform to full scale. This may be done in full or in parts, as shown on drawings or as directed by the Engineer-in-Charge. Steel tape shall be used for measurements.

Fabrication: Fabrication shall generally be done as specified in IS 800. Great accuracy shall be observed in the fabrication of various members, so that these can be assembled without being unduly packed, strained or forced into position and when built up, shall be true and free from twist, kinks, buckles or open joints. The steel section shall be straight or to be straightened or flattened by pressure unless required to be of curvilinear form and shall free from twists. These shall be cut square either by shearing or sawing to correct length and measured by steel tape. No tow pieces shall be welded or joined to make up for the required length of member.

During execution, the steel members shall be securely bolted or otherwise fastened when necessary temporarily braced to provide for all loads including those due to erection equipment's and its operation to be carried safely by structure during erection. The steel members shall be placed in proper position as per approved drawing, final riveting or permanent bolting shall be done only after proper alignment has been checked and confirmed.

Trusses shall be lifted only at nodes. The trusses above 10 m in span shall not be lifted by slinging at two mid points of rafters, which shall be temporary braced by a wooden member of a suitable section. After the trusses are placed in position, purlins and wind bracings shall be fixed as soon as possible.

Welding: Welding shall generally be done by electric arc process as per IS 816 and IS 823. The electric arc method is usually adopted and is economical. Gas welding shall only by resorted to using oxyacetylene flame with specific approval of the Engineer-in-charge. Gas welding shall not be permitted for structural steel work Gas welding required heating of the members to be welded along with the welding rod and is likely to create temperature stresses in the welded members. Precautions shall therefore be taken to avoid distortion of the members due to these temperature stresses.

As far as possible every effort shall be made to limit the welding that must be done after the structure is erected so as to avoid the improper welding that is likely to be done due to heights and difficult positions on scaffolding etc. apart from the aspect of economy. The maximum dia of electrodes for welding work shall be as per IS 814. Joint surfaces which are to be welded together shall be free from loose mill scale, rust, paint, grease or other foreign matter, which adversely affect the quality of weld and workmanship.

#### 10.0 FILLING EXCAVATED EARTH IN FOUNDATION TRENCHES AND PLINTH OR UNDER FLOORS:

As soon as the work in foundation has been completed and measured, the sides of foundations shall be cleared of all debris, bricks bats, mortar dropping etc, and filled with earth in layers not exceeding 30cms, each layer shall be adequately watered, rammed and consolidated before the succeeding one is laid. Earth shall be rammed with iron rammers where feasible, and with the butt ends crowbars where rammer cannot be used.

The plinth shall be similarly filled with earth in layers not exceeding 30cms, adequately watered and consolidated by ramming with iron or wooden rammers. When filling reaches the finished level, the surface shall be flooded with water for at least 24 hours, allowed to dry and then rammed and consolidated, in order to avoid any settlement at a later stage.

#### 11.0 DISMANTLING AND DEMOLISHING:

The demolition shall always be well planned before hand and shall generally be done in reverse order of the one in which the structure was constructed. Necessary propping, shoring and or under pinning shall be provided to ensure the safety of the adjoining work or property before dismantling and demolishing is taken up and the work shall be carried out in such a way that no damage is caused to the adjoining work or property. Wherever specified, temporary enclosures or partitions and necessary scaffolding with suitable double scaffolding and proper cloth covering shall also be provided, as directed by the Engineer-in-Charge.

Necessary precautions shall be taken to keep noise and dust nuisance to the minimum. The demolition work shall be proceeded with in such a way that it causes the least damage and nuisance to the adjoining building and the public.

PART-III SCC

Dismantling shall be done in a systematic manner. All materials which are likely to be damaged by dropping from a height or by demolishing roofs, masonry etc. shall be carefully removed first. Chisels and cutters may be used carefully as directed. The dismantled articles shall be removed manually or otherwise, lowered to the ground (and not thrown) and then properly stacked as directed by the Engineer-in-Charge.

Where existing fixing is done by nails, screws, bolts, rivets, etc., dismantling shall be done by taking out the fixing with proper tools and not by tearing or ripping off.

Any serviceable material, obtained during dismantling or demolition, shall be separated out and stacked properly as directed by the Engineer-in-Charge within a lead of 50 metres. All unserviceable materials, rubbish etc. shall be disposed off as directed by the Engineer-in-Charge.

#### 12.0 TESTS FOR QUALITY CONTROL:

The various tests shall be carried out by the contractor as and when instructed by the Engineer-in-charge and no separate payment shall be made unless otherwise specified in the schedule of rates. Following tests /test certificate to be produced by the contractor at his own cost as and when directed by the Engineer-in-charge.

- (i) Water for construction and curing ('PH' value should not be less than 6.)
- (ii) Cube test for RCC work. (Test to be performed in presence of company representative).
- (iii) Manufacture Test certificate for steel materials, M.S. rod, Tor steel should be produced prior to its use in construction.
- (iv)Brick test as per BIS 1077 and BIS 3495 (part 1 and 2)
- (v) Test for fine and course aggregate
- (vi)Any other tests as per the direction of Engineer-in-charge.

#### 13.0 MEASUREMENT & PAYMENT:

Payment for all works done shall be made on the basis of actual work done as per the schedule of rates. For all extra work done on the advice of the Company's Engineer and which is not included in the schedule of rates, deviation order for the same shall be made on the rates as decided by the Company's Engineer.

#### 14.0 RECORD KEEPING:

- (i) A site order book will be maintained at site which will be in the custody of the Engineer-in-charge or his representative and all instructions given to the Contractor will be recorded in the site order book and the same has to be signed by the contractor to comply with the instruction given therein.
- (ii) A register to be maintained at site which will be in the custody of the Engineer-in-charge or his representative to maintain the records of cement the same has to be signed by the contractor.
- (iii) A separate register to be maintained at site by the contractor to record the works executed and a remarks column to be added in this to record the hindrance.
- **15.0** In case of any ambiguity/conflict among various documents the decision of Engineer-in-charge will be final and binding.

#### 16.0 GENERAL HEALTH, SAFETY & ENVIRONMENT (HSE) POINTS:

- 1. It will be solely the Contractor's responsibility to fulfill all the legal formalities with respect to the Health, Safety and Environmental aspects of the entire job (namely; the person employed by him, the equipment, the environment, etc.) under the jurisdiction of the district of that state where it is operating. Ensure that all sub-contractors hired by him comply with the same requirement as the contractor himself and shall be liable for ensuring compliance all HSE laws by the sub or sub-sub-contractors.
- 2. Every person deployed by the contractor in a mine must wear safety gadgets to be provided by the contractor. The Contractor shall provide proper Personnel Protective Equipment as per the hazard identified

PART-III SCC

and risk assessed for the job and conforming to statutory requirement and company PPE schedule. Safety appliances like protective footwear, Safety Helmet and Full Body harness has to be DGMS approved. Necessary supportive document shall have to be submitted as proof. If the Contractor fails to provide the safety items as mentioned above to the working personnel, the Contractor may apply to the Company (OIL) for providing the same. OIL will provide the safety items, if available. But in turn, OIL will recover the actual cost of the items by deducting from Contractor's Bill. However, it will be the Contractor's sole responsibility to ensure that the persons engaged by him in the mines use the proper PPE while at work. All the safety gears mentioned above are to be provided to the working personnel before commencement of the work.

- 3. The Contractor shall prepare written Safe Operating Procedure (SOP) for the work to be carried out, including an assessment of risk, wherever possible and safe methods to deal with it/them. The SOP should clearly state the risk arising to men, machineries & material from the mining operation / operations to be done by the contractor and how it is to be managed.
- 4. The contractor shall provide a copy of the SOP to the person designated by the mine owner who shall be supervising the contractor's work.
- 5. Keep an up to date SOP and provide a copy of changes to a person designated by the Mine Owner /Agent /Manager.
- 6. Contractor has to ensure that all work is carried out in accordance with the Statute and SOP and for the purpose he may deploy adequate qualified and competent personnel for the purpose of carrying out the job in a Contractor 1 Company SCC safe manner. For work of a specified scope/nature, he should develop and provide to the mine owner a site specific code of practice in line.
- 7. All persons deployed by the contractor for working in a mine must undergo Mines Vocational Training, initial medical examination, PME. They should be issued cards stating the name of the contractor and the work and its validity period, indicating status of MVT, IME & PME.
- 8. The contractor shall submit to DGMS returns indicating Name of his firm, Registration number, Name and address of person heading the firm, Nature of work, type of deployment of work persons, Number of work persons deployed, how many work persons hold VT Certificate, how many work persons undergone IME and type of medical coverage given to the work persons.
- 9. The return shall be submitted quarterly (by 10th of April, July, October & January) for contracts of more than one year. However, for contracts of less than one year, returns shall be submitted monthly.
- 10. It will be entirely the responsibility of the Contractor/his Supervisor/representative to ensure strict adherence to all HSE measures and statutory rules during operation in OIL's installations and safety of workers engaged by him. The crew members will not refuse to follow any instruction given by company's Installation Manager / Safety Officer / Engineer / Official / Supervisor/Junior Engineer for safe operation.
- 11. Any compensation arising out of the job carried out by the Contractor whether related to pollution, Safety or Health will be paid by the contractor only.
- 12. Any compensation arising due to accident of the Contractor's personnel while carrying out the job, will be payable by the contractor.
- 13. The contractor shall have to report all incidents including near miss to Installation Manager / departmental representative of the concerned department of OIL.
- 14. The contractor has to keep a register of the persons employed by him/her. The contractor's supervisor shall take and maintain attendance of his men every day for the work, punctually.
- 15. If the company arranges any safety class / training for the working personnel at site (company employee, contractor worker, etc.) the contractor will not have any objection to any such training.
- 16. The health check-up of contractor's personnel is to be done by the contractor in authorized Health Centers as per OIL's requirement & proof of such test(s) is to be submitted to OIL. The frequency of periodic

**PART-III SCC** 

medical examinations should be every five years for the employees below 45 years of age and every three years for employees of 45 years of age and above.

- 17. To arrange daily tool box meeting and regular site safety meetings and maintain records.
- 18. Records of daily attendance, accident report etc. are to be maintained in Form B, E, J (as per Mines Rules 1955) by the contractor.
- 19. A contractor employee must, while at work, take reasonable care for the health and safety of people who are at the employee's place of work and who may be affected by the employee's act or omissions at work.
- 20. A contractor employee must, while at work, cooperate with his or her employer or other persons so far as is necessary to enable compliance with any requirement under the act or the regulations that is imposed in the interest of health, safety and welfare of the employee or any other person.
- 21. Contractor's arrangements for health and safety management shall be consistent with those for the mine owner.
- 22. In case Contractor is found non-compliant of HSE laws as required company will have the right for directing the contractor to take action to comply with the requirements, and for further non-compliance, the contractor will be penalized prevailing relevant Acts/Rules/Regulations.
- 23. When there is a significant risk to health, environment or safety of a person or place arising because of a non-compliance of HSE Measures Company will have the right to direct the contractor to cease work until the non-compliance is corrected.
- 24. The contractor should prevent the frequent change of his contractual employees as far as practicable.
- 25. The contractor should frame a mutually agreed bridging document between OIL & the contractor with roles and responsibilities clearly defined.
- 26. For any HSE matters not specified in the contract document, the contractor will abide the relevant and prevailing Acts/rules/regulations/ pertaining to Health, Safety and Environment.
- **17.0** The Contractor shall deposit the PAN and GST registration number (if applicable, as per Statutory GST Regulations) as and when required by the Company. If the above are not available with the bidder, the bidder must apply for the same after signing of the Contract and submit the same within 45 days of signing the contract (or as and when advised by the Company, after 45 days of signing the contract). Moreover, the statutory guidelines of Goods and Service Tax (GST) shall be adhered to by the bidder
- **18.0** The bidder must provide the following minimum numbers of equipment in operational condition capable of providing uninterrupted services under the contract as and when required.

#### LIST OF MATERIALS & EQUIPMENTS TO BE SUPPLIED BY CONTRACTOR:

<ul> <li>Concrete mixer machine -</li> </ul>	02 Nos.
Vibrator -	O4 Nos.
<ul> <li>Welding and cutting set -</li> </ul>	01 No
Hydraulic Excavator -	01 No

19.0 A Hindrance Register shall be maintained in the enclosed Format to record all hindrances encountered during execution of works against the contract. The items of work affected due to any hindrance shall be clearly recorded in the Hindrance Register and the Engineer-in-charge of the Company as well as the site representative of the Contractor will sign on the register against the recorded hindrance. In case of encountering multiple hindrances simultaneously over a period of time affecting the same item or different items, the net period of hindrance will be worked out considering the overlapping period.

**PART-III SCC** 

- 20.0 Company reserves the right to initiate actions against the bidder / contractor during processing of tender and / or during continuation of the contract as per OIL's Banning Policy dated  $6^{th}$  Jan 2017 available at OIL's website.
- **21.0** Defect liability period shall be 6 months beyond the date of completion of works as certified by Engineer-In-Charge. During defect liability period, all corrective works shall be carried out entirely at Contractor's own expenses. If such corrective works are not carried out within a reasonable time, the Company, at its discretion, may have such remedial works carried out by other agencies and charge the cost thereof to the Contractor. This amount shall be deducted from contractor's bill/ Retention money/ Performance security.

E- TENDER NO.: CDC9676P19 PART-IV SCPME

# OIL INDIA LIMITED (A Govt. of India Enterprise) Contracts, Duliajan WORKS CONTRACT

Schedule of company's Plants, Materials and Equipments

- A. SCHEDULE OF MATERIALS AVAILABLE AT THE COMPANY'S STORES/STOCK PILES for permanent incorporation in works and
- B. SCHEDULE OF COMPANY'S PLANTS AND EQUIPMENTS for use in the execution of work.
- 1) MATERIALS: Cement (Will be issued from Company's godown at Duliajan or other go-downs)
- 2) PLANTS AND EQUIPMENT: Nil

#### NOTE:

- 1. All empty cement bags must be returned to Materials Godown Duliajan failing which Rs 8/-(Rupees Eight only) per bag for empty cement bags will be recovered from the Contractor's bill.
- 2. The Contractor is to arrange transport of the above materials to site of work and for safety thereof for which no extra payment will be made.
- 3. If the materials listed above are not available suitable substitute will be provided by the Company and Contractor shall incorporate the same in the works without extra cost.
- 4. Containers must be returned to Company in good condition.
- 5. Plants and equipment if issued to Contractor must be under proper watch so that no part is pilfered. These must be handled only by Company's operators. Contractor shall be responsible for any loss or damage to these plants and equipment while these are under his/their custody.
- 6. Materials issued to Contractor must be under proper watch & ward so that no part is pilfered. If any pilferation takes place the matter will be referred to appropriate Govt. authorities for legal action as well as realization of the materials issued.
- 7. Cement issued to Contractor by the Company is meant only for the specific Company work relating to the Contract. However, if any quantity of Cement is left over from the quantities issued for any reason whatsoever, on the completion / cancellation / termination of the Contract the same shall have to be returned to the Company in full within one week of completion/cancellation of the work failing which the matter will be referred to appropriate Govt. authorities for legal action as well as realization of the Cement.
- 8. All other materials issue to the Contractor by the Company if subsequently found to be in excess of the actual requirement will have to be returned by the Contractor within two weeks of completion of the work failing which the cost of all such materials will be recovered from the Contactor at double the value of materials without any reference to him.

To, CGM-CONTRACTS OIL INDIA LIMITED DULIAJAN-786602

#### **SUB: SAFETY MEASURES**

<u>DESCRIPTION OF WORK/SERVICE</u>: Construction of maintenance godown at Well-50 including supply of all materials except cement.

Sir.

We hereby confirm that we have fully understood the safety measures to be adopted during execution of the above contract and that the same have been explained to us by the concerned authorities. We also give the following assurances.

- a) Only experienced and competent persons shall be engaged by us for carrying out work under the said contract.
- b) The names of the authorized persons who would be supervising the jobs on day to day basis from our end are the following:

i)	)	 
ii)		
iii)		

The above personnel are fully familiar with the nature of jobs assigned and safety precautions required.

- c) Due notice would be given for any change of personnel under item(b) above.
- d) We hereby accept the responsibility for the safety of all the personnel engaged by us and for the safety of the Company's personnel and property involved during the course of our working under this contract. We would ensure that all the provisions under the Oil Mines Regulations, 2017 and other safety rules related to execution of our work would be strictly followed by our personnel. Any violation pointed out by the Company's Engineers would be rectified forthwith or the work suspended till such time the rectification is completed by us and all expenditure towards this would be on our account.
- e) We confirm that all persons engaged by us would be provided with the necessary Safety Gears at our cost.
- f) All losses caused due to inadequate safety measures or lack of supervision on our part would be fully compensated by us and the Company will not be responsible for any lapses on our part in this regard.
- g) We shall abide by the HSE (Health Safety & Environment) points mentioned in SCC.

(Seal)	Yours Faithfully
Date	M/s

#### PART-VI INTEGRITY PACT

#### **INTEGRITY PACT**

Between

Oil India Limited (OIL) hereinafter referred to as "The Principal"

And

(Name of the bidder).....hereinafter referred to as "The Bidder/Contractor"

#### Preamble:

The Principal intends to award, under laid down organizational procedures, contract/s for **Construction of maintenance godown at Well-50 including supply of all materials except cement**. The Principal values full compliance with all relevant laws and regulations, and the principles of economic use of resources, and of fairness and transparency in its relations with its Bidder/s and Contractor/s.

In order to achieve these goals, the Principal cooperates with the renowned international Non-Governmental Organisation "Transparency International" (TI). Following TI's national and international experience, the Principal will appoint an external independent Monitor who will monitor the tender process and the execution of the contract for compliance with the principles mentioned above.

#### Section 1 - Commitments of the Principal

- (1) The Principal commits itself to take all measures necessary to prevent Corruption and to observe the following principles:-
  - I. No employee of the Principal, personally or through family members, will in connection with the tender for, or the execution of a contract, demand, take a promise for or accept, for him/herself or third person, any material or immaterial benefit which he/she is not legally entitled to.
  - II. The Principal will, during the tender process treat all Bidders with equity and reason. The Principal will in particular, before and during the tender process, provide to all Bidders the same information and will not provide to any Bidder confidential/ additional information through which the Bidder could obtain an advantage in relation to the tender process or the contract execution.
  - III. The Principal will exclude from the process all known prejudiced persons.
- (2) If the Principal obtains information on the conduct of any of its employees which is a criminal offence under the relevant Anti-Corruption Laws of India, or if there be a substantive suspicion in this regard, the Principal will inform its Vigilance Office and in addition can initiate disciplinary actions.

#### Section 2 - Commitments of the Bidder/Contractor

- (1) The Bidder/Contractor commits itself to take all measures necessary to prevent corruption. He commits himself to observe the following principles during his participation in the tender process and during the contract execution.
  - I. The Bidder/Contractor will not, directly or through any other person or firm, offer, promise or give to any of the Principal's employees involved in the tender process or the execution of the contract or to any third person any material or immaterial benefit which he/she is not legally entitled to, in order to obtain in exchange any advantage of any kind whatsoever during the tender process or during the execution of the contract.
- II. The Bidder/Contractor will not enter with other Bidders into any undisclosed agreement or understanding, whether formal or informal. This applies in particular to prices, specifications, certifications, subsidiary contracts, submission or non-submission of bids or any other actions to restrict competitiveness or to introduce cartelisation in the bidding process.
- III. The Bidder/Contractor will not commit any offence under the relevant anticorruption Laws of India; further the Bidder/Contractor will not use improperly, for purposes of competition or personal gain, or pass on to others, any information or document provided by the Principal as part of the business

Contractor 1 Company

#### PART-VI INTEGRITY PACT

relationship, regarding plans, technical proposals and business details, including information contained or transmitted electronically.

- IV. The Bidder/Contractor will, when presenting his bid, disclose any and all payments he has made, is committed to or intends to make to agents, brokers or any other intermediaries in connection with the award of the contract.
- (2) The Bidder/Contractor will not instigate third persons to commit offences outlined above or be an accessory to such offences.
- (3) The Bidder/Contractor signing Integrity Pact shall not approach the Courts while representing the matters to IEMs and he/she will await their decision in the matter.

#### Section 3 - Disqualification from tender process and exclusion from future Contracts

If the Bidder, before contract award has committed a transgression through a violation of Section 2 or in any other form such as to put his reliability or risibility as Bidder into question, the Principal is entitled to disqualify the Bidder from the tender process or to terminate the contract, if already signed, for such reason.

- 1. If the Bidder/Contractor has committed a transgression through a violation of Section 2 such as to put his reliability or credibility into question, the Principal is entitled also to exclude the Bidder/Contractor from future contract award processes. The imposition and duration of the exclusion will be determined by the severity of the transgression. The severity will be determined by the circumstances of the case, in particular the number of transgressions, the position of the transgressions within the company hierarchy of the Bidder and the amount of the damage. The exclusion will be imposed for a minimum of 6 months and maximum of 3 years.
- 2. The Bidder accepts and undertakes to respect and uphold the Principal's Absolute right to resort to and impose such exclusion and further accepts and undertakes not to challenge or question such exclusion on any ground, including the lack of any hearing before the decision to resort to such exclusion is taken. This undertaking is given freely and after obtaining independent legal advice.
- 3. If the Bidder/Contractor can prove that he has restored/recouped the Damage caused by him and has installed a suitable corruption prevention system, the Principal may revoke the exclusion prematurely.
- 4. A transgression is considered to have occurred if in light of available evidence no reasonable doubt is possible.
- 5. Integrity Pact, in respect of a particular contract, shall be operative from the date Integrity Pact is signed by both the parties till the final completion of the contract or as mentioned in Section 9-Pact Duration whichever is later. Any violation of the same would entail disqualification of the bidders and exclusion from future business dealings.

#### Section 4 - Compensation for Damages

- 1. If the Principal has disqualified the Bidder from the tender process prior to the award according to Section 3, the Principal is entitled to demand and recover from the Bidder liquidated damages equivalent to Earnest Money Deposit / Bid Security.
- 2. If the Principal has terminated the contract according to Section 3, or if the Principal is entitled to terminate the contract according to section 3, the Principal shall be entitled to demand and recover from the Contractor liquidated damages equivalent to Security Deposit / Performance Bank Guarantee.
- 3. The bidder agrees and undertakes to pay the said amounts without protest or demur subject only to condition that if the Bidder/Contractor can prove and establish that the exclusion of the Bidder from the tender process or the termination of the contract after the contract award has caused no damage

Contractor 2 Company

#### PART-VI INTEGRITY PACT

or less damage than the amount or the liquidated damages, the Bidder/Contractor shall compensate the Principal only to the extent of the damage in the amount proved.

#### Section 5 - Previous transgression

- 1. The Bidder declares that no previous transgression occurred in the last 3 years with any other Company in any country conforming to the TI approach—or with any other Public Sector Enterprise in India that could justify his exclusion from the tender process.
- 2. If the Bidder makes incorrect statement on this subject, he can be disqualified from the tender process or the contract, if already awarded, can be terminated for such reason.

#### Section 6 - Equal treatment of all Bidders/Contractor/Subcontractors

- 1. The Principal will enter into Pacts on identical terms with all bidders and contractors.
- 2. The Bidder / Contractor undertake(s) to procure from all subcontractors a commitment in conformity with this Integrity Pact. The Bidder/Contractor shall be responsible for any violation(s) of the provisions laid down in this agreement/Pact by any of its sub-contractors/sub-vendors.
- 3. The Principal will disqualify from the tender process all bidders who do not sign this Pact or violate its provisions.

# Section 7 - Criminal charges against violating Bidders/Contractors/Subcontractors

If the Principal obtains knowledge of conduct of a Bidder, Contractor or Subcontractor, or of an employee or a representative or an associate of a Bidder, Contractor or Subcontractor, which constitutes corruption, or if the Principal has substantive suspicion in this regard, the Principal will inform the Vigilance Office.

# Section 8 - External Independent Monitor/Monitors (three in number depending on the size of the contract) (to be decided by the Chairperson of the Principal)

- 1. The Principal appoints competent and credible external independent Monitor for this Pact. The task of the Monitor is to review independently and objectively, whether and to what extent the parties comply with the obligations under this agreement.
- 2. The Monitor is not subject to instructions by the representatives of the parties and performs his functions neutrally and independently. He reports to the Chairperson of the Board of the Principal.
- 3. The Contractor accepts that the Monitor has the right to access without restriction to all Project documentation of the Principal including that provided by the Contractor. The Contractor will also grant the Monitor, upon his request and demonstration of a valid interest, unrestricted and unconditional access to his project documentation. The same is applicable to Subcontractors. The Monitor is under contractual obligation to treat the information and documents of the Bidder/Contractor/Subcontractor with confidentiality.
- 4. The Principal will provide to the Monitor sufficient information about all meetings among the parties related to the Project provided such meetings could have an impact on the contractual relations between the Principal and the Contractor. The parties offer to the Monitor the option to participate in such meetings.
- 5. As soon as the Monitor notices, or believes to notice, a violation of this agreement, he will so inform the Management of the Principal and request the Management to discontinue or heal the violation, or to take other relevant action. The monitor can in this regard submit non-binding recommendations. Beyond this, the Monitor has no right to demand from the parties that they act in a specific manner, refrain from action or tolerate action. However, the Independent External Monitor shall give an opportunity to the bidder / contractor to present its case before making its recommendations to the Principal.

Contractor 3 Company

#### PART-VI INTEGRITY PACT

- 6. The Monitor will submit a written report to the Chairperson of the Board of the Principal within 8 to 10 weeks from the date of reference or intimation to him by the 'Principal' and, should the occasion arise, submit proposals for correcting problematic situations.
- 7. If the Monitor has reported to the Chairperson of the Board a substantiated suspicion of an offence under relevant Anti-Corruption Laws of India, and the Chairperson has not, within reasonable time, taken visible action to proceed against such offence or reported it to the Vigilance Office, the Monitor may also transmit this information directly to the Central Vigilance Commissioner, Government of India.
- 8. The word 'Monitor' would include both singular and plural.

#### Section 9 - Pact Duration

This Pact begins when both parties have legally signed it. It expires for the Contractor 12 months after the last payment under the respective contract, and for all other Bidders 6 months after the contract has been awarded.

If any claim is made/ lodged during this time, the same shall be binding and continue to be valid despite the lapse of this pact as specified above, unless it is discharged/determined by Chairperson of the Principal.

#### Section 10 - Other provisions

- 1. This agreement is subject to Indian Law. Place of performance and jurisdiction is the Registered Office of the Principal, i.e. New Delhi. The Arbitration clause provided in the main tender document / contract shall not be applicable for any issue / dispute arising under Integrity Pact.
- 2. Changes and supplements as well as termination notices need to be made in writing. Side agreements have not been made.
- 3. If the Contractor is a partnership or a consortium, this agreement must be, signed by all partners or consortium members.
- 4. Should one or several provisions of this agreement turn out to be invalid, the remainder of this agreement remains valid. In this case, the parties will strive to come to an agreement to their original intensions.

For the Principal	for the Bidder/Contractor
Place: Duliajan.	Witness 1:
Date:	Witness 2:

Contractor 4 Company

	TENDER NO. : CDC9676P19: Construction of maintenance godown at Well-50 including st	upply of all mater	ials excep	t cemen	t	
	NAME OF THE FIRM:					
	VENDOR CODE:					
	PRICE BIDDING FORMAT					OIL's
SI. No.	Description of Work	Qty	UOM	Curr.	Rate	Total
	Group A SEC-A	Α			D	X=A*D
10	Jungle cutting and clearing including removal of cut materials upto 100m from site and disposing as directed (all jungle to be cut at ground level). For light jungle including plants and trees upto 300mm girth. (OIL SOR-41.1.5)	1600.00	M2	INR	1.72	2752.00
20	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means over areas (exceeding 30cm in depth. 1.5m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m, disposed earth to be levelled and neatly dressed. All kinds of soil.( Rate as per CPWD 2016, Item No-2.6.1)	185.00	M3	INR	122.56	22673.60
30	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift upto 1.5 m.( Rate as per CPWD 2016, Item No-2.25)	185.00	М3	INR	124.48	23028.80
40	Supplying and filling in plinth with sand under floors including, watering, ramming consolidating and dressing complete(cost of sand will be paid separately). (Rate as per CPWD-2016, Item No- 2.27)	162	М3	INR	1017.07	164765.34
50	Surface dressing of the ground including removing vegetation and in-equalities not exceeding 15 cm deep and disposal of rubbish, lead upto 50 m and lift upto 1.5 m.All kinds of soil (Rate as per CPWD 2016, Item No-2.28.1)	504.00	M2	INR	13.68	6894.72
60	Collecting / excavating sand, soil, silt, ordinary earth from any source, load into lorries, transport it to distant place of work including procuring earth and laying in layer of 150mm thickness and compacting, profile properly made for taking measurement, including all measurable lead upto 30m and lift as required. (The contractor shall be responsible for all formalities of supply of earth such as purchase of land including royalties, monopoly / other statutory taxes as required from any distance.) (OIL SOR-41.7.2)	171	М3	INR	359.79	61524.09
70	Supplying & aying in position cement concrete of specified grade excluding the cost of centring and shuttering - All work upto plinth level: 1:3:6 ( 1 Cement: 3 coarse sand : 6 graded stone aggregate 20 mm nominal size)(Rate as per CPWD 2016, Item No- 4.1.5)	54.00	M3	INR	3936.09	212548.86
80	Supplying and Providing and laying damp-proof course 40mm thick with cement concrete 1:2:4 (1 cement:2 coarse sand(zone -III):4 graded stone aggregate 12.5 mm nominal size. (Rate as per CPWD 2016, Item No- 4.10)	12.00	M2	INR	235.29	2823.48
90	Supplying & Providing & Laying in position specified grade of reinforced cement concrete excluding the cost of centring, shuttering, finishing and reinforcement - All work upto plinth level : 1:1.5:3 (1 cement: 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size).(Rate as per CPWD 2016, Item No- 5:1.2).	62.00	M3	INR	3879.76	240545.12
100	Supplying & Providing cncrete work in walls (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts etc. upto floor five level excluding cost of centring, shuttering, finishing and reinforcement: 1:1.5:3 (1 cement: 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size) (Rate as per CPWD 2016, Item No- 5.2.2)	68.00	M3	INR	4785.44	325409.92
110	Cement mortar 1:4 (1 cement : 4 coarse sand) (Rate as per CPWD 2016, Item No- 6.1.1)		М3	INR	7052.93	282117.20
120	Supplying & providing Half brick masonry with F.P.S. bricks of class designation 75 in superstructure above plinth		M2	INR	927.14	463570.00
130	Supplying and Extra for placing in position 2 Nos. 6mm dia. M.S. bars at every third course of half brick masonry(with F.P.S. Bricks) (Rate as per CPWD 2016, Item No- 6.15)	550.00	M2	INR	54.01	29705.50
140	Supplying & providing 12mm cement plaster of mix:1:4 (1 cement : 4 fine sand) (Rate as per CPWD 2016, Item No- 13.1.1)	515.00	M2	INR	142.40	73336.00
150	Suppling & providing 15mm cement plaster on the rough side of single or half brick wall of mix:1:4 (1 cement : 4 fine sand) (Rate as per CPWD 2016, Item No- 13.2.1)	1490.00	M2	INR	163.61	243778.90
160	Suppling & providing 6mm cement plaster of mix:1:3 (1 cement : 3 fine sand) (Rate as per CPWD 2016, Item No- 13.16.1)	515.00	M2	INR	121.93	62793.95
170	Supplying & providing Cement plaster skirting (up to 30cm height) with cement mortar 1:3 (1 cement : 3 coarse sand) finished with a floating coat of neat cement.18mm thick. (Rate as per CPWD 2016, Item No- 11.6.1)	25.00	M2	INR	347.89	8697.25
180	Supplying & centring and shuttering including strutting, propping etc. and removal of form for : Foundations, footings, bases of columns, etc. for mass concrete. (Rate as per CPWD 2016, Item No- 5.9.1)	170.00	M2	INR	196.52	33408.40
190	Supplying & Centring and shuttering including strutting, propping etc. and removal of form for: Suspended floors, roofs, landings, balconies and access platform.(Rate as per CPWD 2016, Item No- 5.9.3)	180.00	M2	INR	441.28	79430.40
200	Supplying, Centring and shuttering including strutting, propping etc. and remova of form for: Lintels, beams, plinth beams, girders, bressumers and cantilevers. (Rate as per CPWD 2016, Item No- 5.9.5)	500	M2	INR	355.08	177540.00
210	Supplying,Centring and shuttering including strutting, propping etc. and removal of form for: Columns, Pillars, Piers, Abutments, Posts and Struts. (Rate as per CPWD 2016, Item No- 5.9.6)	221.00	M2	INR	483.68	106893.28
220	Supplying, Centring and shuttering including strutting, propping etc and removal or form tor: Stairs, (excluding landings) except spiral-staircases. (Rate as per CPWD 2016, Item No- 5.9.7)	23.00	M2	INR	428.87	9864.01
230	Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more (Refer CPWD SOR 2016, Item No. 5.22.6)	16115.00	KG	INR	62.25	1003158.75
240	Supplying and Steel work in built up tubular (round, square or rectangular hollow tubes etc.)including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer, including welding and bolted with special shaped washers etc. complete. Hot finished seamless type tubes. (Rate as per CPWD 2016, Item No-10.16.2)	7200.00	KG	INR	90.21	649512.00
250	Providing and fixing M.S. fan clamp type I or II of 16 mm dia M.S. bar, bent to shape with hooked ends in R.C.C. slabs or beams during laying, including painting the exposed portion of loop, all as per standard design complete.	50	EA	INR	110.82	5541.00
260	Supplying and Steel work welded in built up sections/ framed work, including cutting, hoisting,fixing in position and applying a priming coat of approveed steel primer using structural steel as required. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works. (Rate as per CPWD 2016, Item No- 10.25.2)	4500.00	KG	INR	88.02	396090.00

270	Supplying & Fixing on wall face unplasticised - PVC moulded fittings/ accessories for unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansionBend 87.5*-110 mm Bend. (Rate as per CPWD 2016, Item No- 12.42.5.2)	60.00	EA	INR	107.45	6447.00
280	Supplying & Installation of precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-Charge) 0.50mm +/- 5% total coated thickness (TCT). Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat' 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches while transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-Charge. The sheet shall be fixed using self drilling / self tapping screws of size (5.5x 55mm) with EPDM seal or with polymer coated J or L hooks, bolts and nuts 8mm diameter with bitumen and C.I. limpet washers or with G.I. limpet washers filled with white lead complete upto any pitch in horizontal / vertical or curved surfaces excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required. (Rate as per CPWD 2016, Item No-12.50)	478.00	M2	INR	529.12	252919.36
290	Supplying & Fixing precoated galvanised steel sheet roofing accessories 0.50 mm + 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws or with polymer coated J or L hooks, bolts and nuts and or G.I. seam bolts and nuts, G.I. plain and bitumen washers complete: Ridges plain (500 - 600mm). (Rate as per CPWD 2016, Item No- 12.51.1)	40.00	М	INR	347.08	13883.20
300	Supplying & Fixing precoated galvanised steel sheet roofing accessories 0.50 mm + 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws or with polymer coated J or L hooks, bolts and nuts and or G.I. seam bolts and nuts, G.I. plain and bitumen washers complete:  Barge board (Upto 300 mm). (Rate as per CPWD 2016, Item No- 12.51.4)	100.00	М	INR	307.33	30733.00
310	:Supplying & Fixing precoated galvanised steel sheet roofing accessories 0.50 mm + 5% total coated thickness (TCT), Zinc coating 120gsm as per IS: 277 in 240mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns using self drilling/ self tapping screws or with polymer coated J or L hooks, bolts and nuts and or G.I. seam bolts and nuts, G.I. plain and bitumen washers complete: Gutter .(600 mm over all girth) (Rate as per CPWD 2016, Item No- 12.51.6)	78.00	М	INR	824.31	64296.18
320	Supplying & Fixing chicken wire netting with timber beads on timber frame (or with steel flat on steel frame). (Rate as per OIL SOR 2016, Item No- 41.78.1)	76.00	M2	INR	598.60	45493.60
330	Supplying & Fixing in position collapsible steel shutters with vertical channels 20x10x2mm and braced with flat iron diagonals 20x5mm size with top and bottom rail of T-iron 40x40x6mm with 40mm dia, steel pulleys complete with bolts, nuts, locking arrangement, stoppers, handles, including applying a priming coat of approved steel primer.(Rate as per CPWD 2016, Item No- 10.3)	12.00	M2	INR	5679.57	68154.84
340	Supplying & Fixing 1mm thick M.S. sheet door with frame of 40x40x6mm angle iron and 3mm M.S. gusset plates		2831.29	5662.58		
350	Supplying & providing Wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position :Kiln seasoned and chemically treated Hollock wood. (Rate as per CPWD 2016, Item No- 9.1.3)	4.50	М3	INR	54644.57	245900.57
360	Supplying and Providing and fixing frame for false ceiling in true horizontal level, suspended on interlocking metal grid of hot dipped galvanized steel sections (galvanized @ 120 grams/ sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x28 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick (minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size 24x25 mm made of 0.30 mm thick (minimum) sheet to be interlocked at middle of the 1200x600 mm panel to form grids of 600x600 mm and wall angle of size 24x24x0.3 mm and laying false ceiling tiles of approved texture in the grid including, required cutting/making, opening for services like diffusers, grills, light fittings,fixtures, smoke detectors etc. Main "T" runners to be suspended from ceiling using GI slotted cleats of size 27 x 37 x 25 x1.6 mm fixed to ceiling with 12.5 mm dia and 50 mm long dash fasteners, 4 mm GI adjustable rods with galvanized butterfly level clips of size 85 x 30 x 0.8 mm spaced at 1200 mm center to center along main T, bottom exposed width of 24 mm of all T-sections shall be prepainted with polyester paint, all complete for all heights as per specifications, rawings and as directed by Engineer-in-charge. (Rate as per CPWD 2016, Item No- 12.58)	323.00	M2	INR	443.89	143376.47
370	Providing and fixing multi-purpose cement board(High pressure steam cured) with suitalble screws for cement particle board in ceiling etc complete (framework to be paid separtely). 6 mm thick cement fibre board as per IS: 14862.(Rate as per CPWD 2016, Item No- 12.26.1)	323.00	M2	INR	530.34	171299.82
380	Supplying & providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25mm to 40mm thick: Particle Board 12mm thick Pre-laminated particle board with decorative lamination on both sides, Grade I, Type II, IS :12823 marked.(Rate as per CPWD 2016, Item No- 9.7.5.4)	40	M2	INR	1408.23	56329.20
390	Supplying & Fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25mm to 40mm thick: 5.5 mm thick float glass pane thick Pre-laminated particle board with decorative lamination on both sides, Grade I, Type II, IS:12823 marked.(Rate as per CPWD 2016, Item No- 9.7.7.1)	24.00	M2	INR	1197.60	28742.40
400	P/F ISI marked flush door shutter - non-decorative 30mm thick i/c stainless steel butt hinges: ( Rate as per CPWD 2016, Item No- 9.21.2)	2.00	M2	INR	1578.54	3157.08
410	Supplying & Fixing bright finished brass tower bolts (barrel type) with necessary screws etc. complete: 250x10mm. (Rate as per CPWD 2016, Item No- 9.74.1)	6.00	EA	INR	299.04	1794.24
420	Supplying & Fixing chromium plated brass handles with necessary screws etc. complete: 125mm.(Rate as per CPWD 2016, Item No- 9.92.1)	4.00	EA	INR	202.15	808.60
430	Supplying & Fixing rolling shutters of approved make, made of required size M.S. laths interlocked together through their entire length and jointed together at the end by end locks mounted on specially designed pipe shaft with brackets, side guides and arrangements for inside and outside locking with push and pull operation complete including the cost of providing and fixing necessary 27.5cm long wire springs grade No.2 and M.S. top cover of required thickness for rolling shutters. (Rate as per CPWD 2016, Item No- 10.6.1)	16.00	M2	INR	2259.55	36152.80
440	Supplying & Fixing glass panes with putty and glazing clips in steel doors, windows,clerestory windows all complete with 4.0 mm thick glass panes. (Rate as per CPWD 2016, Item No- 10.30.1)	21.00	M2	INR	666.69	14000.49

	Supplying & Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade: New work (Two or more coats applied @ 1.43 ltr/10 sqm over and including base coat of water proofing cement paint applied @ 2.20 kg/10 sqm). (Rate as per CPWD 2016, Item No- 13.47.1)	615	M2	INR	98.14	60356.10
	Supplying & Painting with synthetic enamel paint of approved brand and manufacture to give an even shade:Two or more coats on new work. (Rate as per CPWD 2016, Item No- 13.61.1)	780.00	M2	INR	80.26	62602.80
	Supplying & Application of white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. (Rate as per CPWD 2016, Item No- 13.8)	750.00	M2	INR	90.35	67762.50
480	Supplying & Wall painting with premium acrylic emulsion paint of interior grade, having VOC (VolatileOrganic Compound) content less than 50 grams/ litre. of approved brand and manufacture, including applying additional coats wherever required to achieve even shade and colour: Two Coats.(Rate as per CPWD 2016, Item No-13.83.2)	750.00	M2	INR	73.20	54900.00
490	Services with welding and cutting set in carrying out miscellaneous repairs / new construction involving steel work (services of one welder and one jugall per set) to be supplied by the contractor. (New welding set inclusive fuel etc. to be supplied by the contractor).(Rate as per OIL SOR 2016, Item No- 41.5.1)	10	PD8	INR	1812.14	18121.40
500	Supplying and construction of 40mm thick marble chips flooring rubbed and polished to granolithic finish, under layer 34mm thick cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 12.5mm nominal size) and top layer 6mm thick with white, black, chocolate, grey, yellow or green marble chips of sizes from 1mm to 4mm nominal size laid in cement marble powder mix 3:1 (3 cement : 1 marble powder) by weight in proportion of 4:7 (4 cement marble powder mix : 7 marble chips) by volume including cement slurry etc. complete:Dark shade pigment with ordinary cement. (Rate as per CPWD 2016, Item No- 11.9.1)	330.00	M2	INR	549.19	181232.70
510	Supplying and Hydraulic Excavator (3D) with driver and fuel.(Rate as per OIL SOR 2016, Item No- 0020)	3.00	DAY	INR	7984.99	23954.97
520	Supplying and diluting and injecting chemical emulsion for POST CONSTRUCTIONAL antitermite treatment (excluding the cost of chemical emulsion). Along the external wall below concrete or masonry apron using chemical emulsion @ 2.25 litres per linear metre including drilling and plugging holes etc.: With Chlorpyriphos/Lindane E.C. 20% with 1% concentration. (Rate as per CPWD 2016, Item No- 2.35.2.1)	105.00	М	INR	23.64	2482.20
			•		Total =	₹ 63,48,966.67

\*\*\*Bidder's Quoted offer is

(percentage) above the Company's Internal Estimated Cost

\*\*\* The bidders should offer their percentage in figures upto two decimal places only.
\*\*\* If bidder's quoted offer is at par with the Company's Internal Estimated Cost, select "at par" from the above dropdown list.
\*\*\* If bidder's quoted offer is above Company's Internal Estimated Cost, fill the above blank cell with quoted percentage (upto 10% above on Company's I.E. cost).

#### Please note that :-

The bidder should not quote their rates for individual items. They should only fill up the percentage in the blank cell as advised above. The bids with overall rates quoted below at par (below 0.00 %) and above (+10%) of Company's internal estimated Cost will be rejected outright. 1.0

- 2.0 The Rates of Company's Internal Estimate are exclusive of P.F. & GST. The Bidders must quote their rates excluding P.F. & GST.

  3.0 The Wages Component for the Work is (Civil Part): 22.95 %

  4.0 The Contractor must quote considering the prevailing minimum labour wage rate for each day of work.

- 5.0 Offers not furnished in the above format as per instruction given shall be summarily rejected.

### (To be typed on the letter head of the bidder)

To CGM-CONTRACTS OIL INDIA LIMITED DULIAJAN

Dear Sirs,

#### Sub: UNDERTAKING/DECLARATION BY THE BIDDER (S) IN RESPECT OF TENDER NO. CDC\_\_\_\_\_\_

(To be submitted by the Bidders who are not covered under EPF&MP Act, 1952)

- That our Firm/Company shall be responsible to comply with all the applicable labour laws in respect of the present Contract.
- That we are fully conversant with the applicable laws and confirm that our Firm/Company is not covered under the Employees Provident Funds and Misc. Provisions Act, 1952 and applicable Rules there under, and therefore I we have not obtained any registration or Provident Fund Code under the Act.
- That if, during the period of the present Contract, we/our Firm /Company comes within the coverage of the aforesaid Acts or any other statutes; we shall comply with the same and submit the necessary documents to OIL. We further confirm that we will indemnify OIL towards any future statutory compliances/claims raised from any corner including statutory authorities against the Labour engaged by our Firm/Company in the Contract.
- That in the event of any contravention towards the applicable laws found on our part in respect of the present Contract, we undertake to indemnify OIL and deposit the claims, if any.
- That we shall fulfill all the obligations arising from under the labour laws in force from time to time and keep OIL indemnified against any loss/liability arising out of failure of our avoiding the laws.

We, further agree and undertake that in case of any violation of the above undertaking, OIL shall be at liberty to take appropriate action against us in terms of the Tender including but not limited to termination of contract and debarment from future business with OIL.

I/We declare that the information given above is true and any misstatement or misrepresentation or suppression of facts in connection with the above undertaking may entail rejection of the bid and cancellation of contract, if awarded.

Yours faithfully,	
1. Authorized Signatory (BIDDER)	
Place:-	
Date:-	

### CERTIFICATE OF ANNUAL TURNOVER & NET WORTH

TO BE ISSUED BY PRACTISING	G <b>CHARTERED ACCOUNT</b> HEAD	ANTS' FIRM ON THEIR LETTER
<u>T</u>	O WHOM IT MAY CONCE	<u>RN</u>
	of the Bidder) for the last thre	From the audited financial statements of the (3) completed accounting years upto
YEAR	TURN OVER	NET WORTH
	In INR (Rs.)	In INR (Rs.)
e:		

Signature

#### FORM OF BID SECURITY (BANK GUARANTEE FORMAT)

CONTRAC	INDIA LIMITED, CTS DEPARTMENT, IN, ASSAM, INDIA, PIN-786602
offer Date INDIA LINKNOW AL the Comp	(hereinafter called "the Bidder") has submitted their ted for the provision of certain services (hereinafter called "the Bid") against OIL MITED, Duliajan, Assam, India (hereinafter called the Company's) Tender No LL MEN BY these presents that we (Name of Bank) of (Name of Country) having our registered office at (hereinafter called "Bank") are bound unto pany in the sum of (* ) for which payment well and truly to be made to Company, binds itself, its successors and assignees by these presents.
SEALED v	with the said Bank this day of 20
1. I 2. 7 3. 7 4. 7	IDITIONS of these obligations are:  If the Bidder withdraws their Bid within its original/extended validity; or  The Bidder modifies/revises their bid suomoto; or  The Bidder does not accept the contract; or  The Bidder does not furnish Performance Security Deposit within the stipulated time as per tender/contract; or  If it is established that the Bidder has submitted fraudulent documents or has indulged into corrupt and fraudulent practice.
way of le demand C	rtake to pay to Company up to the above amount upon receipt of its first written demand (by etter/fax/cable), without Company having to substantiate its demand provided that in its Company will note that the amount claimed by it is due to it owing to the occurrence of any of tions, specifying the occurred condition or conditions.
	rantee will remain in force up to and including the date (**/) and any demand in respect hould reach the Bank not later than the above date.
The detail	ls of the Issuing Bank and Controlling Bank are as under:
A. Iss	suing Bank:
BA	ANK FAX NO:
BA	ANK EMAIL ID:
BA	ANK TELEPHONE NO.:
IFS	SC CODE OF THE BANK:
B. Co	ontrolling Office:
	ddress of the Controlling Office of the BG issuing Bank: ame of the Contact Person at the Controlling Office with Mobile No. and e-mail address:
SIGNATUI	RE AND SEAL OF THE GUARANTORS
Name of E	Bank & Address

#### Page No. 2

Witness
Address
(Signature, Name and Address)
Date:
Place:

\* The Bidder should insert the amount of the guarantee in words and figures.

\*\* Date of expiry of Bank Guarantee should be minimum 30 days after the end of the validity period of the Bid/as specified in the Tender.

#### Note:

The Bank Guarantee issuing bank branch shall ensure the following:

- a) The Bank Guarantee issued by the bank shall be routed through SFMS platform as per the following details:
  - i) "MT 760/MT 760 COV" for issuance of bank guarantee.
  - ii) "MT 760/MT 767 COV" for amendment of bank guarantee.

The above message/intimation shall be sent through SFMS(indicating the Tender Number) by the BG issuing bank branch to Axis Bank, Duliajan Branch, IFS Code: UTIB0001129, Branch address: AXIS Bank Ltd., Duliajan Branch, Daily Bazar, Jyotinagar, Duliajan, District Dibrugarh, PIN: 786602.

b) Bank Guarantee issued by a Scheduled Bank in India at the request of some other Non-Scheduled Bank of India shall not be acceptable.

#### FORM OF PERFORMANCE BANK GUARANTEE

(TO BE FURNISHED BY THE CONTRACTOR IN CASE OF SUBMITTING PERFORMANCE SECURITY IN THE FORM OF BANK GUARANTEE AFTER ISSUE OF LOA)

M/s OIL INDIA LIMITED, CONTRACTS DEPARTMENT DULIAJAN, ASSAM, INDIA, PIN-786602
WHEREAS (Name and address of Contractor) (hereinafter calle "Contractor") had undertaken, in pursuance of Contract No to execute (Brief Description of the Work) (hereinafter called "the Contract").
AND WHEREAS it has been stipulated by you in the said Contract that the Contractor shall furnish you with a Bank Guarantee as security for compliance with Contractor's obligations in accordance with the Contract.
AND WHEREAS we have agreed to give the Contractor such a Bank Guarantee; NOW THEREFORE we hereby affirm that we are Guarantors on behalf of the Contractor, up to a total of (Amount of Guarantee in figures) (in words), such amount being payable in the types an proportions of currencies in which the Contract price is payable, and we undertake to pay you, upon your first written demand and without cavil or argument, any sum or sums within the limits of guarantee sum as aforesaid without your needing to prove or to show grounds or reasons for your demand for the sum specified therein. We hereby waive the necessity of your demanding the said defining the Contractor before presenting us with the demand.
We further agree that no change or addition to or other modification of the terms of the Contract or th work to be performed there under or of any of the Contract documents which may be made between you and the Contractor shall in any way cease us from any liability under this guarantee, and we hereb waive notice of such change, addition or modification.
This guarantee is valid until theday of
The details of the Issuing Bank and Controlling Bank are as under:
A. Issuing Bank: BANK FAX NO: BANK EMAIL ID: BANK TELEPHONE NO: IFSC CODE OF THE BANK:
B. Controlling Office:
Address of the Controlling Office of the BG issuing Bank: Name of the Contact Person at the Controlling Office with Mobile No. and e-mail address:
SIGNATURE AND SEAL OF THE GUARANTORS
Designation

Contd.... P/2

#### Page No. 2

Name of Bank	
Address	
Witness	
Address	
	_
Date:	
Place:	

#### Note:

The Bank Guarantee issuing bank branch shall ensure the following:

- a) The Bank Guarantee issued by the bank shall be routed through SFMS platform as per the following details:
  - i) "MT 760/MT 760 COV" for issuance of bank guarantee.
  - ii) "MT 760/MT 767 COV" for amendment of bank guarantee.

The above message/intimation shall be sent through SFMS (indicating the Contract Number) by the BG issuing bank branch to Axis Bank, Duliajan Branch, IFS Code: UTIB0001129, Branch address: AXIS Bank Ltd., Duliajan Branch, Daily Bazar, Jyotinagar, Duliajan, District Dibrugarh, PIN: 786602.

b) Bank Guarantee issued by a Scheduled Bank in India at the request of some other Non-Scheduled Bank of India shall not be acceptable.

## FORMAT FOR HINDRANCE REGISTER

because of this hindrance	of hindrance	hindrance	if any	hindrance days	Remarks
			папу	uays	

Signature of Engineer-in-charge

**Signature of HoD** 

**Signature of Contractor's Representative** 

# Format of undertaking by Bidders towards submission of authentic information/documents (To be typed on the letter head of the bidder)

Ref. No	Date
Sub: Undertaking of auther	icity of information/documents submitted
Ref: Your tender No	
To, CGM - Contracts Contracts Deptt, OIL, Duliajan	
Sir,	
	n against your above-referred tender, we hereby undertake that tents have been submitted by us.
We take full responsibility fabove cited bid.	r the submission of authentic information/documents against t
information/documents subm reject our bid at any stage inc	any stage of the tender/contract agreement, in case any of the ted by us are found to be false/forged/fraudulent, OIL has right uding forfeiture of our EMD and/or PBG and/or cancel the away other penal action on us, as deemed fit.
Yours faithfully,	
For (Name of the firm	)
Signature of Authorised Sign	ory
Name:	
Designation:	
Phone No.	
Place:	
Date:	
(Affix Seal of the Organization	here, if applicable)