

OIL INDIA LIMITED
(A Government of India Enterprise)
P.O. Duliajan, Pin – 786602
Dist-Dibrugarh, Assam

AMENDMENT NO. 8 DATED 18.04.2025 TO TENDER NO. SDG7023P25 dated 17.07.2024

AA) This amendment is issued to amend Technical specifications of the tender (Annexure AA) as below in place of existing:

Tender Clause No	Existing Tender Clause	Amended Clause
Clause No.: 10.4.1	<p>Camera:</p> <ol style="list-style-type: none"> 1. Shall have minimum 4 MP resolution. 2. Shall be pan/tilt/zoom (PTZ) type or Bullet fixed type True IP camera (as per locations mentioned under 10.4). 3. All camera shall be Motorized Varifocal with minimum 22X optical zoom. 4. Shall have certification for use in Hazardous Area Zone-1, Class-I, Division-1 & 2, Group C& D. Camera & housing shall be of same make. 5. Shall be fitted with explosion proof fittings and FLP junction boxes in the hazardous area. 6. All camera enclosure shall have IP66 or higher. 7. Operating environment: 0 to 50 degC, 10 to 90 %RH (non-condensing). 8. Shall be equipped with defogger, wiper & washer system. 9. Shall have minimum illumination of Color: 0.01 Lux & B/W: 0.001 Lux. Capable for Day/Night Vision (Low flux). 10. All cables, power or signal cables shall be armoured. The cables (wherever required) shall have sufficient length to carry out pad drilling for 4+1 cluster well on a straight line/ diagonally or to reach up to 120 m from DAS Bunk House, whichever is higher. 11. All CCTV signal cables shall be routed separately in a channel/compartments of cable trays (not along with power cables). 12. Bidder shall consider necessary Mounting arrangement & pole, as required for installation of CCTV camera at the designated locations. 	<p>Camera:</p> <ol style="list-style-type: none"> 1. Shall have minimum 4 MP resolution. 2. Shall be pan/tilt/zoom (PTZ) type or Bullet fixed type True IP camera (as per locations mentioned under 10.4). 3. All camera shall be Motorized Varifocal with minimum 22X optical zoom. 4. Shall have certification for use in Hazardous Area Zone-1, Class-I, Division-1 & 2, Group C& D. Camera & housing shall be of same make. 5. Shall be fitted with explosion proof fittings and FLP junction boxes in the hazardous area. 6. All camera enclosure shall have IP66 or higher. 7. Operating environment: 0 to 50 degC, 10 to 90 %RH (non-condensing). 8. Shall be equipped with defogger, wiper & washer system. 9. Shall have minimum illumination of Color: 0.01 Lux & B/W: 0.001 Lux. Capable for Day/Night Vision (Low flux). 10. All cables, power or signal cables shall be armoured. The cables (wherever required) shall have sufficient length to carry out pad drilling for 4+1 cluster well on a straight line/ diagonally or to reach up to 120 m from DAS Bunk House, whichever is higher. 11. All CCTV signal cables shall be routed separately in a channel/compartments of cable trays (not along with power cables). 12. Bidder shall consider necessary Mounting arrangement & pole, as required for installation of CCTV camera at the designated locations. <p>13. CCTV cameras shall have valid security testing certification issued by Standardisation Testing and Quality Certification (STQC) Laboratory, or any other agency notified by MeitY (Ministry of Electronics and Information Technology). This is as per Office Memorandum No. W-43/11/2021-IPHW dated 11.03.2024 issued by MeitY (IPHW Division).</p> <p>In case such Certifications are not available at the time of submitting the offer, the same shall be submitted during Pre-Dispatch</p>

		<p>Inspection. The bidder shall categorically confirm the same in their offer.</p> <p>As a statutory requirement, if any changes shall be notified by Government guidelines at the time of supply, same shall be complied by the bidder and binding on the bidder.</p>
--	--	--

BB) All other terms and condition of the tender remain unchanged.

**Sd/-
(TUHIN ROY), DGM-FP 07
FOR GM- MATERIALS
FOR RESIDENT CHIEF EXECUTIVE**