

Amendment No. 01

to

Tender No.: SJG1275P26 dated 19.02.2026

1.0 The following amendments are being carried out in Annexure-I (Technical Specifications):

Sl. No.	Clause No.	Existing item description	Amended item description
1	Annexure-I, Technical Specifications (Item No.1)	Overshot assembly with Basket Grapple to catch Sucker Rod Body API Rod Size: 1 inch Maximum OD of Overshot = 2 5/16inch Tubing size: 2 7/8inch EUE, 6.5 ppf Basket Grapple size = 1 inch Basket Grapple Control = 1 inch Top thread connection = 1 3/8inch API sucker rod thread	Overshot assembly with Basket Grapple to catch Sucker Rod Body API Rod Size: 1 inch Maximum OD of Overshot = 2 5/16inch Tubing size: 2 7/8inch EUE, 6.5 ppf Basket Grapple size = 1 inch Basket Grapple Control = 1 inch Top thread connection = 1 3/8inch API sucker rod thread (1" Sucker rod pin connection).
2	Annexure-I, Technical Specifications (Item No.2)	Overshot with Basket Grapple to catch Sucker Rod PIN API Rod Size: 1 inch Tubing size: 2 7/8inch EUE N-80, 6.5ppf Maximum OD of Overshot = 2 5/16 inch Basket Grapple size = 1.375 inch Basket Grapple Control = 1.375 inch Top thread connection = 1 3/8inch API sucker rod thread	Overshot with Basket Grapple to catch Sucker Rod PIN API Rod Size: 1 inch Tubing size: 2 7/8inch EUE N-80, 6.5ppf Maximum OD of Overshot = 2 5/16 inch Basket Grapple size = 1.375 inch Basket Grapple Control = 1.375 inch Top thread connection = 1 3/8inch API sucker rod thread (1" Sucker rod pin connection).
3	Annexure-I, Technical Specifications (Item No.3)	Overshot with Sprial Grapple to catch Sucker Rod Coupling (Slim Hole) API Rod Size: 1 inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Spiral Grapple size = 2 inch Spiral Grapple Control = 2 inch Top connection = 1 3/8inch API sucker rod thread	Overshot with Sprial Grapple to catch Sucker Rod Coupling (Slim Hole) API Rod Size: 1 inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Spiral Grapple size = 2 inch Spiral Grapple Control = 2 inch Top connection = 1 3/8inch API sucker rod thread (1" Sucker rod pin connection).
4	Annexure-I, Technical Specifications (Item No.4)	Overshot with Basket Grapple to catch Sucker Rod BODY Rod Size: 7/8inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 7/8inch Basket Grapple Control = 7/8inch	Overshot with Basket Grapple to catch Sucker Rod BODY Rod Size: 7/8inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 7/8inch Basket Grapple Control = 7/8inch

		Top thread connection = 1 3/16inch API sucker rod thread	Top thread connection = 1 3/16inch API sucker rod thread (7/8" Sucker rod pin connection).
5	Annexure-I, Technical Specifications (Item No.5)	Overshot with Basket Grapple to catch Sucker Rod PIN API Rod Size: 7/8inch Tubing size: 2 7/8inch EUE, 6.5ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.187inch Basket Grapple Control = 1.187inch Top thread connection = 1 3/16inch API sucker rod thread	Overshot with Basket Grapple to catch Sucker Rod PIN API Rod Size: 7/8inch Tubing size: 2 7/8inch EUE, 6.5ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.187inch Basket Grapple Control = 1.187inch Top thread connection = 1 3/16inch API sucker rod thread (7/8" Sucker rod pin connection).
6	Annexure-I, Technical Specifications (Item No.6)	Overshot with Sprial Grapple to catch Sucker Rod Coupling (Slim Hole) Rod Size: 7/8inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Spiral Grapple size = 1.812inch Spiral Grapple Control = 1.812inch Top connection = 1 3/16inch API sucker rod thread	Overshot with Sprial Grapple to catch Sucker Rod Coupling (Slim Hole) Rod Size: 7/8inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Spiral Grapple size = 1.812inch Spiral Grapple Control = 1.812inch Top connection = 1 3/16inch API sucker rod thread (7/8" Sucker rod pin connection).
7	Annexure-I, Technical Specifications (Item No.7)	Overshot with Basket Grapple to catch Sucker Rod Body Rod Size: 3/4inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 0.75inch Basket Grapple Control = 0.75inch Top thread connection = 1 1/16inch API sucker rod thread	Overshot with Basket Grapple to catch Sucker Rod Body Rod Size: 3/4inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 0.75inch Basket Grapple Control = 0.75inch Top thread connection = 1 1/16inch API sucker rod thread (3/4" Sucker rod pin connection).
8	Annexure-I, Technical Specifications (Item No.8)	Overshot with Basket Grapple to catch Sucker Rod PIN API Rod Size: 3/4inch Tubing size: 2 7/8inch EUE N-80, 6.5ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.0625inch Basket Grapple Control = 1.0625inch Top connection = 1 1/16inch API sucker rod thread	Overshot with Basket Grapple to catch Sucker Rod PIN API Rod Size: 3/4inch Tubing size: 2 7/8inch EUE N-80, 6.5ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.0625inch Basket Grapple Control = 1.0625inch Top connection = 1 1/16inch API sucker rod thread (3/4" Sucker rod pin connection).

9	Annexure-I, Technical Specifications (Item No.9)	Overshot with Basket Grapple to catch Sucker Rod Coupling (Slim Hole) API Rod Size: 3/4inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.625inch Basket Grapple Control = 1.625inch Top connection = 1 1/16inch API sucker rod thread	Overshot with Basket Grapple to catch Sucker Rod Coupling (Slim Hole) API Rod Size: 3/4inch Tubing size: 2 7/8inch EUE, 6.5 ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.625inch Basket Grapple Control = 1.625inch Top connection = 1 1/16inch API sucker rod thread (3/4" Sucker rod pin connection).
10	Annexure-I, Technical Specifications (Item No.10)	Overshot with Basket Grapple to catch Sucker Rod Body API Polish Rod Size: 1 1/2inch Maximum OD of Overshot = 2 5/16inch Tubing size: 2 7/8inch EUE, 6.5 ppf Basket Grapple size = 1 1/2inch Basket Grapple Control = 1 1/2inch Top thread connection = 1 3/8inch API sucker rod thread	Overshot with Basket Grapple to catch Sucker Rod Body API Polish Rod Size: 1 1/2inch Maximum OD of Overshot = 2 5/16inch Tubing size: 2 7/8inch EUE, 6.5 ppf Basket Grapple size = 1 1/2inch Basket Grapple Control = 1 1/2inch Top thread connection = 1 3/8inch API sucker rod thread (1" Sucker rod pin connection).
11	Annexure-I, Technical Specifications (Item No.11)	Overshot with Basket Grapple to catch Sucker Rod Pin API Polish Rod Size: 1 1/2inch Tubing size: 2 7/8inch EUE, 6.5ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.377inch Basket Grapple Control = 1.377inch Top thread connection = 1 3/8inch API sucker rod thread	Overshot with Basket Grapple to catch Sucker Rod Pin API Polish Rod Size: 1 1/2inch Tubing size: 2 7/8inch EUE, 6.5ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.375 inch Basket Grapple Control = 1.375 inch Top thread connection = 1 3/8inch API sucker rod thread (1" Sucker rod pin connection).
12	Annexure-I, Technical Specifications (Item No.31)	Basket Grapple for 2 5/16 inch Overshot to catch Sucker Rod Pin API Polish Rod Size: 1 1/2inch Tubing size: 2 7/8inch EUE, 6.5ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.377inch Basket Grapple Control = 1.377inch	Basket Grapple for 2 5/16 inch Overshot to catch Sucker Rod Pin API Polish Rod Size: 1 1/2inch Tubing size: 2 7/8inch EUE, 6.5ppf Maximum OD of Overshot = 2 5/16inch Basket Grapple size = 1.375 inch Basket Grapple Control = 1.375 inch

2.0 Moreover, the bid closing date is being extended as under:

A) Bid closing date & time: **08.04.2026 at 13:00 (IST)**

B) Technical bid opening date & time: **08.04.2026 at 14:00 (IST)**

3.0 All other terms & conditions of the tender remain unchanged.

A. R. Padhy
Manager (C&P)
Oil India Limited