

**AMENDMENT NO.1 TO TENDER GEM/2025/B/6135932**

This amendment has been issued for the following instead of existing. All other terms and conditions of the tender remain unchanged.

<b>Sl No.</b>	<b>Clause No.</b>	<b>Earlier Clause</b>	<b>Revised Clause</b>
<b>01</b>	<b>20/ 99072975 of ANNEXURE – I TECHNICAL SPECIFICATION/SCOPE OF WORK/SPECIAL TERMS &amp; CONDITIONS of NIT.</b>	<p><b><u>TAPE,CO-EXTRUDED POLYETHYLENE</u></b></p> <p>The tape shall be Co-Extruded Polyethylene Tape suitable for cold application OR Extruded hot calendared Polyethylene tape suitable for cold application. The inner tape shall have the butyl rubber adhesive on both sides and the outer tape shall have butyl rubber adhesive on one side only. A non-sticking separator strip (release film) shall be provided in the rolls to eliminate sticking of adhesive when the tape is in roll form.The consistency of the adhesive layer shall be such that under tension it flows on uneven steel surfaces. The adhesive layer shall be completely compatible with the properties of the primer. The inner tape must be self-amalgamating with the inner layer of outer Tape. It shall be standard product of the supplier having established history of excellent performance.</p> <p>PROPERTIES: The physical properties of the tape shall be as given below</p>	<p><b><u>TAPE,CO-EXTRUDED POLYETHYLENE</u></b></p> <p>The tape shall be Co-Extruded Polyethylene Tape suitable for cold application OR Extruded hot calendared Polyethylene tape suitable for cold application. The inner tape shall have the butyl rubber adhesive on both sides and the outer tape shall have butyl rubber adhesive on one side only. A non-sticking separator strip (release film) shall be provided in the rolls to eliminate sticking of adhesive when the tape is in roll form.The consistency of the adhesive layer shall be such that under tension it flows on uneven steel surfaces. The adhesive layer shall be completely compatible with the properties of the primer. The inner tape must be self-amalgamating with the inner layer of outer Tape. It shall be standard product of the supplier having established history of excellent performance.</p> <p>PROPERTIES: The physical properties of the tape shall be as given below</p>

Sl No.	Clause No.	Earlier Clause	Revised Clause																																																																								
		<table border="1"> <thead> <tr> <th>Parameters</th> <th>Value / Requirement</th> <th>Unit</th> <th>Test Method</th> </tr> </thead> <tbody> <tr> <td>Application temperature</td> <td>0° C to + 60° C</td> <td>Deg.C</td> <td></td> </tr> <tr> <td>Operating Temperature</td> <td>0° C to + 50° C</td> <td>Deg.C</td> <td></td> </tr> <tr> <td>Total coating Thickness</td> <td>2.5 to 3.0</td> <td>mm</td> <td>ASTM G12</td> </tr> <tr> <td><b>Thickness of Inner layer Tape</b></td> <td></td> <td><b>mm</b></td> <td><b>ASTM D1000</b></td> </tr> <tr> <td><b>Thickness of adhesive facing the steel pipe</b></td> <td><b>0.178</b></td> <td></td> <td></td> </tr> <tr> <td><b>Thickness of backing (carrier film)</b></td> <td><b>0.305</b></td> <td></td> <td></td> </tr> <tr> <td><b>Thickness of adhesive facing the outer</b></td> <td><b>0.152</b></td> <td></td> <td></td> </tr> </tbody> </table>	Parameters	Value / Requirement	Unit	Test Method	Application temperature	0° C to + 60° C	Deg.C		Operating Temperature	0° C to + 50° C	Deg.C		Total coating Thickness	2.5 to 3.0	mm	ASTM G12	<b>Thickness of Inner layer Tape</b>		<b>mm</b>	<b>ASTM D1000</b>	<b>Thickness of adhesive facing the steel pipe</b>	<b>0.178</b>			<b>Thickness of backing (carrier film)</b>	<b>0.305</b>			<b>Thickness of adhesive facing the outer</b>	<b>0.152</b>			<table border="1"> <thead> <tr> <th>Parameters</th> <th>Value / Requirement</th> <th>Unit</th> <th>Test Method</th> </tr> </thead> <tbody> <tr> <td>Application temperature</td> <td>0° C to + 60° C</td> <td>Deg.C</td> <td></td> </tr> <tr> <td>Operating Temperature</td> <td>0° C to + 50° C</td> <td>Deg.C</td> <td></td> </tr> <tr> <td>Total coating Thickness</td> <td>2.5 to 3.0</td> <td>mm</td> <td>ASTM G12</td> </tr> <tr> <td><b>Thickness of Inner Layer Tape</b></td> <td></td> <td></td> <td><b>ASTM D1000</b></td> </tr> <tr> <td><b>Total Thickness</b></td> <td><b>≥0.75</b></td> <td><b>mm</b></td> <td></td> </tr> <tr> <td><b>Thickness of Outer Layer Tape</b></td> <td></td> <td></td> <td><b>ASTM D1000</b></td> </tr> <tr> <td><b>Total Thickness</b></td> <td><b>≥0.5</b></td> <td><b>mm</b></td> <td></td> </tr> <tr> <td>Width of the tape</td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>Deviation in width</td> <td>±1.5</td> <td></td> <td></td> </tr> </tbody> </table>	Parameters	Value / Requirement	Unit	Test Method	Application temperature	0° C to + 60° C	Deg.C		Operating Temperature	0° C to + 50° C	Deg.C		Total coating Thickness	2.5 to 3.0	mm	ASTM G12	<b>Thickness of Inner Layer Tape</b>			<b>ASTM D1000</b>	<b>Total Thickness</b>	<b>≥0.75</b>	<b>mm</b>		<b>Thickness of Outer Layer Tape</b>			<b>ASTM D1000</b>	<b>Total Thickness</b>	<b>≥0.5</b>	<b>mm</b>		Width of the tape	100			Deviation in width	±1.5		
Parameters	Value / Requirement	Unit	Test Method																																																																								
Application temperature	0° C to + 60° C	Deg.C																																																																									
Operating Temperature	0° C to + 50° C	Deg.C																																																																									
Total coating Thickness	2.5 to 3.0	mm	ASTM G12																																																																								
<b>Thickness of Inner layer Tape</b>		<b>mm</b>	<b>ASTM D1000</b>																																																																								
<b>Thickness of adhesive facing the steel pipe</b>	<b>0.178</b>																																																																										
<b>Thickness of backing (carrier film)</b>	<b>0.305</b>																																																																										
<b>Thickness of adhesive facing the outer</b>	<b>0.152</b>																																																																										
Parameters	Value / Requirement	Unit	Test Method																																																																								
Application temperature	0° C to + 60° C	Deg.C																																																																									
Operating Temperature	0° C to + 50° C	Deg.C																																																																									
Total coating Thickness	2.5 to 3.0	mm	ASTM G12																																																																								
<b>Thickness of Inner Layer Tape</b>			<b>ASTM D1000</b>																																																																								
<b>Total Thickness</b>	<b>≥0.75</b>	<b>mm</b>																																																																									
<b>Thickness of Outer Layer Tape</b>			<b>ASTM D1000</b>																																																																								
<b>Total Thickness</b>	<b>≥0.5</b>	<b>mm</b>																																																																									
Width of the tape	100																																																																										
Deviation in width	±1.5																																																																										

Sl No.	Clause No.	Earlier Clause				Revised Clause			
		<b>layer tape.</b>				Impact Resistance	10 impacts at least	No holiday with a test voltage of 15 KV	Should Pass DIN EN 12068
		<b>Total Thickness</b>	<b>0.635</b>						
		<b>Thickness of the outer layer Tape</b>							
		<b>Thickness of adhesive facing the inner layer tape.</b>	<b>0.305</b>						
		<b>Thickness of backing (carrier film)</b>	<b>0.33</b>						
		<b>Total Thickness</b>	<b>0.635</b>						
		Width of the tape	100						
		Deviation in width	±1.5						
						<b>** Other parameters (annexure G &amp; H) remain same.</b>			

Sl No.	Clause No.	Earlier Clause				Revised Clause
		Impact Resistance	10 impacts at least	No holiday with a test voltage of 15 KV	Should Pass DIN EN 12068	

Sl No.	Clause No.	Earlier Clause	Revised Clause
02	Special Terms and Conditions for both item nos. 10 and 20 of <b>ANNEXURE – I TECHNICAL SPECIFICATION/SCOPE OF WORK/SPECIAL TERMS &amp; CONDITIONS</b> of NIT.	<p><b>01. Testing and Inspection:</b>  All the properties mentioned in the specification shall be tested at manufacturer's works place with their in house test facilities as per applicable standard. The testing shall be witnessed by OIL approved Third party inspection agency. The supplier shall submit the copy of test certificates duly witnessed and endorsed by OIL approved Third party inspection agency.</p> <p><b>THIRD PARTY INSPECTION:</b> All items shall be inspected by any one of following OIL approved Third Party Inspection agencies. The bidder has to arrange and bear for the Third Party Inspection at manufacturer's plant as per the broad scope of work mentioned herein. Bidder should confirm that items/equipment/material supplied by them will be inspected by any of the following third party inspection agencies at their own cost. Third Party Inspection Report shall be submitted along with the dispatch document. <b>Bidder to include the Third Party Inspection charges in their quoted price.</b></p> <ul style="list-style-type: none"> <li>(i) M/s Lloyds</li> <li>(ii) M/s Bureau Veritas</li> <li>(iii) M/s Rites</li> <li>(iv) M/s IRCLASS System and Solutions Private Limited</li> <li>(v) M/s Tuboscope Vetco</li> <li>(vi) M/s DNV MES India Private Limited</li> </ul>	<p><b>01. Testing and Inspection:</b>  A manufacturer's standard Quality Assurance Plan (QAP) is to be submitted by the Coating manufacturer for review and approval by OIL before starting the production. The QAP shall identify all inspection activities and test, their frequency and relevant inspection authorities.</p> <p>All the properties mentioned in the specification shall be tested at manufacturer's works place with their in-house test facilities as per the approved QAP. The testing shall be witnessed by OIL approved Third-party inspection agency. The supplier shall submit the copy of test certificates duly witnessed and endorsed by OIL approved Third-party inspection agency.</p> <p><b>THIRD PARTY INSPECTION:</b> All items shall be inspected by any one of following OIL approved Third Party Inspection agencies. The bidder has to arrange and bear for the Third Party Inspection at manufacturer's plant as per the broad scope of work mentioned herein. Bidder should confirm that items/equipment/material supplied by them will be inspected by any of the following third party inspection agencies at their own cost. Third Party Inspection Report shall be submitted along with the dispatch document. <b>Bidder to include the Third Party Inspection charges in their quoted price.</b></p> <ul style="list-style-type: none"> <li>(i) M/s Lloyds</li> </ul>

Sl No.	Clause No.	Earlier Clause	Revised Clause
		<p><b>THE SCOPE OF THIRD PARTY INSPECTION SHALL COVER THE FOLLOWING:</b>  The OIL approved Third party inspection agency shall witness the testing of all the properties mentioned in the material specifications at manufacturer's works place with their in-house test facilities as per applicable standard.</p> <p>All the test certificates are to be witnessed and endorsed by the OIL approved TPI agency and the same are to be submitted by the manufacturer along with the delivery of materials.</p>	<p>(ii) M/s Bureau Veritas  (iii) M/s Rites  (iv) M/s IRCLASS System and Solutions Private Limited  (v) M/s Tuboscope Vetco  (vi) M/s DNV MES India Private Limited</p> <p><b>THE SCOPE OF THIRD PARTY INSPECTION SHALL COVER THE FOLLOWING:</b>  The OIL approved Third party inspection agency shall witness the testing of all the properties mentioned in the material specifications at manufacturer's works place with their in-house test facilities as per approved QAP.</p> <p>All the test certificates are to be witnessed and endorsed by the OIL approved TPI agency and the same are to be submitted by the manufacturer along with the delivery of materials.</p>